

# The XePersian Package



Persian for L<sup>A</sup>T<sub>E</sub>X, using XeT<sub>E</sub>X engine

Vafa Khalighi  
[persian-tex@tug.org](mailto:persian-tex@tug.org)

July 10, 2014      Version 13.9

If you want to report any bugs or typos and corrections in the documentation, or ask for any new features, or suggest any improvements, or ask any questions about the package, then please do not send any direct email to me; I will not answer any direct email. Instead please use the issue tracker:

<https://sourceforge.net/p/xepersian-project/tickets>

In doing so, please always explain your issue well enough, always include a minimal working example showing the issue, and always choose the appropriate label for your query (i.e. if you are reporting any bugs, choose ‘bug’ label).

# Contents

<b>1</b>	<b>Introduction</b>	<b>4</b>	<b>3</b>	<b>Latin and Persian Environment</b>	<b>41</b>
1.1	Important Notes . . . . .	4	3.1	latitems and parsitems environments . . . . .	42
1.2	XePersian Info On The Terminal and In The Log File . . . . .	4	3.2	Short Latin and Persian Texts	42
<b>2</b>	<b>Basics</b>	<b>5</b>	3.3	Miscellaneous Commands . . . . .	42
2.1	Loading The Package . . . . .	5	3.4	New Commands . . . . .	43
2.2	XePersian's Symbol . . . . .	6	3.5	Additional Counters . . . . .	43
2.3	Commands for Version number, and Date of The Package	6	3.6	Things To Know About \setdigitfont, \setmathsf digitfont, and \setmathtt digitfont . . . . .	43
2.4	Options of The Package . . . . .	6	<b>4</b>	<b>New Conditionals</b>	<b>44</b>
2.4.1	extrafootnotefeatures Option . . . . .	6	4.1	Shell escape (or write18) conditional . . . . .	44
2.4.2	Kashida Option . . . . .	7	<b>5</b>	<b>Bilingual Captions</b>	<b>44</b>
2.4.3	quickindex Option . . . . .	7	5.1	Support For Various Packages . . . . .	44
2.4.4	quickindex-variant1 Option . . . . .	7	5.1.1	Things You Should Know about Support For enumerate Package . . . . .	44
2.4.5	quickindex-variant2 Option . . . . .	7	5.2	Index Generation . . . . .	45
2.4.6	localise Option . . . . .	7	5.3	Converting Your FarsiTEX Files To XePersian or Unicode . . . . .	45
2.4.7	Localizations of the keys and key values of graphicx package . . . . .	35	<b>6</b>	<b>Extra Packages And Classes</b>	<b>46</b>
2.4.8	Localizations of font features and font feature options . . . . .	36	6.1	Magazine Typesetting . . . . .	46
2.5	A Sample Input T <sub>E</sub> X File . . . . .	38	6.1.1	Introduction . . . . .	46
2.6	Font Commands . . . . .	39	6.1.2	Usage . . . . .	46
2.6.1	Basic Font Commands	39	6.1.3	Front Page . . . . .	46
2.6.2	Defining Extra Persian and Latin Fonts . . . . .	39	6.1.4	Inside . . . . .	48
2.6.3	Choosing Persian Sans Font . . . . .	41	6.1.5	The article environment . . . . .	48
2.6.4	Choosing Persian Mono Font . . . . .	41	6.1.6	The editorial environment . . . . .	49
2.6.5	Choosing Persian Iranic Font . . . . .	41	6.1.7	The shortarticle environment . . . . .	50
2.6.6	Choosing Persian Navar Font . . . . .	41	6.1.8	Commands between articles . . . . .	50
2.6.7	Choosing Persian Pook Font . . . . .	41	6.1.9	Customization . . . . .	50
2.6.8	Choosing Persian Sayeh Font . . . . .	41	6.1.10	Front Page . . . . .	51
2.6.9	Choosing Latin Sans Font . . . . .	41	6.1.11	Inside The Magazine . . . . .	52
2.6.10	Choosing Latin Mono Font . . . . .	41	6.1.12	Class Options . . . . .	53

6.2.4	Creating Questions . . .	54	7.24	extarticle-xepersian.def . . . . .	87
6.2.5	The <code>question</code> Environment . . . . .	54	7.25	extbook-xepersian.def . . . . .	87
6.2.6	Question Numbers . . .	55	7.26	<code>extrafootnotefeatures-xepersian.def</code> . . . . .	87
6.2.7	The Form and the Mask	55	7.27	extreport-xepersian.def . . . . .	87
6.2.8	Typesetting corrections	55	7.28	flowfram-xepersian.def . . . . .	88
6.2.9	Important Note . . . .	55	7.29	footnote-xepersian.def . . . . .	88
6.3	Customising The Package . . .	56	7.30	framed-xepersian.def . . . . .	90
6.3.1	The <code>question</code> environment . . . . .	56	7.31	glossaries-xepersian.def . . . . .	91
6.3.2	The Form and the Mask	56	7.32	hyperref-xepersian.def . . . . .	92
6.3.3	The correction . . . . .	56	7.33	imsproc-xepersian.def . . . . .	93
<b>7</b>	<b>xepersian implementation</b>	<b>57</b>	7.34	kashida-xepersian.def . . . . .	96
7.1	<code>algorithms-xepersian.def</code> . . . . .	57	7.35	listings-xepersian.def . . . . .	97
7.2	<code>algorithm-xepersian.def</code> . . . . .	57	7.36	loadingorder-xepersian.def . . . . .	97
7.3	<code>amsart-xepersian.def</code> . . . . .	57	7.37	<code>localise-xepersian.def</code> . . . . .	98
7.4	<code>amsbook-xepersian.def</code> . . . . .	58	7.38	<code>memoir-xepersian.def</code> . . . . .	99
7.5	<code>article-xepersian.def</code> . . . . .	59	7.39	<code>latex-localise-messages-xepersian.def</code> . . . . .	99
7.6	<code>artikel1-xepersian.def</code> . . . . .	60	7.40	<code>minitoc-xepersian.def</code> . . . . .	100
7.7	<code>artikel2-xepersian.def</code> . . . . .	60	7.41	<code>latex-localise-misc-xepersian.def</code> . . . . .	100
7.8	<code>artikel3-xepersian.def</code> . . . . .	60	7.42	<code>natbib-xepersian.def</code> . . . . .	107
7.9	<code>backref-xepersian.def</code> . . . . .	60	7.43	<code>packages-localise-xepersian.def</code> . . . . .	112
7.10	<code>buditutesidenote-xepersian.def</code> . . . . .	61	7.44	<code>parsidigits.map</code> . . . . .	115
7.11	<code>bidimoderncv-xepersian.def</code> . . . . .	62	7.45	<code>rapport1-xepersian.def</code> . . . . .	115
7.12	<code>boek3-xepersian.def</code> . . . . .	62	7.46	<code>rapport3-xepersian.def</code> . . . . .	116
7.13	<code>boek-xepersian.def</code> . . . . .	62	7.47	<code>refrep-xepersian.def</code> . . . . .	116
7.14	<code>bookest-xepersian.def</code> . . . . .	63	7.48	<code>report-xepersian.def</code> . . . . .	116
7.15	<code>book-xepersian.def</code> . . . . .	63	7.49	<code>scrartcl-xepersian.def</code> . . . . .	116
7.16	<code>breqn-xepersian.def</code> . . . . .	63	7.50	<code>scrbook-xepersian.def</code> . . . . .	117
7.17	<code>latex-localise-commands-xepersian.def</code> . . . . .	64	7.51	<code>scrrept-xepersian.def</code> . . . . .	118
7.18	<code>color-localise-xepersian.def</code> . . . . .	83	7.52	<code>tkz-linknodes-xepersian.def</code> . . . . .	118
7.19	<code>xepersian-localise-commands-xepersian.def</code> . . . . .	83	7.53	<code>tocloft-xepersian.def</code> . . . . .	119
7.20	<code>enumerate-xepersian.def</code> . . . . .	84	7.54	<code>xepersian.sty</code> . . . . .	119
7.21	<code>fontspec-xetex-xepersian.def</code> . . . . .	85	7.55	<code>xepersian-magazine.cls</code> . . . . .	132
7.22	<code>latex-localise-environments-xepersian.def</code> . . . . .	86	7.56	<code>xepersian-mathsdigitspec.sty</code> . . . . .	149
7.23	<code>xepersian-localise-environments-xepersian.def</code> . . . . .	87	7.57	<code>xepersian-multiplechoice.sty</code> . . . . .	154
			7.58	<code>xepersian-persiancal.sty</code> . . . . .	156
			<b>8</b>	<b>Change History</b>	<b>195</b>

# 1 Introduction

XePersian is a package for typesetting Persian/English documents with Xe<sup>L</sup>ATE<sub>X</sub>. The package includes adaptations for use with many other commonly-used packages.

## 1.1 Important Notes

- ☒ The XePersian package only works with XeTeX engine.
- ☒ Before reading this documentation, you should have read the documentation of the bidi package. The XePersian package automatically loads bidi package with `RTLdocument` option enabled and hence any commands that bidi package offers, is also available in XePersian package. Here, in this documentation, we will not repeat any of bidi package's commands.
- ☒ In previous versions ( $\leq 1.0.3$ ) of XePersian, a thesis class provided for typesetting thesis. As of version 1.0.4, we no longer provide this class because we are not familiar with specification of a thesis in Iran and even if we were, the specifications are different from University to University. XePersian is a general package like L<sup>A</sup>TEX and should not provide any class for typesetting thesis. So if you really want to have a class file for typesetting thesis, then you should ask your University/department to write one for you.

## 1.2 XePersian Info On The Terminal and In The Log File

If you use XePersian package to write any input TeX document, and then run `xelatex` on your document, in addition to what bidi package writes to the terminal and to the log file, the XePersian package also writes some information about itself to the terminal and to the log file, too. The information is something like:

```
*****
*
* xepersian package (Persian for LaTeX, using XeTeX engine)
*
* Description: The package supports Persian
* typesetting, using fonts provided in the
* distribution.
*
* Copyright © 2008-2014 Vafa Khalighi
*
* v13.9, 2014/07/10
*
* License: LaTeX Project Public License, version
* 1.3c or higher (your choice)
*
* Location on CTAN: /macros/xetex/latex/xepersian
*
```

```

* Issue tracker: https://sourceforge.net/p/xepersian-project/tickets
*
* Support: persian-tex@tug.org
*****

```

## 2 Basics

### 2.1 Loading The Package

You can load the package in the ordinary way;

```
\usepackage [Options] {xepersian}
```

Where **options** of the package are explained later in [subsection 2.4](#).

When loading the package, it is important to know that:

- ❶ **xepersian** should be the last package that you load, because otherwise you are certainly going to overwrite **bidi** and **XePersian** package's definitions and consequently, you will not get the expected output.
- ❷ In fact, in addition to **bidi**, **XePersian** also makes sure that some specific packages are loaded before **bidi** and **XePersian**; these are those packages that **bidi** and **XePersian** modifies them for bidirectional and Persian/English typesetting.

If you load **XePersian** before any of these packages, then you will get an error saying that you should load **XePersian** or **bidi** as your last package. When it says that you should load **bidi** package as your last package, it really means that you should load **XePersian** as your last package as **bidi** package is loaded automatically by **XePersian** package.

For instance, consider the following minimal example:

```

1 \documentclass{minimal}
2 \usepackage{xepersian}
3 \usepackage{enumerate}
4 \settextfont{XB Niloofar}
5 \begin{document}
6 این فقط یک آزمایش است
7 \end{document}

```

Where **enumerate** is loaded after **XePersian**. If you run **xelatex** on this document, you will get an error which looks like this:

```

! Package xepersian Error: Oops! you have loaded package enumerate
after xepersian package. Please load package enumerate before
xepersian package, and then try to run xelatex on your document
again.

```

```

See the xepersian package documentation for explanation.
Type H <return> for immediate help.
...
1.5 \begin{document}
?

```

## 2.2 XePersian's Symbol

As you may know lion symbolizes T<sub>E</sub>X but lion does not symbolizes XePersian. Simorgh<sup>1</sup> (shown on the first page of this documentation) symbolizes XePersian.

## 2.3 Commands for Version number, and Date of The Package

```
\xepersianversion \xepersiandate
```

 \xepersianversion gives the current version of the package.

 \xepersiandate gives the current date of the package.

```

1 \documentclass{article}
2 \usepackage{xepersian}
3 \settextfont{XB Niloofer}
4 \begin{document}
5 \begin{latin}
6 This is typeset by \textsf{\XePersian} package, \xepersianversion,
7 \xepersiandate.
8 \end{latin}
9 \end{document}
```

## 2.4 Options of The Package

There are six options:

### 2.4.1 extrafootnotefeatures Option

This is just the extrafootnotefeatures Option of bidi package. If you enable this option, you can typeset footnotes in paragraph form or in multi-columns (from two-columns to ten-columns). For more details, please read the manual of bidi package.

---

<sup>1</sup>Simorgh is an Iranian benevolent, mythical flying creature which has been shown on the titlepage of this documentation. For more details see <http://en.wikipedia.org/wiki/Simurgh>

#### 2.4.2 Kashida Option

If you pass `Kashida` option to the package, you will use Kashida for stretching words for better output quality and getting rid of underfull or overfull `\hbox` messages.

Note that you can not use `Kashida` option when you are using Nastaliq-like font (well, you still can use `Kashida` option when you use any Nastaliq-like font, but I can not guarantee high quality output!).

The following two commands are provided when you activate the `Kashida` option:

```
\KashidaOn \KashidaOff
```

☞ `\KashidaOn` enables Kashida and is active by default when `Kashida` option is activated.

☞ `\KashidaOff` disables Kashida.

#### 2.4.3 quickindex Option

When you generally want to prepare index for your Persian documents, you need to first run `xelatex`, then `xindy`, and again `xelatex` on your document respectively, which is very time consuming. The `quickindex` option gives you the index with only and only one run of `xelatex`. To use this feature, you will need to run `xelatex --shell-escape` on your `TeX` document; otherwise you get an error which indicates that shell escape (or `write18`) is not enabled.

This option is now obsolete and equivalent to `quickindex-variant2` option.

#### 2.4.4 quickindex-variant1 Option

Same as `quickindex` Option but uses variant one (in which `\i` is grouped under `\l`) for sorting Persian alphabets.

#### 2.4.5 quickindex-variant2 Option

Same as `quickindex` Option but uses variant two (in which `\i` is a separate letter) for sorting Persian alphabets.

#### 2.4.6 localise Option

The `localise` option is now active by default; it allows you to use most frequently-used `LATEX` commands and environments in Persian, almost like what `TeX-e-Parsi` offers. This is still work in progress and we wish to add lots more Persian equivalents of `LATEX` and `TeX` commands and environments. The Persian equivalents of `LATEX` and `TeX` commands are shown in [Table 1](#), The Persian equivalents of

XePersian commands are shown in [Table 2](#), Persian equivalents of L<sup>A</sup>T<sub>E</sub>X environments are shown in [Table 3](#) and Persian equivalents of XePersian environments are shown in [Table 4](#)

Please note that the Persian equivalents of L<sup>A</sup>T<sub>E</sub>X and T<sub>E</sub>X commands and environments are only available after loading `xepersian` package. This means that you have to write all commands or environments that come before `\usepackage{xepersian}`, in its original form, i.e. `\documentclass`.

Not only you can use Persian equivalents of L<sup>A</sup>T<sub>E</sub>X and T<sub>E</sub>X commands and environments, but still original L<sup>A</sup>T<sub>E</sub>X and T<sub>E</sub>X commands and environments work too.

The T<sub>E</sub>X L<sup>A</sup>T<sub>E</sub>X and XePersian commands and environments and their Persian equivalents listed in [Table 1](#), [Table 2](#), [Table 3](#) and [Table 4](#) is not the whole story; If any command and environment in [Table 1](#), [Table 2](#), [Table 3](#) and [Table 4](#) have a starred version, their starred version also work. For example in [Table 1](#), the Persian equivalent of `\chapter` is `\فصل`. I know that `\chapter` has a starred version, so this means `*\فصل` is also the Persian equivalent of `\chapter*`. Is that clear?

However there is more; you can localise any other commands/environments you want. You can use the following commands to localise your own commands/environments:

```
\eqcommand{\<command-name in Persian\>}{\<original LATEX command-name\>}
\eqenvironment{\<environment-name in Persian\>}{\<original LATEX environment-name\>}
```

Table 1: The Equivalent L<sup>A</sup>T<sub>E</sub>X and T<sub>E</sub>X Commands

Command in T <sub>E</sub> X or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
<code>\@arstrut</code>	\شمع جدول
<code>\above</code>	\فوق
<code>\abovedisplayshortskip</code>	\فاصله کوتاه بالای نمایش
<code>\abovedisplayskip</code>	\فاصله بالای نمایش
<code>\abstractname</code>	\عنوان چکیده
<code>\accent</code>	\اکسنت
<code>\active</code>	\فعال
<code>\addcontentsline</code>	\بیفزاسطر فهرست
<code>\addpenalty</code>	\اضافه برجیمه
<code>\address</code>	\نشانی
<code>\addtocontents</code>	\بیفزابه فهرست
<code>\addtocounter</code>	\اضافه برشمارنده
<code>\addtolength</code>	\اضافه برعده
<code>\addvspace</code>	\بیفزافضای و
<code>\adjdemerits</code>	\تنظیم بد نمایی
<code>\advance</code>	\بیفزابر

*Continued on next page*

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\afterassignment	\بعدازانتساب
\aftergroup	\بعدازگروه
\aleph	\الف
\aliasfontfeature	\خصیصه مستعار قلم
\aliasfontfeatureoption	\انتخاب خصیصه مستعار قلم
\allowbreak	\شکستنی
\alloc@	\تخصیصی افته
\allocationnumber	\شکست نمایش مجاز
\allowdisplaybreaks	\حروف بزرگ
\Alph	\حروف کوچک
\alph	\نام همچنین
\alsoname	\و
\and	\زاویه
\angle	\عنوان پیوست
\appendixname	\تقریب
\approx	\عربی
\arabic	\آرگ
\arg	\رنگ خط جدول
\arrayrulecolor	\فاصله ستونهای آرایه
\arraycolsep	\ضخامت خط جدول
\arrayrulewidth	\کشیدگی آرایه
\arraystretch	\در آغاز نوشتار
\AtBeginDocument	\در پایان نوشتار
\AtEndDocument	\در اننهای طبقه
\AtEndOfClass	\در اننهای سبک
\AtEndOfPackage	\نویسنده
\author	\مطلوب پشت
\backmatter	\شکاف پشت
\backslash	\بد نمایی
\badness	\میله
\bar	\فاصله کرسی
\baselineskip	\کشش فاصله کرسی
\baselinestretch	\پردازش دسته ای
\batchmode	\شروع
\begin	\شروع چپ
\beginL	\شروع راست
\beginR	\شروع گروه
\begingroup	\فاصله کوتاه پایین نمایش
\belowdisplayshortskip	\فاصله پایین نمایش
\belowdisplayskip	

Continued on next page

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\bf	\سیاه
\bfdefault	\بیش فرض سیاه
\bfseries	\شمايل سیاه
\bgroup	\شرگروه
\bibitem	\مرجوع
\bibliography	\كتاب نامه
\bibliographystyle	\اسبک کتاب نامه
\bibname	\عنوان كتاب نامه
\bigskip	\پرسنلند
\bigskipamount	\مقدار پرسنلند
\botfigrule	\خط پایین شناور
\botmark	\علامت پایین
\bottompagesizekip	\کادر تا پایین
\bottomfraction	\نسبت پایین
\box	\کادر
\boxmaxdepth	\حد اکثر عمق کادر
\break	\ بشکن
\bullet	\گلوله
\@cclv	\دوپن @ پنج
\@cclvi	\دوپن @ شش
\caption	\شرح
\catcode	\اکرده
\cc	\رونوشت
\ccname	\نام رونوشت
\cdot	\ نقطه وسط
\cdots	\ نقاط وسط
\centering	\تنظيم از وسط
\centerline	\خطوط وسط
\ch@ck	\چک @ ن
\chapter	\فصل
\chaptername	\عنوان فصل
\char	\نويسه
\chardef	\تعريف نويسه
\CheckCommand	\برسی فرمان
\cite	\مرجع
\ClassError	\خطای طبقه
\ClassInfo	\اطلاع طبقه
\ClassWarning	\هشدار طبقه
\ClassWarningNoLine	\هشدار طبقه بی سطر
\cleaders	\انسانگر مرکزی

*Continued on next page*

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\cleardoublepage	\ادوصفه‌پاک
\clearpage	\صفحه‌پاک
\cline	\خطنایر
\closein	\بیندورودی
\closeout	\بیندخروجی
\closing	\بستن
\clubpenalty	\جریمه‌سربند
\clubsuit	\جاج
\colbotmark	\علامت‌پایین‌ستون‌اول
\colfirstmark	\علامت‌اول‌ستون‌اول
\color	\رنگ
\colorbox	\کادررنگ
\coltopmark	\علامت‌بالای‌ستون‌اول
\columncolor	\رنگ‌ستون
\columnsep	\بین‌ستون
\columnwidth	\پهنه‌ای‌ستون
\columnseprule	\خط‌بین‌ستون
\contentsline	\سطر‌فهرست
\contentsname	\عنوان‌فهرست‌مطالب
\copy	\کپی
\copyright	\حق‌تالیف
\count	\شمار
\count@	\شمار@
\countdef	\تعريف‌شمار
\cr	\سخ
\crcrcr	\اسخ‌سخ
\csname	\نام‌فرمان
\CurrentOption	\گزینه‌جاری
\dashbox	\کادر‌بینابین
\dashv	\بینابین‌ع
\@date	\تاریخ@
\date	\تاریخ
\day	\روز
\dblbotfigrule	\خط‌پایین‌شناور‌پهن
\dblbottomfraction	\نسبت‌پهن‌پایین
\dblfigrule	\خط‌بالای‌شناور‌پهن
\dblfloatpagefraction	\نسبت‌صفحه‌شناور‌پهن
\dblfloatsep	\فاصله‌بین‌شناور‌پهن
\dblfntlocatecode	\کد‌مکان‌غیره‌مانطور
\dbltextfloatsep	\فاصله‌متن‌و‌شناور‌پهن

*Continued on next page*

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\dbltopfraction	\نسبت پهن بالا
\DeclareFixedFont	\اعلان قلم ثابت
\DeclareGraphicsExtensions	\اعلان پسوند گرافیک
\DeclareGraphicsRule	\اعلان دستور گرافیک
\DeclareOldFontCommand	\اعلان فرمان قلم قدیمی
\DeclareOption	\اعلان گزینه
\DeclareRobustCommand	\اعلان فرمان قوی
\DeclareSymbolFont	\اعلان قلم علائم
\deadcycles	\دوربسته
\def	\تر
\define@key	\تعريف @ کلید
\definecolor	\تعريف رنگ
\deg	\درجہ
\delcode	\اکد ج داساز
\delimiter	\ا ج داساز
\delimiterfactor	\ضریب ج داساز
\depth	\ا گودی
\diamondsuit	\ا خشت
\dim	\ا بعاد
\dimen	\ا بعد
\dimen@	\ا بعد @
\dimen@i	\ا بعد @ یک
\dimen@ii	\ا بعد @ دو
\dimendef	\تعريف بعد
\discretionary	\تیره گذاری
\displaybreak	\اشکست نمایش
\displayindent	\تورفتگی نمایش
\displaystyle	\سیک نمایش
\displaywidth	\عرض نمایش
\divide	\ تقسیم
\documentclass	\طبقه نوشتار
\do	\کن
\dospecials	\تعویض کدها
\dot	\ نقطه
\doteq	\ نقطه مساوی
\dotfill	\ پر نقطه ا
\dots	\ نقطاط
\doublebox	\کادر دولا
\doublerulesepcolor	\رنگ فاصله دو خط جدول
\doublerulesep	\فاصله بین دو خط

*Continued on next page*

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\downarrow	\فلش‌پایین
\dp	\عمق
\dump	\تخليه
\edef	\ترجمه
\egroup	\پاگروه
\eject	\أنتهاي فاصله
\else	\اگرنه
\em	\تاکيد
\emergencystretch	\کشش لاجرم
\emph	\موکد
\empty	\@_پوچ
\emptyset	\پوچ
\end	\مجموعه‌پوچ
\endL	\پایان
\endR	\پایان چپ
\endcsname	\پایان راست
\endfirsthead	\پایان نام فرمان
\endfoot	\پایان اولین سر
\endgraf	\پایان پا
\endgroup	\ته بند
\endhead	\پایان گروه
\endinput	\پایان سر
\endlastfoot	\پایان ورودی
\enlargethispage	\پایان آخرین پا
\endline	\گسترش اين صفحه
\endlinechar	\اه سطر
\enspace	\نويسه‌تہ سطر
\enskip	\ان دورى
\eqcommand	\ان فاصله
\eqenvironment	\فرمان جانشين
\eqref	\محيط جانشين
\errhelp	\ارجاع فر
\errmessage	\كمک خطا
\errorcontextlines	\پيام خطا
\errorstopmode	\اسطربمن خطا
\escapechar	\پردازش توقف خطا
\euro	\نويسه‌ويژه
\evensidemargin	\يورو
\everycr	\حاشيه زوج
	\هرسخ

*Continued on next page*

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\everydisplay	\هرنمايش
\everyhbox	\هرکادرا
\everyjob	\هرکار
\everymath	\هررياضي
\everypar	\هربند
\everyvbox	\هرکادرو
\ExecuteOptions	\اجrai گزينه ها
\exhyphenpenalty	\جريمه اضافي تيره بندی
\expandafter	\بگستر پس از
\extracolsep	\فاصله اضافي بين ستونها
\@firstofone	\اولی ازيك
\@firstoftwo	\اولی ازدو
\f@ur	\ج@ار
\fam	\خانواده
\fancypage	\صفحه تجملی
\fbox	\کادر ربا
\fboxrule	\ضخامت کادر ربا
\fboxsep	\حاشیه کادر ربا
\fcolorbox	\کادر ربارنگ
\fi	\رگ
\figurename	\عنوان شکل
\filbreak	\پرسکن
\fill	\پر
\firstmark	\علامت اول
\flat	\پهن
\floatpagefraction	\نسبت صفحه شناور
\floatingpenalty	\جريمه شناور
\floatsep	\فاصله بين شناور
\flushbottom	\تنظيم از پايین
\fmtname	\شكلي بندی
\fmtversion	\رده شكل بندی
\fnssymbol	\نشانه
\font	\قلم
\fontdimen	\بعد قلم
\fontencoding	\رمز يقه قلم
\fontfamily	\فamil قلم
\fontname	\نام قلم
\fontseries	\شمايل قلم
\fontshape	\شكل قلم
\fontsize	\اندازه قلم

Continued on next page

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\footheight	\بلندای پایین صفحه
\footins	\درج زیرنویس
\footnote	\زیرنویس
\footnotemark	\علامت زیرنویس
\footnoterule	\خط زیرنویس
\footnotesep	\فاصله تازیرنویس
\footnotesize	\اندازه زیرنویس
\footnotetext	\متن زیرنویس
\footskip	\فاصله تا پایین صفحه
\frame	\فریم
\framebox	\کادر با خطر
\frenchspacing	\فواصل یکنواخت لاتین
\frontmatter	\مطلوب پیش
\futurelet	\بعدگذار
\@gobble	\@خور حریصانه
\@gobbletwo	\@خور حریصانه دو
\@gobblefour	\@خور حریصانه چهار
\@gtempa	\@عاقت آ
\@gtempb	\@عاقت ب
\gdef	\ترع
\GenericInfo	\الگوی اطلاع
\GenericWarning	\الگوی هشدار
\GenericError	\الگوی خطأ
\global	\عام
\globaldefs	\تعاریف عام
\glossary	\الفت نامه
\glossaryentry	\فقره فرهنگ
\goodbreak	\خوش شکن
\graphpaper	\کاغذ گراف
\guillemotleft	\گیومه چپ
\guillemotright	\گیومه راست
\guilsinglleft	\گیومه تکی چپ
\guilsinglright	\گیومه تکی راست
\halign	\ردیف ا
\hang	\برو تو
\hangafter	\بعد از سطر
\hangindent	\تورفتگی ثابت
\hbadness	\بدنمایی ا
\hbox	\کادرا
\headheight	\بلندای سر صفحه

Continued on next page

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\headsep	\فاصله از سرصفحه
\headtoname	\سر به نام
\heartsuit	\دل
\height	\بلندی
\hfil	\پرا
\hfill	\پررا
\hfilneg	\رفع پرا
\hfuzz	\پر زافقی
\hideskip	\فاصله مخفی
\hidewidth	\عرض پنهان
\hline	\خط پر
\hoffset	\حاشیه
\holdinginserts	\حفظ درج
\hrboxsep	\فاصله اگرد
\hrule	\خطا
\rulefill	\پرخطا
\hsize	\طول سطر
\hskip	\فاصله
\hspace	\فضای
\hss	\هر دوا
\ht	\ارتفاع
\huge	\بزرگ
\Huge	\بزرگ تر
\hyperlink	\ابر پیوند
\hypersetup	\بارگذاری ابر
\hypertarget	\هدف ابر
\hyphenation	\تیره بندی
\hyphenchar	\نویسه تیره
\hyphenpenalty	\جریمه تیره بندی
\@ifclassloaded	@\گر کلاس فراخوانی شده
\@ifdefinable	@\گر ترشدنی
\@ifnextchar	@\گر نویسه بعدی
\@ifpackageloaded	@\گر سبک فراخوانی شده
\@ifstar	@\گر ستاره
\@ifundefined	@\گر تعریف نشده
\if	\اگر
\if@tempswa	\اگر @ سواقت آ
\ifcase	\اگر انواع
\ifcat	\اگر رد
\ifdefined	\اگر تعریف شده

Continued on next page

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\ifdim	\اگر بعد
\ifeof	\اگرته پرونده
\iff	\اگر
\iffalse	\اگر نادرست
\IfFileExists	\اگر پرونده موجود
\ifhbox	\اگر کادرا
\ifhmode	\اگر حالت ا
\ifinner	\اگر درونی
\ifmmode	\اگر حالت ریاضی
\ifnum	\اگر عدد
\ifodd	\اگر فرد
\ifthenelse	\اگر آنگاه دیگر
\iftrue	\اگر درست
\ifvbox	\اگر کادرو
\ifvmode	\اگر حالت و
\ifvoid	\اگر تهی
\ifx	\اگر قائم
\ignorespaces	\فاصله خالی راندیده بگیر
\immediate	\فوری
\include	\شامل
\includegraphics	\درج تصویر
\includeonly	\مشمولین
\indent	\تورفتگی
\index	\درنمايه
\indexentry	\استعلام
\indexname	\عنوان نمایه
\indexspace	\فاصله رهنما
\input	\ورودی
\InputIfFileExists	\ورود پرونده گرموجود
\inputlineno	\شماره سطر ورودی
\insert	\درج
\insertpenalties	\جریمه درج
\interfootnotelinepenalty	\جریمه بین سطرهای زیرنویس
\interdisplaylinepenalty	\جریمه بین سطرهای نمایش
\interlinepenalty	\جریمه بین سطرها
\intertext	\متن داخلی
\intertextsep	\فاصله شناور در متن
\invisible	\مخفي
\itdefault	\پيش فرض اي
\itshape	\شكلي ايتاليك

Continued on next page

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\item	\فقره
\itemindent	\تورفتگی فقره
\itemsep	\فاصله فقره
\iterate	\تکرارکن
\itshape	\شکل ای
\jobname	\نام کار
\jot	\قلپ
\kern	\دوری
\kill	\الگو
\label	\برچسب
\labelenumi	\برچسب شمارش یک
\labelenumii	\برچسب شمارش دو
\labelenumiii	\برچسب شمارش سه
\labelenumiv	\برچسب شمارش چهار
\labelitemi	\برچسب فقره یک
\labelitemii	\برچسب فقره دو
\labelitemiii	\برچسب فقره سه
\labelitemiv	\برچسب فقره چهار
\labelsep	\فاصله از برچسب
\labelwidth	\پنهانی برچسب
\language	\زبان
\large	\درشت
\Large	\درشت تر
\LARGE	\درشت درشت
\lastbox	\آخرین کادر
\lastkern	\آخرین دوری
\lastpenalty	\آخرین جریمه
\lastskip	\آخرین فاصله
\LaTeX	\لاتک
\LaTeXe	\لاتک ای
\lccode	\اکدکوچک
\ldots	\نقاط خ
\leaders	\نشانگر
\leavevmode	\ترک و
\left	\چپ
\leftmargin	\حاشیه چپ
\leftmargini	\حاشیه چپ یک
\leftmarginii	\حاشیه چپ دو
\leftmarginiii	\حاشیه چپ سه
\leftmarginiv	\حاشیه چپ چهار

Continued on next page

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\leftmarginv	\حاشیه چپ پنج
\leftmarginvi	\حاشیه چپ شش
\leftmark	\علامت چپ
\leftskip	\کادر تاچپ
\leftskip	\فاصله ابتدای سطر
\let	\بگذار
\line	\سطر
\linebreak	\سطر شکن
\linepenalty	\جریمه سطر
\lineskip	\فاصله سطرها
\lineskiplimit	\حد فاصله سطر
\linespread	\کشش فاصله سطر
\linethickness	\ضخامت خط
\linewidth	\پهنه ای سطر
\listfigurename	\عنوان فهرست اشکال
\listfiles	\لیست پرونده ها
\listoffigures	\فهرست اشکال
\listoftables	\فهرست جداول
\listparindent	\تورفتگی بند لیست
\listtablename	\عنوان فهرست جداول
\LoadClass	\بارگذار طبقه
\LoadClassWithOptions	\بارگذار طبقه باگزینه
\location	\مکان
\long	\بلند
\loop	\حلقه
\looseness	\گسیختگی
\lower	\انتقال پایین
\@makeother	\@دیگر
\@m	\@زار
\@M	\@زار
\@Mi	\@زاریک
\@Mii	\@زاردو
\@Miii	\@زارسه
\@Miv	\@زارچهار
\@MM	\یس@زار
\m@ne	\من@ا
\mag	\بزرگ نمایی
\magstep	\گام
\magstephalf	\نیم گام
\mainmatter	\مطلوب اصلی

*Continued on next page*

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\makeatletter	\ات حرف
\makeatother	\ات دیگر
\makebox	\کادر بی خط
\makeglossary	\اساخت فرهنگ
\makeindex	\تهیه نمایه
\makelabel	\اساخت برچسب
\makelabels	\اساخت برچسب ها
\MakeLowercase	\اساخت حروف کوچک
\maketitle	\عنوان ساز
\MakeUppercase	\اساخت حروف بزرگ
\marginpar	\در حاشیه
\marginparpush	\فاصله دو حاشیه
\marginparsep	\فاصله تا حاشیه
\marginparwidth	\پهنه ای حاشیه
\mark	\علامت
\markboth	\علامت در دو طرف
\markright	\علامت در راست
\mathaccent	\عرب ریاضی
\mathchar	\نویسه ریاضی
\mathchardef	\تعریف نویسه ریاضی
\mathcode	\کد ریاضی
\mathrm	\ریاضی رومان
\maxdeadcycles	\حداکثر تکرار
\maxdepth	\حداکثر عمق صفحه
\maxdimen	\بعد بیشین
\mbox	\کادر بی
\mdseries	\شمایل نازک
\meaning	\معنا
\mediumseries	\نازک
\medmuskip	\فاصله متوسط ریاضی
\medskip	\پرش متوسط
\medskipamount	\مقدار پرش متوسط
\medspace	\فضای متوسط
\message	\پیام
\MessageBreak	\پیام شکن
\minrowclearance	\حداقل فاصله ردیف
\mkern	\دوری ریاضی
\month	\ماه
\moveleft	\انتقال بچپ
\moveright	\انتقال برآست

Continued on next page

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\mskip	\فاصله‌ریاضی
\m@th	\ری@ضی
\multicolumn	\چندستونی
\multiply	\ضرب
\multispan	\چندادغام
\muskip	\میوفاصله
\muskipdef	\تعریف میوفاصله
\@namedef	\@ترنام
\@nameuse	\@کاربردنام
\@ne	\یک@
\name	\نام
\natural	\طبیعی
\nearrow	\باریک
\nearrower	\باریکتر
\NeedsTeXFormat	\اشکلبندی موردنیاز
\neg	\منفی
\negmedspace	\فضای متوسط منفی
\negthickspace	\فضای ضخیم منفی
\negthinspace	\دوری کوچک منفی
\newboolean	\بولی‌نو
\newbox	\کادر جدید
\newcommand	\فرمان‌نو
\newcount	\شمارجدید
\newcounter	\شمارنده‌جدید
\newdimen	\بعد‌جدید
\newenvironment	\محیط‌نو
\newfam	\اخانواده‌جدید
\newfont	\قلم‌نو
\newhelp	\اکمک‌جدید
\newif	\اگر‌جدید
\newinsert	\درج‌جدید
\newlabel	\برچسب‌جدید
\newlength	\تعریف‌بعد‌جدید
\newline	\اسطر‌جدید
\newlinechar	\نویسه‌سطر‌جدید
\newmuskip	\میوفاصله‌جدید
\newpage	\صفحه‌جدید
\newread	\بخوان‌جدید
\newsavebox	\تعریف‌کادر‌جدید
\newskip	\فاصله‌جدید

*Continued on next page*

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\newtheorem	\قضیه جدید
\newtoks	\جزء جدید
\newwrite	\بنویس جدید
\noalign	\بی ردیف
\nobreak	\نشکن
\nobreakspace	\فاصله نشکستنی
\nocite	\ بدون سند
\noexpand	\انگستر
\nofiles	\ بدون پرونده
\noindent	\ بدون تورفتگی
\nointerlineskip	\بی فاصله سطر
\nolimits	\ بدون حد
\nolinebreak	\ سطرنشکن
\nonstopmode	\ پردازش بدون توقف
\nonfrenchspacing	\ فوacial متعارف لاتین
\nonumber	\ بدون شماره
\nopagebreak	\ صفحه نشکن
\normalbaselines	\ کرسیهای متعارف
\normalbaselineskip	\ فاصله کرسی متعارف
\normalcolor	\ رنگ عادی
\normalfont	\ قلم عادی
\normallineskip	\ فاصله سطر متعارف
\normallineskiplimit	\ احدهاصله سطر متعارف
\normalmarginpar	\ در حاشیه عادی
\normalsize	\ اندازه عادی
\notag	\ بدون اتیکت
\null	\ نول
\nullfont	\ قلم تهی
\number	\ عدد
\numberline	\ سطربعدی
\numberwithin	\ شماره مطابق
\@evenfoot	\ پایین صفحه زوج
\@evenhead	\ بالای صفحه زوج
\@oddfoot	\ پایین صفحه فرد
\@oddhead	\ بالای صفحه فرد
\@outeqntrue	\ شماره بیرون درست
\@outeqnfalset	\ شماره بیرون نادرست
\obeylines	\ سطربه سطر
\obeyspaces	\ فضاعمال
\oddsidemargin	\ حاشیه فرد

Continued on next page

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\offinterlineskip	\اسطوربی فاصله
\omit	\حذف
\@onlypreamble	\@تهادر پیش درآمد
\onecolumn	\یک ستون
\onlynotes	\نهایاد داشت ها
\onlyslides	\نهای اسلاید ها
\openin	\باز کن ورودی
\openout	\باز کن خروجی
\OptionNotUsed	\گزینه مصرف نشده
\or	\یا
\outer	\برونی
\output	\صفحه بندی
\outputpenalty	\حریمه صفحه بندی
\overfullrule	\علامت سرریز
\@preamblecmds	\@فرمان های پیش درآمد
\p@	\پو
\PackageError	\خطای سبک
\PackageInfo	\اطلاع سبک
\PackageWarning	\هشدار سبک
\PackageWarningNoLine	\هشدار سبک بی سطر
\pagebreak	\صفحه شکن
\pagecolor	\رنگ صفحه
\pagedepth	\عمق صفحه
\pagefillstretch	\کشش پر ر صفحه
\pagefillstretch	\کشش پر ر صفحه
\pagefilstretch	\کشش پر صفحه
\pagegoal	\غايت صفحه
\pagename	\نام صفحه
\pagenumbering	\شماره گذاری صفحه
\pageref	\رجوع صفحه
\pagerulewidth	\ضخامت خط صفحه
\pageshrink	\فشردگی صفحه
\pagestretch	\کشش صفحه
\pagestyle	\سبک صفحه
\pagetotal	\جمع صفحه
\paperheight	\بلندای کاغذ
\paperwidth	\پهنای کاغذ
\par	\بند
\paragraph	\پاراگراف
\parallel	\موازی

Continued on next page

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\parbox	\کادرپار
\parfillskip	\فاصله ته بند
\parindent	\تورفتگی سربند
\parsep	\فاصله بند لیست
\parshape	\شکل بند
\parskip	\فاصله بند
\part	\بخش
\partname	\عنوان بخش
\partopsep	\فاصله بالای لیست بند
\PassOptionToClass	\ارسال گزینه به کلاس
\PassOptionToPackage	\ارسال گزینه به پکیج
\path	\مسیر
\patterns	\الگوها
\pausing	\مکث
\penalty	\جریمه
\phantom	\غیب
\poptabs	\الگوی قبلی
\postdisplaypenalty	\جریمه پس نمایش
\predisplaydirection	\جهت پیش نمایش
\predisplaypenalty	\جریمه پیش نمایش
\predisplaysize	\اندازه پیش نمایش
\pretolerance	\پیش حد بدنمایی
\prevdepth	\عمق قبلی
\prevgraf	\بند قبلی
\printindex	\نمایه در اینجا
\ProcessOptions	\پردازش گزینه ها
\protect	\تامین
\providemode	\تهیه فرمان
\ProvidesClass	\آماده سازی طبقه
\ProvidesFile	\آماده سازی پرونده
\ProvidesPackage	\آماده سازی سبک
\pushtabs	\ثبت الگو
\quad	\کواد
\quad	\کوکواد
\@outputpagerestore	\@باز آبی خروج صفحه
\radical	\رادیکال
\raggedbottom	\پایین بی تنظیم
\raggedleft	\تنظيم از راست
\raggedright	\تنظيم از چپ
\raise	\انتقال بالا

Continued on next page

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\raisebox	\بالابر
\raisetag	\ترفیع اتیکت
\rangleleft	\زاویه ر
\rceil	\سقف ر
\read	\بخوان
\ref	\رجوع
\reflectbox	\کادر قرینه
\refname	\عنوان مراجع
\refstepcounter	\گام شمارنده مرجع
\relax	\راحت
\removelastskip	\رفع آخرین فاصله
\renewcommand	\فرمان ازنو
\renewenvironment	\محیط ازنو
\repeat	\ازنو
\RequirePackage	\اسیک موردنیاز
\RequirePackageWithOptions	\اسیک موردنیاز با گزینه
\resizebox	\کادر کشیده
\reversemarginpar	\در راهشیه معکوس
\rfloor	\کفر
\right	\راست
\rightmargin	\حاشیه راست
\rightmark	\علامت راست
\rightpageskip	\کادر تاراست
\rightskip	\فاصله انتهای سطر
\rmdefault	\روم من عادی
\rmfamily	\فamilی رومن
\Roman	\روم من بزرگ
\roman	\روم من کوچک
\romannumeral	\اعد در رومی
\rotatebox	\کادر چرخان
\rowcolor	\رنگ ردیف
\rule	\خط
\@secondoftwo	\@ دومی از دو
\@spaces	\فضاها
\samepage	\همین صفحه
\savebox	\مقدار کادر
\sbox	\مقکادر
\scalebox	\کادر اندازه
\scdefault	\پیش فرض تمام بزرگ
\scshape	\شکل تمام بزرگ

*Continued on next page*

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\scriptfont	\قلم <sub>توان</sub>
\scriptscriptfont	\قلم <sub>توان توان</sub>
\scriptscriptstyle	\سبک <sub>نه نوشته نوشته</sub>
\scriptsize	\اندازه <sub>پانویس</sub>
\scriptstyle	\سبک <sub>نه نوشته</sub>
\scrollmode	\پردازش <sub>گذرنی</sub>
\section	\قسمت
\secdef	\تعريف <sub>قسمت</sub>
\see	\بینید
\seealso	\نیز <sub>بینید</sub>
\seename	\نام <sub>بینید</sub>
\selectfont	\قلم <sub>بردار</sub>
\setboolean	\تنظیم <sub>بولی</sub>
\setbox	\در <sub>کادر</sub>
\setcounter	\مقدار <sub>شمارنده</sub>
\setkeys	\مقدار <sub>کلیدها</sub>
\setlength	\مقدار <sub>بعد</sub>
\setminus	\تنظيم <sub>منها</sub>
\SetSymbolFont	\تعريف <sub>قلم علائم</sub>
\settodepth	\تنظيم <sub>به عمق</sub>
\settoheight	\تنظيم <sub>به ارتفاع</sub>
\settowidth	\مقدار <sub>بعد به اندازه</sub>
\sfcode	\اکد <sub>ضریب فاصله</sub>
\sfdefault	\پیش <sub>فرض سف</sub>
\sffamily	\فamilی <sub>سن سریف</sub>
\shadowbox	\کادر <sub>رسایه دار</sub>
\sharp	\تیر
\shipout	\بفرست
\shortstack	\پشته <sub>کوتاه</sub>
\show	\نمایش <sub>بده</sub>
\showbox	\نمایش <sub>بده کادر</sub>
\showboxbreadth	\میزان <sub>نمایش کادر</sub>
\showboxdepth	\عمق <sub>نمایش کادر</sub>
\showlists	\نمایش <sub>بده لیستها</sub>
\showthe	\نمایش <sub>بده محتوا</sub>
\simplefontmode	\حالت <sub>ساده قلم</sub>
\sixt@n	@\شانزد
\skewchar	\نویسه <sub>اریب</sub>
\skip	\فاصله
\skip@	@\فاصله

Continued on next page

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\skipdef	\تعريف فاصله
\sl	\خوابیده
\sldefault	\پیش فرض خو
\slshape	\شكل خوابیده
\sloppy	\راحت چین
\slshape	\شمایل خو
\small	\کوچک
\smallskip	\پرش کوتاه
\smallskipamount	\مقدار پرش کوتاه
\smash	\کوب
\smile	\الخند
\snglfntlocatecode	\اگدامان همانطور
\space	\فضا
\spacefactor	\ضریب فاصله
\spaceskip	\فاصله کلمات
\spadesuit	\پیک
\span	\ادغام
\special	\ویرژ
\splitmaxdepth	\حد اکثر عمق ستون
\splittopskip	\فاصله بالای ستون
\star	\ستاره
\stepcounter	\گام شمارنده
\stretch	\کشی
\string	\رشته
\strut	\شمع
\strutbox	\کادر شمع
\subitem	\زیربند
\subparagraph	\زیرپاراگراف
\subsection	\زیرقسمت
\substack	\زیرپشتہ
\subsubitem	\زیرزیربند
\subsubsection	\زیرزیرقسمت
\subset	\زیرمجموعه
\subsepeq	\زیرمجموعه مس
\supereject	\منتهای صفحه
\suppressfloats	\حذف مکان شناور
\@tempa	\@موقت آ
\@tempb	\@موقت ب
\@tempc	\@موقت پ
\@tempd	\@موقت ت

Continued on next page

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\@tempe	موقت@\ کادرقت آ
\@tempboxa	@\
\@tempcnta	شماقت آ@\ شماقت ب
\@tempcntb	@\
\@tempdima	بعدقت آ@\ بعدقت ب
\@tempdimb	@\
\@tempdimc	بعدقت پ@\ فاقت آ
\@tempskipa	@\
\@tempskipb	فاقت ب@\ فاقت ب
\@tempswafalse	@\
\@tempswatrue	سواقت آنادرست@\ سواقت آدرست
\@temptokena	@\ جزقت آ
\@thefnmark	انگ زیرنویس@\ سومی ازسه
\@thirdofthree	@\
\tabbingsep	فاصله جاگذاری
\tabcolsep	فاصله بین ستونها
\tableofcontents	فهرست مطالب
\tablename	عنوان جدول
\tabskip	فاصله ستونها
\tabularnewline	ته سطر جدول
\tag	ایکت
\telephone	تلفن
\TeX	اتک
\text	متن
\textbullet	گلوله متنی
\textfont	اقلم متن
\textemdash	ام دش متنی
\textendash	ان دش متنی
\textexclamdown	تعجب وارونه متنی
\textperiodcentered	نقطه وسط متنی
\textquestiondown	سؤال وارونه متنی
\textquotedblleft	نقل چپ متنی دول
\textquotedblright	نقل راست متنی دول
\textquoteright	نقل متنی چپ
\textvisiblespace	نقل متنی راست
\textbackslash	فضای نمایان متنی
\textbar	شکافت پشت متنی
\textgreater	امیله متنی
\textless	بزرگ تر متنی
	کمتر متنی\

Continued on next page

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\textbf	\متن سیاه
\textcircled	\مدور متنی
\textcolor	\رنگ متن
\textcompwordmark	\انسان کلمه مرکب متن
\textfloatsep	\فاصله متن و شناور
\textfraction	\نسبت متن
\textheight	\بلندای متن
\textindent	\متن تورفتہ
\textit	\متن ایتالیک
\textmd	\متن نازک
\textnormal	\متن نرمال
\textregistered	\ثبتی متنی
\textrm	\متن رومان
\textsc	\متن تمام بزرگ
\textsf	\متن سن سریف
\textsl	\متن خوابیده
\textstyle	\سیک متنی
\textsuperscript	\بالانویس متنی
\texttrademark	\علامت تجاری متنی
\texttt	\متن تایپ
\textup	\متن ایستاده
\textwidth	\پهناز متن
\thanks	\ازیرنویس عنوان
\the	\محتوی
\thempfn	\اين زيرنویس
\thicklines	\خط هاضخیم
\thickmuskip	\فاصله زياد ریاضی
\thinmuskip	\فاصله کم ریاضی
\thickspace	\فضاضخیم
\thinlines	\خط هانازک
\thinspace	\دوری کوچک
\thisfancypage	\اين صفحه تجملی
\thispagestyle	\سیک این صفحه
\thr@@	@\سه
\tilde	\مد
\tiny	\ظریف
\time	\زمان
\times	\ضرب در
\title	\عنوان
\to	\به

Continued on next page

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\today	\امروز
\toks	\جزء
\toksdef	\تعريف جزء
\tolerance	\حدبدنمايی
\top	\بالا
\topfigrule	\خط بالاي شناور
\topfraction	\نسبت بالا
\topmargin	\حاشيه بالا
\topmark	\علامت بالا
\toppageskip	\کادر تابلا
\topsep	\فاصله بالاي ليست
\topskip	\فاصله بالا
\totalheight	\بلنداي کل
\tracingall	\ردگيري کل
\tracingcommands	\ردگيري فرامين
\tracinglostchars	\ردگيري حروف
\tracingmacros	\ردگيري ماکروها
\tracingonline	\ردگيري نمایشی
\tracingoutput	\ردگيري صفحه بندی
\tracingpages	\ردگيري صفحات
\tracingparagraphs	\ردگيري بندها
\tracingrestores	\ردگيري بازگردنی
\tracingstats	\ردگيري آمارها
\triangle	\مثلث
\ttdefault	\پيش فرض تاپ
\ttfamily	\فamil تاپ
\tw@	@\دو
\twocolumn	\دوستون
\typein	\درنويس
\typeout	\برنويس
\uccode	\كذبزرك
\uchyph	\تيره بندی بزرگ
\undefined	\تعريف نشده
\underline	\ازيرخط
\unhbox	\بي کادرا
\unhcopy	\بي کپي
\unitlength	\واحد طول
\unkern	\برگشت دورى
\unpenalty	\برگشت جريمہ
\unskip	\برگشت فاصله

*Continued on next page*

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\unvbox	\بی کارو
\unvcopy	\بی کپی و
\updefault	\پیش فرض ایستاده
\upshape	\شکل ایستاده
\usebox	\از کار
\usecounter	\با شمارشگر
\usefont	\اگزینش قلم
\usepackage	\سیک لازم
\@vobeyspaces	\فضاهای فعال
\@void	\@ تهی
\vadjust	\تنظیم و
\valign	\ردیف و
\value	\محتوای شمارنده
\vbadness	\بد نمایی و
\vbox	\کارو
\vcenter	\کار رو سط
\verb	\همانطور
\vfil	\پرو
\vfill	\پر رو
\vfilneg	\رفع پرو
\vfuzz	\پر زعمودی
\visible	\نمایان
\vline	\خط عمود
\voffset	\حاشیه و
\voidb@x	\ک @ در تهی
\vpageref	\رجوع صفحه ع
\vrboxsep	\فاصله و گرد
\vref	\رجوع
\rule	\خط و
\vsiz	\طول صفحه
\vskip	\فاصله و
\vspace	\فضای و
\vsplit	\شکست و
\vss	\هر دو و
\vtop	\کار گردد
\wd	\عرض
\whiledo	\مادام بکن
\widehat	\کلاه پهن
\widetilde	\مد پهن
\widowpenalty	\جریمه تهند

Continued on next page

Command in TeX or L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Command
\width	\پهنا
\wlog	\درکارنامه
\write	\بنویس
\@xobeysp	\فضای لاتین
\@xxxii	@\سی@دو
\xdef	\ترگ
\xleaders	\نشانگرگسترشی
\xspaceskip	\فاصله اضافی کلمات
\year	\سال
\z@	\فر
\z@skip	\فرافصله

Table 2: The Equivalent XePersian Commands

Command in XePersian	Equivalent Persian Command
\autofootnoterule	\خط زیرنویس خودکار
\AutoMathsDigits	\اعداد فرمولهای خودکار
\DefaultMathsDigits	\اعداد فرمولهای لاتین
\deflatinfont	\تعریف قلم لاتین
\defpersianfont	\تعریف قلم پارسی
\hboxL	\کادر اچپ
\hboxR	\کادر است
\keyval@eq@alias@key	\معادل @ کلید
\Latincite	\مرجع لاتین
\latinfont	\قلم لاتین
\latintoday	\امروز لاتین
\leftfootnoterule	\خط زیرنویس چپ
\lr	\امتن لاتین
\LRE	\چپ براست
\LTRdblcol	\دوسنونی چپ
\LTRfootnote	\پانویس
\LTRfootnotetext	\امتن پانویس
\LTRthanks	\پانویس عنوان
\persianday	\روز پارسی
\persianfont	\قلم پارسی
\PersianMathsDigits	\اعداد فرمولهای پارسی
\persianmonth	\ماه پارسی
\persianyear	\سال پارسی
\plq	\علامت چپ نقل قول پارسی
\prq	\علامت راست نقل قول پارسی

*Continued on next page*

Command in XePersian	Equivalent Persian Command
\rightfootnoterule	\خط‌زیرنویس‌راست
\rl	\متن‌پارسی
\RLE	\راست‌بچپ
\RTLdblcol	\دوسنونی‌راست
\RTLfootnote	\پانوشت
\RTLfootnotetext	\متن‌پانوشت
\RTLthanks	\پانوشت‌عنوان
\@SepMark	\@علامت‌بین
\SepMark	\علامت‌بین
\setdefaultbibitems	\بگذارم‌رجوعات‌عادی
\setdefaultmarginpar	\بگذارد‌رحاشیه‌عادی
\setdigitfont	\اگزینش‌قلم‌اعداد‌فرمولها
\setfootnoteLR	\بگذارزیرنویس‌چپ
\setfootnoteRL	\بگذارزیرنویس‌راست
\setlatintextfont	\اگزینش‌قلم‌لاتین‌متن
\setLTR	\بگذارم‌تن‌چپ
\setLTRbibitems	\بگذارم‌رجوعات‌چپ
\setLTRmarginpar	\بگذارد‌رحاشیه‌چپ
\setRTL	\بگذارم‌تن‌راست
\setRTLbibitems	\بگذارم‌رجوعات‌راست
\setRTLmarginpar	\بگذارد‌رحاشیه‌راست
\setttextfont	\اگزینش‌قلم‌متن
\textwidthfootnoterule	\خط‌زیرنویس‌پنهانی‌متن
\twocolumnstableofcontents	\فهرست‌مطالب‌دوستونی
\unsetfootnoteRL	\انگذارزیرنویس‌راست
\unsetLTR	\انگذارم‌تن‌چپ
\unsetRTL	\انگذارم‌تن‌راست
\vboxL	\کادر‌رواز‌چپ
\vboxR	\کادر‌رواز‌راست
\XeLaTeX	\ازی‌لاتک
\XePersian	\ازی‌پرشین
\xepersianversion	\اگونه‌زی‌پرشین
\xepersiandate	\تاریخ‌اگونه‌زی‌پرشین
\XeTeX	\ازی‌تک

Table 3: The Equivalent L<sup>A</sup>T<sub>E</sub>X Environments

Environment in L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Environment
abstract	چکیده
appendix	پیوست
array	آرایه
center	وسط‌چین

*Continued on next page*

**Environment in L<sup>A</sup>T<sub>E</sub>X    Equivalent Persian Environment**

description	توضیح
displaymath	ریاضی نمایشی
document	نوشتار
enumerate	شمارش
figure	شکل
figure*	* شکل
filecontents	محتوای پرونده
filecontents*	* محتوای پرونده*
flushleft	چپ چین
flushright	راست چین
itemize	فقرات
letter	نامه
list	لیست
longtable	جدول دراز
lrbox	کادر رج
math	ریاضی
matrix	ماتریس
minipage	صفحه کوچک
multicols	چند ستونی ها
multiline	چند خطی
note	یادداشت
overlay	ابداشت
picture	تصویر
quotation	اقتباس
quote	نقل
slide	اسلاید
sloppypar	پار نامرتب
split	شکافتن
subarray	زیر آرایه
tabbing	جاگذاری
table	لوح
table*	لوح*
tabular	جدول
tabular*	جدول*
thebibliography	مراجع
theindex	محتوای نمایه
titlepage	صفحه عنوان
trivlist	لیست بدروی
verbatim	همانطور که هست
verbatim*	* همانطور که هست

*Continued on next page*

Environment in L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian Environment
verse	شعر

Table 4: The Equivalent XePersian Environments

Environment in XePersian	Equivalent Persian Environment
latin	لاتین
LTR	متن چپ
LTRitems	دسته‌بندی چپ
persian	پارسی
RTL	متن راست
RTLitems	دسته‌بندی راست

**Localisation of position arguments.** Some environments like `tabular` and some commands like `\parbox` have an argument which specifies the position. Table [Table 5](#) shows their localisations.

Table 5: The Equivalent L<sup>A</sup>T<sub>E</sub>X position arguments

Position argument in L <sup>A</sup> T <sub>E</sub> X	Equivalent Persian position argument
b	ز
c	و
C	س
h	ا
H	آ
J	ت
l	ج
L	ف
m	م
p	پ
P	ص
r	ر
R	ا
s	ک
t	ب

☞ There are two ps in [Table 5](#), first p and its Persian equivalent پ stand for paragraph (used in `tabular` and similar environments) and the second p and its Persian equivalent ص stand for page (used in float-like environments).

#### 2.4.7 Localizations of the keys and key values of `graphicx` package

The equivalent Persian keys and key values of `graphicx` package is shown in [Table 6](#) and [Table 7](#) respectively.

Table 6: Persian Equivalent keys of `graphicx` package

Original Key	Equivalent Persian Key
draft	پیش‌نویس
origin	مبدأ
clip	بی‌اضافه
keepaspectratio	حفظ تناسب
natwidth	پهناهی طبیعی
natheight	بلندای طبیعی
bb	مختصات
viewport	محدوده نمایش
trim	حذف اطراف
angle	زاویه
width	پهنا
height	بلند
totalheight	بلندای کل
scale	ضریب
type	نوع
ext	پسوند
read	خواندنی
command	فرمان
x	طول
y	عرض
units	واحد

Table 7: Persian Equivalent key values of graphicx package

Original Key value	Equivalent Persian Key value
b	ز
B	ک
false	نادرست
l	ج
r	ر
t	ب
true	درست

#### 2.4.8 Localizations of font features and font feature options

The equivalent Persian font features and font feature options is shown in [Table 8](#) and [Table 9](#) respectively.

Table 8: Persian Equivalent font features

Original font feature	Equivalent Persian font feature
ExternalLocation	مکان خارجی
ExternalLocation	مسیر
Renderer	تحویل‌دهنده
BoldFont	قلم سیاه

*Continued on next page*

Original font feature	Equivalent Persian font feature
Language	زبان
Script	خط
UprightFont	قلم عمودی
ItalicFont	قلم ایتالیک
BoldItalicFont	قلم ایتالیک سیاه
SlantedFont	قلم خوابیده
BoldSlantedFont	قلم خوابیده سیاه
SmallCapsFont	قلم کلاه کوچک
UprightFeatures	ویرگی های قلم عمودی
BoldFeatures	ویرگی های قلم سیاه
ItalicFeatures	ویرگی های قلم ایتالیک
BoldItalicFeatures	ویرگی های قلم ایتالیک سیاه
SlantedFeatures	ویرگی های قلم خوابیده
BoldSlantedFeatures	ویرگی های قلم خوابیده سیاه
SmallCapsFeatures	ویرگی های قلم کلاه کوچک
SizeFeatures	ویرگی های اندازه
Scale	ضریب
WordSpace	فضای کلمه
PunctuationSpace	فضای نقطه گذاری
FontAdjustment	تنظیم قلم
LetterSpace	فضای حرف
HyphenChar	نویسه تیره
Color	رنگ
Opacity	کدری
Mapping	نگاشت
Weight	سنگینی
Width	پهنا
OpticalSize	اندازه چشمی
FakeSlant	خوابیده تقلیبی
FakeStretch	کشش تقلیبی
FakeBold	سیاه تقلیبی
AutoFakeSlant	خوابیده تقلیبی خودکار
AutoFakeBold	سیاه تقلیبی خودکار
Ligatures	دویاچند حرف متصل به هم
Alternate	متناوب
Variant	گوناگون
Variant	مجموعه سبکی
CharacterVariant	گوناگونی نویسه
Style	سبک
Annotation	بادداشت

*Continued on next page*

Original font feature	Equivalent Persian font feature
RawFeature	ویرگی‌های کال
CharacterWidth	پهنای نویسه
Numbers	ارقام
Contextuals	متخی
Diacritics	تفکیک کننده‌ها
Letters	حروف
Kerning	دوری
VerticalPosition	موقعیت عمودی
Fractions	کسر

Table 9: Persian Equivalent font feature options

font feature	font feature option	Persian font feature option
Language	Default	بیش‌فرض
Language	Parsi	پارسی
Script	Parsi	پارسی
Script	Latin	لاتین
Style	MathScript	اسکریپت ریاضی
Style	MathScriptScript	اسکریپت اسکریپت ریاضی

## 2.5 A Sample Input TeX File

```

1 \documentclass{article}
2 \usepackage{xepersian}
3 \settextfont[XB Niloofar]
4 \title{یک سند نمونه}
5 \author{نام نویسنده}
6 \begin{document}
7 \maketitle
8 \tableofcontents
9 \part{عنوان بخش}
10 ...
11 \section{عنوان قسمت}
12 ...
13 \subsection{عنوان زیرقسمت}
14 ...
15 \subsubsection{عنوان زیر زیرقسمت}
16 ...
17 \end{document}

```

## 2.6 Font Commands

### 2.6.1 Basic Font Commands

```
\settextfont [Options] {\fontname}
\setlatintextfont [Options] {\fontname}
\setdigitfont [Options] {\fontname}
\setmathsf digitfont [Options] {\fontname}
\setmathtt digitfont [Options] {\fontname}
```

- ☞ Options in any font command in this documentation are anything that `fontspec` package provides as the option of loading fonts, except `Script` and `Mapping`.
- ☞ `\settextfont` will choose the default font for Persian texts of your document. If you do not use this command at all, the `Persian Modern`<sup>2</sup> font will be used for Persian texts of your document.
- ☞ `\setlatintextfont` will choose the font for Latin texts of your document. If you do not use this command at all, the default `TEX` font (fonts used in this documentation) will be used for Latin texts of your document.
- ☞ `\setdigitfont` will choose the Persian font for digits in math mode. By default, digits in math mode will appear in Persian form and if you do not use this command at all, the `Persian Modern` font for digits in math mode will be used.
- ☞ `\setmathsf digitfont` will choose the Persian font for digits in math mode inside `\mathsf`. By using this command, digits in math mode inside `\mathsf` will appear in Persian form and if you do not use this command at all, you will get default `TEX` font for digits in math mode inside `\mathsf` and digits appear in their original form (Western).
- ☞ `\setmathtt digitfont` will choose the Persian font for digits in math mode inside `\mathtt`. By using this command, digits in math mode inside `\mathtt` will appear in Persian form and if you do not use this command at all, you will get default `TEX` font for digits in math mode inside `\mathtt` and digits appear in their original form (Western).

### 2.6.2 Defining Extra Persian and Latin Fonts

```
\defpersianfont\CS [Options] {\fontname}
\deflatinfont\CS [Options] {\fontname}
```

- ☞ With `\defpersianfont`, you can define extra Persian fonts.

<sup>2</sup>You do not need to install `Persian Modern` fonts since they are already included in your TeX distribution.

```
\defpersianfont\Nastaliq[Scale=1]{IranNastaliq}
```

In this example, we define \Nastaliq to stand for IranNastaliq font.

- ☞ With \deflatinfont, you can define extra Latin fonts.

```
\deflatinfont\junicode[Scale=1]{Junicode}
```

In this example, we define \junicode to stand for Junicode font.

### 2.6.3 Choosing Persian Sans Font

```
\setpersiansansfont [Options] {\<font name>}  
\persiansffamily \textpersiansf{\<text>}
```

### 2.6.4 Choosing Persian Mono Font

```
\setpersianmonofont [Options] {\<font name>}  
\persianttfamily \textpersiantt{\<text>}
```

### 2.6.5 Choosing Persian Iranic Font

```
\setiranicfont [Options] {\<font name>}  
\iranicfamily \textiranic{\<text>}
```

### 2.6.6 Choosing Persian Navar Font

```
\setnavarfont [Options] {\<font name>}  
\navarfamilly \textnavar{\<text>}
```

### 2.6.7 Choosing Persian Pook Font

```
\setpookfont [Options] {\<font name>}  
\pookfamily \textpook{\<text>}
```

### 2.6.8 Choosing Persian Sayeh Font

```
\setsayehfont [Options] {\<font name>}  
\sayehfamily \textsayeh{\<text>}
```

### 2.6.9 Choosing Latin Sans Font

```
\setlatinsansfont [Options] {\<font name>}  
\sffamily \textsf{\<text>}
```

### 2.6.10 Choosing Latin Mono Font

```
\setlatinmonofont [Options] {\<font name>}  
\ttfamily \texttt{\<text>}
```

## 3 Latin and Persian Environment

```
\begin{latin} <text> \end{latin}  
\begin{persian} <text> \end{persian}
```

☞ latin environment both changes direction of the paragraphs to LTR and font to Latin font.

 `\begin{persian}` environment both changes direction of the Paragraphs to RTL and font to Persian font.

### 3.1 `latinitems` and `parsiitems` environments

```
\begin{latinitems}
  \item <text>
  ...
\end{latinitems}
```

 `latinitems` environment is similar to `LTRItems` environment but changes the font to Latin font.

```
\begin{parsiitems}
  \item <text>
  ...
\end{parsiitems}
```

 `parsiitems` environment is similar to `RTLItems` environment but changes the font to Persian font.

### 3.2 Short Latin and Persian Texts

```
\lr{<text>} \rl{<text>}
```

 With `\lr` command, you can typeset short LTR texts.

 With `\rl` command, you can typeset short RTL texts.

### 3.3 Miscellaneous Commands

```
\persianyear \persianmonth \persianday
\today \latintoday \twocolumnstableofcontents \XePersian
\plq \prq
```

 `\persianyear` is Persian equivalent of `\year`.

 `\persianmonth` is Persian equivalent of `\month`.

 `\persianday` is Persian equivalent of `\day`.

 `\today` typesets current Persian date and `\latintoday` typesets current Latin date.

 `\twocolumnstableofcontents` typesets table of contents in two columns. This requires that you have loaded `multicol` package before `XePersian` package, otherwise an error will be issued.

- ☞ \XePersian typesets XePersian's logo.
- ☞ \plq and \prq typeset Persian left quote and Persian right quote respectively.

### 3.4 New Commands

\Latincite

- ☞ \Latincite functions exactly like \cite command with only one difference; the reference to biblabel item is printed in Latin font in the text.

### 3.5 Additional Counters

XePersian defines several additional counters to what already L<sup>A</sup>T<sub>E</sub>X offers. These counters are **harfi**, **adadi**, and **tartibi**. In addition, the following commands are also provided:

\harfinumeral{\langle integer\rangle} \adadinumeral{\langle integer\rangle} \tartibinumeral{\langle integer\rangle}

- ☞ The range of **harfi** counter is integers between 1 and 32 (number of the Persian alphabets) and **adadi** and **tartibi** counters, are integers between 0 and 999,999,999.
- ☞ For **harfi** counter, if you give an integer bigger than 32 or a negative integer (if you give integer 0, it returns nothing), then you get error and for **adadi** and **tartibi** counters, if you give an integer bigger than 999,999,999, then you get an error message.
- ☞ For **adadi** and **tartibi** counters, if you give an integer less than 0 (a negative integer), then **adadi** and **tartibi** counters return **adadi** and **tartibi** form of the integer 0, respectively.
- ☞ \harfinumeral returns the **harfi** form of  $\langle integer \rangle$ , where  $1 \leq \langle integer \rangle \leq 32$  and \adadinumeral, and \tartibinumeral return **adadi**, and **tartibi** form of  $\langle integer \rangle$  respectively, where  $0 \leq \langle integer \rangle \leq 999,999,999$ .

### 3.6 Things To Know About \setdigitfont, \setmathsf digitfont, and \setmathtt digitfont

\DefaultMathsDigits \PersianMathsDigits \AutoMathsDigits

- ☞ As we discussed before, \setdigitfont will choose the Persian font for digits in math mode. By default, digits in math mode will appear in Persian form and if you do not use this command at all, the Persian Modern font for digits in math mode will be used.

☞ As we discussed before, `\setmathsf digitfont`, and `\setmathtt digitfont` will choose the Persian sans serif and typewriter fonts for digits in math mode. By using this command, digits in math mode will appear in Persian form and if you do not use this command at all, you will get default TeX font for digits in math mode and digits appear in their original form (Western).

If you use `\setdigitfont`, `\setmathsf digitfont`, and `\setmathtt digitfont`, then you should know that:

- ☞ By default, `\AutoMathsDigits` is active, which means that in Persian mode, you get Persian digits in math mode and in Latin mode, you get TeX's default font and digits in math mode.
- ☞ If you use `\PersianMathsDigits` anywhere, you will overwrite XePersian's default behaviour and you will always get Persian digits in math mode.
- ☞ If you use `\DefaultMathsDigits` anywhere, again you will overwrite XePersian's default behaviour and you will always get TeX's default font and digits in math mode.

## 4 New Conditionals

### 4.1 Shell escape (or write18) conditional

```
\ifwritexviii
    <material when Shell escape (or write18) is enabled>
\else
    <material when Shell escape (or write18) is not enabled>
\fi
```

## 5 Bilingual Captions

XePersian sets caption bilingually. This means if you are in RTL mode, you get Persian caption and if you are in LTR mode, you get English caption.

### 5.1 Support For Various Packages

In addition to what `bidi` package supports, XePersian also support a few packages. This support is more about language aspect rather than directionality. These packages are `algorithmic`, `algorithm`, `enumerate`, and `backref` packages.

#### 5.1.1 Things You Should Know about Support For `enumerate` Package

The `enumerate` package gives the `enumerate` environment an optional argument which determines the style in which the counter is printed.

An occurrence of one of the tokens `A`, `a`, `I`, `i`, or `1` produces the value of the counter printed with (respectively) `\Alph`, `\alph`, `\Roman`, `\roman` or `\arabic`.

In addition with the extra support that XePersian provides, an occurrence of one of the tokens `l`, `س`, or `ت` produces the value of the counter printed with (respectively) `\harfi`, `\adadi`, or `\tartibi`.

These letters may be surrounded by any strings involving any other  $\text{\TeX}$  expressions, however the tokens `A`, `a`, `I`, `i`, `1`, `l`, `س`, `ت` must be inside a `{}` group if they are not to be taken as special.

To see an Example, please look at `enumerate` package documentation.

## 5.2 Index Generation

For generating index, you are advised to use `xindy` program, any other program such as `makeindex` is not recommended.

## 5.3 Converting Your Farsi $\text{\TeX}$ Files To XePersian or Unicode

There is a python program written by Mostafa Vahedi that enables you to convert Farsi $\text{\TeX}$  files to XePersian or unicode. This program can be found in `doc` folder with the name `ftxe-0.12.py`. To convert your Farsi $\text{\TeX}$  files to XePersian, put `ftxe-0.12.py` in the same directory that your Farsi $\text{\TeX}$  file is, and then open a terminal/command prompt and do the following:

```
python ftxe-0.12.py file.ftx file.tex
```

This will convert your `file.ftx` (Farsi $\text{\TeX}$  file) to `file.tex` (XePersian file).

The general syntax of using the python script is as follow:

```
python ftxe-0.12.py [-r] [-s] [-x] [-u] input-filename1 input-filename2
```

Where

`-r` (DEFAULT) recursively consider files included in the given files

`-s` do not recursively consider files

`-x` (DEFAULT) insert XePersian related commands

`-u` only convert to unicode (and not to XePersian)

Please note that the python script will not work with versions of python later than 2.6. So you are encouraged to use version 2.6 of python to benefit from this python script.

## 6 Extra Packages And Classes

### 6.1 Magazine Typesetting

#### 6.1.1 Introduction

`xepersian-magazine` class allows you to create magazines, newspapers and any other types of papers. The output document has a front page and as many inner pages as desired. Articles appear one after another, telling the type, number of columns, heading, subheading, images, author and so forth. It is possible to change the aspect of (almost) everything therefore it is highly customisable. Commands to add different titles, headings and footers are also provided.

#### 6.1.2 Usage

To create<sup>3</sup> a magazine just load the class as usual<sup>4</sup>, with

```
\documentclass [Options] {xepersian-magazine}
```

at the beginning of your source file. The class options are described in [subsubsection 6.1.12](#).

From this point it is possible to include packages and renew class commands described in [subsubsection 6.1.9](#).

#### 6.1.3 Front Page

As every magazine, `xepersian-magazine` has its own front page. It includes main headings, an index, the magazine logo and other useful information. This environment should be the first you use within `xepersian-magazine` class but it is not mandatory.

```
\firstimage \firstarticle
```

The first two commands you can use inside the `frontpage` environment are `\firstimage` and `\firstarticle` which include, respectively, the main image and the main heading in the front page. The first one takes two arguments `(image)` and `(description)`. Notice that second argument is optional and it declares the image caption; `(image)` defines the relative path to the image. In order to include the first piece of article use

---

<sup>3</sup>For a sample file, please look at `magazine-sample.tex` in the `doc` folder

<sup>4</sup>You also need to load `graphicx`, `xunicode` and `xepersian` packages respectively, after loading the document class and choose fonts for the main text, Latin text and digits in maths formulas. For more detail see [section 2](#) of the documentation.

```
\firstarticle{\langle title\rangle}{\langle opening\rangle}{\langle time\rangle}
```

first two arguments are mandatory and represent heading and the opening paragraph. Last argument is optional (you can leave it blank) and indicates the time when article happened.

```
\secondarticle
```

The second piece of article is included using the command `\secondarticle` just as the first article. The main difference are that this second piece has two more arguments and it does not include an image.

```
\secondarticle{\langle title\rangle}{\langle subtitle\rangle}{\langle opening\rangle}{\langle pagesof\rangle}{\langle time\rangle}
```

The new arguments `\langle subtitle\rangle` and `\langle pagesof\rangle` define a subtitle and the name of the section for this piece of article.

```
\thirdarticle
```

The third piece of article is the last one in the `xepersian-magazine` front page. It works like the `\secondarticle`.

```
\thirdarticle{\langle title\rangle}{\langle subtitle\rangle}{\langle opening\rangle}{\langle pagesof\rangle}{\langle time\rangle}
```

The arguments meaning is the same as `\secondarticle` command.

The front page includes three information blocks besides the news: `indexblock` which contains the index, `authorblock` which includes information about the author and a `weatherblock` containing a weather forecast. All these three environments are mostly a frame in the front page therefore they can be redefined to fit your personal wishes but I kept them to give an example and to respec the original `xepersian-magazine` format.

```
\indexitem
```

The `indexblock` environment contains a manually editted index of `xepersian-magazine`. It takes one optional argument `\langle title\rangle` and places a title over the index block. To add entries inside the index just type

```
\indexitem{\langle title\rangle}{\langle reference\rangle}
```

inside the environment. The `\langle title\rangle` is the index entry text and the `\langle reference\rangle` points to a article inside `xepersian-magazine`. It will be more clear when you read [subsubsection 6.1.4](#). In order to get a correct output, it is necessary to leave a blank line between index items.

The `authorblock` environment can include whatever you would like. I called it `authorblock` because I think it is nice to include some author reference in the

front page: who you are, why are you doing this... This environment creates a frame box in the bottom right corner of the front page with your own logo at the top.

```
\weatheritem
```

Finally, the **weatherblock** lets you include a weather forecast. It takes one optional argument  $\langle title \rangle$  that places a title over the weather block. It can fit up to three weather icons with maximum and minimum temperatures, description and name. To add each of the weather entries type the following

```
\weatheritem{\langle image \rangle}{\langle day-name \rangle}{\langle max \rangle}{\langle min \rangle}{\langle short-des \rangle}
```

The first argument includes the path to the weather icon (i.e. sunny or rainy),  $\langle day-name \rangle$  like Monday,  $\langle max \rangle$  and  $\langle min \rangle$  are the highest and lowest day temperatures and  $\langle short-des \rangle$  is a brief description of the weather condition: partly cloudy, sunny and windy ...

#### 6.1.4 Inside

Once we have created the front page we should include all articles inside our magazine. **xepersian-magazine** arranges all articles one after each other, expanding headings all over the page and splitting the article text in the number of columns we wish. There are three different environments to define a piece of article: the **article** environment described in [subsubsection 6.1.5](#), the **editorial** environment [subsubsection 6.1.6](#) for opinion articles and the **shortarticle** environment explained in [subsubsection 6.1.7](#).

#### 6.1.5 The article environment

The main environment to include a piece of article is called **article**. It takes four arguments that set up the headings and structure of the article.

```
\begin{article}{\langle num-of-columns \rangle}{\langle title \rangle}{\langle subtitle \rangle}{\langle pagesof \rangle}{\langle label \rangle}
...{\langle text \rangle}...
\end{article}
```

The first argument  $\langle num-of-columns \rangle$  sets the number of columns the article will be divided whereas  $\langle label \rangle$  is used when pointing an article from the index in the front page. The rest of the arguments are easy to understand.

Inside the **article** environment, besides the main text of the article, it is possible to include additional information using several class commands.

```
\authorandplace \timestamp
```

The `\authorandplace{<author>}{<place>}` inserts the name of the editor and the place where the article happened in the way many magazines do. Another useful command is `\timestamp{<time>}` which includes the time and a separator just before the text. These two commands should be used before the text because they type the text as the same place they are executed.

```
\image
```

To include images within the text of an article, `xepersian-magazine` provides an `\image` command. Since `multicol` package does not provide any float support for its `multicols` environment, I created a macro that includes an image only if that is possible, calculating if there is enough space for the image. It is not the best solution but it works quite well and I could not find a better one. To include an image use the command and its two arguments: the relative path to the image and a short description.

```
\image{<image>}{<description>}
```

```
\columntitle \expandedtitle
```

Within the text of the article, it is possible to add column and expanded titles. The main difference between them is that the first one keeps inside the width of an article column whereas the second expands all over the width of the page, breaking all the columns. Their use is analogous, as follows

```
\columntitle{<type>}{<text>}\expandedtitle{<type>}{<text>}
```

These two commands use `fancybox` package features. That is why there are five different types of titles which correspond mainly with fancybox ones: `shadowbox`, `doublebox`, `ovalbox`, `Ovalbox` and `lines`.

### 6.1.6 The editorial environment

In addition to the editorial article environment, one can use the editorial environment to create editorial or opinion texts. The main feature is that it transforms the style of the heading. Although this environment accepts all the commands article takes, it does not make any sense to use the `\authorandplace` command within it since it includes an author argument. To create an editorial text use

```
\begin{editorial}{<num-of-columns>}{<title>}{<author>}{<label>}
...<text>...
\end{editorial}
```

All arguments have the same meaning as article environment (see [subsubsection 6.1.5](#)).

### 6.1.7 The shortarticle environment

The shortarticle environment creates a block of short article. Although it has its own title and subtitle, each piece of article within it may have a title. To use it just type:

```
\begin{shortarticle}{<num-of-columns>}{<title>}{<subtitle>}{<label>}
...<text>...
\shortarticleitem{<title>}{<text>}
...
\end{shortarticle}
```

You can also specify the number of columns of the block like editorial and article environments. To add a piece of article inside the shortarticle use the `\shortarticleitem`, indicating a title and the text of the issue.

### 6.1.8 Commands between articles

```
\articlesep \newsection
```

There are two commands you can use among the articles inside `xepersian-magazine`: `\articlesep` and `\newsection`. The first one does not take any parameter and just draws a line between two articles. The second changes the content of `\xepersian@section` to the new `<section name>`. From the point it is used, all articles which follow will be grouped within the new section.

```
\newsection{<section name>}
```

### 6.1.9 Customization

`xepersian-magazine` includes many commands which can be used to customize its aspect, from the front page to the last page. I will list them grouped so it is easy to find them. Treat them as standard `LATeX` commands, using `\renewcommand` to change their behaviour.

### 6.1.10 Front Page

```
\customlogo \customminilogo \custommagazinename
```

When creating a magazine, everyone wants to show its own logo instead of `xepersian-magazine` default heading. To achieve this, you need to put the following command at the preamble of your document:

```
\customlogo{\text}  
\customminilogo{\text}  
\custommagazinename{\text}
```

```
\edition \editionformat
```

The edition text has to be declared in the preamble of the document. One important thing to know is that `\author`, `\date` and `\title` have no effect inside `xepersian-magazine` since the magazine date is taken from `\today` command and the other two are only for the title page (if using `\maketitle`).

```
\indexFormat \indexEntryFormat \indexEntryPageTxt  
\indexEntryPageFormat \indexEntrySeparator
```

When defining the index in the front page, there are several commands to customize the final index style. `\indexFormat` sets the format of the title; `\indexEntryFormat`, the format of each index entry; `\indexEntryPageTxt` and `\indexEntryPageFormat` lets you define which is the text that goes with the page number and its format. Finally, `xepersian-magazine` creates a thin line between index entries, you can redefine it using `\indexEntrySeparator`. To get the index with `\xepersian@indexwidth` is provided.

```
\weatherFormat \weatherTempFormat \weatherUnits
```

Relating to the weather block, the title format can be changed redefining `\weatherFormat`. In order to customize the format of the temperature numbers and their units it is necessary to redefine `\weatherTempFormat` and `\weatherUnits` respectively.

```
\*TitleFormat \*SubtitleFormat \*TextFormat
```

The main article that appear in the front page can change their formats. To obtain that there are three standard commands to modify the title, subtitle and text style. You just have to replace the star (\*) with first, second or third depending on which article you are editing. Note that first piece of article has no subtitle therefore it does not make any sense to use the non-existent command `\firstSubtitleFormat`.

```
\pictureCaptionFormat \pagesFormat
```

Two other elements to configure are the picture captions and the pages or section format in the entire document. To proceed just redefine the macros `\pictureCaptionFormat` and `\pagesFormat`.

### 6.1.11 Inside The Magazine

```
\innerTitleFormat \innerSubtitleFormat \innerAuthorFormat  
\innerPlaceFormat
```

The articles inside `xepersian-magazine` may have a different format from the ones in the front page. To change their title or subtitle format redefine `\innerTitleFormat` and `\innerSubtitleFormat`. The article text format matches the document general definition. When using the `\authorandplace` command, you might want to change the default style. Just renew `\innerAuthorFormat` and `\innerPlaceFormat` to get the results.

```
\timestampTxt \timestampSeparator \timestampFormat
```

The `\timestamp` command described in [subsubsection 6.1.5](#) lets you introduce the time of the event before the article text. You can configure its appearance by altering several commands: `\timestampTxt` which means the text after the timestamp; `\timestampSeparator` which defines the element between the actual timestamp and the beginning of the text and, finally, `\timestampFormat` to change the entire timestamp format.

```
\innerTextFinalMark
```

`xepersian-magazine` puts a small black square at the end of the article. As I wanted to create a highly customizable L<sup>A</sup>T<sub>E</sub>X class I added the macro `\innerTextFinalMark` to change this black square. This item will appear always following the last character of the text with the~ character.

```
\minraggedcols \raggedFormat
```

The `\minraggedcols` counter is used to tell `xepersian-magazine` when article text should be ragged instead of justified. The counter represents the minimum number of columns that are needed in order to use ragged texts. For example, if `\minraggedcols` is set to 3, all articles with 3 columns or more will be ragged. Articles with 1, 2 columns will have justified text. By default, `\minraggedcols` is set to 4.

The `\raggedFormat` macro can be redefined to fit user ragged style. Default value is `\RaggedLeft`.

```
\heading \foot
```

`xepersian-magazine` includes package `fancyhdr` for changing headings and footers. Although it is possible to use its own commands to modify `xepersian-magazine` style, there are two commands to change headings and foot appearance. Place them in the preamble of your `xepersian-magazine` document.

```
\heading{\langle left\rangle}{\langle center\rangle}{\langle right\rangle}  
\foot{\langle left\rangle}{\langle center\rangle}{\langle right\rangle}
```

If you still prefer to use `fancyhdr` macros, use them after the `frontpage` environment.

`xepersian-magazine` by default places no headers and footers. If you want headers and footers, then after loading `xepersian` package, you should write `\pagestyle{fancy}` at the preamble of your document.

### 6.1.12 Class Options

The `xepersian-magazine` class is in itself an alteration of the standard `article` class, thus it inherits most of its class options but `twoside`, `twocolumn`, `notitlepage` and `a4paper`. If you find problems when loading other article features, please let me know to fix it. There are also five own options that `xepersian-magazine` implements.

**a3paper** (false) This option makes `xepersian-magazine` 297 mm width by 420 mm height. This option is implemented because the standard `article` class does not allow this document size.

**9pt** (false) Allows the 9pt font size that `article` class does not include (default is 10pt).

**columnlines** columnlines (false) Adds lines between columns in the entire `xepersian-magazine`. The default line width is 0.1pt but it is possible to change this by setting length `\columnlines` in the preamble.

**showgrid** (false) This option is only for developing purposes. Because the front page has a personal design using the `textpos` package, I created this grid to make easier the lay out.

## 6.2 Typesetting Multiple-choice Questions

### 6.2.1 Introduction

`xepersian-multiplechoice` is a package for making multiple choices questionnaires under L<sup>A</sup>T<sub>E</sub>X. A special environment allows you to define questions and possible answers. You can specify which answers are correct and which are not. `xepersian-multiplechoice` not only formats the questions for you, but also generates a “form” (a grid that your students will have to fill in), and a “mask” (the same grid, only with correct answers properly checked in). You can then print the mask on a slide

and correct the questionnaires more easily by superimposing the mask on top of students' forms.

### 6.2.2 Usage

Here we now explain the usage of this package, however there are four example files, namely `test-question-only.tex`, `test-solution-form.tex`, `test-empty-form.tex` and `test-correction.tex`, available in doc folder that you may want to look at.

### 6.2.3 Loading The Package

You can load the package as usual by:

```
\usepackage [Options] {xepersian-multiplechoice}
```

The available options are described along the text, where appropriate.

### 6.2.4 Creating Questions

Here's a simple example demonstrating how to produce a new question:

```
1 \begin{question}{سؤال}
2 \false ١ جواب
3 \true ٢ جواب
4 \false ٣ جواب
5 \false ٤ جواب
6 \end{question}
7 \begin{correction}
8 جواب واقعی و علت اینکه این جواب، جواب واقعی هست
9 \end{correction}
```

### 6.2.5 The question Environment

The `question` environment allows you to insert questions into your document. It takes one mandatory argument which specifies the actual question's text. The question will be displayed in a frame box, the size of the line.

```
\true \false
```

The proposed answers are displayed below the question in a list fashion (the question environment is a list-based one). Instead of using `\item` however, use either `\true` or `\false` to insert a possible answer.

### 6.2.6 Question Numbers

The `question` environment is associated with a L<sup>A</sup>T<sub>E</sub>X counter named `question`. This counter stores the number of the next (or current) question. It is initialized to 1, and automatically incremented at the end of `question` environments. You might want to use it to format question titles. For instance, you could decide that each question belongs to a subsection in the `article` class, and use something like this before each question: `\subsection*{Question \thequestion}`

### 6.2.7 The Form and the Mask

```
\makeform \makemask
```

Based on the questions appearing in your document, `xepersian-multiplechoice` has the ability to generate a “form” (a grid that your students will have to fill in), and a “mask” (the same grid, only with correct answers properly checked in). This can make the correction process easier.

To generate a form and a mask, use the macros `\makeform` and `\makemask`. `xepersian-multiplechoice` uses two auxiliary files to build them. These files have respectively an extension of `frm` and `msk`. If you use these macros, you will need two passes of L<sup>A</sup>T<sub>E</sub>X in order to get a correctly formatted document.

### 6.2.8 Typesetting corrections

The “correction” mode allows you to automatically typeset and distribute corrections to your students. These corrections are slightly modified versions of your questionnaire: each possible answer is prefixed with a small symbol (a visual clue) indicating whether the answer was correct or wrong. In addition, you can typeset explanations below each question.

To activate the correction mode, use the `correction` option. It is off by default.

To typeset explanations below the questions, use the `correction` environment (no argument). The contents of this environment is displayed only in correction mode. In normal mode, it is simply discarded.

In addition, note that `xepersian-multiplechoice` cancels the actions performed by `\makeform` and `\makemask` in `correction` mode. This is to avoid further edition of the source when typesetting a correction.

### 6.2.9 Important Note

Currently, `xepersian-multiplechoice` requires that you provide a constant number of proposed answers across all questions in your `xepersian-multiplechoice`. This is something natural when you want to build forms, but this might me too restrictive otherwise, I’m not sure, so it is possible that this restriction will be removed in future versions.

Currently, there is a built-in mechanism for checking that the number of proposed answers remains constant: when `xepersian-multiplechoice` encounters the

first occurrence of the `question` environment, it remembers the number of proposed answers from there. Afterwards, any noticed difference in subsequent occurrences will generate an error. As a consequence, you never have to tell `xepersian-multiplechoice` explicitly what that number is.

## 6.3 Customising The Package

### 6.3.1 The `question` environment

```
\questionspace \answerstitlefont \answernumberfont
```

`\questionspace` is the amount of extra vertical space to put under the question, before the list of proposed answers. This is a L<sup>A</sup>T<sub>E</sub>X length that defaults to `0pt`.

Before the list of possible answers, a short title is displayed (for English, it reads “Possible answers:”). The `\answerstitlefont` macro takes one mandatory argument which redefines the font to use for the answers title. By default, `\bfseries` is used.

Each proposed answer in the list is numbered automatically (and alphabetically). The `\answernumberfont` macro takes one mandatory argument which redefines the font to use for displaying the answer number. By default, `\bfseries` is used.

### 6.3.2 The Form and the Mask

```
\headerfont \X
```

The `\headerfont` macro takes one mandatory argument which redefines the font to use for the headers (first line and first column) of the form and mask arrays. By default, `\bfseries` is used.

In the mask, correct answers are checked in by filling the corresponding cell with an “X” character. If you want to change this, call the `\X` macro with one (mandatory) argument.

### 6.3.3 The correction

```
\truesymbol \falsesymbol
```

In correction mode, labels in front of answers are modified to give a visual clue about whether the answer was correct or wrong. By default, a cross and a small arrow are used. You can change these symbols by using the `\truesymbol` and

`\falsesymbol` macros. For instance, you could give a fancier look to your correction by using the `pifont` package and issuing:

```
\truesymbol{\ding{'063}~}
\falsesymbol{\ding{'067}~}
```

```
\correctionstyle
```

The appearance of the contents of the correction environment can be adjusted by using the `\correctionstyle` macro. By default, `\itshape` is used.

## 7 **xepersian** implementation

### 7.1 algorithmic-xepersian.def

```
1 \ProvidesFile{algorithmic-xepersian.def}[2010/07/25 v0.2 adaptations for algorithmic package]
2 \def\algorithmicrequire{\if@RTL\textbf{ :}\else\textbf{Require:}\fi}
3 \def\algorithmicensure{\if@RTL\textbf{ :}\else\textbf{Ensure:}\fi}
```

### 7.2 algorithm-xepersian.def

```
4 \ProvidesFile{algorithm-xepersian.def}[2010/07/25 v0.2 adaptations for algorithm package]
5 \def\ALG@name{\if@RTL else\Algorithm\fi}
6 \def\ALGS@name{ }
7 \def\listalgorithname{\if@RTL \ALGS@name\else List of \ALG@name s\fi}
```

### 7.3 amsart-xepersian.def

```
8 \ProvidesFile{amsart-xepersian.def}[2013/04/26 v0.3 adaptations for amsart class]
9 \renewcommand \theprt {\@tartibi\c@part}
10 \def\appendix{\par\c@section\z@\c@subsection\z@
11   \let\sectionname\appendixname
12   \def\thesection{\@harfi\c@section}}
13
14 \long\def\@footnotetext#1{%
15   \insert\footins{%
16     \if@RTL\@footnote\@RTLtrue\else\@RTLfalse\fi%
17     \normalfont\footnotesize
18     \interlinepenalty\interfootnotelinepenalty
19     \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
20     \floatingpenalty\@MM \hsize\columnwidth
21     \parboxrestore \parindent\normalparindent \sloppy
22     \protected\edef\@currentlabel{%
23       \csname p@footnote\endcsname\@thefnmark}%
24     \makefntext{%
25       \rule\z@\footnotesep\ignorespaces\if@RTL\@footnote\@else\latinfont\fi\unskip\strut\par}%
26
27
28
29
30
31 \long\def\@RTLfootnotetext#1{%
32   \insert\footins{%
33     \@RTLtrue%
34     \normalfont\footnotesize
35     \interlinepenalty\interfootnotelinepenalty
```

```

36 \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
37 \floatingpenalty\@MM \hsize\columnwidth
38 \parboxrestore \parindent\normalparindent \sloppy
39 \protected@edef\@currentlabel{%
40   \csname p@footnote\endcsname\@thefnmark}%
41 \makefntext{%
42   \rule{z@\footnotesep\ignorespaces\persianfont #1\unskip\strut\par}}}
43
44
45
46
47
48
49
50 \long\def\@LTRfootnotetext#1{%
51   \insert\footins{%
52     \ifRTLfalse%
53     \normalfont\footnotesize
54     \interlinepenalty\interfootnotelinepenalty
55     \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
56     \floatingpenalty\@MM \hsize\columnwidth
57     \parboxrestore \parindent\normalparindent \sloppy
58     \protected@edef\@currentlabel{%
59       \csname p@footnote\endcsname\@thefnmark}%
60     \makefntext{%
61       \rule{z@\footnotesep\ignorespaces\latinfont #1\unskip\strut\par}}}}
62
63
64 \footdir@temp\footdir@ORG@xepersian@amsart@footnotetext\@footnotetext{\bidi@footdir@footnote}%
65 \footdir@temp\footdir@ORG@xepersian@amsart@RTLfootnotetext\@RTLfootnotetext{R}%
66 \footdir@temp\footdir@ORG@xepersian@amsart@LTRfootnotetext\@LTRfootnotetext{L}%
67

```

## 7.4 amsbook-xepersian.def

```

68 \ProvidesFile{amsbook-xepersian.def}[2013/04/26 v0.4 adaptations for amsbook class]
69 \def\frontmatter{\cleardoublepage\pagenumbering{harfi}}
70 \renewcommand \theprt {\@tartibi\c@prt}
71 \def\appendix{\par
72   \c@chapter\z@\c@section\z@
73   \let\chaptername\appendixname
74   \def\thechapter{\@harfi\c@chapter}}
75
76 \long\def\@footnotetext#1{%
77   \insert\footins{%
78     \if@RTL@footnote\@RTLtrue\else\@RTLfalse\fi%
79     \normalfont\footnotesize
80     \interlinepenalty\interfootnotelinepenalty
81     \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
82     \floatingpenalty\@MM \hsize\columnwidth

```

```

83   \@parboxrestore \parindent\normalparindent \sloppy
84   \protected@edef@\currentlabel{%
85     \csname p@footnote\endcsname\@thefnmark}%
86   \@makefntext{%
87     \rule{z@}{\footnotesep}\ignorespaces\if@RTL@footnote#1\else\latinfont#1\fi\unskip\strut\par}%
88
89
90
91
92
93 \long\def@\RTLfootnotetext#1{%
94   \insert\footins{%
95     \if@RTLtrue{%
96       \normalfont\footnotesize
97       \interlinepenalty\interfootnotelinepenalty
98       \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
99       \floatingpenalty\@MM \hsize\columnwidth
100      \parboxrestore \parindent\normalparindent \sloppy
101      \protected@edef@\currentlabel{%
102        \csname p@footnote\endcsname\@thefnmark}%
103      \@makefntext{%
104        \rule{z@}{\footnotesep}\ignorespaces\persianfont #1\unskip\strut\par}}}%
105
106
107
108
109
110
111
112 \long\def@\LTRfootnotetext#1{%
113   \insert\footins{%
114     \if@RTLfalse{%
115       \normalfont\footnotesize
116       \interlinepenalty\interfootnotelinepenalty
117       \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
118       \floatingpenalty\@MM \hsize\columnwidth
119       \parboxrestore \parindent\normalparindent \sloppy
120       \protected@edef@\currentlabel{%
121         \csname p@footnote\endcsname\@thefnmark}%
122       \@makefntext{%
123         \rule{z@}{\footnotesep}\ignorespaces\latinfont #1\unskip\strut\par}}}%
124
125 \footdir@temp\footdir@ORG@xpersian@amsbook@footnotetext\@footnotetext{\bidi@footdir@footnote}%
126 \footdir@temp\footdir@ORG@xpersian@amsbook@RTLfootnotetext\@RTLfootnotetext{R}%
127 \footdir@temp\footdir@ORG@xpersian@amsbook@LTRfootnotetext\@LTRfootnotetext{L}%
128

```

## 7.5 article-xpersian.def

129 \ProvidesFile{article-xpersian.def}[2010/07/25 v0.2 adaptations for standard article class]

```

130 \renewcommand \thepart {\@tartibi\c@part}
131 \renewcommand\appendix{\par
132   \setcounter{section}{0}%
133   \setcounter{subsection}{0}%
134   \gdef\thesection{\@harfi\c@section}}

```

## 7.6 artikel1-xepersian.def

```

135 \ProvidesFile{artikel1-xepersian.def}[2010/07/25 v0.1 adaptations for artikel1 class]
136 \renewcommand*\thepart{\@tartibi\c@part}
137 \renewcommand*\appendix{\par
138   \setcounter{section}{0}%
139   \setcounter{subsection}{0}%
140   \gdef\thesection{\@harfi\c@section}}

```

## 7.7 artikel2-xepersian.def

```

141 \ProvidesFile{artikel2-xepersian.def}[2010/07/25 v0.1 adaptations for artikel2 class]
142 \renewcommand*\thepart{\@tartibi\c@part}
143 \renewcommand*\appendix{\par
144   \setcounter{section}{0}%
145   \setcounter{subsection}{0}%
146   \gdef\thesection{\@harfi\c@section}}

```

## 7.8 artikel3-xepersian.def

```

147 \ProvidesFile{artikel3-xepersian.def}[2010/07/25 v0.1 adaptations for artikel3 class]
148 \renewcommand*\thepart{\@tartibi\c@part}
149 \renewcommand*\appendix{\par
150   \setcounter{section}{0}%
151   \setcounter{subsection}{0}%
152   \gdef\thesection{\@harfi\c@section}}

```

## 7.9 backref-xepersian.def

```

153 \ProvidesFile{backref-xepersian.def}[2010/07/25 v0.1 adaptations for backref package]
154 \def\backrefpagesname{\if@RTL else\ pages\fi}
155 \def\BR@Latincitex[#1]{#2}%
156   \BRorg@Latincitex[{#1}]{#2}%
157   \ifBR@verbose
158     \PackageInfo{backref}{back Latin cite `string`#2`string'}%
159   \fi
160   \Hy@backout{#2}%
161 }
162 \AtBeginDocument{%
163   \@ifundefined{NAT@parse}{%
164     \global\let\BRorg@Latincitex\@Latincitex
165     \global\let\@Latincitex\BR@Latincitex
166   }{%
167     \@ifpackageloaded{hyperref}{%
168       \def\hyper@natlinkstart#1{\Hy@backout{#1}}%
169     }%
170     \PackageInfo{backref}{** backref set up for natbib **}%

```

```
171 }%
172 }%
```

## 7.10 `budituftesidenote-xepersian.def`

```
173 \ProvidesFile{budituftesidenote-xepersian.def}[2011/06/18 v0.1 xepersian changes to buditufte
174 \long\def\@LTRbudituftesidenote@sidenote[#1][#2]#3{%
175   \let\cite\@budituftesidenote@infofootnote@cite% use the in-sidenote \cite command
176   \gdef\@budituftesidenote@citations{}% clear out any old citations
177   \ifthenelse{\NOT\isempty{#2}}{%
178     \gsetlength{\@budituftesidenote@sidenote@vertical@offset}{#2}%
179   }{%
180     \gsetlength{\@budituftesidenote@sidenote@vertical@offset}{0pt}%
181   }%
182   \ifthenelse{\isempty{#1}}{%
183     % no specific footnote number provided
184     \stepcounter\@mpfn%
185     \protected@xdef\@thefnmark{\thempfn}%
186     \@footnotemark\@LTRfootnotetext[\@budituftesidenote@sidenote@vertical@offset]{\latinfont#3}%
187   }{%
188     % specific footnote number provided
189     \begingroup%
190       \csname c@\@mpfn\endcsname #1\relax%
191       \unrestored@protected@xdef\@thefnmark{\thempfn}%
192     \endgroup%
193     \@footnotemark\@LTRfootnotetext[\@budituftesidenote@sidenote@vertical@offset]{\latinfont#3}%
194   }%
195   \@budituftesidenote@print@citations% print any citations
196   \let\cite\@budituftesidenote@normal@cite% go back to using normal in-text \cite command
197   \unskip\ignorespaces% remove extra white space
198   \kern-\multiplefootnotemarker% remove \kern left behind by sidenote
199   \kern\multiplefootnotemarker\relax% add new \kern here to replace the one we yanked
200 }
201 \long\def\@RTLbudituftesidenote@sidenote[#1][#2]#3{%
202   \let\cite\@budituftesidenote@infofootnote@cite% use the in-sidenote \cite command
203   \gdef\@budituftesidenote@citations{}% clear out any old citations
204   \ifthenelse{\NOT\isempty{#2}}{%
205     \gsetlength{\@budituftesidenote@sidenote@vertical@offset}{#2}%
206   }{%
207     \gsetlength{\@budituftesidenote@sidenote@vertical@offset}{0pt}%
208   }%
209   \ifthenelse{\isempty{#1}}{%
210     % no specific footnote number provided
211     \stepcounter\@mpfn%
212     \protected@xdef\@thefnmark{\thempfn}%
213     \@footnotemark\@RTLfootnotetext[\@budituftesidenote@sidenote@vertical@offset]{\persianfont#3}%
214   }{%
215     % specific footnote number provided
216     \begingroup%
217       \csname c@\@mpfn\endcsname #1\relax%
```

```

218     \unrestored@protected@xdef\@thefnmark{\thempfn}%
219     \endgroup%
220     \@footnotemark\@RTLfootnotetext[\@bidiutfesidenote@sidenote@vertical@offset]{\persianfont#}
221   }%
222   \@bidiutfesidenote@print@citations%           print any citations
223   \let\cite\@bidiutfesidenote@normal@cite%      go back to using normal in-text \cite command
224   \unskip\ignorespaces%                         remove extra white space
225   \kern-\multiplefootnotemarker%               remove \kern left behind by sidenote
226   \kern\multiplefootnotemarker\relax% add new \kern here to replace the one we yanked
227 }
228 \renewcommand\LTRmarginnote[2][0pt]{%
229   \let\cite\@bidiutfesidenote@infootnote@cite%  use the in-sidenote \cite command
230   \gdef\@bidiutfesidenote@citations{}%          clear out any old citations
231   \LTRbidiutfesidenotemarginpar{\hbox{}\vspace*{#1}\@bidiutfesidenote@marginnote@font\latinf
232   \@bidiutfesidenote@print@citations%           print any citations
233   \let\cite\@bidiutfesidenote@normal@cite%      go back to using normal in-text \cite command
234 }
235 \renewcommand\RTLmarginnote[2][0pt]{%
236   \let\cite\@bidiutfesidenote@infootnote@cite%  use the in-sidenote \cite command
237   \gdef\@bidiutfesidenote@citations{}%          clear out any old citations
238   \RTLbidiutfesidenotemarginpar{\hbox{}\vspace*{#1}\@bidiutfesidenote@marginnote@font\persia
239   \@bidiutfesidenote@print@citations%           print any citations
240   \let\cite\@bidiutfesidenote@normal@cite%      go back to using normal in-text \cite command
241 }

```

## 7.11 **bidimoderncv-xepersian.def**

```

242 \ProvidesFile{bidimoderncv-xepersian.def}[2010/07/25 v0.1 adaptations for bidimoderncv class]
243 \def\refname{\if@RTL else\ Publications\fi}

```

## 7.12 **boek3-xepersian.def**

```

244 \ProvidesFile{boek3-xepersian.def}[2010/07/25 v0.1 adaptations for boek3 class]
245 \renewcommand*\thepart{\@tartibi\c@part}
246 \renewcommand*\frontmatter{%
247   \cleardoublepage
248   \@mainmatterfalse
249   \pagenumbering{harfi}}
250 \renewcommand*\appendix{\par
251   \setcounter{chapter}{0}%
252   \setcounter{section}{0}%
253   \gdef\@chapapp{\appendixname}%
254   \gdef\thechapter{\@harfi\c@chapter}}

```

## 7.13 **boek-xepersian.def**

```

255 \ProvidesFile{boek-xepersian.def}[2010/07/25 v0.1 adaptations for boek class]
256 \renewcommand*\thepart{\@tartibi\c@part}
257 \renewcommand*\frontmatter{%
258   \cleardoublepage
259   \@mainmatterfalse
260   \pagenumbering{harfi}}

```

```

261 \renewcommand*\appendix{\par
262   \setcounter{chapter}{0}%
263   \setcounter{section}{0}%
264   \gdef\@chapapp{\appendixname}%
265   \gdef\thechapter{\@harfi\c@chapter}}

```

### 7.14 bookest-xepersian.def

```

266 \ProvidesFile{bookest-xepersian.def}[2010/07/25 v0.1 adaptations for bookest class]
267 \renewcommand \thepart {\@startibi\c@part}
268 \renewcommand\appendix{\par
269   \setcounter{chapter}{0}%
270   \setcounter{section}{0}%
271   \gdef\@chapapp{\appendixname}%
272   \gdef\thechapter{\@harfi\c@chapter}
273 }%end appendix

```

### 7.15 book-xepersian.def

```

274 \ProvidesFile{book-xepersian.def}[2010/07/25 v0.2 adaptations for standard book class]
275 \renewcommand\frontmatter{%
276   \cleardoublepage
277   \mainmatterfalse
278   \pagenumbering{harfi}}
279 \renewcommand \thepart {\@startibi\c@part}
280 \renewcommand\appendix{\par
281   \setcounter{chapter}{0}%
282   \setcounter{section}{0}%
283   \gdef\@chapapp{\appendixname}%
284   \gdef\thechapter{\@harfi\c@chapter}
285 }%end appendix

```

### 7.16 breqn-xepersian.def

```

286 \ProvidesFile{breqn-xepersian.def}[2010/07/25 v0.1 adaptations for breqn package]
287 \def\@dmath[#1]{\if@RTL\@RTLfalse\addfontfeatures{Mapping=farsidigits}\fi%
288   \everydisplay\expandafter{\the\everydisplay \display@setup}%
289   \if@noskipsec \leavevmode \fi
290   \if@inlabel \leavevmode \global\@inlabelfalse \fi
291   \if\eq@group\else\eq@prelim\fi
292   \setkeys{breqn}{#1}%
293   \the\eqstyle
294   \eq@setnumber
295   \begingroup
296   \eq@setup@a
297   \eq@startup
298 }
299 \def\@dgroup[#1]{\if@RTL\@RTLfalse\addfontfeatures{Mapping=farsidigits}\fi%
300   \let\eq@group\@True \global\let\eq@GRP@first@dmath\@True
301   \global\GRP@queue\emptytoks \global\setbox\GRP@box\box\voidb@x
302   \global\let\GRP@label\empty
303   \global\grp@wdL\z@\global\grp@wdR\z@\global\grp@wdT\z@

```

```

304 \global\grp@linewidth{z@\global\grp@wdNum{z@}
305 \global\let\grp@eqs@numbered{\@False}
306 \global\let\grp@aligned{\@True}
307 \global\let\grp@shiftnumber{\@False}
308 \eq@prelim
309 \setkeys{breqn}{#1}%
310 \if\grp@hasNumber \grp@setnumber \fi
311 }
312 \def\dseries[#1]{\if@RTL\@RTLfalse\addfontfeatures{Mapping=farsiDigits}\fi%
313 \let\display@setup\dseries@display@setup
314 % Question: should this be the default for dseries???
315 \global\eq@wdCond{z@}
316 \dmath[layout={M},#1]%
317 \mathsurround{z@}\math \penalty\@Mi
318 \let\endmath\ends@math
319 \def\premath{%
320 \ifdim\lastskip<.3em \unskip
321 \else\ifnum\lastpenalty<\@M \dquad\fi\fi
322 }%
323 \def\postmath{\unpenalty\eq@addpunct \penalty\intermath@penalty \dquad \ignorespaces}%
324 \ignorespaces
325 }

```

## 7.17 latex-localise-commands-xepersian.def

```

326 \ProvidesFile{latex-localise-commands-xepersian.def}[2014/02/05 v0.3 Persian localisation of La
327 \eqcommand{ }{@arstrut}
328 \eqcommand{ }{above}
329 \eqcommand{ }{abovedisplayshortskip}
330 \eqcommand{ }{abovedisplayskip}
331 \eqcommand{ }{abstractname}
332 \eqcommand{ }{accent}
333 \eqcommand{ }{active}
334 \eqcommand{ }{addcontentsline}
335 \eqcommand{ }{addpenalty}
336 \eqcommand{ }{address}
337 \eqcommand{ }{addtocontents}
338 \eqcommand{ }{addtocounter}
339 \eqcommand{ }{addtolength}
340 \eqcommand{ }{addvspace}
341 \eqcommand{ }{adjdemerits}
342 \eqcommand{ }{advance}
343 \eqcommand{ }{afterassignment}
344 \eqcommand{ }{aftergroup}
345 \eqcommand{ }{aleph}
346 \eqcommand{ }{aliasfontfeature}
347 \eqcommand{ }{aliasfontfeatureoption}
348 \eqcommand{ }{allowbreak}
349 \eqcommand{ @}{alloc@}
350 \eqcommand{ }{allocationnumber}

```

```

351 \eqcommand{      }{allowdisplaybreaks}
352 \eqcommand{      }{Alph}
353 \eqcommand{      }{alph}
354 \eqcommand{      }{alsoname}
355 \eqcommand{ }{and}
356 \eqcommand{      }{angle}
357 \eqcommand{      }{appendixname}
358 \eqcommand{      }{approx}
359 \eqcommand{      }{arabic}
360 \eqcommand{      }{arg}
361 \eqcommand{      }{arrayrulecolor}
362 \eqcommand{      }{arraycolsep}
363 \eqcommand{      }{arrayrulewidth}
364 \eqcommand{      }{arraystretch}
365 \eqcommand{      }{AtBeginDocument}
366 \eqcommand{      }{AtEndDocument}
367 \eqcommand{      }{AtEndOfClass}
368 \eqcommand{      }{AtEndOfPackage}
369 \eqcommand{      }{author}
370 \eqcommand{      }{backmatter}
371 \eqcommand{      }{backslash}
372 \eqcommand{      }{badness}
373 \eqcommand{      }{bar}
374 \eqcommand{      }{baselineskip}
375 \eqcommand{      }{baselinestretch}
376 \eqcommand{      }{batchmode}
377 \eqcommand{      }{begin}
378 \eqcommand{      }{beginL}
379 \eqcommand{      }{beginR}
380 \eqcommand{      }{begingroup}
381 \eqcommand{      }{belowdisplayshortskip}
382 \eqcommand{      }{belowdisplayskip}
383 \eqcommand{      }{bf}
384 \eqcommand{      }{bfdefault}
385 \eqcommand{      }{bfseries}
386 \eqcommand{      }{bgroup}
387 \eqcommand{      }{bibitem}
388 \eqcommand{      }{bibliography}
389 \eqcommand{      }{bibliographystyle}
390 \eqcommand{      }{bibname}
391 \eqcommand{      }{bigskip}
392 \eqcommand{      }{bigskipamount}
393 \eqcommand{      }{botfigrule}
394 \eqcommand{      }{botmark}
395 \eqcommand{      }{bottompageskip}
396 \eqcommand{      }{bottomfraction}
397 \eqcommand{      }{box}
398 \eqcommand{      }{boxmaxdepth}
399 \eqcommand{      }{break}
400 \eqcommand{      }{bullet}

```

```

401 \eqcommand{ @ }{@cclv}
402 \eqcommand{ @ }{@cclvi}
403 \eqcommand{ }{caption}
404 \eqcommand{ }{catcode}
405 \eqcommand{ }{cc}
406 \eqcommand{ }{ccname}
407 \eqcommand{ }{cdot}
408 \eqcommand{ }{cdots}
409 \eqcommand{ }{centering}
410 \eqcommand{ }{centerline}
411 \eqcommand{ @ }{ch@ck}
412 \eqcommand{ }{chapter}
413 \eqcommand{ }{chaptername}
414 \eqcommand{ }{char}
415 \eqcommand{ }{chardef}
416 \eqcommand{ }{CheckCommand}
417 \eqcommand{ }{cite}
418 \eqcommand{ }{ClassError}
419 \eqcommand{ }{ClassInfo}
420 \eqcommand{ }{ClassWarning}
421 \eqcommand{ }{ClassWarningNoLine}
422 \eqcommand{ }{cleaders}
423 \eqcommand{ }{cleardoublepage}
424 \eqcommand{ }{clearpage}
425 \eqcommand{ }{cline}
426 \eqcommand{ }{closein}
427 \eqcommand{ }{closeout}
428 \eqcommand{ }{closing}
429 \eqcommand{ }{clubpenalty}
430 \eqcommand{ }{clubsuit}
431 \eqcommand{ }{colbotmark}
432 \eqcommand{ }{colfirstmark}
433 \eqcommand{ }{color}
434 \eqcommand{ }{colorbox}
435 \eqcommand{ }{coltopmark}
436 \eqcommand{ }{columncolor}
437 \eqcommand{ }{columnsep}
438 \eqcommand{ }{columnwidth}
439 \eqcommand{ }{columnseprule}
440 \eqcommand{ }{contentsline}
441 \eqcommand{ }{contentsname}
442 \eqcommand{ }{copy}
443 \eqcommand{ }{copyright}
444 \eqcommand{ }{count}
445 \eqcommand{ @}{count@}
446 \eqcommand{ }{countdef}
447 \eqcommand{ }{cr}
448 \eqcommand{ }{crcr}
449 \eqcommand{ }{csname}
450 \eqcommand{ }{CurrentOption}

```

```

451 \eqcommand{      }{dashbox}
452 \eqcommand{      }{dashv}
453 \eqcommand{@ }{@date}
454 \eqcommand{ }{date}
455 \eqcommand{ }{day}
456 \eqcommand{      }{dblbotfigrule}
457 \eqcommand{      }{dblbottomfraction}
458 \eqcommand{      }{dblfigrule}
459 \eqcommand{      }{dblfloatpagefraction}
460 \eqcommand{      }{dblfloatsep}
461 \eqcommand{      }{dblfnllocatecode}
462 \eqcommand{      }{dbltextfloatsep}
463 \eqcommand{      }{dbltopfraction}
464 \eqcommand{      }{DeclareFixedFont}
465 \eqcommand{      }{DeclareGraphicsExtensions}
466 \eqcommand{      }{DeclareGraphicsRule}
467 \eqcommand{      }{DeclareOldFontCommand}
468 \eqcommand{      }{DeclareOption}
469 \eqcommand{      }{DeclareRobustCommand}
470 \eqcommand{      }{DeclareSymbolFont}
471 \eqcommand{      }{deadcycles}
472 \eqcommand{ }{def}
473 \eqcommand{ @ }{define@key}
474 \eqcommand{      }{definecolor}
475 \eqcommand{ }{deg}
476 \eqcommand{      }{delcode}
477 \eqcommand{      }{delimiter}
478 \eqcommand{      }{delimiterfactor}
479 \eqcommand{      }{depth}
480 \eqcommand{      }{diamondsuit}
481 \eqcommand{      }{dim}
482 \eqcommand{      }{dimen}
483 \eqcommand{ @ }{dimen@}
484 \eqcommand{ @ }{dimen@i}
485 \eqcommand{ @ }{dimen@ii}
486 \eqcommand{      }{dimendef}
487 \eqcommand{      }{discretionary}
488 \eqcommand{      }{displaybreak}
489 \eqcommand{      }{displayindent}
490 \eqcommand{      }{displaystyle}
491 \eqcommand{      }{displaywidth}
492 \eqcommand{      }{divide}
493 \eqcommand{      }{documentclass}
494 \eqcommand{ }{do}
495 \eqcommand{      }{dospecials}
496 \eqcommand{      }{dot}
497 \eqcommand{      }{doteq}
498 \eqcommand{      }{dotfill}
499 \eqcommand{      }{dots}
500 \eqcommand{      }{doublebox}

```

```

501 \eqcommand{      }{\doublerulesepcolor}
502 \eqcommand{      }{\doublerulesep}
503 \eqcommand{      }{\downarrow}
504 \eqcommand{ }{\dp}
505 \eqcommand{ }{\dump}
506 \eqcommand{ }{\edef}
507 \eqcommand{ }{\egroup}
508 \eqcommand{ }{\eject}
509 \eqcommand{ }{\else}
510 \eqcommand{ }{\em}
511 \eqcommand{ }{\emergencystretch}
512 \eqcommand{ }{\emph}
513 \eqcommand{@ }{\emptyset}
514 \eqcommand{ }{\emptyset}
515 \eqcommand{ }{\emptyset}
516 \eqcommand{ }{\end}
517 \eqcommand{ }{\endL}
518 \eqcommand{ }{\endR}
519 \eqcommand{ }{\endcsname}
520 \eqcommand{ }{\endfirsthead}
521 \eqcommand{ }{\endfoot}
522 \eqcommand{ }{\endgraf}
523 \eqcommand{ }{\endgroup}
524 \eqcommand{ }{\endhead}
525 \eqcommand{ }{\endinput}
526 \eqcommand{ }{\endlastfoot}
527 \eqcommand{ }{\enlargethispage}
528 \eqcommand{ }{\endline}
529 \eqcommand{ }{\endlinechar}
530 \eqcommand{ }{\enspace}
531 \eqcommand{ }{\enskip}
532 \eqcommand{ }{\eqcommand}
533 \eqcommand{ }{\eqenvironment}
534 \eqcommand{ }{\eqref}
535 \eqcommand{ }{\errhelp}
536 \eqcommand{ }{\errmessage}
537 \eqcommand{ }{\errorcontextlines}
538 \eqcommand{ }{\errorstopmode}
539 \eqcommand{ }{\escapechar}
540 \eqcommand{ }{\euro}
541 \eqcommand{ }{\evensidemargin}
542 \eqcommand{ }{\everycr}
543 \eqcommand{ }{\everydisplay}
544 \eqcommand{ }{\everyhbox}
545 \eqcommand{ }{\everyjob}
546 \eqcommand{ }{\everymath}
547 \eqcommand{ }{\everypar}
548 \eqcommand{ }{\everyvbox}
549 \eqcommand{ }{\ExecuteOptions}
550 \eqcommand{ }{\exhyphenpenalty}

```

```

551 \eqcommand{      }{expandafter}
552 \eqcommand{          }{extracolsep}
553 \eqcommand{@      }{@firstofone}
554 \eqcommand{@      }{@firstoftwo}
555 \eqcommand{@ }{f@ur}
556 \eqcommand{    }{fam}
557 \eqcommand{    }{fancypage}
558 \eqcommand{    }{fbox}
559 \eqcommand{    }{fboxrule}
560 \eqcommand{    }{fboxsep}
561 \eqcommand{    }{fcolorbox}
562 \eqcommand{ }{fi}
563 \eqcommand{    }{figurename}
564 \eqcommand{    }{filbreak}
565 \eqcommand{ }{fill}
566 \eqcommand{    }{firstmark}
567 \eqcommand{ }{flat}
568 \eqcommand{        }{floatpagefraction}
569 \eqcommand{        }{floatingpenalty}
570 \eqcommand{        }{floatsep}
571 \eqcommand{        }{flushbottom}
572 \eqcommand{        }{fmtname}
573 \eqcommand{        }{fmtversion}
574 \eqcommand{        }{fnsymbol}
575 \eqcommand{ }{font}
576 \eqcommand{    }{fontdimen}
577 \eqcommand{    }{fontencoding}
578 \eqcommand{    }{fontfamily}
579 \eqcommand{    }{fontname}
580 \eqcommand{    }{fontseries}
581 \eqcommand{    }{fontshape}
582 \eqcommand{    }{fontsize}
583 \eqcommand{        }{footheight}
584 \eqcommand{        }{footins}
585 \eqcommand{        }{footnote}
586 \eqcommand{        }{footnotemark}
587 \eqcommand{        }{footnoterule}
588 \eqcommand{        }{footnotesep}
589 \eqcommand{        }{footnotesign}
590 \eqcommand{        }{footnotetext}
591 \eqcommand{        }{footskip}
592 \eqcommand{ }{frame}
593 \eqcommand{    }{framebox}
594 \eqcommand{        }{frenchspacing}
595 \eqcommand{    }{frontmatter}
596 \eqcommand{    }{futurelet}
597 \eqcommand{@ }{@gobble}
598 \eqcommand{@ }{@gobbletwo}
599 \eqcommand{@ }{@gobblefour}
600 \eqcommand{@ }{@gtmpa}

```

```

601 \eqcommand{@ }{@gtempb}
602 \eqcommand{ }{gdef}
603 \eqcommand{ }{GenericInfo}
604 \eqcommand{ }{GenericWarning}
605 \eqcommand{ }{GenericError}
606 \eqcommand{ }{global}
607 \eqcommand{ }{globaldefs}
608 \eqcommand{ }{glossary}
609 \eqcommand{ }{glossaryentry}
610 \eqcommand{ }{goodbreak}
611 \eqcommand{ }{graphpaper}
612 \eqcommand{ }{guillemotleft}
613 \eqcommand{ }{guillemotright}
614 \eqcommand{ }{guilsinglleft}
615 \eqcommand{ }{guilsinglright}
616 \eqcommand{ }{halign}
617 \eqcommand{ }{hang}
618 \eqcommand{ }{hangafter}
619 \eqcommand{ }{hangindent}
620 \eqcommand{ }{hbadness}
621 \eqcommand{ }{hbox}
622 \eqcommand{ }{headheight}
623 \eqcommand{ }{headsep}
624 \eqcommand{ }{headtoname}
625 \eqcommand{ }{heartsuit}
626 \eqcommand{ }{height}
627 \eqcommand{ }{hfil}
628 \eqcommand{ }{hfill}
629 \eqcommand{ }{hfilneg}
630 \eqcommand{ }{hfuzz}
631 \eqcommand{ }{hideskip}
632 \eqcommand{ }{hidewidth}
633 \bidi@csletcs{ }{hline}% this is an exception
634 \eqcommand{ }{hoffset}
635 \eqcommand{ }{holdinginserts}
636 \eqcommand{ }{hrboxsep}
637 \eqcommand{ }{hrule}
638 \eqcommand{ }{rulefill}
639 \eqcommand{ }{hsize}
640 \eqcommand{ }{hskip}
641 \eqcommand{ }{hskip}
642 \eqcommand{ }{hss}
643 \eqcommand{ }{ht}
644 \eqcommand{ }{huge}
645 \eqcommand{ }{Huge}
646 \eqcommand{ }{hyperlink}
647 \eqcommand{ }{hypersetup}
648 \eqcommand{ }{hypertarget}
649 \eqcommand{ }{hyphenation}
650 \eqcommand{ }{hyphenchar}

```

```

651 \eqcommand{ }{hyphenpenalty}
652 \eqcommand{@ }{@ifclassloaded}
653 \eqcommand{@ }{@ifdefinable}
654 \eqcommand{@ }{@ifnextchar}
655 \eqcommand{@ }{@ifpackageloaded}
656 \eqcommand{@ }{@ifstar}
657 \eqcommand{@ }{@undefined}
658 \eqcommand{ }{if}
659 \eqcommand{ @ }{@if@tempswa}
660 \eqcommand{ }{ifcase}
661 \eqcommand{ }{ifcat}
662 \eqcommand{ }{ifdefined}
663 \eqcommand{ }{ifdim}
664 \eqcommand{ }{ifeof}
665 \eqcommand{ }{iff}
666 \eqcommand{ }{iffalse}
667 \eqcommand{ }{IfFileExists}
668 \eqcommand{ }{ifhbox}
669 \eqcommand{ }{ifhmode}
670 \eqcommand{ }{ifinner}
671 \eqcommand{ }{ifmmode}
672 \eqcommand{ }{ifnum}
673 \eqcommand{ }{ifodd}
674 \eqcommand{ }{ifthenelse}
675 \eqcommand{ }{iftrue}
676 \eqcommand{ }{ifvbox}
677 \eqcommand{ }{ifvmode}
678 \eqcommand{ }{ifvoid}
679 \eqcommand{ }{ifx}
680 \eqcommand{ }{ignorespaces}
681 \eqcommand{ }{immediate}
682 \eqcommand{ }{include}
683 \eqcommand{ }{includegraphics}
684 \eqcommand{ }{includeonly}
685 \eqcommand{ }{indent}
686 \eqcommand{ }{index}
687 \eqcommand{ }{indexentry}
688 \eqcommand{ }{indexname}
689 \eqcommand{ }{indexspace}
690 \eqcommand{ }{input}
691 \eqcommand{ }{InputIfFileExists}
692 \eqcommand{ }{inputlineno}
693 \eqcommand{ }{insert}
694 \eqcommand{ }{insertpenalties}
695 \eqcommand{ }{interfootnotelinepenalty}
696 \eqcommand{ }{interdisplaylinepenalty}
697 \eqcommand{ }{interlinepenalty}
698 \eqcommand{ }{intertext}
699 \eqcommand{ }{intertextsep}
700 \eqcommand{ }{invisible}

```

```

701 \eqcommand{ }{itdefault}
702 \eqcommand{ }{itshape}
703 \eqcommand{ }{item}
704 \eqcommand{ }{itemindent}
705 \eqcommand{ }{itemsep}
706 \eqcommand{ }{iterate}
707 \eqcommand{ }{itshape}
708 \eqcommand{ }{jobname}
709 \eqcommand{ }{jot}
710 \eqcommand{ }{kern}
711 \eqcommand{ }{kill}
712 \eqcommand{ }{label}
713 \eqcommand{ }{labelenumi}
714 \eqcommand{ }{labelenumii}
715 \eqcommand{ }{labelenumiii}
716 \eqcommand{ }{labelenumiv}
717 \eqcommand{ }{labelitemi}
718 \eqcommand{ }{labelitemii}
719 \eqcommand{ }{labelitemiii}
720 \eqcommand{ }{labelitemiv}
721 \eqcommand{ }{labelsep}
722 \eqcommand{ }{labelwidth}
723 \eqcommand{ }{language}
724 \eqcommand{ }{large}
725 \eqcommand{ }{Large}
726 \eqcommand{ }{LARGE}
727 \eqcommand{ }{lastbox}
728 \eqcommand{ }{lastkern}
729 \eqcommand{ }{lastpenalty}
730 \eqcommand{ }{lastskip}
731 \eqcommand{ }{LaTeX}
732 \eqcommand{ }{LaTeXe}
733 \eqcommand{ }{lccode}
734 \eqcommand{ }{ldots}
735 \eqcommand{ }{leaders}
736 \eqcommand{ }{leavevmode}
737 \eqcommand{ }{left}
738 \eqcommand{ }{leftmargin}
739 \eqcommand{ }{leftmargini}
740 \eqcommand{ }{leftmarginii}
741 \eqcommand{ }{leftmarginiii}
742 \eqcommand{ }{leftmarginiv}
743 \eqcommand{ }{leftmarginv}
744 \eqcommand{ }{leftmarginvi}
745 \eqcommand{ }{leftmark}
746 \eqcommand{ }{leftpageskip}
747 \eqcommand{ }{leftskip}
748 \eqcommand{ }{let}
749 \eqcommand{ }{line}
750 \eqcommand{ }{linebreak}

```

```

751 \eqcommand{ }{\linepenalty}
752 \eqcommand{ }{\lineskip}
753 \eqcommand{ }{\lineskiplimit}
754 \eqcommand{ }{\linespread}
755 \eqcommand{ }{\linethickness}
756 \eqcommand{ }{\linewidth}
757 \eqcommand{ }{\listfigurename}
758 \eqcommand{ }{\listfiles}
759 \eqcommand{ }{\listoffigures}
760 \eqcommand{ }{\listoftables}
761 \eqcommand{ }{\listparindent}
762 \eqcommand{ }{\listtablename}
763 \eqcommand{ }{\LoadClass}
764 \eqcommand{ }{\LoadClassWithOptions}
765 \eqcommand{ }{\location}
766 \eqcommand{ }{\long}
767 \eqcommand{ }{\looseness}
768 \eqcommand{ }{\lower}
769 \eqcommand{@ }{\@makeother}
770 \eqcommand{@ }{\@m}
771 \eqcommand{ @ }{\@M}
772 \eqcommand{ @ }{\@Mi}
773 \eqcommand{ @ }{\@Mii}
774 \eqcommand{ @ }{\@Miii}
775 \eqcommand{ @ }{\@Miv}
776 \eqcommand{ @ }{\@MM}
777 \eqcommand{ @ }{\@ne}
778 \eqcommand{ }{\mag}
779 \eqcommand{ }{\magstep}
780 \eqcommand{ }{\magstephalf}
781 \eqcommand{ }{\mainmatter}
782 \eqcommand{ }{\makeatletter}
783 \eqcommand{ }{\makeatother}
784 \eqcommand{ }{\makebox}
785 \eqcommand{ }{\makeglossary}
786 \eqcommand{ }{\makeindex}
787 \eqcommand{ }{\makelabel}
788 \eqcommand{ }{\makelabels}
789 \eqcommand{ }{\MakeLowercase}
790 \eqcommand{ }{\maketitle}
791 \eqcommand{ }{\MakeUppercase}
792 \eqcommand{ }{\marginpar}
793 \eqcommand{ }{\marginparpush}
794 \eqcommand{ }{\marginparsep}
795 \eqcommand{ }{\marginparwidth}
796 \eqcommand{ }{\mark}
797 \eqcommand{ }{\markboth}
798 \eqcommand{ }{\markright}
799 \eqcommand{ }{\mathaccent}
800 \eqcommand{ }{\mathchar}

```

```

801 \eqcommand{ }{mathchardef}
802 \eqcommand{ }{mathcode}
803 \eqcommand{ }{mathrm}
804 \eqcommand{ }{maxdeadcycles}
805 \eqcommand{ }{maxdepth}
806 \eqcommand{ }{maxdimen}
807 \eqcommand{ }{mbox}
808 \eqcommand{ }{mdseries}
809 \eqcommand{ }{meaning}
810 \eqcommand{ }{mediumseries}
811 \eqcommand{ }{medmuskip}
812 \eqcommand{ }{medskip}
813 \eqcommand{ }{medskipamount}
814 \eqcommand{ }{medspace}
815 \eqcommand{ }{message}
816 \eqcommand{ }{MessageBreak}
817 \eqcommand{ }{minrowclearance}
818 \eqcommand{ }{mkern}
819 \eqcommand{ }{month}
820 \eqcommand{ }{moveleft}
821 \eqcommand{ }{moveright}
822 \eqcommand{ }{mskip}
823 \eqcommand{ @ }{m@th}
824 \eqcommand{ }{multicolumn}
825 \eqcommand{ }{multiply}
826 \eqcommand{ }{multispan}
827 \eqcommand{ }{muskip}
828 \eqcommand{ }{muskipdef}
829 \eqcommand{@ }{@namedef}
830 \eqcommand{@ }{@nameuse}
831 \eqcommand{ @}{@ne}
832 \eqcommand{ }{name}
833 \eqcommand{ }{natural}
834 \eqcommand{ }{nearrow}
835 \eqcommand{ }{nearrower}
836 \eqcommand{ }{NeedsTeXFormat}
837 \eqcommand{ }{neg}
838 \eqcommand{ }{negmedspace}
839 \eqcommand{ }{negthickspace}
840 \eqcommand{ }{negthinspace}
841 \eqcommand{ }{newboolean}
842 \eqcommand{ }{newbox}
843 \eqcommand{ }{newcommand}
844 \eqcommand{ }{newcount}
845 \eqcommand{ }{newcounter}
846 \eqcommand{ }{newdimen}
847 \eqcommand{ }{newenvironment}
848 \eqcommand{ }{newfam}
849 \eqcommand{ }{newfont}
850 \eqcommand{ }{newhelp}

```

```

851 \eqcommand{ }{newinsert}
852 \eqcommand{ }{newlabel}
853 \eqcommand{ }{newlength}
854 \eqcommand{ }{newline}
855 \eqcommand{ }{newlinechar}
856 \eqcommand{ }{newmuskip}
857 \eqcommand{ }{newpage}
858 \eqcommand{ }{newread}
859 \eqcommand{ }{newsavebox}
860 \eqcommand{ }{newskip}
861 \eqcommand{ }{newtheorem}
862 \eqcommand{ }{newtoks}
863 \eqcommand{ }{newwrite}
864 \eqcommand{ }{noalign}
865 \eqcommand{ }{nobreak}
866 \eqcommand{ }{nobreakspace}
867 \eqcommand{ }{nocite}
868 \eqcommand{ }{noexpand}
869 \eqcommand{ }{nofiles}
870 \eqcommand{ }{noindent}
871 \eqcommand{ }{nointerlineskip}
872 \eqcommand{ }{nolimits}
873 \eqcommand{ }{nolinebreak}
874 \eqcommand{ }{nonstopmode}
875 \eqcommand{ }{nonfrenchspacing}
876 \eqcommand{ }{nonumber}
877 \eqcommand{ }{nopagebreak}
878 \eqcommand{ }{normalbaselines}
879 \eqcommand{ }{normalbaselineskip}
880 \eqcommand{ }{normalcolor}
881 \eqcommand{ }{normalfont}
882 \eqcommand{ }{normallineskip}
883 \eqcommand{ }{normallineskiplimit}
884 \eqcommand{ }{normalmarginpar}
885 \eqcommand{ }{normalsize}
886 \eqcommand{ }{notag}
887 \eqcommand{ }{null}
888 \eqcommand{ }{nullfont}
889 \eqcommand{ }{number}
890 \eqcommand{ }{numberline}
891 \eqcommand{ }{numberwithin}
892 \eqcommand{ }{@evenfoot}
893 \eqcommand{ }{@evenhead}
894 \eqcommand{ }{@oddfoot}
895 \eqcommand{ }{@oddhead}
896 \eqcommand{ }{@outeqntrue}
897 \eqcommand{ }{@outeqnfase}
898 \eqcommand{ }{obeylines}
899 \eqcommand{ }{obeyspaces}
900 \eqcommand{ }{oddsidemargin}

```

```

901 \eqcommand{      }{offinterlineskip}
902 \eqcommand{ }{omit}
903 \eqcommand{@      }{@onlypreamble}
904 \eqcommand{ }{onecolumn}
905 \eqcommand{      }{onlynotes}
906 \eqcommand{      }{onlyslides}
907 \eqcommand{      }{openin}
908 \eqcommand{      }{openout}
909 \eqcommand{      }{OptionNotUsed}
910 \eqcommand{ }{or}
911 \eqcommand{      }{outer}
912 \eqcommand{      }{output}
913 \eqcommand{      }{outputpenalty}
914 \eqcommand{      }{overfullrule}
915 \eqcommand{@      }{@preamblecmds}
916 \eqcommand{@ }{p@}
917 \eqcommand{      }{PackageError}
918 \eqcommand{      }{PackageInfo}
919 \eqcommand{      }{PackageWarning}
920 \eqcommand{      }{PackageWarningNoLine}
921 \eqcommand{      }{pagebreak}
922 \eqcommand{      }{pagecolor}
923 \eqcommand{      }{pagedepth}
924 \eqcommand{      }{pagefillstretch}
925 \eqcommand{      }{pagefillstretch}
926 \eqcommand{      }{pagefilstretch}
927 \eqcommand{      }{pagegoal}
928 \eqcommand{      }{pagename}
929 \eqcommand{      }{pagenumbering}
930 \eqcommand{      }{pageref}
931 \eqcommand{      }{pagerulewidth}
932 \eqcommand{      }{pageshrink}
933 \eqcommand{      }{pagestretch}
934 \eqcommand{      }{pagestyle}
935 \eqcommand{      }{pagetotal}
936 \eqcommand{      }{paperheight}
937 \eqcommand{      }{paperwidth}
938 \bidi@csdefcs{ }{par}%
% this is an exception since \par is redefined only in some circumstances
939 \eqcommand{      }{paragraph}
940 \eqcommand{      }{parallel}
941 \eqcommand{      }{parbox}
942 \eqcommand{      }{parfillskip}
943 \eqcommand{      }{parindent}
944 \eqcommand{      }{parsep}
945 \eqcommand{      }{parshape}
946 \eqcommand{      }{parskip}
947 \eqcommand{      }{part}
948 \eqcommand{      }{partname}
949 \eqcommand{      }{partopsep}
950 \eqcommand{      }{PassOptionToClass}

```

```

951 \eqcommand{ }{\PassOptionToPackage}
952 \eqcommand{ }{\path}
953 \eqcommand{ }{\patterns}
954 \eqcommand{ }{\pausing}
955 \eqcommand{ }{\penalty}
956 \eqcommand{ }{\phantom}
957 \eqcommand{ }{\poptabs}
958 \eqcommand{ }{\postdisplaypenalty}
959 \eqcommand{ }{\predisplaydirection}
960 \eqcommand{ }{\predisplaypenalty}
961 \eqcommand{ }{\predisplaysize}
962 \eqcommand{ }{\pretolerance}
963 \eqcommand{ }{\prevdepth}
964 \eqcommand{ }{\prevgraf}
965 \eqcommand{ }{\printindex}
966 \eqcommand{ }{\ProcessOptions}
967 \eqcommand{ }{\protect}
968 \eqcommand{ }{\providetcommand}
969 \eqcommand{ }{\ProvidesClass}
970 \eqcommand{ }{\ProvidesFile}
971 \eqcommand{ }{\ProvidesPackage}
972 \eqcommand{ }{\pushtabs}
973 \eqcommand{ }{\quad}
974 \eqcommand{ }{\quad}
975 \eqcommand{@ }{\@outputpagerestore}
976 \eqcommand{ }{\radical}
977 \eqcommand{ }{\raggedbottom}
978 \eqcommand{ }{\raggedleft}
979 \eqcommand{ }{\raggedright}
980 \eqcommand{ }{\raise}
981 \eqcommand{ }{\raisebox}
982 \eqcommand{ }{\raisetag}
983 \eqcommand{ }{\rangle}
984 \eqcommand{ }{\rceil}
985 \eqcommand{ }{\read}
986 \eqcommand{ }{\ref}
987 \eqcommand{ }{\reflectbox}
988 \eqcommand{ }{\refname}
989 \eqcommand{ }{\refstepcounter}
990 \eqcommand{ }{\relax}
991 \eqcommand{ }{\removelastskip}
992 \eqcommand{ }{\renewcommand}
993 \eqcommand{ }{\renewenvironment}
994 \eqcommand{ }{\RequirePackage}
995 \eqcommand{ }{\RequirePackageWithOptions}
996 \eqcommand{ }{\resizebox}
997 \eqcommand{ }{\reversemarginpar}
998 \eqcommand{ }{\rfloor}
999 \eqcommand{ }{\right}
1000 \eqcommand{ }{\rightmargin}

```

```

1001 \eqcommand{ }{rightmark}
1002 \eqcommand{ }{rightpageskip}
1003 \eqcommand{ }{rightskip}
1004 \eqcommand{ }{rmdefault}
1005 \eqcommand{ }{rmfamily}
1006 \eqcommand{ }{Roman}
1007 \eqcommand{ }{roman}
1008 \eqcommand{ }{romannumberal}
1009 \eqcommand{ }{rotatebox}
1010 \eqcommand{ }{rowcolor}
1011 \eqcommand{ }{rule}
1012 \eqcommand{@ }{@secondoftwo}
1013 \eqcommand{@ }{@spaces}
1014 \eqcommand{ }{samepage}
1015 \eqcommand{ }{savebox}
1016 \eqcommand{ }{sbox}
1017 \eqcommand{ }{scalebox}
1018 \eqcommand{ }{scdefault}
1019 \eqcommand{ }{scshape}
1020 \eqcommand{ }{setkeys}
1021 \eqcommand{ }{scriptfont}
1022 \eqcommand{ }{scriptscriptfont}
1023 \eqcommand{ }{scriptscriptstyle}
1024 \eqcommand{ }{scriptsize}
1025 \eqcommand{ }{scripstyle}
1026 \eqcommand{ }{scrollmode}
1027 \eqcommand{ }{section}
1028 \eqcommand{ }{secdef}
1029 \eqcommand{ }{see}
1030 \eqcommand{ }{seealso}
1031 \eqcommand{ }{seename}
1032 \eqcommand{ }{selectfont}
1033 \eqcommand{ }{setboolean}
1034 \eqcommand{ }{setbox}
1035 \eqcommand{ }{setcounter}
1036 \eqcommand{ }{setlength}
1037 \eqcommand{ }{setminus}
1038 \eqcommand{ }{SetSymbolFont}
1039 \eqcommand{ }{settodepth}
1040 \eqcommand{ }{settoheight}
1041 \eqcommand{ }{settowidth}
1042 \eqcommand{ }{sfcode}
1043 \eqcommand{ }{sfdefault}
1044 \eqcommand{ }{sffamily}
1045 \eqcommand{ }{shadowbox}
1046 \eqcommand{ }{sharp}
1047 \eqcommand{ }{shipout}
1048 \eqcommand{ }{shortstack}
1049 \eqcommand{ }{show}
1050 \eqcommand{ }{showbox}

```

```

1051 \eqcommand{      }{\showboxbreadth}
1052 \eqcommand{      }{\showboxdepth}
1053 \eqcommand{      }{\showlists}
1054 \eqcommand{      }{\showthe}
1055 \eqcommand{      }{\simplefontmode}
1056 \eqcommand{ @}{\sixt@n}
1057 \eqcommand{      }{\skewchar}
1058 \eqcommand{      }{\skip}
1059 \eqcommand{ @}{\skip@}
1060 \eqcommand{      }{\skipdef}
1061 \eqcommand{      }{\sl}
1062 \eqcommand{      }{\sldefault}
1063 \eqcommand{      }{\slshape}
1064 \eqcommand{      }{\sloppy}
1065 \eqcommand{      }{\slshape}
1066 \eqcommand{      }{\small}
1067 \eqcommand{      }{\smallskip}
1068 \eqcommand{      }{\smallskipamount}
1069 \eqcommand{      }{\smash}
1070 \eqcommand{      }{\smile}
1071 \eqcommand{      }{\snglfntlocatecode}
1072 \eqcommand{      }{\space}
1073 \eqcommand{      }{\spacefactor}
1074 \eqcommand{      }{\spaceskip}
1075 \eqcommand{      }{\spadesuit}
1076 \eqcommand{      }{\span}
1077 \eqcommand{      }{\special}
1078 \eqcommand{      }{\splitmaxdepth}
1079 \eqcommand{      }{\splittopskip}
1080 \eqcommand{      }{\star}
1081 \eqcommand{      }{\stepcounter}
1082 \eqcommand{      }{\stretch}
1083 \eqcommand{      }{\string}
1084 \eqcommand{      }{\strut}
1085 \eqcommand{      }{\strutbox}
1086 \eqcommand{      }{\subitem}
1087 \eqcommand{      }{\subparagraph}
1088 \eqcommand{      }{\subsection}
1089 \eqcommand{      }{\substack}
1090 \eqcommand{      }{\subsubitem}
1091 \eqcommand{      }{\subsubsection}
1092 \eqcommand{      }{\subset}
1093 \eqcommand{      }{\subsetseteq}
1094 \eqcommand{      }{\supereject}
1095 \eqcommand{      }{\suppressfloats}
1096 \eqcommand{@}{\@tempa}
1097 \eqcommand{@}{\@tempb}
1098 \eqcommand{@}{\@tempc}
1099 \eqcommand{@}{\@tempd}
1100 \eqcommand{@}{\@tempe}

```

```

1101 \eqcommand{@ }{@tempboxa}
1102 \eqcommand{@ }{@tempcnta}
1103 \eqcommand{@ }{@tempcntb}
1104 \eqcommand{@ }{@tempdima}
1105 \eqcommand{@ }{@tempdimb}
1106 \eqcommand{@ }{@tempdimc}
1107 \eqcommand{@ }{@tempskipa}
1108 \eqcommand{@ }{@tempskipb}
1109 \eqcommand{@ }{@tempswafalse}
1110 \eqcommand{@ }{@tempswatrue}
1111 \eqcommand{@ }{@temptokena}
1112 \eqcommand{ }{@thefnmark}
1113 \eqcommand{@ }{@thirdofthree}
1114 \eqcommand{ }{@tabbingsep}
1115 \eqcommand{ }{@tabcolsep}
1116 \eqcommand{ }{@tableofcontents}
1117 \eqcommand{ }{@tablename}
1118 \eqcommand{ }{@tabskip}
1119 \eqcommand{ }{@tabularnewline}
1120 \eqcommand{ }{@tag}
1121 \eqcommand{ }{@telephone}
1122 \eqcommand{ }{@TeX}
1123 \eqcommand{ }{@text}
1124 \eqcommand{ }{@textbullet}
1125 \eqcommand{ }{@textfont}
1126 \eqcommand{ }{@textemdash}
1127 \eqcommand{ }{@textendash}
1128 \eqcommand{ }{@textexclamdown}
1129 \eqcommand{ }{@textperiodcentered}
1130 \eqcommand{ }{@textquestiondown}
1131 \eqcommand{ }{@textquotedblleft}
1132 \eqcommand{ }{@textquotedblright}
1133 \eqcommand{ }{@textquotelleft}
1134 \eqcommand{ }{@textquoteright}
1135 \eqcommand{ }{@textvisiblespace}
1136 \eqcommand{ }{@textbackslash}
1137 \eqcommand{ }{@textbar}
1138 \eqcommand{ }{@textgreater}
1139 \eqcommand{ }{@textless}
1140 \eqcommand{ }{@textbf}
1141 \eqcommand{ }{@textcircled}
1142 \eqcommand{ }{@textcolor}
1143 \eqcommand{ }{@textcompwordmark}
1144 \eqcommand{ }{@textfloatsep}
1145 \eqcommand{ }{@textfraction}
1146 \eqcommand{ }{@textheight}
1147 \eqcommand{ }{@textindent}
1148 \eqcommand{ }{@textit}
1149 \eqcommand{ }{@textmd}
1150 \eqcommand{ }{@textnormal}

```

```

1151 \eqcommand{ }{textregistered}
1152 \eqcommand{ }{textrm}
1153 \eqcommand{ }{textsc}
1154 \eqcommand{ }{textsf}
1155 \eqcommand{ }{textsl}
1156 \eqcommand{ }{textstyle}
1157 \eqcommand{ }{textsuperscript}
1158 \eqcommand{ }{texttrademark}
1159 \eqcommand{ }{texttt}
1160 \eqcommand{ }{textup}
1161 \eqcommand{ }{textwidth}
1162 \eqcommand{ }{thanks}
1163 \eqcommand{ }{the}
1164 \eqcommand{ }{thempfn}
1165 \eqcommand{ }{thicklines}
1166 \eqcommand{ }{thickmuskip}
1167 \eqcommand{ }{thinmuskip}
1168 \eqcommand{ }{thickspace}
1169 \eqcommand{ }{thinlines}
1170 \eqcommand{ }{thinspace}
1171 \eqcommand{ }{thisfancypage}
1172 \eqcommand{ }{thispagestyle}
1173 \eqcommand{ @}{thr@@}
1174 \eqcommand{ }{tilde}
1175 \eqcommand{ }{tiny}
1176 \eqcommand{ }{time}
1177 \eqcommand{ }{times}
1178 \eqcommand{ }{title}
1179 \eqcommand{ }{to}
1180 \eqcommand{ }{today}
1181 \eqcommand{ }{toks}
1182 \eqcommand{ }{toksdef}
1183 \eqcommand{ }{tolerance}
1184 \eqcommand{ }{top}
1185 \eqcommand{ }{topfigrule}
1186 \eqcommand{ }{topfraction}
1187 \eqcommand{ }{topmargin}
1188 \eqcommand{ }{topmark}
1189 \eqcommand{ }{toppageskip}
1190 \eqcommand{ }{topsep}
1191 \eqcommand{ }{topskip}
1192 \eqcommand{ }{totalheight}
1193 \eqcommand{ }{tracingall}
1194 \eqcommand{ }{tracingcommands}
1195 \eqcommand{ }{tracinglostchars}
1196 \eqcommand{ }{tracingmacros}
1197 \eqcommand{ }{tracingonline}
1198 \eqcommand{ }{tracingoutput}
1199 \eqcommand{ }{tracingpages}
1200 \eqcommand{ }{tracingparagraphs}

```

```

1201 \eqcommand{      }{tracingrestores}
1202 \eqcommand{      }{tracingstats}
1203 \eqcommand{  }{triangle}
1204 \eqcommand{      }{ttdefault}
1205 \eqcommand{      }{ttfamily}
1206 \eqcommand{ @}{two@}
1207 \eqcommand{      }{twocolumn}
1208 \eqcommand{      }{typein}
1209 \eqcommand{      }{typeout}
1210 \eqcommand{      }{uccode}
1211 \eqcommand{      }{uchyph}
1212 \eqcommand{      }{underline}
1213 \eqcommand{      }{unhbox}
1214 \eqcommand{      }{unhcopy}
1215 \eqcommand{      }{unitlength}
1216 \eqcommand{      }{unkern}
1217 \eqcommand{      }{unpenalty}
1218 \eqcommand{      }{unskip}
1219 \eqcommand{      }{unvbox}
1220 \eqcommand{      }{unvcopy}
1221 \eqcommand{      }{updefault}
1222 \eqcommand{      }{upshape}
1223 \eqcommand{      }{usebox}
1224 \eqcommand{      }{usecounter}
1225 \eqcommand{      }{usefont}
1226 \eqcommand{      }{usepackage}
1227 \eqcommand{@ }{ @}{vobeyspaces}
1228 \eqcommand{@ }{ @}{void}
1229 \eqcommand{      }{vadjust}
1230 \eqcommand{      }{valign}
1231 \eqcommand{      }{value}
1232 \eqcommand{      }{vbadness}
1233 \eqcommand{      }{vbox}
1234 \eqcommand{      }{vcenter}
1235 \eqcommand{      }{verb}
1236 \eqcommand{      }{vfil}
1237 \eqcommand{      }{vfill}
1238 \eqcommand{      }{vfilneg}
1239 \eqcommand{      }{vfuzz}
1240 \eqcommand{      }{visible}
1241 \eqcommand{      }{vline}
1242 \eqcommand{      }{voffset}
1243 \eqcommand{ @ }{ @}{voidb@x}
1244 \eqcommand{      }{vpageref}
1245 \eqcommand{      }{vrboxsep}
1246 \eqcommand{      }{vref}
1247 \eqcommand{      }{vrule}
1248 \eqcommand{      }{vsized}
1249 \eqcommand{      }{vskip}
1250 \eqcommand{      }{vspace}

```

```

1251 \eqcommand{ }{vsplit}
1252 \eqcommand{ }{vss}
1253 \eqcommand{ }{vtop}
1254 \eqcommand{ }{wd}
1255 \eqcommand{ }{whiledo}
1256 \eqcommand{ }{widehat}
1257 \eqcommand{ }{widetilde}
1258 \eqcommand{ }{widowpenalty}
1259 \eqcommand{ }{width}
1260 \eqcommand{ }{wlog}
1261 \eqcommand{ }{write}
1262 \eqcommand{@ }{@obeysp}
1263 \eqcommand{ @ }{@xxxii}
1264 \eqcommand{ }{xdef}
1265 \eqcommand{ }{xleaders}
1266 \eqcommand{ }{xspaceskip}
1267 \eqcommand{ }{year}
1268 \eqcommand{@ }{z@}
1269 \eqcommand{@ }{z@skip}

```

## 7.18 color-localise-xepersian.def

```

1270 color}      {-localise-xepersian.def}[2011/03/01 v0.1 localising color package]
1271 0}{rgb}{ }  \0,,0}
1272 1}{rgb}{ }  \1,,1}
1273 1}{rgb}{ }  \0,,0}
1274 0}{rgb}{ }  \1,,0}
1275 0}{rgb}{ }  \0,,1}
1276 1}{cmyk}{ } \0,,0,0}
1277 0}{cmyk}{ } \1,,0,0}
1278 0}{cmyk}{ } \0,,1,0}

```

## 7.19 xepersian-localise-commands-xepersian.def

```

1279 \ProvidesFile{xepersian-localise-commands-xepersian.def}[2012/07/25 v0.2 Persian localisation o
1280 \eqcommand{ }{autofootnoterule}
1281 \eqcommand{ }{AutoMathsDigits}
1282 \eqcommand{ }{DefaultMathsDigits}
1283 \eqcommand{ @ }{keyval@eq@alias@key}
1284 \eqcommand{ }{deflatinfont}
1285 \eqcommand{ }{defpersianfont}
1286 \eqcommand{ }{hboxL}
1287 \eqcommand{ }{hboxR}
1288 \eqcommand{ }{Latincite}
1289 \eqcommand{ }{latinfont}
1290 \eqcommand{ }{latintoday}
1291 \eqcommand{ }{leftfootnoterule}
1292 \eqcommand{ }{lr}
1293 \eqcommand{ }{LRE}
1294 \eqcommand{ }{LTRdblcol}
1295 \eqcommand{ }{LTRfootnote}

```

```

1296 \eqcommand{ }{LTRfootnotetext}
1297 \eqcommand{ }{LTRthanks}
1298 \eqcommand{ }{persianday}
1299 \eqcommand{ }{persianfont}
1300 \eqcommand{ }{PersianMathsDigits}
1301 \eqcommand{ }{persianmonth}
1302 \eqcommand{ }{persianyear}
1303 \eqcommand{ }{plq}
1304 \eqcommand{ }{prq}
1305 \eqcommand{ }{rightfootnoterule}
1306 \eqcommand{ }{rl}
1307 \eqcommand{ }{RLE}
1308 \eqcommand{ }{RTLdblcol}
1309 \eqcommand{ }{RTLfootnote}
1310 \eqcommand{ }{RTLfootnotetext}
1311 \eqcommand{ }{RTLthanks}
1312 \eqcommand{@ }{@SepMark}
1313 \eqcommand{ }{SepMark}
1314 \eqcommand{ }{setdefaultbibitems}
1315 \eqcommand{ }{setdefaultmarginpar}
1316 \eqcommand{ }{setdigitfont}
1317 \eqcommand{ }{setfootnoteLR}
1318 \eqcommand{ }{setfootnoteRL}
1319 \eqcommand{ }{setlatintextfont}
1320 \eqcommand{ }{setLTR}
1321 \eqcommand{ }{setLTRbibitems}
1322 \eqcommand{ }{setLTRmarginpar}
1323 \eqcommand{ }{setRTL}
1324 \eqcommand{ }{setRTLbibitems}
1325 \eqcommand{ }{setRTLmarginpar}
1326 \eqcommand{ }{settextfont}
1327 \eqcommand{ }{textwidthfootnoterule}
1328 \eqcommand{ }{twocolumnstableofcontents}
1329 \eqcommand{ }{unsetfootnoteRL}
1330 \eqcommand{ }{unsetLTR}
1331 \eqcommand{ }{unsetRTL}
1332 \eqcommand{ }{vboxL}
1333 \eqcommand{ }{vboxR}
1334 \eqcommand{ }{XeLaTeX}
1335 \eqcommand{ }{XePersian}
1336 \eqcommand{ }{xepersianversion}
1337 \eqcommand{ }{xepersiandate}
1338 \eqcommand{ }{XeTeX}

```

## 7.20 enumerate-xepersian.def

```

1339 \ProvidesFile{enumerate-xepersian.def}[2010/07/25 v0.1 adaptations for enumerate package]
1340 \def\@enloop@{%
1341   \ifx\entemp@\relax \def\@tempa{\@enLabel\harfi} \else
1342   \ifx\entemp@\relax \def\@tempa{\@enLabel\adadi} \else

```

## 7.21 `fontspec-xetex-xepersian.def`

```
1356 \ProvidesFile{fontspec-xetex-xepersian.def}[2014/10/07 v0.1 fixes for fontspec-xetex package]
1357 \ExplSyntaxOn
1358 \DeclareDocumentCommand \aliasfontfeature {mm}
1359 {
1360   \keys_if_exist:nnTF {fontspec} {#1}
1361   {
1362     \keys_define:nn {fontspec}
1363     { #2 .code:n = { \keys_set:nn {fontspec} { #1 = {##1} } } }
1364   }
1365   {
1366     \keys_if_exist:nnTF {fontspec-renderer} {#1}
1367   }
1368   \keys_define:nn {fontspec-renderer}
1369   { #2 .code:n = { \keys_set:nn {fontspec-renderer} { #1 = {##1} } } }
1370 }
1371 {
1372   \keys_if_exist:nnTF {fontspec-preparse} {#1}
1373   {
1374     \keys_define:nn {fontspec-preparse}
1375     { #2 .code:n = { \keys_set:nn {fontspec-preparse} { #1 = {##1} } } }
1376   }
1377   {
1378     \keys_if_exist:nnTF {fontspec-preparse-external} {#1}
1379   }
1380   \keys_define:nn {fontspec-preparse-external}
1381   {
1382     #2 .code:n =
1383     { \keys_set:nn {fontspec-preparse-external} { #1 = {##1} } }
1384   }
1385 }
1386 {
1387   \__fontspec_warning:nx {rename-feature-not-exist} {#1}
1388 }
1389 }
```

```

1390      }
1391      }
1392  }
1393 \ExplSyntaxOff

```

## 7.22 latex-localise-environments-xepersian.def

```

1394 \ProvidesFile{latex-localise-environments-xepersian.def}[2010/07/25 v0.2 Persian localisation of
1395 \eqenvironment{ }{abstract}
1396 \eqenvironment{ }{appendix}
1397 \eqenvironment{ }{array}
1398 \eqenvironment{ }{center}
1399 \eqenvironment{ }{description}
1400 \eqenvironment{ }{displaymath}
1401 \eqenvironment{ }{document}
1402 \eqenvironment{ }{enumerate}
1403 \eqenvironment{ }{figure}
1404 \eqenvironment{ *}{figure*}
1405 \eqenvironment{ }{filecontents}
1406 \eqenvironment{ *}{filecontents*}
1407 \eqenvironment{ }{flushleft}
1408 \eqenvironment{ }{flushright}
1409 \eqenvironment{ }{itemize}
1410 \eqenvironment{ }{letter}
1411 \eqenvironment{ }{list}
1412 \eqenvironment{ }{longtable}
1413 \eqenvironment{ }{lrbox}
1414 \eqenvironment{ }{math}
1415 \eqenvironment{ }{matrix}
1416 \eqenvironment{ }{minipage}
1417 \eqenvironment{ }{multiline}
1418 \eqenvironment{ }{note}
1419 \eqenvironment{ }{overlay}
1420 \eqenvironment{ }{picture}
1421 \eqenvironment{ }{quotation}
1422 \eqenvironment{ }{quote}
1423 \eqenvironment{ }{slide}
1424 \eqenvironment{ }{sloppypar}
1425 \eqenvironment{ }{split}
1426 \eqenvironment{ }{subarray}
1427 \eqenvironment{ }{tabbing}
1428 \eqenvironment{ }{table}
1429 \eqenvironment{ *}{table*}
1430 \eqenvironment{ }{tabular}
1431 \eqenvironment{ *}{tabular*}
1432 \eqenvironment{ }{thebibliography}
1433 \eqenvironment{ }{theindex}
1434 \eqenvironment{ }{titlepage}
1435 \eqenvironment{ }{trivlist}
1436 \eqenvironment{ }{verse}

```

## 7.23 xepersian-localise-environments-xepersian.def

```
1437 \ProvidesFile{xepersian-localise-environments-xepersian.def}[2010/07/25 v0.1 Persian localisat
1438 \eqenvironment{ }{latin}
1439 \eqenvironment{ }{LTR}
1440 \eqenvironment{ }{LTRitems}
1441 \eqenvironment{ }{modernpoem}
1442 \eqenvironment{ *}{modernpoem*}
1443 \eqenvironment{ }{persian}
1444 \eqenvironment{ }{RTL}
1445 \eqenvironment{ }{RTLitems}
1446 \eqenvironment{ }{traditionalpoem}
1447 \eqenvironment{ *}{traditionalpoem*}
```

## 7.24 extarticle-xepersian.def

```
1448 \ProvidesFile{extarticle-xepersian.def}[2010/07/25 v0.1 adaptations for extarticle class]
1449 \renewcommand{\thepart}{\@tartibi\c@part}
1450 \renewcommand{\appendix}{\par
1451   \setcounter{section}{0}%
1452   \setcounter{subsection}{0}%
1453   \gdef\thesection{\@harfi\c@section}}
```

## 7.25 extbook-xepersian.def

```
1454 \ProvidesFile{extbook-xepersian.def}[2010/07/25 v0.1 adaptations for extbook class]
1455 \renewcommand{\frontmatter}{%
1456   \cleardoublepage
1457   \mainmatterfalse
1458   \pagenumbering{harfi}}
1459 \renewcommand{\thepart}{\@tartibi\c@part}
1460 \renewcommand{\appendix}{\par
1461   \setcounter{chapter}{0}%
1462   \setcounter{section}{0}%
1463   \gdef\@chapapp{\appendixname}%
1464   \gdef\thechapter{\@harfi\c@chapter}
1465 }%end appendix
```

## 7.26 extrafootnotefeatures-xepersian.def

```
1466 \ProvidesFile{extrafootnotefeatures-xepersian.def}[2012/01/01 v0.2 footnote macros for extrafoo
1467 \renewcommand{\foottextfont}{\footnotesize\if@RTL@footnote\else\latinfont\fi}
1468 \renewcommand{\LTRfoottextfont}{\footnotesize\latinfont}
1469 \renewcommand{\RTLfoottextfont}{\footnotesize\persianfont}
```

## 7.27 extreport-xepersian.def

```
1470 \ProvidesFile{extreport-xepersian.def}[2010/07/25 v0.1 adaptations for extreport class]
1471 \renewcommand{\thepart}{\@tartibi\c@part}
1472 \renewcommand{\appendix}{\par
1473   \setcounter{chapter}{0}%
1474   \setcounter{section}{0}%
1475   \gdef\@chapapp{\appendixname}}%
```

```
1476 \gdef\thechapter{\@harfi\c@chapter}}
```

## 7.28 flowfram-xepersian.def

```
1477 \ProvidesFile{flowfram-xepersian.def}[2010/07/25 v0.1 adaptations for flowfram package]
1478 \def\@outputpage{%
1479 \begingroup
1480   \let\protect\noexpand
1481   \resetactivechars
1482   \global\let\@if@newlist\if@newlist
1483   \global\@newlistfalse\parboxrestore
1484   \shipout\vbox{\set@typeset@protect
1485     \aftergroup
1486     \endgroup
1487     \aftergroup
1488     \set@typeset@protect
1489     \reset@font\normalsize\normalsfcodes
1490     \let\label@gobble
1491     \let\index@gobble
1492     \let\glossary@gobble
1493     \baselineskip\z@skip
1494     \lineskip\z@skip
1495     \lineskiplimit\z@
1496     \vskip\topmargin\moveoveright\themargin
1497     \vbox{%
1498       \vskip\headheight
1499       \vskip\headsep
1500       \box\@outputbox
1501     }%
1502   \global\let\if@newlist\@if@newlist
1503   \stepcounter{page}%
1504   \setcounter{displayedframe}{0}%
1505   \let\firstmark\botmark}
```

## 7.29 footnote-xepersian.def

```
1506 \ProvidesFile{footnote-xepersian.def}[2013/04/26 v0.4 footnote macros for xepersian package]
1507
1508
1509
1510 \long\def\@footnotetext#1{\insert\footins{%
1511   \if@RTL\footnote\@RTLtrue\else\@RTLfalse\fi%
1512   \reset@font\footnotesize
1513   \interlinepenalty\interfootnotelinepenalty
1514   \splittopskip\footnotesep
1515   \splitmaxdepth \dp\strutbox \floatingpenalty \z@MM
1516   \hsize\columnwidth \parboxrestore
1517   \protected@edef\@currentlabel{%
1518     \csname p@footnote\endcsname\@thefnmark
1519   }%
1520   \color@begingroup
```

```

1521     \@makefntext{%
1522     \rule{z@\footnotesep}{ignorespaces\if@RTL@footnote#1\else\latinfont#1\fi\@finalstrut\strut}%
1523     \color@endgroup}%
1524
1525
1526
1527
1528
1529 \long\def\@RTLfootnotetext#1{\insert\footins{%
1530     \@RTLtrue%
1531     \reset@font\footnotesize
1532     \interlinepenalty\interfootnotelinepenalty
1533     \splittopskip\footnotesep
1534     \splitmaxdepth \dp\strutbox \floatingpenalty \OMM
1535     \hsize\columnwidth \parboxrestore
1536     \protected@edef\@currentlabel{%
1537         \csname p@footnote\endcsname\@thefnmark
1538     }%
1539     \color@begingroup
1540         \@makefntext{%
1541             \rule{z@\footnotesep}{ignorespaces\persianfont #1\@finalstrut\strutbox}%
1542             \color@endgroup}%
1543
1544
1545
1546
1547
1548 \long\def\@LTRfootnotetext#1{\insert\footins{%
1549     \@RTLfalse%
1550     \reset@font\footnotesize
1551     \interlinepenalty\interfootnotelinepenalty
1552     \splittopskip\footnotesep
1553     \splitmaxdepth \dp\strutbox \floatingpenalty \OMM
1554     \hsize\columnwidth \parboxrestore
1555     \protected@edef\@currentlabel{%
1556         \csname p@footnote\endcsname\@thefnmark
1557     }%
1558     \color@begingroup
1559         \@makefntext{%
1560             \rule{z@\footnotesep}{ignorespaces\latinfont #1\@finalstrut\strutbox}%
1561             \color@endgroup}%
1562
1563 \footdir@temp\footdir@ORG@xpersian@footnotetext\@footnotetext{\bidi@footdir@footnote}%
1564 \footdir@temp\footdir@ORG@xpersian@RTLfootnotetext\@RTLfootnotetext{R}%
1565 \footdir@temp\footdir@ORG@xpersian@LTRfootnotetext\@LTRfootnotetext{L}%
1566
1567
1568
1569 \long\def\@mpfootnotetext#1{%
1570 \ifbidi@autofootnoterule\ifnum\c@mpfootnote=\@ne\if@RTL@footnote\global\let\bidi@mpfootnoterule

```

```

1571 \global\setbox\@mpfootins\vbox{\if@RTL@footnote\@RTLtrue\else\@RTLfalse\fi%
1572   \unvbox\@mpfootins
1573   \reset@font\footnotesize
1574   \hsize\columnwidth
1575   \parboxrestore
1576   \protected@edef\@currentlabel
1577     {\csname p@mpfootnote\endcsname\@thefnmark}%
1578   \color@begingroup
1579     \makefntext{%
1580       \rule{z@\footnotesep\ignorespaces\if@RTL@footnote#1\else\latinfont#1\fi\@finalstrut\strutbox}%
1581     }%
1582
1583
1584
1585
1586
1587 \long\def\@mpRTLfootnotetext#1{%
1588   \ifbidi@autofootnoterule\ifnum\c@mpfootnote=\@ne\global\let\bidi@mpfootnoterule\right@footno%
1589   \global\setbox\@mpfootins\vbox{\@RTLtrue%
1590     \unvbox\@mpfootins
1591     \reset@font\footnotesize
1592     \hsize\columnwidth
1593     \parboxrestore
1594     \protected@edef\@currentlabel
1595       {\csname p@mpfootnote\endcsname\@thefnmark}%
1596     \color@begingroup
1597       \makefntext{%
1598         \rule{z@\footnotesep\ignorespaces\persianfont #1\@finalstrut\strutbox}%
1599       }%
1600
1601
1602 \long\def\@mpLTRfootnotetext#1{%
1603   \ifbidi@autofootnoterule\ifnum\c@mpfootnote=\@ne\global\let\bidi@mpfootnoterule\left@footno%
1604   \global\setbox\@mpfootins\vbox{\@RTLfalse%
1605     \unvbox\@mpfootins
1606     \reset@font\footnotesize
1607     \hsize\columnwidth
1608     \parboxrestore
1609     \protected@edef\@currentlabel
1610       {\csname p@mpfootnote\endcsname\@thefnmark}%
1611     \color@begingroup
1612       \makefntext{%
1613         \rule{z@\footnotesep\ignorespaces\latinfont #1\@finalstrut\strutbox}%
1614       }%

```

### 7.30 framed-xepersian.def

```

1615 \ProvidesFile{framed-xepersian.def}[2012/06/05 v0.1 xepersian adaptations for framed package for%
1616 \renewenvironment{titled-frame}[1]{%
1617   \def\FrameCommand{\fboxsep8pt\fboxrule2pt

```

```
1618 \TitleBarFrame{\textbf{\#1}}%
1619 \def\FirstFrameCommand{\fboxsep8pt\fboxrule2pt
1620   \TitleBarFrame[$\if@RTL\blacktriangleleft\else\blacktriangleright\fi$]{\textbf{\#1}}%
1621 \def\MidFrameCommand{\fboxsep8pt\fboxrule2pt
1622   \TitleBarFrame[$\if@RTL\blacktriangleleft\else\blacktriangleright\fi$]{\textbf{\#1}\ (\if@RT
1623 \def\LastFrameCommand{\fboxsep8pt\fboxrule2pt
1624   \TitleBarFrame{\textbf{\#1}\ (\if@RTL\else\cont\fi)}}}%
1625 \MakeFramed{\advance\hspace{-20pt}\FrameRestore}%
1626 % note: 8 + 2 + 8 + 2 = 20. Don't use \width because the frame title
1627 % could interfere with the width measurement.
1628 {\endMakeFramed}
```

## 7.31 glossaries-xepersian.def

```

1665   \gls@disablepagerefexpansion
1666   \protected@xdef\@glslocref{\the\glsentrycounter}%
1667 \endgroup
1668 \@gls@checkmkidxchars\@glslocref
1669 \expandafter\ifx\the\glsentrycounter\the\glsentrycounter
1670   \def\@glo@counterprefix{}%
1671 \else
1672   \protected@edef\@glsHlocref{\the\glsentrycounter}%
1673   \@gls@checkmkidxchars\@glsHlocref
1674   \edef\@do@gls@getcounterprefix{\noexpand\@gls@getcounterprefix
1675     {\@glslocref}{\@glsHlocref}}%
1676   }%
1677   \@do@gls@getcounterprefix
1678 \fi
1679 \ifglsxindy
1680   \expandafter\@glo@check@mkidxrangechar\@glsnumberformat\@nil
1681   \def\@glo@range{}%
1682   \expandafter\if\@glo@prefix(\relax
1683     \def\@glo@range{:open-range}%
1684   \else
1685     \expandafter\if\@glo@prefix)\relax
1686     \def\@glo@range{:close-range}%
1687   \fi
1688 \fi
1689 \glossary[{\csname glo@\#1@type\endcsname}{}%
1690   (indexentry :tkey (\csname glo@\#1@index\endcsname)
1691   :locref \string"\{@glo@counterprefix}\{@glslocref}\string" %
1692   :attr \string"\@gls@counter\@glo@suffix\string"
1693   \@glo@range
1694   )
1695   }%
1696 \else
1697   \@set@glo@numformat{\@glo@numfmt}{\@gls@counter}{\@glsnumberformat}%
1698   {\@glo@counterprefix}%
1699   \glossary[{\csname glo@\#1@type\endcsname}{}%
1700   \string\glossaryentry{\csname glo@\#1@index\endcsname
1701   \@gls@encapchar\@glo@numfmt}\{@glslocref}{}%
1702 \fi
1703 }

```

### 7.32 hyperref-xepersian.def

```

1704 \ProvidesFile{hyperref-xepersian.def}[2013/04/09 v0.5 bilingual captions for hyperref package]
1705   \def\equationautorefname{\if@RTL else\quad Equation\fi}%
1706   \def\footnoteautorefname{\if@RTL else\quad footnote\fi}%
1707   \def\itemautorefname{\if@RTL else\quad item\fi}%
1708   \def\figureautorefname{\if@RTL else\quad Figure\fi}%
1709   \def\tableautorefname{\if@RTL else\quad Table\fi}%
1710   \def\partautorefname{\if@RTL else\quad Part\fi}%
1711   \def\appendixautorefname{\if@RTL else\quad Appendix\fi}%

```

```

1712 \def\chapterautorefname{\if@RTL else\ chapter\fi}%
1713 \def\sectionautorefname{\if@RTL else\ section\fi}%
1714 \def\subsectionautorefname{\if@RTL else\ subsection\fi}%
1715 \def\subsubsectionautorefname{\if@RTL else\ subsubsection\fi}%
1716 \def\paragraphautorefname{\if@RTL else\ paragraph\fi}%
1717 \def\ subparagraphautorefname{\if@RTL else\ subparagraph\fi}%
1718 \def\FancyVerbLineautorefname{\if@RTL else\ line\fi}%
1719 \def\theoremautorefname{\if@RTL else\ Theorem\fi}%
1720 \def\pageautorefname{\if@RTL else\ page\fi}%
1721 \AtBeginDocument{%
1722 \let\HyOrg@appendix\appendix
1723 \def\appendix{%
1724   \ltx@ifundefined{chapter}{%
1725     {\gdef\theHsection{\Alph{section}}}{%
1726       {\gdef\theHchapter{\Alph{chapter}}}{%
1727         \xdef\Hy@chapapp{\Hy@appendixstring}%
1728         \HyOrg@appendix
1729       }%
1730     }%
1731   \pdfstringdefDisableCommands{%
1732     \let\lr@\firstofone
1733     \let\rl@\firstofone
1734     \def\XePersian{\XePersian}
1735   }%

```

### 7.33 imsproc-xepersian.def

```

1736 \ProvidesFile{imsproc-xepersian.def}[2013/04/26 v0.3 implementation of imsproc class for xepersian]
1737 \newenvironment{thebibliography}[1]{%
1738   \@bibtitlestyle
1739   \normalfont\bibliofont\labelsep .5em\relax
1740   \renewcommand\theenumiv{\arabic{enumiv}}\let\p@enumiv\empty
1741   \if@RTL\if@LTRbibitems@\RTLfalse\else\fi\else\if@RTLbibitems@\RTLtrue\else\fi\fi
1742   \list{\@biblabel{\theenumiv}}{\settowidth\labelwidth{\@biblabel{#1}}%
1743     \leftmargin\labelwidth\advance\leftmargin\labelsep
1744     \usecounter{enumiv}}%
1745   \sloppy \clubpenalty\OM \widowpenalty\clubpenalty
1746   \sfcode`.=\OM
1747 }{%
1748   \def\@noitemerr{\@latex@warning{Empty `thebibliography' environment}}%
1749   \endlist
1750 }
1751 \def\theindex{\restonecoltrue\if@twocolumn\restonecolfalse\fi
1752   \columnseprule\z@\columnsep 35\p@
1753   \indextitlestyle
1754   \thispagestyle{plain}%
1755   \let\item\idxitem
1756   \parindent\z@ \parskip\z@\@plus.3\p@\relax
1757   \if@RTL\raggedleft\else\raggedright\fi
1758   \hyphenpenalty\OM

```

```

1759   \footnotesize}
1760 \def\@idxitem{\par\hangindent \if@RTL-\fi2em}
1761 \def\subitem{\par\hangindent \if@RTL-\fi2em\hspace*{1em}}
1762 \def\subsubitem{\par\hangindent \if@RTL-\fi3em\hspace*{2em}}
1763 \renewcommand \theprt {\@startibi\c@prt}
1764 \def\appendix{\par\c@section\z@ \c@subsection\z@
1765   \let\sectionname\appendixname
1766   \def\thesection{\@harfi\c@section}}
1767 \def\right@footnoterule{%
1768   \hbox to \columnwidth
1769   {\beginR \vbox{\kern-.4\p@
1770     \hrule\@width 5pc\kern11\p@\kern-\footnotesep}\hfil\endR}}
1771 \def\left@footnoterule{\kern-.4\p@
1772   \hrule\@width 5pc\kern11\p@\kern-\footnotesep}
1773 \def\@makefnmark{%
1774   \leavevmode
1775   \raise.9ex\hbox{\footnotesize\sf@size\z@\normalfont\@thefnmark}%
1776 }
1777
1778
1779
1780 \long\def\@footnotetext#1{%
1781   \insert\footins{%
1782     \if@RTL@footnote\@RTLtrue\else\@RTLfalse\fi%
1783     \normalfont\footnotesize
1784     \interlinepenalty\interfootnotelinepenalty
1785     \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
1786     \floatingpenalty\@MM \hsize\columnwidth
1787     \parboxrestore \parindent\normalparindent \sloppy
1788     \protected@edef\@currentlabel{%
1789       \csname p@footnote\endcsname\@thefnmark}%
1790     \@makefntext{%
1791       \rule{z@\footnotesep}{\ignorespaces\if@RTL@footnote#1\else\latinfont#1\fi\unskip\strut\par}}}
1792
1793
1794
1795
1796
1797 \long\def\@RTLfootnotetext#1{%
1798   \insert\footins{%
1799     \if@RTLtrue%
1800     \normalfont\footnotesize
1801     \interlinepenalty\interfootnotelinepenalty
1802     \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
1803     \floatingpenalty\@MM \hsize\columnwidth
1804     \parboxrestore \parindent\normalparindent \sloppy
1805     \protected@edef\@currentlabel{%
1806       \csname p@footnote\endcsname\@thefnmark}%
1807     \@makefntext{%
1808       \rule{z@\footnotesep}{\ignorespaces\persianfont #1\unskip\strut\par}}}

```

```

1809
1810
1811
1812
1813
1814
1815
1816 \long\def\@LTRfootnotetext#1{%
1817   \insert\footins{%
1818     \RTLfalse%
1819     \normalfont\footnotesize
1820     \interlinepenalty\interfootnotelinepenalty
1821     \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
1822     \floatingpenalty\@MM \hsize\columnwidth
1823     \@parboxrestore \parindent\normalparindent \sloppy
1824     \protected@edef\@currentlabel{%
1825       \csname p@footnote\endcsname@\thefnmark}%
1826     \@makefntext{%
1827       \rule{z@\footnotesep}\ignorespaces\latinfont #1\unskip\strut\par}}}
1828
1829 \footdir@temp\footdir@ORG@xepersian@imsproc@footnotetext\@footnotetext{\bidi@footdir@footnote}%
1830 \footdir@temp\footdir@ORG@xepersian@imsproc@RTLfootnotetext\@RTLfootnotetext{R}%
1831 \footdir@temp\footdir@ORG@xepersian@imsproc@LTRfootnotetext\@LTRfootnotetext{L}%
1832
1833 \def\part{\startsection{part}{0}%
1834   \z@\{ \linespacing\@plus\linespacing\}\.5\linespacing}%
1835   {\normalfont\bfseries\if@RTL\raggedleft\else\raggedright\fi}%
1836 \def\@tocline#1#2#3#4#5#6#7{\relax
1837   \ifnum #1>\c@tocdepth % then omit
1838   \else
1839     \par \addpenalty\@secpenalty\addvspace{#2}%
1840     \begingroup \hyphenpenalty\@M
1841     \@ifempty{#4}{%
1842       \tempdima\csname r@tocindent\endcsname\relax
1843     }{%
1844       \tempdima#4\relax
1845     }%
1846     \parindent\z@ \if@RTL\rightskip\else\leftskip\fi#3\relax \advance\if@RTL\rightskip\else\leftskip\fi#5\leavevmode\hskip-\pnumwidth
1847     \if@RTL\leftskip\else\rightskip\fi\pnumwidth plus4em \parfillskip-\pnumwidth
1848     #5\nobreak\relax
1849     \hfil\hbox to\pnumwidth{\tocpagenum{#7}}\par
1850     \nobreak
1851   \endgroup
1852 \fi}%
1853 \renewcommand\thesubsection {\thesection\SepMark\arabic{subsection}}
1854 \renewcommand\thesubsubsection {\thesubsection \SepMark\arabic{subsubsection}}
1855 \renewcommand\theparagraph {\thesubsubsection\SepMark\arabic{paragraph}}
1856 \renewcommand\thesubparagraph {\theparagraph\SepMark\arabic{subparagraph}}
1857 \def\maketitle{\par
1858   \topnum\z@ % this prevents figures from falling at the top of page 1

```

```

1859  \@setcopyright
1860  \thispagestyle{firstpage}%
1861  \uppercaseonnonmath\shorttitle
1862  \ifx\@empty\shortauthors \let\shortauthors\shorttitle
1863  \else \andify\shortauthors
1864  \fi
1865  \@maketitle@hook
1866  \begingroup
1867  \@maketitle
1868  \toks@{\exp{\shortauthors}}\temptokena\exp{\shorttitle}%
1869  \toks4{\def\\{\ignorespaces}}% defend against questionable usage
1870  \edef\@tempa{%
1871    \nx\markboth{\the\toks4
1872    \nx\MakeUppercase{\the\toks@}{\the\temptokena}}%
1873  \@tempa
1874  \endgroup
1875  \c@footnote\z@
1876  \@cleartopmattertags
1877 }

```

### 7.34 kashida-xepersian.def

```

1878 \ProvidesFile{kashida-xepersian.def}[2013/11/15 v0.3 implementation of Kashida for xepersian pac
1879 \chardef\xepersian@zwj="200D % zero-width joiner
1880
1881 \chardef\xepersian@D=10 % dual-joiner class
1882 \chardef\xepersian@L=11 % lam
1883 \chardef\xepersian@R=12 % right-joiner
1884 \chardef\xepersian@A=13 % alef
1885 \chardef\xepersian@V=256 % vowel or other combining mark (to be ignored)
1886 \def\xepersian@kashida{\xepersian@zwj\nobreak%
1887   \leaders\hrule height \XeTeXglyphbounds2 \the\XeTeXcharglyph"0640 depth \XeTeXglyphbounds4 \v
1888
1889 \def\setclass#1#2{\def\thecharlist{#1}\def\charlist{#2}%
1890   \expandafter\dosetclass\charlist,\end}
1891 \def\dosetclass#1,#2\end{%
1892   \def\test{#1}\def\charlist{#2}%
1893   \ifx\test\empty\let\next\finishsetclass
1894   \else \XeTeXcharclass "\test = \thecharlist
1895     \let\next\dosetclass \fi
1896   \expandafter\next\charlist,,\end}
1897 \def\finishsetclass#1,,\end{%
1898
1899 \setclass \xepersian@A {0622,0623,0625,0627}
1900 \setclass \xepersian@R {0624,0629,062F,0630,0631,0632,0648,0698}
1901 \setclass \xepersian@D {0626,0628,062A,062B,062C,062D,062E}
1902 \setclass \xepersian@O {0633,0634,0635,0636,0637,0638,0639,063A}
1903 \setclass \xepersian@D {0640,0641,0642,0643,0645,0646,0647,0649,064A}
1904 \setclass \xepersian@D {067E,0686,06A9,06AF,06CC}
1905 \setclass \xepersian@L {0644}

```

```

1906 \setclass \xepersian@V {064B,064C,064D,064E,064F,0650,0651,0652}
1907
1908 \XeTeXinterchartoks \xepersian@D \xepersian@D = {\xepersian@kashida}
1909 \XeTeXinterchartoks \xepersian@L \xepersian@D = {\xepersian@kashida}
1910 \XeTeXinterchartoks \xepersian@D \xepersian@L = {\xepersian@kashida}
1911 \XeTeXinterchartoks \xepersian@L \xepersian@L = {\xepersian@kashida}
1912 \XeTeXinterchartoks \xepersian@D \xepersian@R = {\xepersian@kashida}
1913 \XeTeXinterchartoks \xepersian@D \xepersian@A = {\xepersian@kashida}
1914 \XeTeXinterchartoks \xepersian@L \xepersian@R = {\xepersian@kashida}
1915 \XeTeXinterchartoks \xepersian@L \xepersian@A = {}
1916
1917 \newcommand{\KashidaOn}{\XeTeXinterchartokenstate=1}
1918 \newcommand{\KashidaOff}{\XeTeXinterchartokenstate=0}
1919 \KashidaOn

```

### 7.35 listings-xepersian.def

```

1920 \ProvidesFile{listings-xepersian.def}[2010/07/25 v0.2 bilingual captions for listings package]
1921 \def\lstlistingname{\if@RT \else\ Listing\fi}
1922 \def\lstlistlistingname{\if@RTL \else\ Listings\fi}

```

### 7.36 loadingorder-xepersian.def

```

1923 \ProvidesFile{loadingorder-xepersian.def}[2012/01/01 v0.3 making sure that xepersian is the last
1924 \bidi@isloaded{algorithmic}
1925 \bidi@isloaded{algorithm}
1926 \bidi@isloaded{backref}
1927 \bidi@isloaded{enumerate}
1928 \bidi@isloaded{tocloft}
1929 \bidi@isloaded{url}
1930 \AtBeginDocument{
1931   \if@bidi@algorithmicloaded@\else
1932     \bidi@isloaded[{\PackageError{xepersian}{Oops! you have loaded package algorithmic after xepersian}}
1933   \fi%
1934   \if@bidi@algorithmloaded@\else
1935     \bidi@isloaded[{\PackageError{xepersian}{Oops! you have loaded package algorithm after xepersian}}
1936   \fi%
1937   \if@bidi@backrefloaded@\else
1938     \bidi@isloaded[{\PackageError{xepersian}{Oops! you have loaded package backref after xepersian}}
1939   \fi%
1940   \if@bidi@enumerateloaded@\else
1941     \bidi@isloaded[{\PackageError{xepersian}{Oops! you have loaded package enumerate after xepersian}}
1942   \fi%
1943   \if@bidi@tocloftloaded@\else
1944     \bidi@isloaded[{\PackageError{xepersian}{Oops! you have loaded package tocloft after xepersian}}
1945   \fi%
1946   \if@bidi@urlloaded@\else
1947     \bidi@isloaded[{\PackageError{xepersian}{Oops! you have loaded package url after xepersian pack}}%
1948   \fi%
1949 }

```

### 7.37 localise-xepersian.def

```
1950 \ProvidesFile{localise-xepersian.def}[2014/07/10 v0.2b Persian localisation of LaTeX2e]
1951 \newcommand{\makezwnjletter}{\catcode`=11\relax}
1952 \makezwnjletter
1953 \newcommand*\eqcommand[2]{\if@bidi@csprimitive{#2}{\bidi@csletcs{#1}{#2}}{\bidi@csdefcs{#1}{#2}}}
1954 \newcommand*\eqenvironment[2]{\newenvironment{#1}{\csname#2\endcsname}{\csname end#2\endcsname}}
1955 \@ifpackageloaded{keyval}{%
1956 \newcommand*\keyval@eq@alias@key[4][KV]{%
1957   \bidi@csletcs{#1@#2@#3}{#1@#2@#4}%
1958   \bidi@csletcs{#1@#2@#3@default}{#1@#2@#4@default}}%
1959 }{\@ifpackageloaded{xkeyval}{%
1960 \newcommand*\keyval@eq@alias@key[4][KV]{%
1961   \bidi@csletcs{#1@#2@#3}{#1@#2@#4}%
1962   \bidi@csletcs{#1@#2@#3@default}{#1@#2@#4@default}}%
1963 }{}}
1964 \input{latex-localise-commands-xepersian.def}
1965 \input{xepersian-localise-commands-xepersian.def}
1966 \input{latex-localise-environments-xepersian.def}
1967 \input{xepersian-localise-environments-xepersian.def}
1968 \input{latex-localise-messages-xepersian.def}
1969 \input{latex-localise-misc-xepersian.def}
1970 \input{packages-localise-xepersian.def}
1971 \aliasfontfeature{ExternalLocation}{ }
1972 \aliasfontfeature{ExternalLocation}{ }
1973 \aliasfontfeature{Renderer}{ }
1974 \aliasfontfeature{BoldFont}{ }
1975 \aliasfontfeature{Language}{ }
1976 \aliasfontfeature{Script}{ }
1977 \aliasfontfeature{UprightFont}{ }
1978 \aliasfontfeature{ItalicFont}{ }
1979 \aliasfontfeature{BoldItalicFont}{ }
1980 \aliasfontfeature{SlantedFont}{ }
1981 \aliasfontfeature{BoldSlantedFont}{ }
1982 \aliasfontfeature{SmallCapsFont}{ }
1983 \aliasfontfeature{UprightFeatures}{ }
1984 \aliasfontfeature{BoldFeatures}{ }
1985 \aliasfontfeature{ItalicFeatures}{ }
1986 \aliasfontfeature{BoldItalicFeatures}{ }
1987 \aliasfontfeature{SlantedFeatures}{ }
1988 \aliasfontfeature{BoldSlantedFeatures}{ }
1989 \aliasfontfeature{SmallCapsFeatures}{ }
1990 \aliasfontfeature{SizeFeatures}{ }
1991 \aliasfontfeature{Scale}{ }
1992 \aliasfontfeature{WordSpace}{ }
1993 \aliasfontfeature{PunctuationSpace}{ }
1994 \aliasfontfeature{FontAdjustment}{ }
1995 \aliasfontfeature{LetterSpace}{ }
1996 \aliasfontfeature{HyphenChar}{ }
1997 \aliasfontfeature{Color}{ }
```

```

1998 \aliasfontfeature{Opacity}{ }
1999 \aliasfontfeature{Mapping}{ }
2000 \aliasfontfeature{Weight}{ }
2001 \aliasfontfeature{Width}{ }
2002 \aliasfontfeature{OpticalSize}{ }
2003 \aliasfontfeature{FakeSlant}{ }
2004 \aliasfontfeature{FakeStretch}{ }
2005 \aliasfontfeature{FakeBold}{ }
2006 \aliasfontfeature{AutoFakeSlant}{ }
2007 \aliasfontfeature{AutoFakeBold}{ }
2008 \aliasfontfeature{Ligatures}{ }
2009 \aliasfontfeature{Alternate}{ }
2010 \aliasfontfeature{Variant}{ }
2011 \aliasfontfeature{Variant}{ }
2012 \aliasfontfeature{CharacterVariant}{ }
2013 \aliasfontfeature{Style}{ }
2014 \aliasfontfeature{Annotation}{ }
2015 \aliasfontfeature{RawFeature}{ }
2016 \aliasfontfeature{CharacterWidth}{ }
2017 \aliasfontfeature{Numbers}{ }
2018 \aliasfontfeature{Contextuals}{ }
2019 \aliasfontfeature{Diacritics}{ }
2020 \aliasfontfeature{Letters}{ }
2021 \aliasfontfeature{Kerning}{ }
2022 \aliasfontfeature{VerticalPosition}{ }
2023 \aliasfontfeature{Fractions}{ }
2024 \aliasfontfeatureoption{Language}{Default}{ }
2025 \aliasfontfeatureoption{Language}{Parsi}{ }
2026 \aliasfontfeatureoption{Script}{Parsi}{ }
2027 \aliasfontfeatureoption{Script}{Latin}{ }
2028 \aliasfontfeatureoption{Style}{MathScript}{ }
2029 \aliasfontfeatureoption{Style}{MathScriptScript}{ }

```

### 7.38 memoir-xepersian.def

```

2030 \ProvidesFile{memoir-xepersian.def}[2010/07/25 v0.1 adaptations for memoir class]
2031 \renewcommand{\@memfront}{%
2032   \@smemfront\pagenumbering{harfi}%
2033   \renewcommand{\setthesection}{\thechapter\@SepMark\harfi{section}}%
2034   \renewcommand*{\thebook}{\@tartibi\c@book}%
2035   \renewcommand*{\thepart}{\@tartibi\c@part}%
2036   \renewcommand{\appendix}{\par%
2037     \setcounter{chapter}{0}%
2038     \setcounter{section}{0}%
2039     \gdef\@chapapp{\appendixname}%
2040     \gdef\thechapter{\@harfi\c@chapter}%
2041     \anappendixtrue}%

```

### 7.39 latex-localise-messages-xepersian.def

```

2042 latex}      \localise-messages-xepersian.def}[2011/03/01 v0.1 localising LaTeX2e messages]

```

## 7.40 minitoc-xepersian.def

```
2043 \ProvidesFile{minitoc-xepersian.def}[2010/07/25 v0.1 bilingual captions for minitoc package]
2044 \def\ptctitle{\if@RTL else\ Table of Contents\fi}%
2045 \def\plftitle{\if@RTL else\ List of Figures\fi}%
2046 \def\pltttitle{\if@RTL else\ List of Tables\fi}%
2047 \def\mtctitle{\if@RTL else\ Contents\fi}%
2048 \def\mlftitle{\if@RTL else\ Figures\fi}%
2049 \def\mltttitle{\if@RTL else\ Tables\fi}%
2050 \def\stctitle{\if@RTL else\ Contents\fi}%
2051 \def\slftitle{\if@RTL else\ Figures\fi}%
2052 \def\sltttitle{\if@RTL else\ Tables\fi}%
```

## 7.41 latex-localise-misc-xepersian.def

```
2053 \ProvidesFile{latex-localise-misc-xepersian.def}[2012/01/01 v0.2 miscellaneous Persian localisa
2054 %]1#  \
2055   \@  \    @ \    \
2056   \1#  \
2057   \1# @\
2058   \1# @\
2059 {\@  \    \
2060 }2#1# @\ \
2061 %1#  \    @\    \    \    \
2062   \2#  \    @\    \
2063 {{2#1#  \
2064 undefined\    \  \
2065
2066 %{\ \    \    \    \1#}    \ \} \1#  \ \
2067   \ { \    \    \
2068   \  \  \
2069
2070
2071 \  \  \ %} \#1
2072   \1#}  \ \ %  \
2073     \  \  \
2074   }%
2075   \
2076   \  \  \
2077 }
2078 \= \  \
2079
2080
2081 \@ifdefinitionfileloaded{latex-xetex-bidi}{%
2082 \def\xffloat #1[#2]{%
2083   \@nodocument
2084   \def\@capttype {\#1}%
2085   \def\@fps {\#2}%
2086   \@onellevel@sanitize \@fps
2087   \def\@reserved@b {!}%
2088   \ifx\@reserved@b \@fps
```

```

2089      \@fpsadddefault
2090  \else
2091      \ifx \@fps \empty
2092          \@fpsadddefault
2093      \fi
2094  \fi
2095  \ifhmode
2096      \@bsphack
2097      \@floatpenalty -\@Mii
2098  \else
2099      \@floatpenalty-\@Miii
2100  \fi
2101 \ifinner
2102     \parmoderr\@floatpenalty\z@
2103 \else
2104     \next\currbox\freelist
2105     {%
2106         \@tempcnta \sixt@n
2107         \expandafter \tfor \expandafter \reserved@a
2108             \expandafter :\expandafter =\@fps
2109         \do
2110             {%
2111                 \if \reserved@a h%
2112                     \ifodd \@tempcnta
2113                     \else
2114                         \advance \@tempcnta \one
2115                     \fi
2116                 \fi
2117                 \if \reserved@a %
2118                     \ifodd \@tempcnta
2119                     \else
2120                         \advance \@tempcnta \one
2121                     \fi
2122                 \fi
2123                 \if \reserved@a t%
2124                     \setfpsbit \tw@%
2125                 \fi
2126                 \if \reserved@a %
2127                     \setfpsbit \tw@%
2128                 \fi
2129                 \if \reserved@a b%
2130                     \setfpsbit 4%
2131                 \fi
2132                 \if \reserved@a %
2133                     \setfpsbit 4%
2134                 \fi
2135                 \if \reserved@a p%
2136                     \setfpsbit 8%
2137                 \fi
2138                 \if \reserved@a %

```

```

2139          \@setfpsbit 8%
2140          \fi
2141          \if \reserved@a !%
2142              \ifnum \@tempcnta>15
2143                  \advance\@tempcnta -\sixt@n\relax
2144              \fi
2145          \fi
2146      }%
2147      \@tempcntb \csname ftype@\@capttype \endcsname
2148      \multiply \@tempcntb \@xxxii
2149      \advance \@tempcnta \@tempcntb
2150      \global \count\currbox \@tempcnta
2151  }%
2152  \@fltovf
2153 \fi
2154 \global \setbox\currbox
2155   \color@vbox
2156     \normalcolor
2157     \vbox \bgroup
2158       \hsize\columnwidth
2159       \parboxrestore
2160       \floatboxreset
2161 }
2162 \let\bm@\bm@c
2163 \let\bm@\bm@l
2164 \let\bm@\bm@r
2165 \let\bm@\bm@b
2166 \let\bm@\bm@t
2167 \let\bm@\bm@s
2168 \long\def\@iiiparbox#1#2[#3]#4#5{%
2169   \leavevmode
2170   \pboxswfalse
2171   \if@RTLtab\@bidi@list\minipage\parbox\nobtrue\fi
2172   \if@RTL\if#1\@bidi@list\minipage\parboxtrue\else\if#1b\@bidi@list\minipage\parboxtrue\else\
2173   \setlength\tempdima{#4}%
2174   \begin\tempboxa\vbox{\hsize\tempdima\parboxrestore#5\par}%
2175   \ifx\relax#2\else
2176     \setlength\tempdimb{#2}%
2177     \edef\parboxto{to\the\tempdimb}%
2178   \fi
2179   \if#1b\vbox
2180     \else\if#1\vbox
2181     \else\if#1\vtop
2182     \else\if vtop\#1
2183     \else\ifmmode\vcenter
2184     \else\pboxswtrue \$\vcenter
2185     \fi\fi\fi\fi\fi
2186   \parboxto{\let\hss\vss\let\unhbox\unvbox
2187     \csname bm@#3\endcsname}%
2188   \if\pboxsw \m@th$\fi

```

```

2189  \end@tempboxa}
2190 \def\@iiminipage#1#2[#3]{%
2191   \leavevmode
2192   \pboxswfalse
2193   \if@RTLtab\@bidi@list@minipage@parbox@not@nobtrue\fi
2194   \if@RTL\if#1\@bidi@list@minipage@parboxtrue\else\if#1\@bidi@list@minipage@parboxtrue\else
2195   \setlength\@tempdima{#4}%
2196   \def\@mpargs{{#1}{#2}[#3]{#4}}%
2197   \setbox\@tempboxa\vbox\bgroup
2198     \color@begingroup
2199     \hsize\@tempdima
2200     \textwidth\hsize \columnwidth\hsize
2201     \parboxrestore
2202     \def\@mpfn{mpfootnote}\def\thempfn{\thempfootnote}\c@mpfootnote\z@
2203     \let\@footnotetext\@mpfootnotetext
2204     \let\@LTRfootnotetext\@mpLTRfootnotetext
2205     \let\@RTLfootnotetext\@mpRTLfootnotetext
2206     \let\@listdepth\@mplistdepth \@mplistdepth\z@
2207     \minipagerestore
2208     \setminipage%
2209 \def\@testpach#1{\@chclass \ifnum \lastchclass=\tw@ 4 \else
2210   \ifnum \lastchclass=3 5 \else
2211     \z@ \if #1\@chnum \z@ \else
2212       \if \chnum@#1 \z@ \else
2213         \if \if@RTLtab#1r\else#1l\fi\@chnum \one \else
2214           \if \if@RTLtab#1 \else#1 \fi\@chnum \one \else
2215             \if \if@RTLtab#1\else#1r\fi\@chnum \tw@ \else
2216               \if \if@RTLtab#1 \else#1 \fi\@chnum \tw@ \else
2217                 \@chclass \if #1\one \else
2218                   \if #1@\tw@ \else
2219                     \if #1p3 \else
2220                       \if 3 #1 \else \z@ \preamerr 0\fi
2221                     \fi \fi \fi \fi \fi \fi \fi \fi \fi
2222 \fi}%
2223 }{}}
2224 \ifdefdefinitionfileloaded{array-xetex-bidi}{%
2225 \def\@testpach{\@chclass
2226 \ifnum \lastchclass=6 \one \chnum \one \else
2227   \ifnum \lastchclass=7 5 \else
2228     \ifnum \lastchclass=8 \tw@ \else
2229       \ifnum \lastchclass=9 \thr@@
2230     \else \z@
2231     \ifnum \lastchclass = 10 \else
2232       \edef\@nextchar{\expandafter\string\@nextchar}%
2233       \chnum
2234       \if \@nextchar c\z@ \else
2235         \if \@nextchar @z\ \else
2236           \if \@nextchar \if@RTLtab r\else l\fi\one \else
2237             \if \@nextchar \if@RTLtab else\ fi\one\ \else
2238               \if \@nextchar \if@RTLtab l\else r\fi\tw@ \else

```



```

2289   \if \@nextchar 5 \else
2290   \z@ \@chclass \z@ \@preamerr \z@ \fi \fi
2291   \fi \fi
2292
2293 \def\@classz{\@classx
2294   \tempcnta \count@
2295   \prepnext@tok
2296   \addtopreamble{\ifcase \@chnum
2297     \hfil
2298     \adl@putlrc{\d@llarbegin \insert@column \d@llarend}\hfil \or
2299     \hskip1sp\adl@putlrc{\d@llarbegin \insert@column \d@llarend}\hfil \or
2300     \hfil\hskip1sp\adl@putlrc{\d@llarbegin \insert@column \d@llarend}\or
2301     \setbox\adl@box\hbox \adl@startmbox{\@nextchar}\insert@column
2302     \adl@endmbox\or
2303     \setbox\adl@box\vtop \startpbox{\@nextchar}\insert@column \endpbox \or
2304     \setbox\adl@box\vbox \startpbox{\@nextchar}\insert@column \endpbox
2305   \prepnext@tok}
2306 \def\adl@class@start{4}
2307 \def\adl@class@iiiorvii{7}
2308
2309 \else
2310 \def\@testpach#1{\@chclass \ifnum \@lastchclass=\tw@ 4\relax \else
2311   \ifnum \@lastchclass=\thr@@ 5\relax \else
2312     \z@ \if #1\@chnum \z@ \else
2313       \if @chnum\z@\ #1 \else
2314         \if \if@RTLtab#1r\else#11\fi\@chnum \cne \else
2315           \if \if@RTLtab#1 \else#1 \fi\@chnum \cne \else
2316             \if \if@RTLtab#11\else#1r\fi\@chnum \tw@ \else
2317               \if \if@RTLtab#1 \else#1 \fi\@chnum \tw@ \else
2318                 \@chclass
2319                   \if #1|\cne \let\@arrayrule\adl@arrayrule \else
2320                     \if #1:\cne \let\@arrayrule\adl@arraydashrule \else
2321                       \if #1;\cne \let\@arrayrule\adl@argarraydashrule \else
2322                         \if #1@\tw@ \else
2323                           \if #1p\thr@@ \else
2324                             \if @thr#1 \else\z@ \@preamerr 0\fi
2325                               \fi \fi
2326
2327 \def\@arrayclassz{\ifcase \@lastchclass \acolampacol \or \ampacol \or
2328   \or \or \@addamp \or
2329   \acolampacol \or \firststampfalse \acol \fi
2330   \edef\@preamble{\@preamble
2331     \ifcase \@chnum
2332       \hfil\adl@putlrc{$\relax\sharp$}\hfil
2333       \or \adl@putlrc{$\relax\sharp$}\hfil
2334       \or \hfil\adl@putlrc{$\relax\sharp$}\fi}
2335 \def\@tabclassz{\ifcase \@lastchclass \acolampacol \or \ampacol \or
2336   \or \or \@addamp \or
2337   \acolampacol \or \firststampfalse \acol \fi
2338   \edef\@preamble{\@preamble

```



```

2389 \let\@float@Hx\@xfloat
2390 \def\@xfloat#1[{\@ifnextchar{H}{\@float@HH{#1}}}{\@ifnextchar{ }{\@float@{1#} } []{\@float@Hx{#1}}
2391 \def\@float@HH#1[H]{%
2392   \expandafter\let\csname end#1\endcsname\float@endH
2393   \let\@currbox\float@box
2394   \def\@capttype{#1}\setbox\@floatcapt=\vbox{ }%
2395   \expandafter\ifx\csname fst@#1\endcsname\relax
2396     \@flstylefalse\else\@flstyletrue\fi
2397   \setbox\@currbox\color@vbox\normalcolor
2398   \vbox\bgroup \hsize\columnwidth \parboxrestore
2399   \floatboxreset \setnobreak
2400   \ignorespaces}
2401 \def\@float@[ ]#1{%
2402   \expandafter\let\csname end#1\endcsname\float@endH
2403   \let\@currbox\float@box
2404   \def\@capttype{#1}\setbox\@floatcapt=\vbox{ }%
2405   \expandafter\ifx\csname fst@#1\endcsname\relax
2406     \@flstylefalse\else\@flstyletrue\fi
2407   \setbox\@currbox\color@vbox\normalcolor
2408   \vbox\bgroup \hsize\columnwidth \parboxrestore
2409   \floatboxreset \setnobreak
2410   \ignorespaces}
2411 }{%
2412 \begingroup \catcode `|=0 \catcode `=[ 1
2413 \catcode`]=2 \catcode `\\=12 \catcode `\\=12
2414 \catcode`\\=12 |gdef|@x@xepersian@localize@verbatim#1|[|] |1#]{|} { }
2415 |gdef|@sx@xepersian@localize@verbatim#1|[[*] |1#]{[*] } { }
2416 |endgroup
2417 \def\ {|\overline{verbatim}\frenchspacing\@vobeyspaces\@x@xepersian@localize@verbatim}
2418 \def\end {\{if@newlist\leavevmode\fi\endtrivlist}
2419 \ExplSyntaxOn
2420 \AtBeginDocument{\@namedef{ *}{|\overline{verbatim}\fontspec_print_visible_spaces:\@sx@xepersian@localize@verbatim}}
2421 \ExplSyntaxOff
2422 \expandafter\let\csname end * \endcsname =\end

```

## 7.42 natbib-xepersian.def

```

2423 \ProvidesFile{natbib-xepersian.def}[2011/08/01 v0.1 adaptations for natbib package]
2424 \renewcommand{\NAT@set@cites}{%
2425   \ifNAT@numbers
2426     \ifNAT@super \let\cite\NAT@citesuper
2427       \def\NAT@mbox##1{\unskip\nobreak\textsuperscript{##1}}%
2428       \let\citeyearpar=\citeyear
2429       \let\NAT@space\relax
2430       \def\NAT@super@kern{\kern\p@}%
2431   \else
2432     \let\NAT@mbox=\mbox
2433     \let\cite\NAT@citemum
2434     \let\NAT@space\NAT@spacechar
2435     \let\NAT@super@kern\relax

```

```

2436     \fi
2437     \let\@citex\NAT@citexnum
2438     \let\@Latincitex\NAT@Latin@citexnum
2439     \let\@biblabel\NAT@biblabelnum
2440     \let\@bibsetup\NAT@bibsetnum
2441     \renewcommand\NAT@idxtxt{\NAT@name\NAT@spacechar\NAT@open\NAT@num\NAT@close}%
2442     \def\natexlab##1{##1}%
2443     \def\NAT@penalty{\penalty\@m}%
2444 \else
2445     \let\@cite\NAT@cite
2446     \let\@citex\NAT@citex
2447     \let\@Latincitex\NAT@Latin@citex
2448     \let\@biblabel\NAT@biblabel
2449     \let\@bibsetup\NAT@bibsetup
2450     \let\NAT@space\NAT@spacechar
2451     \let\NAT@penalty\empty
2452     \renewcommand\NAT@idxtxt{\NAT@name\NAT@spacechar\NAT@open\NAT@date\NAT@close}%
2453     \def\natexlab##1{##1}%
2454 \fi}
2455 \newcommand\NAT@Latin@citex{}
2456 \def\NAT@Latin@citex{%
2457   [#1] [#2]#3{%
2458     \NAT@reset@parser
2459     \NAT@sort@cites{#3}%
2460     \NAT@reset@citea
2461     \@cite{\lrf{\let\NAT@nm\empty\let\NAT@year\empty
2462       @for@citeb:=\NAT@cite@list\do
2463         {\@safe@activestrue
2464           \edef\@citeb{\expandafter\firstrfone\@citeb\empty}%
2465           \@safe@activefalse
2466           \ifundefined{b@\@citeb}{\extra@b@\@citeb}{\@citea}%
2467             {\reset@font\bfseries ?}\NAT@citeundefined
2468             \PackageWarning{natbib}%
2469             {Citation `@\@citeb' on page \thepage\space undefined}\def\NAT@date{}%
2470             {\let\NAT@last@nm=\NAT@nm\let\NAT@last@yr=\NAT@year
2471               \NAT@parse{\@citeb}%
2472               \ifNAT@longnames\ifundefined{bv@\@citeb}{\extra@b@\@citeb}{%
2473                 \let\NAT@name=\NAT@all@names
2474                 \global\cnamedef{bv@\@citeb}{\extra@b@\@citeb}{}{}%
2475               \fi
2476               \ifNAT@full\let\NAT@nm\NAT@all@names\else
2477                 \let\NAT@nm\NAT@name\fi
2478               \ifNAT@swa\ifcase\NAT@ctype
2479                 \if\relax\NAT@date\relax
2480                   \NAT@hyper{\NAT@nmfmt{\NAT@nm}}\NAT@date}%
2481               \else
2482                 \ifx\NAT@last@nm\NAT@nm\NAT@yrsep
2483                   \ifx\NAT@last@yr\NAT@year
2484                     \def\NAT@temp{?}%
2485                     \ifx\NAT@temp\NAT@exlab\PackageWarning{natbib}%

```

```

2486 {Multiple citation on page \thepage: same authors and
2487 year\MessageBreak without distinguishing extra
2488 letter,\MessageBreak appears as question mark}\fi
2489 \NAT@hyper@\{\NAT@exlab\}%
2490 \else\unskip\NAT@spacechar
2491 \NAT@hyper@\{\NAT@date\}%
2492 \fi
2493 \else
2494 \citeda\NAT@hyper@{%
2495 \NAT@nmfmt{\NAT@nm}%
2496 \hyper@natlinkbreak{%
2497 \NAT@aysep\NAT@spacechar}{\citedb\@extra@b@citedb
2498 }%
2499 \NAT@date
2500 }%
2501 \fi
2502 \fi
2503 \or\citeda\NAT@hyper@{\NAT@nmfmt{\NAT@nm}}%
2504 \or\citeda\NAT@hyper@{\NAT@date}%
2505 \or\citeda\NAT@hyper@{\NAT@alias}%
2506 \fi \NAT@def@citeda
2507 \else
2508 \ifcase\NAT@ctype
2509 \if\relax\NAT@date\relax
2510 \citeda\NAT@hyper@{\NAT@nmfmt{\NAT@nm}}%
2511 \else
2512 \ifx\NAT@last@nm\NAT@nm\NAT@yrsep
2513 \ifx\NAT@last@yr\NAT@year
2514 \def\NAT@temp{\?}%
2515 \ifx\NAT@temp\NAT@exlab\PackageWarningNoLine{natbib}%
2516 {Multiple citation on page \thepage: same authors and
2517 year\MessageBreak without distinguishing extra
2518 letter,\MessageBreak appears as question mark}\fi
2519 \NAT@hyper@\{\NAT@exlab\}%
2520 \else
2521 \unskip\NAT@spacechar
2522 \NAT@hyper@\{\NAT@date\}%
2523 \fi
2524 \else
2525 \citeda\NAT@hyper@{%
2526 \NAT@nmfmt{\NAT@nm}%
2527 \hyper@natlinkbreak{\NAT@spacechar\NAT@open\if*\#1*\else#1\NAT@spacechar\fi}%
2528 {\citedb\@extra@b@citedb}%
2529 \NAT@date
2530 }%
2531 \fi
2532 \fi
2533 \or\citeda\NAT@hyper@{\NAT@nmfmt{\NAT@nm}}%
2534 \or\citeda\NAT@hyper@{\NAT@date}%
2535 \or\citeda\NAT@hyper@{\NAT@alias}%

```

```

2536 \fi
2537 \if\relax\NAT@date\relax
2538     \NAT@def@citea
2539 \else
2540     \NAT@def@citea@close
2541 \fi
2542 \fi
2543 \}\ifNAT@swa\else\if*#2*\else\NAT@cmt#2\fi
2544 \if\relax\NAT@date\relax\else\NAT@@close\fi\fi}\{\#1\}{\#2\}}
2545 \newcommand\NAT@Latin@citexnum{%
2546 \def\NAT@Latin@citexnum[#1] [#2]#3{%
2547     \NAT@reset@parser
2548     \NAT@sort@cites{\#3}%
2549     \NAT@reset@citea
2550     \NAT@cite{\lr{\def\NAT@num{-1}\let\NAT@last@yr\relax\let\NAT@nm\empty
2551     \@for\NAT@citeb:=\NAT@cite@list\do
2552     {\@safe@activestrue
2553         \edef\NAT@citeb{\expandafter\@firstofone\NAT@citeb\empty}%
2554         \@safe@activesfalse
2555         \@ifundefined{b@\NAT@citeb\extra@b@\NAT@citeb}{%
2556             {\@reset@font\bfseries?}
2557             \NAT@citeundefined\PackageWarning{natbib}%
2558             {Citation `@\NAT@citeb' on page \thepage\space undefined}}%
2559         {\let\NAT@last@num\NAT@num\let\NAT@last@nm\NAT@nm
2560             \NAT@parse{\NAT@citeb}%
2561             \ifNAT@longnames\@ifundefined{bv@\NAT@citeb\extra@b@\NAT@citeb}{%
2562                 \let\NAT@name=\NAT@all@names
2563                 \global\@namedef{bv@\NAT@citeb\extra@b@\NAT@citeb}{}{}%
2564             }%
2565             \ifNAT@full\let\NAT@nm\NAT@all@names\else
2566                 \let\NAT@nm\NAT@name\fi
2567             \ifNAT@swa
2568                 \ifnum{\NAT@ctype}>\@ne}{%
2569                     \@citea
2570                     \NAT@hyper@{\@ifnum{\NAT@ctype=\tw@}{\NAT@test{\NAT@ctype}}{\NAT@alias}}%
2571                 }%
2572                 \ifnum{\NAT@cmprs}>\z@}{%
2573                     \NAT@ifcat@num\NAT@num
2574                     {\let\NAT@nm=\NAT@num}%
2575                     {\def\NAT@nm{-2}}%
2576                     \NAT@ifcat@num\NAT@last@num
2577                     {\@tempcnta=\NAT@last@num\relax}%
2578                     {\@tempcnta\m@ne}%
2579                     \ifnum{\NAT@nm=\@tempcnta}{%
2580                         \ifnum{\NAT@merge}>\@ne}{%
2581                             \NAT@last@yr\m@box}%
2582                         }%
2583                         \advance\@tempcnta by\@ne
2584                         \ifnum{\NAT@nm=\@tempcnta}{%
2585                             \ifx\NAT@last@yr\relax
2586                                 \def\NAT@last@yr{\NAT@last@yr\@citea}%

```

```

2586          \else
2587              \def@NAT@last@yr{--\NAT@penalty}%
2588          \fi
2589      }{%
2590          \NAT@last@yr@mbox
2591      }%
2592      }%
2593  }{%
2594      \tempswatru
2595  \ifnum{\NAT@merge}>\@ne}{\ifnum{\NAT@last@num=\NAT@num\relax}{\tempswafalse}{}}
2596      \if@tempswa\NAT@citea@mbox\fi
2597  }%
2598  }%
2599      \NAT@def@citea
2600  \else
2601      \ifcase\NAT@ctype
2602          \ifx\NAT@last@nm\NAT@nm \NAT@yrsep\NAT@penalty\NAT@space\else
2603          \NAT@citea \NAT@test{\@ne}\NAT@spacechar\NAT@mbox{\NAT@super@kern\NAT@open}%
2604          \fi
2605          \if*#1*\else#1\NAT@spacechar\fi
2606          \NAT@mbox{\NAT@hyper@{\citemarkfont{\NAT@num}}}}%
2607          \NAT@def@citea@box
2608      \or
2609          \NAT@hyper@citea@space{\NAT@test{\NAT@ctype}}%
2610      \or
2611          \NAT@hyper@citea@space{\NAT@test{\NAT@ctype}}%
2612      \or
2613          \NAT@hyper@citea@space\NAT@alias
2614      \fi
2615  \fi
2616  }%
2617 }%
2618 \ifnum{\NAT@cmprs}>\z@{\NAT@last@yr}{}%
2619 \ifNAT@swa\else
2620     \ifnum{\NAT@ctype=\z@}%
2621         \if*#2*\else\NAT@cmt#2\fi
2622     }{%
2623         \NAT@mbox{\NAT@close}%
2624     \fi
2625 }{#1}{#2}%
2626 }%
2627 \AtBeginDocument{\NAT@set@cites}
2628 \DeclareRobustCommand\Latincite
2629     {\begingroup\let\NAT@ctype\z@\NAT@partrue\NAT@swatru
2630     \ifstar{\NAT@fulltrue\NAT@Latin@cites}{\NAT@fullfalse\NAT@Latin@cites}}
2631 \newcommand\NAT@Latin@cites{\ifnextchar [{\NAT@Latin@citelp}{%
2632     \ifNAT@numbers\else
2633     \NAT@swafalse
2634     \fi
2635     \NAT@Latin@citelp[]}}}
```

```

2636 \newcommand{\NAT@@Latin@@citetp}{}
2637 \def{\NAT@@Latin@@citetp}[#1]{\ifnextchar[\{@Latincitex[#1]\}]{\@Latincitex[] [#1]}}

```

### 7.43 packages-localise-xepersian.def

```

2638 packages}           \localise-xepersian.def}[2013/04/24 v0.2 localising LaTeXe Packages]
2639 color}    \color @localise-xepersian.def}{}}
2640 \ifpackageloaded{multicol}{%
2641 \newenvironment{ }{\begin{multicols}}{\end{multicols}}%
2642 \newenvironment{ }{\begin{multicols*}}{\end{multicols*}}%
2643 }{%
2644 \ifpackageloaded{verbatim}{%
2645 \begingroup
2646 \vrb@catcodes
2647 \lccode`!=`\ \
2648 \catcode`~=`\active \lccode`~=`\^M
2649 \lccode`C=`\C
2650 \lowercase{\endgroup
2651 \def\xepersian@localize@verbatim@start#1{%
2652   \verbatim@startline
2653   \if\noexpand#1\noexpand~%
2654     \let\next\xepersian@localize@verbatim@
2655   \else \def\next{\xepersian@localize@verbatim@#1}\fi
2656   \next}%
2657 \def\xepersian@localize@verbatim@#1{\xepersian@localize@verbatim@#1! \nil}%
2658 \def\xepersian@localize@verbatim@#1! {%
2659   \verbatim@addtoline{#1}%
2660   \futurelet\next\xepersian@localize@verbatim@@@}%
2661 \def\xepersian@localize@verbatim@@@#1\nil{%
2662   \ifx\next\nil
2663     \verbatim@processline
2664     \verbatim@startline
2665     \let\next\xepersian@localize@verbatim@
2666   \else
2667     \def@tempa##1! \nil{##1}%
2668     \temptokena{! }%
2669     \def\next{\expandafter\xepersian@localize@verbatim@test@\tempa#1\nil~}%
2670   \fi \next}%
2671 \def\xepersian@localize@verbatim@test#1{%
2672   \let\next\xepersian@localize@verbatim@test
2673   \if\noexpand#1\noexpand~%
2674     \expandafter\verbatim@addtoline
2675     \expandafter{\the\temptokena}%
2676     \verbatim@processline
2677     \verbatim@startline
2678     \let\next\xepersian@localize@verbatim@
2679   \else \if\noexpand#1
2680     \temptokena\expandafter{\the\temptokena#1}%
2681   \else \if\noexpand#1\noexpand[%
2682     \let\@tempc\empty

```

```

2683           \let\next\xepersian@localize@verbatim@testend
2684       \else
2685           \expandafter\verbatim@addtoline
2686               \expandafter{\the\@temptokena}%
2687           \def\next{\xepersian@localize@verbatim@#1}%
2688       \fi\fi\fi
2689   \next}%
2690 \def\xepersian@localize@verbatim@testend#1{%
2691     \if\noexpand#1\noexpand~%
2692         \expandafter\verbatim@addtoline
2693             \expandafter{\the\@temptokena[]}%
2694         \expandafter\verbatim@addtoline
2695             \expandafter{\@tempc}%
2696         \verbatim@processline
2697         \verbatim@startline
2698         \let\next\xepersian@localize@verbatim@
2699     \else\if\noexpand#1\noexpand]%
2700         \let\next\xepersian@localize@verbatim@@testend
2701     \else\if\noexpand#1\noexpand!%
2702         \expandafter\verbatim@addtoline
2703             \expandafter{\the\@temptokena[]}%
2704         \expandafter\verbatim@addtoline
2705             \expandafter{\@tempc}%
2706         \def\next{\xepersian@localize@verbatim@!}%
2707     \else \expandafter\def\expandafter@\tempc\expandafter
2708         {\@tempc#1}\fi\fi\fi
2709   \next}%
2710 \def\xepersian@localize@verbatim@@testend{%
2711     \ifx\@tempc\@currenvir
2712         \verbatim@finish
2713         \edef\next{\noexpand\end{\@currenvir}}%
2714         \noexpand\xepersian@localize@verbatim@rescan{\@currenvir}%
2715     \else
2716         \expandafter\verbatim@addtoline
2717             \expandafter{\the\@temptokena[]}%
2718         \expandafter\verbatim@addtoline
2719             \expandafter{\@tempc}%
2720         \let\next\xepersian@localize@verbatim@
2721     \fi
2722   \next}%
2723 \def\xepersian@localize@verbatim@rescan#1#2-{%
2724     \if\noexpand~\noexpand#2-\else
2725     \warning{Characters dropped after `\'string\end{#1}'\fi}%
2726   \begingroup\verbatim\frenchspacing\@vobeyspaces
2727   \xepersian@localize@verbatim@start}%
2728 \namedef{*}{\begingroup\verbatim\xepersian@localize@verbatim@start}
2729 \def\end{\endtrivlist\endgroup\@doendpe}
2730 \expandafter\let\csname end*\endcsname=\end
2731 }{}%
2732 \ExplSyntaxOn
2733 \AtBeginDocument{

```



```
2783 {y}{ }{Grot} @ \
2784 {units}{ }{Grot} @ \
2785 {}{}
```

## 7.44 parsidigits.map

```
2786 LHSName "Digits"
2787 RHSName "ParsiDigits"
2788
2789 pass(Unicode)
2790 U+0030 <> U+06F0 ;
2791 U+0031 <> U+06F1 ;
2792 U+0032 <> U+06F2 ;
2793 U+0033 <> U+06F3 ;
2794 U+0034 <> U+06F4 ;
2795 U+0035 <> U+06F5 ;
2796 U+0036 <> U+06F6 ;
2797 U+0037 <> U+06F7 ;
2798 U+0038 <> U+06F8 ;
2799 U+0039 <> U+06F9 ;
2800
2801
2802 U+002C <> U+060C ; comma > arabic comma
2803 U+003F <> U+061F ; question mark -> arabic qm
2804 U+003B <> U+061B ; semicolon -> arabic semicolon
2805
2806 ; ligatures from Knuth's original CMR fonts
2807 U+002D U+002D <> U+2013 ; -- -> en dash
2808 U+002D U+002D U+002D <> U+2014 ; --- -> em dash
2809
2810 U+0027 <> U+2019 ; ' -> right single quote
2811 U+0027 U+0027 <> U+201D ; '' -> right double quote
2812 U+0022 > U+201D ; " -> right double quote
2813
2814 U+0060 <> U+2018 ; ` -> left single quote
2815 U+0060 U+0060 <> U+201C ; `` -> left double quote
2816
2817 U+0021 U+0060 <> U+00A1 ; !` -> inverted exclam
2818 U+003F U+0060 <> U+00BF ; ?` -> inverted question
2819
2820 ; additions supported in T1 encoding
2821 U+002C U+002C <> U+201E ; , , -> DOUBLE LOW-9 QUOTATION MARK
2822 U+003C U+003C <> U+00AB ; << -> LEFT POINTING GUILLEMET
2823 U+003E U+003E <> U+00BB ; >> -> RIGHT POINTING GUILLEMET
```

## 7.45 rapport1-xepersian.def

```
2824 \ProvidesFile{rapport1-xepersian.def}[2010/07/25 v0.1 adaptations for rapport1 class]
2825 \renewcommand*\theprt{\@tartibi\c@part}
2826 \renewcommand*\appendix{\par
2827   \setcounter{chapter}{0}\%}
```

```

2828 \setcounter{section}{0}%
2829 \gdef\@chapapp{\appendixname}%
2830 \gdef\thechapter{\@harfi\c@chapter}%

```

#### 7.46 rapport3-xepersian.def

```

2831 \ProvidesFile{rapport3-xepersian.def}[2010/07/25 v0.2 adaptations for rapport3 class]
2832 \renewcommand*\thechapter{\@tartibi\c@part}
2833 \renewcommand*\appendix{\par
2834   \setcounter{chapter}{0}%
2835   \setcounter{section}{0}%
2836   \gdef\@chapapp{\appendixname}%
2837   \gdef\thechapter{\@harfi\c@chapter}%

```

#### 7.47 refrep-xepersian.def

```

2838 \ProvidesFile{refrep-xepersian.def}[2010/07/25 v0.2 adaptations for refrep class]
2839 \renewcommand \thechapter {\@tartibi\c@part}
2840 \renewcommand\appendix{\par
2841   \setcounter{chapter}{0}%
2842   \setcounter{section}{0}%
2843   \gdef\@chapapp{\appendixname}%
2844   \gdef\thechapter{\@harfi\c@chapter}%
2845 }%end appendix

```

#### 7.48 report-xepersian.def

```

2846 \ProvidesFile{report-xepersian.def}[2010/07/25 v0.2 adaptations for standard report class]
2847 \renewcommand \thechapter {\@tartibi\c@part}
2848 \renewcommand\appendix{\par
2849   \setcounter{chapter}{0}%
2850   \setcounter{section}{0}%
2851   \gdef\@chapapp{\appendixname}%
2852   \gdef\thechapter{\@harfi\c@chapter}%
2853 }%end appendix

```

#### 7.49 scrartcl-xepersian.def

```

2854 \ProvidesFile{scrartcl-xepersian.def}[2010/07/25 v0.2 adaptations for scrartcl class]
2855 \renewcommand*\thechapter{\@tartibi\c@part}
2856 \renewcommand*\appendix{\par%
2857   \setcounter{section}{0}%
2858   \setcounter{subsection}{0}%
2859   \gdef\thesection{\@harfi\c@section}%
2860   \csname appendixmore\endcsname
2861 }
2862 \renewcommand*{\@maybeautodot}[1]{%
2863   \ifx #1\stop\let\@maybeautodot\relax
2864   \else
2865     \ifx #1\harfi \c@autodottrue\fi
2866     \ifx #1\adadi \c@autodottrue\fi
2867     \ifx #1\tartibi \c@autodottrue\fi
2868     \ifx #1\Alpha \c@autodottrue\fi

```

```

2869   \ifx #1\alph \@autodottrue\fi
2870   \ifx #1\Roman \@autodottrue\fi
2871   \ifx #1\roman \@autodottrue\fi
2872   \ifx #1@\harfi \@autodottrue\fi
2873   \ifx #1@\adadi \@autodottrue\fi
2874   \ifx #1@\tartibi \@autodottrue\fi
2875   \ifx #1@\Alph \@autodottrue\fi
2876   \ifx #1@\alph \@autodottrue\fi
2877   \ifx #1@\Roman \@autodottrue\fi
2878   \ifx #1@\roman \@autodottrue\fi
2879   \ifx #1\romannumeral \@autodottrue\fi
2880 \fi
2881 \@@maybeautodot
2882 }

```

## 7.50 scrbook-xepersian.def

```

2883 \ProvidesFile{scrbook-xepersian.def}[2010/07/25 v0.2 adaptations for scrbook class]
2884 \renewcommand*\frontmatter{%
2885   \if@twoside\cleardoubleoddpage\else\clearpage\fi
2886   \@mainmatterfalse\pagenumbering{harfi}%
2887 }
2888 \renewcommand*{\thepart}{\@tartibi\c@part}
2889 \renewcommand*\appendix{\par%
2890   \setcounter{chapter}{0}%
2891   \setcounter{section}{0}%
2892   \gdef\chapapp{\appendixname}%
2893   \gdef\thechapter{\@harfi\c@chapter}%
2894   \csname appendixmore\endcsname
2895 }
2896 \renewcommand*{\@@maybeautodot}[1]{%
2897   \ifx #1@stop\let\@@maybeautodot\relax
2898   \else
2899     \ifx #1@\harfi \@autodottrue\fi
2900     \ifx #1@\adadi \@autodottrue\fi
2901     \ifx #1@\tartibi \@autodottrue\fi
2902     \ifx #1@\Alph \@autodottrue\fi
2903     \ifx #1@\alph \@autodottrue\fi
2904     \ifx #1@\Roman \@autodottrue\fi
2905     \ifx #1@\roman \@autodottrue\fi
2906     \ifx #1@\harfi \@autodottrue\fi
2907     \ifx #1@\adadi \@autodottrue\fi
2908     \ifx #1@\tartibi \@autodottrue\fi
2909     \ifx #1@\Alph \@autodottrue\fi
2910     \ifx #1@\alph \@autodottrue\fi
2911     \ifx #1@\Roman \@autodottrue\fi
2912     \ifx #1@\roman \@autodottrue\fi
2913     \ifx #1\romannumeral \@autodottrue\fi
2914   \fi
2915 \@@maybeautodot

```

```
2916 }
```

## 7.51 scrreprt-xepersian.def

```
2917 \ProvidesFile{scrreprt-xepersian.def}[2010/07/25 v0.2 adaptations for scrreprt class]
2918 \renewcommand*{\thepart}{\@tartibi\c@part}
2919 \renewcommand*\appendix{\par%
2920   \setcounter{chapter}{0}%
2921   \setcounter{section}{0}%
2922   \gdef\@chapapp{\appendixname}%
2923   \gdef\thechapter{\@harfi\c@chapter}%
2924   \csname appendixmore\endcsname
2925 }
2926 \renewcommand*{\@@maybeautodot}[1]{%
2927   \ifx #1\@stop\let\@@maybeautodot\relax
2928   \else
2929     \ifx #1\harfi \autodottrue\fi
2930     \ifx #1\adadi \autodottrue\fi
2931     \ifx #1\tartibi \autodottrue\fi
2932     \ifx #1\Alph \autodottrue\fi
2933     \ifx #1\alph \autodottrue\fi
2934     \ifx #1\Roman \autodottrue\fi
2935     \ifx #1\roman \autodottrue\fi
2936     \ifx #1\@harfi \autodottrue\fi
2937     \ifx #1\@adadi \autodottrue\fi
2938     \ifx #1\@tartibi \autodottrue\fi
2939     \ifx #1\@Alph \autodottrue\fi
2940     \ifx #1\@alph \autodottrue\fi
2941     \ifx #1\@Roman \autodottrue\fi
2942     \ifx #1\@roman \autodottrue\fi
2943     \ifx #1\romannumeral \autodottrue\fi
2944   \fi
2945   \@@maybeautodot
2946 }
```

## 7.52 tkz-linknodes-xepersian.def

```
2947 \ProvidesFile{tkz-linknodes-xepersian.def}[2012/06/13 v0.1 adaptations for tkz-linknodes package]
2948 \renewcommand*{\@SetTab}{%
2949   \let\@alph\@latinalph%
2950   \ifnum \value{C@NumTab}>25\relax%
2951     \setcounter{C@NumTab}{1}%
2952   \else%
2953     \stepcounter{C@NumTab}%
2954   \fi%
2955   \setcounter{C@NumGroup}{0}%
2956 \newcommand*{\PrefixCurrentTab}{\alph{C@NumTab}}
2957   \setboolean{B@FirstLink}{true}
2958   \setboolean{B@NewGroup}{false}
2959   \setcounter{C@NumGroup}{0}
2960   \setcounter{C@CurrentGroup}{0}
```

```

2961 \setcounter{NumC@Node}{0}
2962 \setcounter{NumC@Stop}{0}
2963 \setcounter{C@NextNode}{0}
2964 \setcounter{C@CurrentStop}{0}
2965 \setcounter{C@CurrentNode}{0}
2966 }%

```

### 7.53 tocloft-xepersian.def

```

2967 \ProvidesFile{tocloft-xepersian.def}[2010/07/25 v0.1 bilingual captions for tocloft package]
2968 \renewcommand*{\cftchapname}{\if@RTL else\ chapter\fi}
2969 \renewcommand*{\cftsecname}{\if@RTL else\ section\fi}
2970 \renewcommand*{\cftsubsecname}{\if@RTL else\ subsection\fi}
2971 \renewcommand*{\cftsubsubsecname}{\if@RTL else\ subsubsection\fi}
2972 \renewcommand*{\cftparaname}{\if@RTL else\ paragraph\fi}
2973 \renewcommand*{\cftsubparaname}{\if@RTL else\ subparagraph\fi}
2974 \renewcommand*{\cftfigname}{\if@RTL else\ figure\fi}
2975 \renewcommand*{\cftsubfigname}{\if@RTL else\ subfigure\fi}
2976 \renewcommand*{\cfttabname}{\if@RTL else\ table\fi}
2977 \renewcommand*{\cftsubtabname}{\if@RTL else\ subtable\fi}

```

### 7.54 xepersian.sty

```

2978 \NeedsTeXFormat{LaTeX2e}
2979 \def\xepersianversion{v13.9}
2980 \def\xepersiandate{2014/07/10}
2981 \ProvidesPackage{xepersian}[\xepersiandate\space \xepersianversion\space
2982 Persian typesetting in XeLaTeX]
2983 \RequirePackage{fontspec}
2984 \RequirePackage{xepersian-persiancal}
2985 \RequirePackage{xepersian-mathsdigitspec}
2986 \RequirePackage[RTLdocument]{bidi}
2987 \edef\xepersian@info{*****^J%
2988 * ^J%
2989 * xepersian package (Persian for LaTeX, using XeTeX engine)^J%
2990 * ^J%
2991 * Description: The package supports Persian^J%
2992 * typesetting, using fonts provided in the^J%
2993 * distribution.^J%
2994 * ^J%
2995 * Copyright © 2008-2013 Vafa Khalighi^J%
2996 * ^J%
2997 * \xepersianversion, \xepersiandate^J%
2998 * ^J%
2999 * License: LaTeX Project Public License, version^J%
3000 * 1.3c or higher (your choice)^J%
3001 * ^J%
3002 * Location on CTAN: /macros/xetex/latex/xepersian^J%
3003 * ^J%
3004 * Issue tracker: https://sourceforge.net/p/xepersian-project/tickets^J%
3005 * ^J%

```

```

3006 * Support: persian-tex@tug.org^^J%
3007 ****
3008 \typeout{\xepersian@info}
3009 \edef\xepersian@everyjob{\the\everyjob}
3010 \everyjob{\xepersian@everyjob\typeout{\xepersian@info}}
3011 \def\prq{<}
3012 \def\plq{>}
3013 \def\xepersian@cmds@temp#1{%
3014   \begingroup\expandafter\expandafter\expandafter\endgroup
3015   \expandafter\ifx\csname xepersian@#1\endcsname\relax
3016     \begingroup
3017       \escapechar=-1 %
3018       \edef\x{\expandafter\meaning\csname#1\endcsname}%
3019       \def\y{#1}%
3020       \def\z{\#1->{}}%
3021       \edef\y{\expandafter\z\meaning\y}%
3022     \expandafter\endgroup
3023     \ifx\x\y
3024       \expandafter\def\csname xepersian@#1\expandafter\endcsname
3025       \expandafter{\%
3026         \csname#1\endcsname
3027       }%
3028     \fi
3029   \fi
3030 }%
3031 \xepersian@cmds@temp{shellescape}
3032 \newif\ifwritexviii
3033 \ifnum\xepersian@shellescape=1\relax
3034   \writexviiittrue
3035 \else
3036 \writexviiifalse
3037 \fi
3038 \newfontscript{Parsi}{arab}
3039 \newfontlanguage{Parsi}{FAR}
3040 \ExplSyntaxOn
3041 \DeclareDocumentCommand \settextfont { O{} m } {
3042   \fontspec_select:nn{Script=Parsi,Language=Parsi,Mapping=parsidigits,#1}{#2}
3043   \use:x {
3044     \exp_not:N \ DeclareRobustCommand \exp_not:N \persianfont {
3045       \exp_not:N \fontencoding {\g_fontspec_encoding_tl}
3046       \exp_not:N \fontfamily {\l_fontspec_family_tl} \exp_not:N \selectfont
3047     }
3048   }
3049   \cs_set_eq:NN \rmdefault \l_fontspec_family_tl
3050   \normalfont
3051 }
3052 \settextfont[ExternalLocation,BoldFont={persian-modern-bold},BoldItalicFont={persian-modern-italic}]
3053 \setdigitfont[ExternalLocation,BoldFont={persian-modern-bold},BoldItalicFont={persian-modern-italic}]
3054 \DeclareDocumentCommand \setlatintextfont { O{} m } {
3055   \fontspec_select:nn{Mapping=tex-text,#1}{#2}

```

```

3056 \use:x {
3057   \exp_not:N \ DeclareRobustCommand \exp_not:N \latinfont {
3058     \exp_not:N \fontencoding {\g_fontsspec_encoding_t1}
3059     \exp_not:N \fontfamily {\l_fontspec_family_t1} \exp_not:N \selectfont
3060   }
3061 }
3062 }
3063 \setlatintextfont[ExternalLocation,BoldFont={lmroman10-bold},BoldItalicFont={lmroman10-bolditalic}]
3064 \cs_set_eq:NN \setlatinsansfont \setsansfont
3065 \cs_set_eq:NN \setlatinmonofont \setmonofont
3066 \DeclareDocumentCommand \defpersianfont { m O{} m } {
3067   \fontspec_select:nn{Script=Parsi,Language=Parsi,Mapping=parsidigits,#2}{#3}
3068   \use:x {
3069     \exp_not:N \ DeclareRobustCommand \exp_not:N #1 {
3070       \exp_not:N \fontencoding {\g_fontspec_encoding_t1}
3071       \exp_not:N \fontfamily {\l_fontspec_family_t1} \exp_not:N \selectfont
3072     }
3073   }
3074 }
3075 \DeclareDocumentCommand \deflatinfont { m O{} m } {
3076   \fontspec_select:nn{Mapping=tex-text,#2}{#3}
3077   \use:x {
3078     \exp_not:N \ DeclareRobustCommand \exp_not:N #1 {
3079       \exp_not:N \fontencoding {\g_fontspec_encoding_t1}
3080       \exp_not:N \fontfamily {\l_fontspec_family_t1} \exp_not:N \selectfont
3081     }
3082   }
3083 }
3084 \newcommand\persiansfdefault{}
3085 \newcommand\persianttdefault{}
3086 \newcommand\iranicdefault{}
3087 \newcommand\navardefault{}
3088 \newcommand\pookdefault{}
3089 \newcommand\sayehdefault{}
3090 \DeclareRobustCommand\persiansffamily
3091   {\not@math@alphabet\persiansffamily\mathpersiansf
3092   \fontfamily\persiansfdefault\selectfont}
3093 \DeclareRobustCommand\persianttfamily
3094   {\not@math@alphabet\persianttfamily\mathpersiantt
3095   \fontfamily\persianttdefault\selectfont}
3096 \DeclareRobustCommand\iranicfamily
3097   {\not@math@alphabet\iranicfamily\mathiranic
3098   \fontfamily\iranicdefault\selectfont}
3099 \DeclareRobustCommand\navarfamilly
3100   {\not@math@alphabet\navarfamilly\mathnavar
3101   \fontfamily\navardefault\selectfont}
3102 \DeclareRobustCommand\pookfamily
3103   {\not@math@alphabet\pookfamily\mathpook
3104   \fontfamily\pookdefault\selectfont}
3105 \DeclareRobustCommand\sayehfamily

```

```

3106      {\not@math@alphabet\sayehfamily\mathsayeh
3107          \fontfamily\sayehdefault\selectfont}
3108 \DeclareTextFontCommand{\textpersiansf}{\persiansffamily}
3109 \DeclareTextFontCommand{\textpersiantt}{\persianttfamily}
3110 \DeclareTextFontCommand{\textiranic}{\iranicfamily}
3111 \DeclareTextFontCommand{\textnavar}{\navarfamly}
3112 \DeclareTextFontCommand{\textpook}{\pookfamily}
3113 \DeclareTextFontCommand{\textsayeh}{\sayehfamily}
3114 \DeclareDocumentCommand \setpersiansansfont { O{} m } {
3115   \fontspec_set_family:Nnn \persiansfdefault {Script=Parsi,Language=Parsi,Mapping=parsidigits,#}
3116   \normalfont
3117 }
3118 \DeclareDocumentCommand \setpersianmonofont { O{} m } {
3119   \fontspec_set_family:Nnn \persianttdefault {Script=Parsi,Language=Parsi,Mapping=parsidigits,#}
3120   \normalfont
3121 }
3122 \DeclareDocumentCommand \setnavarfont { O{} m } {
3123   \fontspec_set_family:Nnn \navardefault {Script=Parsi,Language=Parsi,Mapping=parsidigits,#1}{#}
3124   \normalfont
3125 }
3126 \DeclareDocumentCommand \setpookfont { O{} m } {
3127   \fontspec_set_family:Nnn \pookdefault {Script=Parsi,Language=Parsi,Mapping=parsidigits,#1}{#2}
3128   \normalfont
3129 }
3130 \setpookfont[ExternalLocation,ItalicFont={persian-modern-italicoutline},SlantedFont={persian-mo
3131 \DeclareDocumentCommand \setsayehfont { O{} m } {
3132   \fontspec_set_family:Nnn \sayehdefault {Script=Parsi,Language=Parsi,Mapping=parsidigits,#1}{#}
3133   \normalfont
3134 }
3135 \setsayehfont[ExternalLocation,ItalicFont={persian-modern-italicshadow},SlantedFont={persian-mo
3136 \DeclareDocumentCommand \setiranicfont { O{} m } {
3137   \fontspec_set_family:Nnn \iranicdefault {Script=Parsi,Language=Parsi,Mapping=parsidigits,#1}{#}
3138   \normalfont
3139 }
3140 \ExplSyntaxOff
3141 \setiranicfont[ExternalLocation,BoldFont={persian-modern-boldoblique}]{persian-modern-oblique}
3142 \def\resetlatinfont{%
3143 \let\normalfont\latinfont%
3144 \let\reset@font\normalfont%
3145 \latinfont}
3146 \def\setpersianfont{%
3147 \let\normalfont\persianfont%
3148 \let\reset@font\normalfont%
3149 \persianfont}
3150 \bidi@newrobustcmd*{\lr}[1]{\LRE{\@Latintrue\latinfont#1}}
3151 \bidi@newrobustcmd*{\rl}[1]{\RLE{\@Latinfalse\persianfont#1}}
3152 \def\latin{\LTR\LatinAlphs\@Latintrue\@RTL@footnotefalse\resetlatinfont}
3153 \def\endlatin{\endLTR}
3154 \def\persian{\RTL\PersianAlphs\@RTL@footnotetrue\setpersianfont}
3155 \def\endpersian{\endRTL}

```

```

3156 \newenvironment{latinitems}{\begin{LTRitems}\LatinAlphs\@Latintrue\@RTL@footnotefalse\resetlati
3157 \newenvironment{parsiitems}{\begin{RTLitems}\PersianAlphs\@RTL@footnotetrue\setpersianfont\{\c
3158 \let\originaltoday=\today
3159 \def\latintoday{\lr{\originaltoday}}
3160 \def\today{\rl{\persiantoday}}
3161 \def \@LTRmarginparreset {%
3162     \reset@font
3163     \latinfont
3164     \normalsize
3165     \minipagetrue
3166     \everypar{\minipagetrue\everypar{}\beginL}%
3167 }
3168 \DeclareRobustCommand\Latincite{%
3169   \@ifnextchar [{\@tempswatrue\@Latincitex}{\@tempswafalse\@Latincitex[]]}
3170 \def\@Latincitex[#1]#2{\leavevmode
3171   \let\@citea\empty
3172   \@cite{\lr{\@for\@citeb:=#2\do
3173     {\@citea\def\@citea{,\penalty\@m\ }%
3174       \edef\@citeb{\expandafter\firstofone\@citeb\empty}%
3175       \if@filesw\immediate\write\auxout{\string\citation{\@citeb}}\fi
3176       \ifundefined{b@\@citeb}{\hbox{\reset@font\bfseries ?}}%
3177         \G@refundefinedtrue
3178         \G@warning
3179         {Citation `@\citeb' on page \thepage\space undefined}%
3180       {\@cite@fmt{\csname b@\@citeb\endcsname}}}}}{#1}}
3181 \def\@outputpage{%
3182 \begingroup % the \endgroup is put in by \aftergroup
3183   \let \protect \noexpand
3184   \resetactivechars
3185   \global\let\@if@newlist\if@newlist
3186   \global\@newlistfalse
3187   \parboxrestore
3188   \shipout \vbox{%
3189     \set@typeset@protect
3190     \aftergroup \endgroup
3191     \aftergroup \set@typeset@protect
3192       % correct? or just restore by ending
3193       % the group?
3194   \if@specialpage
3195     \global\@specialpagefalse\@nameuse{ps@\@specialstyle}%
3196   \fi
3197   \if@twoside
3198     \ifodd\count\z@ \let\@thehead\@oddhead \let\@tfoot\@oddfoot
3199       \let\@themargin\oddsidemargin
3200     \else \let\@thehead\@evenhead
3201       \let\@tfoot\@evenfoot \let\@themargin\evensidemargin
3202     \fi
3203     \ifx\@thehead\empty \let\@thehead\hfil \fi
3204     \ifx\@tfoot\empty \let\@tfoot\hfil \fi
3205   \else %% not @twoside

```

```

3206   \ifx\@oddhead\@empty \let\@thehead\hfil \fi
3207   \ifx\@oddfoot\@empty \let\@thefoot\hfil \fi
3208 \fi
3209 \reset@font
3210 \normalsize
3211 \if@RTLmain\setpersianfont\else\resetlatinfont\fi
3212 \normalsfcodes
3213 \let\label\gobble
3214 \let\index\gobble
3215 \let\glossary\gobble
3216 \baselineskip\z@skip \lineskip\z@skip \lineskiplimit\z@
3217   \begindvi
3218   \vskip \topmargin
3219   \moveright\themargin \vbox {%
3220     \setbox\@tempboxa \vbox to\headheight{%
3221       \vfil
3222       \color@hbox
3223         \normalcolor
3224       \hb@xt@\textwidth{\if@RTLmain\@RTLtrue\beginR\else\@RTLfalse\beginL\fi\@thehead\if@RTLm
3225         \color@endbox
3226       }%
3227           %% 22 Feb 87
3228     \dp\@tempboxa \z@
3229     \box\@tempboxa
3230     \vskip \headsep
3231     \box\@outputbox
3232     \baselineskip \footskip
3233     \color@hbox
3234       \normalcolor
3235       \hb@xt@\textwidth{\if@RTLmain\@RTLtrue\beginR\else\@RTLfalse\beginL\fi\@thefoot\if@RTLma
3236         \color@endbox
3237       }%
3238   \global\let\if@newlist\@@if@newlist
3239   \global \colht \textheight
3240   \stepcounter{page}%
3241   \let\firstmark\botmark
3242 }
3243 \newcommand\twocolumnstableofcontents{%
3244 @ifpackageloaded{multicol}{%
3245   \begin{multicols}{2}[\section*\{\contentsname}\]%
3246     \small
3247     \starttoc{toc}%
3248   \end{multicols}}
3249 {\PackageError{xepersian}{Oops! you should load multicol package before xepersian package for bei
3250 \def\XePersian{\leavevmode$\smash{\hbox{X}\lower.5ex
3251   \hbox{\kern-.125em\bidi@reflect@box{E}}Persian}}$}
3252 \def\figurename{\if@RTL else\ Figure\fi}
3253 \def\tablename{\if@RTL else\ Table\fi}
3254 \def\contentsname{\if@RTL else\ Contents\fi}

```



```

3305 \else\ifnum#1<1000000 6%
3306 \else\ifnum#1<10000000 7%
3307 \else\ifnum#1<100000000 8%
3308 \else9%
3309 \fi\fi\fi\fi\fi\fi\fi %
3310 \or0000000#1% case 1: Add 8 leading zeros
3311 \or000000#1% case 2: Add 7 leading zeros
3312 \or00000#1% case 3: Add 6 leading zeros
3313 \or0000#1% case 4: Add 5 leading zeros
3314 \or000#1% case 5: Add 4 leading zeros
3315 \or00#1% case 6: Add 3 leading zeros
3316 \or0#1% case 7: Add 2 leading zeros
3317 \or0#1% case 8: Add 1 leading zero
3318 \or#1% case 9: Add no leading zeros
3319 \or%
3320 \nil#2%
3321 \fi%
3322 }
3323 \def\xepersian@adadi#1#2#3#4#5#6#7\or#8\nil#9{%
3324 \ifnum#1#2#3>\z@
3325 \xepersian@milyoongan#1#2#3%
3326 \ifnum#7>\z@\ifnum#4#5#6>\z@\ \else\ \fi\else\ifnum#4#5#6>\z@\ \fi\fi%
3327 \fi%
3328 \ifnum#4#5#6>\z@%
3329 \xepersian@sadgan#4#5#6{#1#2#3}{#4#5}\xepersian@yekani%
3330 \ifnum#4#5#6>\@ne\fi%
3331 %
3332 \ifnum#7>\z@\ \fi%
3333 \fi%
3334 \xepersian@sadgan#7{#4#5#6}1#9%
3335 }
3336 \def\xepersian@milyoongan#1#2#3{%
3337 \ifnum#1#2#3=\@ne%
3338 \xepersian@sadgan#1#2#301\xepersian@yekanii%
3339 %
3340 %
3341 \else%
3342 \xepersian@sadgan#1#2#301\xepersian@yekanii%
3343 %
3344 %
3345 \fi%
3346 }
3347 \def\xepersian@sadgan#1#2#3#4#5#6{%
3348 \ifnum#1>\z@%
3349 \ifnum#4#1>\@ne\xepersian@yekaniv#1\fi%
3350 %
3351 \ifnum#2#3>\z@\ \fi%
3352 \fi%
3353 \ifnum#2#3<20%
3354 \ifnum#5#2#3>\@ne#6{#2#3}\fi%

```

```

3355 \else%
3356 \xepersian@dahgan#2%
3357 \ifnum#3>\z@ \xepersian@yekani#3\fi%
3358 #60%
3359 \fi%
3360 }
3361 \def\xepersian@yekani#1{%
3362 \ifcase#1\empty\or\or\or\or\or\or\or\or\ %
3363 \or\or\or\or\or\or\or\or\or\ %
3364 \or\or\or\or\or\or\or\or\ %
3365 \or\or\%fi\
3366 }
3367 \def\xepersian@yekanii#1{%
3368 \ifcase#1\empty\or\%else\xepersian@yekani{#1}\fi\
3369 }
3370 \def\xepersian@yekaniii#1{%
3371 \ifcase#1\empty\or\%else\xepersian@yekani{#1}\fi\
3372 }
3373 \def\xepersian@yekaniv#1{%
3374 \ifcase#1\empty\or\or\or\or\or\or\or\or\ %
3375 \or\or\or\or\%fi\
3376 }
3377 \def\xepersian@dahgan#1{%
3378 \ifcase#1\or\or\or\or\ %
3379 \or\or\or\or\ %
3380 \or\%fi\
3381 }
3382 \newcommand{\tartibi}[1]{%
3383 \expandafter\tartibi\csname c@#1\endcsname%
3384 }
3385 \newcommand{\@tartibi}[1]{%
3386 \xepersian@numberstring@tartibi{#1}\xepersian@tartibi{ }{ }%
3387 }
3388 \let\tartibinumeral\tartibi%
3389 \def\xepersian@numberstring@tartibi#1#2#3#4{%
3390 \ifnum\number#1<\@ne%
3391 #3%
3392 \else\ifnum\number#1<1000000000 %
3393 \expandafter\xepersian@adadi@tartibi\expandafter{\number#1}#2%
3394 \else%
3395 \xepersian@numberoutofrange{#1}{#4}%
3396 \fi\fi%
3397 }
3398 \def\xepersian@adadi@tartibi#1#2{%
3399 \expandafter\xepersian@adadi@tartibi%
3400 \ifcase%
3401 \ifnum#1<10 1%
3402 \else\ifnum#1<100 2%
3403 \else\ifnum#1<\@m 3%
3404 \else\ifnum#1<\@M 4%

```

```

3405 \else\ifnum#1<100000 5%
3406 \else\ifnum#1<1000000 6%
3407 \else\ifnum#1<10000000 7%
3408 \else\ifnum#1<100000000 8%
3409 \else9%
3410 \fi\fi\fi\fi\fi\fi\fi %
3411 \or0000000#1% case 1: Add 8 leading zeros
3412 \or000000#1% case 2: Add 7 leading zeros
3413 \or00000#1% case 3: Add 6 leading zeros
3414 \or0000#1% case 4: Add 5 leading zeros
3415 \or000#1% case 5: Add 4 leading zeros
3416 \or00#1% case 6: Add 3 leading zeros
3417 \or0#1% case 7: Add 2 leading zeros
3418 \or0#1% case 8: Add 1 leading zero
3419 \or#1% case 9: Add no leading zeros
3420 \or%
3421 \nil#2%
3422 \fi%
3423 }
3424 \def\xepersian@@adadi@tartibi#1#2#3#4#5#6#7\or#8\@nil#9{%
3425 \ifnum#1#2#3>\z@%
3426 \xepersian@milyoongan@tartibi#1#2#3%
3427 \ifnum#7>\z@\ifnum#4#5#6>\z@\ \ \else\ \fi\else\ifnum#4#5#6>\z@\ \ \fi\fi%
3428 \fi%
3429 \ifnum#4#5#6>\z@%
3430 \xepersian@sadgan#4#5#6{#1#2#3}{#4#5}\xepersian@yekani%
3431 \ifnum#4#5#6>\@ne \fi%
3432 %
3433 \ifnum#7>\z@\ \ \fi%
3434 \fi%
3435 \xepersian@sadgan@tartibi#7{#4#5#6}1#9%
3436 }
3437 \def\xepersian@milyoongan@tartibi#1#2#3{%
3438 \ifnum#1#2#3=\@ne%
3439 \xepersian@sadgan@tartibi#1#2#301\xepersian@yekaniii%
3440 %
3441 %
3442 \else%
3443 \xepersian@sadgan#1#2#301\xepersian@yekanii%
3444 %
3445 %
3446 \fi%
3447 }
3448 \def\xepersian@sadgan@tartibi#1#2#3#4#5#6{%
3449 \ifnum#1>\z@%
3450 \ifnum#4#1>\@ne\xepersian@yekaniv#1\fi%
3451 %
3452 \ifnum#2#3>\z@\ \ \fi%
3453 \fi%
3454 \ifnum#2#3<20%

```

```

3455 \ifnum#5#2#3>\@ne\ifnum#1#2#3#4#5=10001 %else#6{#2#3}\fi\fi\
3456 \else%
3457 \xepersian@dahgan#2%
3458 \ifnum#3>\z@\ \ \xepersian@yekanv#3\fi%
3459 #60%
3460 \fi%
3461 }
3462 \def\xepersian@tartibi#1{%
3463 \ifcase#1\or or\ or\ or\ or\ %
3464 \or or\ or\ or\ or\ or\ %
3465 \or or\ or\ or\ or\ %
3466 \or or\ or\ or\ %
3467 \or or\ or\ %fi\
3468 }
3469 \def\xepersian@yekanv#1{%
3470 \ifcase#1\empty\or or\ or\ or\ or\ or\ %
3471 \or or\ or\ or\ or\ or\ or\ %
3472 \or or\ or\ or\ or\ %
3473 \or or\ %fi\
3474 }
3475 \providecommand*\xpg@warning}[1]{%
3476   \PackageWarning{XePersian}%
3477   {#1}}
3478 \if@bidi@csundef{abjadnumeral}{%
3479 \def\abjadnumeral#1{%
3480 \ifnum#1>1999 \xpg@warning{Illegal value (#1) for abjad numeral} {#1}
3481 \else
3482   \ifnum#1<\z@\space\xpg@warning{Illegal value (#1) for abjad numeral}%
3483   \else
3484     \ifnum#1<10\expandafter\abj@num@i\number#1%
3485     \else
3486       \ifnum#1<100\expandafter\abj@num@ii\number#1%
3487       \else
3488         \ifnum#1<\@m\expandafter\abj@num@iii\number#1%
3489         \else
3490           \ifnum#1<\@M\expandafter\abj@num@iv\number#1%since #1<2000, we must have 1000
3491           \fi
3492           \fi
3493           \fi
3494         \fi
3495       \fi
3496     \fi
3497   }
3498 \def\abjad@zero{}%
3499 \def\abj@num@i#1{%
3500   \ifcase#1\or or\ or\ or\ %
3501     \or or\ or\ or\ or\ fi\
3502 \ifnum#1=\z@\abjad@zero\fi}
3503 \def\abj@num@ii#1{%
3504   \ifcase#1\or or\ or\ or\ or\ %

```

```

3505           \or\ or\ or\ or\ fi\
3506   \ifnum#1=\z@\fi\abj@num@i}
3507 \def\abj@num@iii#1{%
3508   \ifcase#1\or\or\or\or\or\or\ %
3509       \or\or\or\or\or\or\ fi\
3510   \ifnum#1=\z@\fi\abj@num@ii}
3511 \def\abj@num@iv#1{%
3512   \ifcase#1\or\ fi\
3513   \ifnum#1=\z@\fi\abj@num@iii}
3514 }{}}
3515   \let\@latinalph\@alph%
3516   \let\@latinAlpha\@Alpha%
3517 \def\PersianAlphs{%
3518   \let\@alph\abjadnumeral%
3519   \let\@Alpha\abjadnumeral%
3520 }
3521 \def\LatinAlphs{%
3522   \let\@alph\@latinalph%
3523   \let\@Alpha\@latinAlpha%
3524 }
3525 \PersianAlphs
3526 @ifdefinitionfileloaded{loadingorder-xetex-bidi}{\input{loadingorder-xepersian.def}}{}
3527 @ifpackageloaded{fontspec-xetex}{\input{fontspec-xetex-xepersian.def}}{}
3528 @ifpackageloaded{listings}{\input{listings-xepersian.def}}{}
3529 @ifpackageloaded{algorithmic}{\input{algorithmic-xepersian.def}}{}
3530 @ifpackageloaded{algorithm}{\input{algorithm-xepersian.def}}{}
3531 @ifpackageloaded{backref}{\input{backref-xepersian.def}}{}
3532 @ifpackageloaded{flowfram}{\input{flowfram-xepersian.def}}{}
3533 @ifpackageloaded{bidi}{\input{footnote-xepersian.def}}{}
3534 @ifpackageloaded{biditufteidenote}{\input{biditufteidenote-xepersian.def}}{}
3535 @ifpackageloaded{breqn}{\input{breqn-xepersian.def}}{}
3536 @ifpackageloaded{enumerate}{\input{enumerate-xepersian.def}}{}
3537 @ifpackageloaded{framed}{\input{framed-xepersian.def}}{}
3538 @ifpackageloaded{glossaries}{\input{glossaries-xepersian.def}}{}
3539 @ifpackageloaded{hyperref}{\input{hyperref-xepersian.def}}{}
3540 @ifpackageloaded{minitoc}{\input{minitoc-xepersian.def}}{}
3541 @ifpackageloaded{natbib}{\input{natbib-xepersian.def}}{}
3542 @ifpackageloaded{tkz-linknodes}{\input{tkz-linknodes-xepersian.def}}{}
3543 @ifpackageloaded{tocloft}{\@ifclassloaded{memoir}{}{\input{tocloft-xepersian.def}}}={}
3544 \@ifclassloaded{article}{\input{article-xepersian.def}}{}
3545 \@ifclassloaded{extarticle}{\input{extarticle-xepersian.def}}{}
3546 \@ifclassloaded{artikel1}{\input{artikel1-xepersian.def}}{}
3547 \@ifclassloaded{artikel2}{\input{artikel2-xepersian.def}}{}
3548 \@ifclassloaded{artikel3}{\input{artikel3-xepersian.def}}{}
3549 \@ifclassloaded{amsart}{\input{amsart-xepersian.def}}{}
3550 \@ifclassloaded{bidimoderncv}{\input{bidimoderncv-xepersian.def}}{}
3551 \@ifclassloaded{report}{\input{report-xepersian.def}}{}
3552 \@ifclassloaded{extreport}{\input{extreport-xepersian.def}}{}
3553 \@ifclassloaded{rapport1}{\input{rapport1-xepersian.def}}{}
3554 \@ifclassloaded{rapport3}{\input{rapport3-xepersian.def}}{}

```

```

3555 \@ifclassloaded{scrartcl}{\input{scrartcl-xepersian.def}}{}
3556 \@ifclassloaded{scrbook}{\input{scrbook-xepersian.def}}{}
3557 \@ifclassloaded{scrreprt}{\input{scrreprt-xepersian.def}}{}
3558 \@ifclassloaded{amsbook}{\input{amsbook-xepersian.def}}{}
3559 \@ifclassloaded{boek3}{\input{boek3-xepersian.def}}{}
3560 \@ifclassloaded{boek}{\input{boek-xepersian.def}}{}
3561 \@ifclassloaded{bookest}{\input{bookest-xepersian.def}}{}
3562 \@ifclassloaded{extbook}{\input{extbook-xepersian.def}}{}
3563 \@ifclassloaded{book}{\input{book-xepersian.def}}{}
3564 \@ifclassloaded{refrep}{\input{refrep-xepersian.def}}{}
3565 \@ifclassloaded{memoir}{\input{memoir-xepersian.def}}{}
3566 \@ifclassloaded{imsproc}{\input{imsproc-xepersian.def}}{}
3567 \DeclareOption{Kashida}{\input{kashida-xepersian.def}}
3568 \DeclareOption{localise}{\input{localise-xepersian.def}}
3569 \DeclareOption{extrafootnotefeatures}{\@extrafootnotefeaturestrue}
3570 \DeclareOption{quickindex}{%
3571 \PackageWarning{xepersian}{Obsolete option}%
3572 \ifwritexviii%
3573 \@ifclassloaded{memoir}{\PackageError{xepersian}{This feature does not yet work with the memoir
3574 \renewcommand\printindex{\newpage%
3575 \immediate\closeout\@indexfile
3576 \immediate\write18{xindy -L persian-variant2 -C utf8 -M texindy -M page-ranges \jobname.idx}
3577 \input{\jobname.ind}}}%
3578 \else
3579 \PackageError{xepersian}{"shell escape" (or "write18") is not enabled. You need to run "xelatex --%
3580 \fi}
3581 \DeclareOption{quickindex-variant1}{%
3582 \ifwritexviii%
3583 \@ifclassloaded{memoir}{\PackageError{xepersian}{This feature does not yet work with the memoir
3584 \renewcommand\printindex{\newpage%
3585 \immediate\closeout\@indexfile
3586 \immediate\write18{xindy -L persian-variant1 -C utf8 -M texindy -M page-ranges \jobname.idx}
3587 \input{\jobname.ind}}}%
3588 \else
3589 \PackageError{xepersian}{"shell escape" (or "write18") is not enabled. You need to run "xelatex --%
3590 \fi}
3591 \DeclareOption{quickindex-variant2}{%
3592 \ifwritexviii%
3593 \@ifclassloaded{memoir}{\PackageError{xepersian}{This feature does not yet work with the memoir
3594 \renewcommand\printindex{\newpage%
3595 \immediate\closeout\@indexfile
3596 \immediate\write18{xindy -L persian-variant2 -C utf8 -M texindy -M page-ranges \jobname.idx}
3597 \input{\jobname.ind}}}%
3598 \else
3599 \PackageError{xepersian}{"shell escape" (or "write18") is not enabled. You need to run "xelatex --%
3600 \fi}
3601 \ExecuteOptions{localise}
3602 \ProcessOptions
3603
3604 \if@extrafootnotefeatures

```

```

3605 \input{extrafootnotefeatures-xetex-bidi.def}
3606 \input{extrafootnotefeatures-xepersian.def}
3607 \fi

```

## 7.55 xepersian-magazine.cls

```

3608 \NeedsTeXFormat{LaTeX2e}
3609 \ProvidesClass{xepersian-magazine}[2010/07/25 v0.2 Typesetting Persian magazines in XeLaTeX]
3610 \RequirePackage{ifthen}
3611 \newlength{\xepersian@imgsize}
3612 \newlength{\xepersian@coltitlesize}
3613 \newlength{\xepersian@pageneed}
3614 \newlength{\xepersian@pageleft}
3615 \newlength{\xepersian@indexwidth}
3616 \newcommand{\xepersian@ncolumns}{0}
3617 \newlength{\columnlines}
3618 \setlength{\columnlines}{0 pt} % no lines by default
3619 \newboolean{xepersian@hyphenatedtitles}
3620 \setboolean{xepersian@hyphenatedtitles}{true}
3621 \newboolean{xepersian@ninepoints}
3622 \setboolean{xepersian@ninepoints}{false}
3623 \newboolean{xepersian@showgrid}
3624 \setboolean{xepersian@showgrid}{false}
3625 \newboolean{xepersian@a3paper}
3626 \setboolean{xepersian@a3paper}{false}
3627 \newboolean{xepersian@insidefrontpage}
3628 \setboolean{xepersian@insidefrontpage}{false}
3629 \newboolean{xepersian@insideweather}
3630 \setboolean{xepersian@insideweather}{false}
3631 \newboolean{xepersian@insideindex}
3632 \setboolean{xepersian@insideindex}{false}
3633 \newcount\xepersian@gridrows
3634 \newcount\xepersian@gridcolumns
3635 \xepersian@gridrows=40
3636 \xepersian@gridcolumns=50
3637 \newcount\minraggedcols
3638 \minraggedcols=5
3639 \DeclareOption{10pt}{\PassOptionsToClass{10pt}{article}}
3640 \DeclareOption{11pt}{\PassOptionsToClass{11pt}{article}}
3641 \DeclareOption{12pt}{\PassOptionsToClass{12pt}{article}}
3642 \DeclareOption{twocolumn}{%
3643 {\ClassWarning{xepersian-magazine}{Option 'twocolumn' not available for xepersian-magazine.}}%
3644 \DeclareOption{notitlepage}{%
3645 {\ClassWarning{xepersian-magazine}{Option 'notitlepage' not available for xepersian-magazine.}}%
3646 \DeclareOption{twoside}{%
3647 {\ClassWarning{xepersian-magazine}{Option 'twoside' not available for xepersian-magazine.}}%
3648 \DeclareOption{9pt}{\setboolean{xepersian@ninepoints}{true}}
3649 \DeclareOption{hyphenatedtitles}{\setboolean{xepersian@hyphenatedtitles}{false}}
3650 \DeclareOption{columnlines}{\setlength{\columnlines}{0.1 pt}}
3651 \DeclareOption{showgrid}{\setboolean{xepersian@showgrid}{true}}%

```

```

3652 \DeclareOption{a3paper}{\setboolean{xepersian@a3paper}{true}}
3653 \ProcessOptions\relax
3654 \LoadClass[10pt, onecolumn, titlepage, a4paper]{article}
3655 \RequirePackage{ifxetex}
3656 \RequirePackage{multido}
3657 \RequirePackage{datetime}
3658 \RequirePackage{multicol}
3659 \RequirePackage{fancyhdr}
3660 \RequirePackage{fancybox}
3661 \ifthenelse{\boolean{xepersian@a3paper}}{%
3662 \RequirePackage[a3paper,headsep=0.5cm,vmargin={2cm,2cm},hmargin={1.5cm,1.5cm}]{geometry}
3663 }{
3664 \RequirePackage[headsep=0.5cm,vmargin={2cm,2cm},hmargin={1.5cm,1.5cm}]{geometry}
3665 }
3666 \RequirePackage[absolute]{textpos} % absoulte positioning
3667 \RequirePackage{hyphenat} % when hyphenate
3668 \RequirePackage{lastpage} % to know the last page number
3669 \RequirePackage{setspace} % set space between lines
3670 \RequirePackage{ragged2e}
3671 \newcommand{\raggedFormat}{\RaggedLeft}
3672 \AtEndOfClass{\xepersianInit}
3673 \ifthenelse{\boolean{xepersian@showgrid}}{%
3674 \AtBeginDocument{
3675 \grid[show]{\xepersian@gridrows}{\xepersian@gridcolumns}}
3676 \advance\minraggedcols by -1
3677 }%
3678 \AtBeginDocument{
3679 \grid[]{\xepersian@gridrows}{\xepersian@gridcolumns}}
3680 \advance\minraggedcols by -1
3681 }
3682 \ifthenelse{\boolean{xepersian@ninepoints}}{%
3683 \renewcommand{\normalsize}{%
3684   \@setfontsize{\normalsize}{9pt}{10pt}%
3685   \setlength{\abovedisplayskip}{5pt plus 1pt minus .5pt}%
3686   \setlength{\belowdisplayskip}{\abovedisplayskip}%
3687   \setlength{\abovedisplayshortskip}{3pt plus 1pt minus 2pt}%
3688   \setlength{\belowdisplayshortskip}{\abovedisplayshortskip}%
3689
3690 \renewcommand{\tiny}{\@setfontsize{\tiny}{5pt}{6pt}}%
3691
3692 \renewcommand{\scriptsize}{\@setfontsize{\scriptsize}{7pt}{8pt}}%
3693
3694 \renewcommand{\small}{%
3695   \@setfontsize{\small}{8pt}{9pt}%
3696   \setlength{\abovedisplayskip}{4pt plus 1pt minus 1pt}%
3697   \setlength{\belowdisplayskip}{\abovedisplayskip}%
3698   \setlength{\abovedisplayshortskip}{2pt plus 1pt}%
3699   \setlength{\belowdisplayshortskip}{\abovedisplayshortskip}%
3700
3701 \renewcommand{\footnotesize}{%

```

```

3702  \setlength{\footnotesize}{8pt}{9pt}%
3703  \setlength{\abovedisplayskip}{4pt plus 1pt minus .5pt}%
3704  \setlength{\belowdisplayskip}{\abovedisplayskip}%
3705  \setlength{\abovedisplayshortskip}{2pt plus 1pt}%
3706  \setlength{\belowdisplayshortskip}{\abovedisplayshortskip}%
3707
3708 \renewcommand{\large}{\@setfontsize{\large}{11pt}{13pt}}
3709 \renewcommand{\Large}{\@setfontsize{\Large}{14pt}{18pt}}
3710 \renewcommand{\LARGE}{\@setfontsize{\LARGE}{18pt}{20pt}}
3711 \renewcommand{\huge}{\@setfontsize{\huge}{20pt}{25pt}}
3712 \renewcommand{\Huge}{\@setfontsize{\Huge}{25pt}{30pt}}
3713 }{%
3714 \def\customwwwTxt#1{\gdef\@customwwwTxt{\lr{#1}}}
3715 \newcommand{\xepersian@wwwFormat}{\sffamily}
3716 \newcommand{\xepersian@www}{%
3717 \raisebox{-3pt}{{\xepersian@wwwFormat\@customwwwTxt}}}
3718 }
3719 \newcommand{\xepersian@edition}{%
3720 \newcommand{\editionFormat}{\large\bfseries\texttt}
3721 \newcommand{\xepersian@editionLogo}{%
3722 \raisebox{-3pt}{%
3723 {\editionFormat\xepersian@edition}}%
3724 }%
3725 }
3726 \newcommand{\indexFormat}{\large\bfseries}
3727 \newcommand{\xepersian@indexFrameTitle}[1]{%
3728 {\begin{flushright}{\indexFormat #1}\end{flushright}}%
3729 }
3730 \newcommand{\indexEntryFormat}{\normalsize}
3731 \newcommand{\xepersian@indexEntry}[1]{%
3732 {\begin{minipage}{13\TPHorizModule}%
3733 \indexEntryFormat\noindent\ignorespaces{#1}%
3734 \end{minipage}}%
3735 \newcommand{\indexEntrySeparator}{\rule{\xepersian@indexwidth}{.1pt}}
3736 \newcommand{\indexEntryPageTxt}{%
3737 \newcommand{\indexEntryPageFormat}{\footnotesize}
3738 {\indexEntryPageFormat{\indexEntryPageTxt{}~#1}}%
3739 }
3740 \newcommand{\headDateTimeFormat}{}
3741 \newcommand{\xepersian@headDateTime}{%
3742 \headDateTimeFormat\date\hspace{5pt}\$\\parallel\$\\hspace{5pt}%
3743 \currenttime %
3744 }
3745 \newcommand{\weatherFormat}{\bfseries}
3746 \newcommand{\xepersian@weather}[1]{%
3747 \noindent{\weatherFormat #1}%
3748 }
3749 \newcommand{\weatherTempFormat}{\small}
3750 \newcommand{\weatherUnits}{\textdegree{}C}
3751 \newcommand{\xepersian@section}[0]{%

```

```

3752 \newcommand{\xepersian@headleft}{%
3753 {\small\bfseries \@custommagazinename} \date
3754 }
3755 \newcommand{\xepersian@headcenter}{%
3756 \xepersian@section{}
3757 }
3758 \newcommand{\xepersian@headright}{%
3759 \small\xepersian@edition%
3760 \hspace*{5pt}\beginL\thepage\ / \pageref{LastPage}\endL
3761 }
3762
3763 \newcommand{\heading}[3]{%
3764 \renewcommand{\xepersian@headleft}{\beginR#1\endR}%
3765 \renewcommand{\xepersian@headcenter}{\beginR#2\endR}%
3766 \renewcommand{\xepersian@headright}{\beginR#3\endR}%
3767 }
3768 \newcommand{\xepersian@footright}{%
3769 {\footnotesize\lr{\copyright\ \@customwwwTxt{}-- - \lr{\XePersian}}}%
3770 }
3771 \newcommand{\xepersian@footcenter}{%
3772 }
3773 \newcommand{\xepersian@footleft}{%
3774 }
3775
3776 \newcommand{\foot}[3]{%
3777 \renewcommand{\xepersian@footleft}{\beginR#1\endR}%
3778 \renewcommand{\xepersian@footcenter}{\beginR#2\endR}%
3779 \renewcommand{\xepersian@footright}{\beginR#3\endR}%
3780 }
3781 \newcommand{\firstTitleFormat}{\Huge\bfseries\flushright}
3782 \newcommand{\xepersian@firstTitle}[1]{%
3783 {%
3784 \begin{spacing}{2.0}{%
3785 \noindent\ignorespaces
3786 \ifthenelse{\boolean{xepersian@hyphenatedtitles}}{%
3787 {\nohyphens{\firstTitleFormat #1}}{%
3788 {\firstTitleFormat #1}}{%
3789 }{%
3790 \end{spacing}}{%
3791 }{%
3792 }{%
3793 \newcommand{\firstTextFormat}{}
3794 \newcommand{\xepersian@firstText}[1]{%
3795 {\noindent\ignorespaces\firstTextFormat #1}{%
3796 }{%
3797 \newcommand{\secondTitleFormat}{\LARGE\bfseries}
3798 \newcommand{\xepersian@secondTitle}[1]{%
3799 \begin{spacing}{1.5}{%
3800 \noindent\ignorespaces\flushright
3801 \ifthenelse{\boolean{xepersian@hyphenatedtitles}}{%

```

```

3802 {\nohyphens{\secondTitleFormat #1}}%
3803 {{\secondTitleFormat #1}}%
3804 }\end{spacing}%
3805 }
3806 \newcommand{\secondSubtitleFormat}{\large}
3807 \newcommand{\xepersian@secondSubtitle}[1]{%
3808 {\noindent\ignorespaces{\secondSubtitleFormat #1}}%
3809 }
3810 \newcommand{\secondTextFormat}{}%
3811 \newcommand{\xepersian@secondText}[1]{%
3812 \begin{multicols}{2}%
3813 {\noindent\ignorespaces\secondTextFormat #1}%
3814 \end{multicols}%
3815 }
3816 \newcommand{\thirdTitleFormat}{\Large\bfseries}
3817 \newcommand{\xepersian@thirdTitle}[1]{%
3818 \begin{spacing}{1.5}{%
3819 \noindent\ignorespaces\flushright
3820 \ifthenelse{\boolean{xepersian@hyphenatedtitles}}{%
3821 {\nohyphens{\thirdTitleFormat #1}}%
3822 {\thirdTitleFormat #1}}%
3823 }\end{spacing}%
3824 }
3825 \newcommand{\thirdSubtitleFormat}{\large}
3826 \newcommand{\xepersian@thirdSubtitle}[1]{%
3827 {{\noindent\ignorespaces\thirdSubtitleFormat #1}}%
3828 \newcommand{\thirdTextFormat}{}%
3829 \newcommand{\xepersian@thirdText}[1]{{\thirdTextFormat #1}}%
3830 \newcommand{\pictureCaptionFormat}{\small\bfseries}
3831 \newcommand{\xepersian@pictureCaption}[1]{%
3832 {\noindent\pictureCaptionFormat #1}}%
3833 }
3834 \newcommand{\pagesFormat}{\bfseries\footnotesize}
3835 \newcommand{\xepersian@pages}[1]{%
3836 {\noindent{\pagesFormat\MakeUppercase{#1}}}%
3837 \newcommand{\innerTitleFormat}{\Huge}%
3838 \newcommand{\xepersian@innerTitle}[1]{%
3839 \begin{flushright}{%
3840 \noindent
3841 \ifthenelse{\boolean{xepersian@hyphenatedtitles}}{%
3842 {\nohyphens{\innerTitleFormat #1}}%
3843 {\innerTitleFormat #1}}%
3844 }%
3845 \\%
3846 \end{flushright}%
3847 }
3848 \newcommand{\innerSubtitleFormat}{\large}
3849 \newcommand{\xepersian@innerSubtitle}[1]{{\innerSubtitleFormat #1}}%
3850 \newcommand{\timestampTxt}{}%
3851 \newcommand{\timestampSeparator}{|}%

```

```

3852 \newcommand{\timestampFormat}{\small}
3853 \newcommand{\timestamp}[1]{%
3854 {\timestampFormat}%
3855 #1~\timestampTxt{}%
3856 }~\timestampSeparator{}%
3857 }
3858 \newcommand{\innerAuthorFormat}{\footnotesize}
3859 \newcommand{\innerPlaceFormat}{\footnotesize\bfseries}
3860 \newcommand{\innerTextFinalMark}{\rule{0.65em}{0.65em}}
3861 \newcommand{\editorialTitleFormat}{\LARGE\textrit}
3862 \newcommand{\xepersian@editorialTitle}[1]{\editorialTitleFormat{#1}}
3863 \newcommand{\editorialAuthorFormat}{\textsc}
3864 \newcommand{\shortarticleTitleFormat}{\LARGE\bfseries}
3865 \newcommand{\xepersian@shortarticleTitle}[1]{{\shortarticleTitleFormat #1}}
3866 \newcommand{\shortarticleSubtitleFormat}{\Large}
3867 \newcommand{\xepersian@shortarticleSubtitle}[1]{{\shortarticleSubtitleFormat #1}}
3868 \newcommand{\shortarticleItemTitleFormat}{\large\bfseries}
3869 \newcommand{\xepersian@shortarticleItemTitle}[1]{{\shortarticleItemTitleFormat #1}}
3870 \renewcommand{\maketitle}{\begin{titlepage}%
3871   \let\footnotesize\small
3872   \let\footnoterule\relax
3873   \let \footnote \thanks
3874   \null\vfil
3875   \vskip 60\p@
3876   \begin{center}%
3877     {\LARGE \@title \par}%
3878     \vskip 1em%
3879     {\LARGE «\xepersian@edition» \par}%
3880     \vskip 3em%
3881     {\large
3882       \lineskip .75em%
3883       \begin{tabular}[t]{c}%
3884         \author
3885       \end{tabular}\par}%
3886       \vskip 1.5em%
3887       {\large \@date \par}%
3888   \end{center}\par
3889   \thanks
3890   \vfild\null
3891   \end{titlepage}%
3892   \setcounter{footnote}{0}%
3893   \global\let\thanks\relax
3894   \global\let\maketitle\relax
3895   \global\let\@thanks\empty
3896   \global\let\@author\empty
3897   \global\let\@date\empty
3898   \global\let\@title\empty
3899   \global\let\title\relax
3900   \global\let\author\relax
3901   \global\let\date\relax

```

```

3902 \global\let\and\relax
3903 }
3904 \newcommand{\xepersian@say}[1]{\typeout{#1}}
3905 \newsavebox{\xepersian@fmbox}
3906 \newenvironment{xepersian@fmpage}[1]
3907 {\begin{lrbox}{\xepersian@fmbox}\begin{minipage}{#1}}
3908 {\end{minipage}\end{lrbox}\fbox{\usebox{\xepersian@fmbox}}}
3909 \newcommand{\image}[2]{
3910 \vspace{5pt}
3911 \setlength{\fboxsep}{1pt}
3912 \addtolength{\xepersian@imgsize}{\columnwidth}
3913 \addtolength{\xepersian@imgsize}{-1\columnsep}
3914 \ifxetex
3915 \setlength{\xepersian@pageneed}{1.5\xepersian@imgsize}
3916 \addtolength{\xepersian@pageneed}{50pt}
3917 \ClassWarning{xepersian-magazine}{%
3918 Image #1 needs: \the\xepersian@pageneed \space %
3919 and there is left: \the\page@free\space%
3920 }
3921 \ifdim \xepersian@pageneed < \page@free
3922
3923 {\centering\fbox{%
3924 \includegraphics[width = \xepersian@imgsize,
3925 height = \xepersian@imgsize,
3926 keepaspectratio ]{#1}}}
3927 \xepersian@pictureCaption{#2}
3928
3929 \vspace{5pt}
3930 \else
3931 \ClassWarning{Image #1 needs more space!}%
3932 It was not inserted!
3933 \fi
3934 \fi
3935 }
3936 \textblockorigin{1cm}{1cm}
3937 \newdimen\xepersian@dx
3938 \newdimen\xepersian@dy
3939 \newcount\xepersian@cx
3940 \newcount\xepersian@cy
3941 \newcommand{\grid}[3][]{%
3942 \xepersian@dx=\textwidth%
3943 \xepersian@dy=\textheight%
3944 \xepersian@cx=#3% %columns
3945 \xepersian@cy=#2% %rows
3946
3947 \count1=#3%
3948 \advance\count1 by 1
3949
3950 \count2=#2%
3951 \advance\count2 by 1

```

```

3952
3953 \divide\xepersian@dx by #3
3954 \divide\xepersian@dy by #2
3955
3956 \setlength{\TPHorizModule}{\xepersian@dx}
3957 \setlength{\TPVertModule}{\xepersian@dy}
3958
3959 \ifthenelse{\equal{#1}{show}}{
3960 \multido{\xepersian@nrow=0+1}{\count2} {
3961 \begin{textblock}{\xepersian@cx}(0,\xepersian@nrow)
3962 \rule[0pt]{\textwidth}{.1pt}
3963 \end{textblock}
3964 }
3965
3966 \multido{\xepersian@ncol=0+1}{\count1} {
3967 \begin{textblock}{\xepersian@cy}(\xepersian@ncol,0)
3968 \rule[0pt]{.1pt}{\textheight}
3969 \end{textblock}
3970 }
3971 \{}%
3972 \newcommand{\xepersianInit}{%
3974 \setlength{\headheight}{14pt}
3975 \renewcommand{\headrulewidth}{0.4pt}
3976
3977 \pagestyle{fancy}
3978
3979 \setlength{\columnseprule}{\columnlines}
3980 \setlength{\fboxrule}{0.1 pt}
3981
3982 \newcommand{\customlogo}[1]{\gdef\@customlogo{\beginR#1\endR}}
3983 \def\customminilogos#1{\gdef\@customminilogos{\beginR#1\endR}}
3984 \def\custommagazinenames#1{\gdef\@custommagazinenames{\beginR#1\endR}}
3985 \newcommand{\logo}[0]{
3986 \%% Heading %%
3987 \noindent\hrulefill\hspace{10pt}\xepersian@editionLogo\hspace{5pt}\xepersian@www
3988 \vspace*{-3pt}
3989 \Large\bfseries \@customlogo
3990 \hrulefill
3991 \hspace{10pt}\xepersian@headDateTime
3992
3993 \large\bfseries \@customminilogos
3994 \hrulefill
3995 \hspace{10pt}\xepersian@headDateTime
3996
3997 \newcommand{\minilogos}[0]{
3998 \large\bfseries \@customminilogos
3999 \large\bfseries \@customminilogos
4000 \vspace*{5pt}

```

```

4002 }
4003 \newcommand{\mylogo}[1]{
4004 {\beginR#1\endR}
4005
4006 \noindent
4007 \xepersian@editionLogo\hspace{5pt}
4008 \hrulefill
4009 \hspace{5pt}\xepersian@headDateTime
4010 }
4011 \newcommand{\edition}[1]{\renewcommand{\xepersian@edition}{#1}}
4012 \newenvironment{frontpage}[0]
4013 {
4014 \setboolean{xepersian@insidefrontpage}{true}
4015 \thispagestyle{empty}
4016 \logo
4017
4018 }%
4019 {
4020 \thispagestyle{empty}
4021 \clearpage
4022 \newpage
4023 \fancyhead{}
4024 \fancyfoot{}
4025 \fancyhead[RO,LE]{\beginR\xepersian@headright\endR}
4026 \fancyhead[LO,RE]{\beginR\xepersian@headleft\endR}
4027 \fancyhead[C]{\beginR\xepersian@headcenter\endR}
4028 \fancyfoot[RO,LE]{\beginR\xepersian@footright\endR}
4029 \fancyfoot[LO,RE]{\beginR\xepersian@footleft\endR}
4030 \fancyfoot[C]{\beginR\xepersian@footcenter\endR}
4031 \renewcommand{\headrulewidth}{0.4pt}
4032 \setboolean{xepersian@insidefrontpage}{false}
4033
4034 }
4035 \newcommand{\firstarticle}[3]
4036 {
4037 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
4038 \ifthenelse{\boolean{xepersian@hyphenatedtitles}}{%
4039 \begin{textblock}{24}(22,5)
4040 }
4041 {
4042 \begin{textblock}{28}(22,5)
4043 }
4044 \vspace{-7pt}
4045 \xepersian@firstTitle{#1}
4046 \end{textblock}
4047 \begin{textblock}{29}(22,10)
4048 \vspace{5pt plus 2pt minus 2pt}
4049
4050 \xepersian@firstText{\timestamp{#3}~#2}
4051

```

```

4052 \end{textblock}
4053
4054 \begin{textblock}{50}(0,15)
4055 \rule{50\TPHorizModule}{.3pt}
4056 \end{textblock}
4057 }{\%else
4058 \ClassError{xepersian-magazine}{%
4059 \protect\firstarticle\space in a wrong place.\MessageBreak
4060 \protect\firstarticle\space may only appear inside frontpage environment.
4061 }{%
4062 \protect\firstarticle\space may only appear inside frontpage environment.
4063 }%
4064 }
4065 }
4066 \newcommand{\secondarticle}[5]
4067 {
4068 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
4069 \begin{textblock}{33}(2,16)
4070 \xepersian@pages{#4}
4071 \vspace{-5pt}
4072 \xepersian@secondTitle{#1}
4073
4074 \vspace*{5pt}
4075
4076 \xepersian@secondSubtitle{#2}
4077
4078 \vspace*{-7pt}
4079
4080 \xepersian@secondText{\timestamp{#5}~#3}
4081
4082 \end{textblock}
4083
4084 \begin{textblock}{33}(2,25)
4085 \vspace{5pt plus 2pt minus 2pt}
4086
4087 \noindent\ignorespaces\rule{33\TPHorizModule}{.3pt}
4088 \end{textblock}
4089 }{\%else
4090 \ClassError{xepersian-magazine}{%
4091 \protect\secondarticle\space in a wrong place.\MessageBreak
4092 \protect\secondarticle\space may only appear inside frontpage environment.
4093 }{%
4094 \protect\secondarticle\space may only appear inside frontpage environment.
4095 }%
4096 }
4097 }
4098 \newcommand{\thirdarticle}[6]
4099 {
4100 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
4101 \begin{textblock}{32}(2,26)

```

```

4102 \xepersian@pages{#5}
4103 \vspace{-5pt}
4104 \setlength{\fboxsep}{1pt}
4105 \xepersian@thirdTitle{#1}
4106
4107 \vspace*{5pt}
4108
4109 \xepersian@thirdSubtitle{#2}
4110
4111 \vspace*{5pt}
4112
4113 {\noindent\ignorespaces %
4114 \ifthenelse{\equal{#4}{} }{}}
4115
4116 \xepersian@thirdText{\timestamp{#6}~#3}
4117
4118 }
4119
4120 \vspace*{5pt}
4121
4122 \end{textblock}
4123 }%{%
4124 {\ClassError{xepersian-magazine}{%
4125 \protect\thirdarticle\space in a wrong place.\MessageBreak
4126 \protect\thirdarticle\space may only appear inside frontpage environment.
4127 }%{%
4128 \protect\thirdarticle\space may only appear inside frontpage environment.
4129 }%{%
4130 }
4131 }
4132 \newcommand{\firstimage}[2]
4133 {
4134 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
4135 \begin{textblock}{18}(2,5)
4136 \setlength{\fboxsep}{1pt}
4137 \ifxetex % only in PDF
4138 \noindent\fbox{\includegraphics[width = 18\TPHorizModule ]{#1}}
4139 \fi
4140
4141 \xepersian@pictureCaption{#2}
4142 \end{textblock}%
4143 }
4144 {\ClassError{xepersian-magazine}{%
4145 \protect\firstimage\space in a wrong place.\MessageBreak
4146 \protect\firstimage\space may only appear inside frontpage environment.
4147 }%{%
4148 \protect\firstimage\space may only appear inside frontpage environment.
4149 }%
4150 }%
4151 \newcommand{\weatheritem}[5]{%

```

```

4152 \ifthenelse{\boolean{xepersian@insideweather}}{
4153 \begin{minipage}{45pt}
4154 \ifxetex
4155 \includegraphics[width=40pt]{#1}
4156 \fi
4157 \end{minipage}
4158 \begin{minipage}{50pt}
4159 \weatherTempFormat
4160 #2\\
4161 \begin{L#3 $| $ #4 \lrf{\weatherUnits{}}}\end{L}\\
4162 #5
4163 \end{minipage}
4164 }{\%else
4165 \ClassError{xepersian-magazine}{%
4166 \protect\weatheritem\space in a wrong place.\MessageBreak
4167 \protect\weatheritem\space may only appear inside weatherblock environment.
4168 }{\%
4169 \protect\weatheritem\space may only appear inside weatherblock environment.\MessageBreak
4170 weatherblock environment may only appear inside frontpage environment.
4171 }{\%
4172 }
4173 }
4174 \newenvironment{weatherblock}[1]
4175 {
4176 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
4177 \setboolean{xepersian@insideweather}{true}
4178 \begin{textblock}{32}(2,38)
4179 \vspace*{-15pt}
4180
4181 \xepersian@weather{\beginR#1\endR}
4182
4183 \vspace*{5pt}
4184
4185 \noindent\begin{xepersian@fmpage}{32\TPHorizModule}
4186 \begin{minipage}{32\TPHorizModule}
4187 \hspace{5pt}
4188
4189 }{\%
4190 \ClassError{xepersian-magazine}{%
4191 weatherblock in a wrong place.\MessageBreak
4192 weatherblock may only appear inside frontpage environment.
4193 }{\%
4194 weatherblock may only appear inside frontpage environment.
4195 }
4196 }
4197 }{\%
4198 {
4199 \end{minipage}
4200 \end{xepersian@fmpage}
4201 \end{textblock}

```

```

4202 \setboolean{xepersian@insideweather}{false}
4203 }
4204 \newenvironment{authorblock}[0]
4205 {
4206 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
4207 \begin{textblock}{15}(36,35)
4208 \setlength{\fboxsep}{5pt}
4209 \begin{xepersian@fmpage}{13\TPHorizModule}
4210 \begin{minipage}{13\TPHorizModule}
4211 \centering
4212 \minilogo
4213
4214 }{%
4215 \ClassError{xepersian-magazine}{%
4216 authorblock in a wrong place.\MessageBreak
4217 authorblock may only appear inside frontpage environment.
4218 }{%
4219 authorblock may only appear inside frontpage environment.
4220 }
4221 }
4222 }
4223 {
4224 \end{minipage}
4225 \end{xepersian@fmpage}
4226 \end{textblock}
4227 }
4228 \newenvironment{indexblock}[1]
4229 {
4230 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
4231 \setboolean{xepersian@insideindex}{true}%let's in
4232 \begin{textblock}{15}(36,16)
4233 \setlength{\xepersian@indexwidth}{13\TPHorizModule}
4234 \xepersian@indexFrameTitle{#1}
4235
4236 \setlength{\fboxsep}{5pt} %espacio entre el frame y la imagen
4237 \begin{xepersian@fmpage}{\xepersian@indexwidth}
4238 \begin{minipage}{\xepersian@indexwidth}
4239 \vspace*{10pt}
4240 }{%
4241 \ClassError{xepersian-magazine}{%
4242 indexblock in a wrong place.\MessageBreak
4243 indexblock may only appear inside frontpage environment.
4244 }{%
4245 indexblock may only appear inside frontpage environment.
4246 }
4247 }
4248 }{%
4249 {
4250 \end{minipage}
4251 \end{xepersian@fmpage}

```

```

4252 \end{textblock}
4253 \setboolean{xepersian@insideindex}{false}%
4254 }%
4255 \newcommand{\indexitem}[2]{%
4256 {%
4257 \ifthenelse{\boolean{xepersian@insideindex}}{%
4258 \xepersian@indexEntry{\#1} \xepersian@indexEntryPage{\pageref{\#2}}}%
4259 %
4260 \vspace{0.5cm}%
4261 %
4262 \noindent\ignorespaces\indexEntrySeparator{}%
4263 }%else
4264 \ClassError{xepersian-magazine}{%
4265 \protect\indexitem\space in a wrong place.\MessageBreak
4266 \protect\indexitem\space may only appear inside indexblock environment.%
4267 }%%
4268 \protect\indexitem\space may only appear inside indexblock environment.\MessageBreak
4269 indexblock environment may only appear inside frontpage environment.%
4270 }%
4271 }%
4272 }%
4273 \newcommand{\xepersian@inexpandedtitle}[1]{%
4274 \begin{minipage}{.95\textwidth}%
4275 \begin{center}%
4276 \noindent\Large\textrm{\bf\begin{R}\end{R}}%
4277 \end{center}%
4278 \end{minipage}%
4279 }%
4280 \newcommand{\expandedtitle}[2]{%
4281 \end{multicols}%
4282 %
4283 \begin{center}%
4284 \setlength{\fboxsep}{5pt}%
4285 \setlength{\shadowsize}{2pt}%
4286 \ifthenelse{\equal{\#1}{shadowbox}}{%
4287 \shadowbox{%
4288 \xepersian@inexpandedtitle{\#2}}%
4289 }%
4290 }{}%
4291 \ifthenelse{\equal{\#1}{doublebox}}{%
4292 \doublebox{%
4293 \xepersian@inexpandedtitle{\#2}}%
4294 }%
4295 }{}%
4296 \ifthenelse{\equal{\#1}{ovalbox}}{%
4297 \ovalbox{%
4298 \xepersian@inexpandedtitle{\#2}}%
4299 }%
4300 }{}%
4301 \ifthenelse{\equal{\#1}{Ovalbox}}{%

```

```

4302 \Ovalbox{%
4303 \xepersian@inexpandedtitle{#2}%
4304 }%
4305 }{%
4306 \ifthenelse{\equal{#1}{lines}}{%
4307 \hrule
4308 \vspace*{8pt}
4309 \begin{center}
4310 \noindent\Large\textrm{bf}{#2}
4311 \end{center}
4312 \vspace*{8pt}
4313 \hrule
4314 }{%
4315 \end{center}
4316
4317 \begin{multicols}{\xepersian@ncolumns[]}
4318 \ifnum \xepersian@ncolumns > \minraggedcols
4319 \raggedFormat
4320 \fi
4321 }
4322 \newcommand{\xepersian@incolumntitle}[2]{%
4323 \begin{minipage}{#1}
4324 \begin{center}
4325 \noindent\normalsize\textrm{bf}{#2}
4326 \end{center}
4327 \end{minipage}
4328 }
4329
4330 \newcommand{\columntitle}[2]{%
4331 \vspace*{5pt}
4332 \begin{center}
4333 \setlength{\fboxsep}{5pt}
4334 \setlength{\shadowsize}{2pt}
4335 \addtolength{\xepersian@coltitsize}{\columnwidth}
4336 \addtolength{\xepersian@coltitsize}{-\columnsep}
4337 \addtolength{\xepersian@coltitsize}{-5pt}
4338 \addtolength{\xepersian@coltitsize}{-\shadowsize}
4339 \ifthenelse{\equal{#1}{shadowbox}}{%
4340 \shadowbox{%
4341 \xepersian@incolumntitle{\xepersian@coltitsize}{#2}%
4342 }%
4343 }{%
4344 \ifthenelse{\equal{#1}{doublebox}}{%
4345 \doublebox{%
4346 \xepersian@incolumntitle{\xepersian@coltitsize}{#2}%
4347 }%
4348 }{%
4349 \ifthenelse{\equal{#1}{ovalbox}}{%
4350 \ovalbox{%
4351 \xepersian@incolumntitle{\xepersian@coltitsize}{#2}%

```

```

4352 }%
4353 }{%
4354 \ifthenelse{\equal{#1}{Ovalbox}}{%
4355 \Ovalbox{%
4356 \xepersian@inolumntitle{\xepersian@coltitsize}{#2}%
4357 }%
4358 }{%
4359 \ifthenelse{\equal{#1}{lines}}{%
4360 \hrule
4361 \vspace*{5pt}
4362 \begin{center}
4363 \noindent\normalsize\textbf{#2}%
4364 \end{center}
4365 \vspace*{5pt}
4366 \hrule
4367 }{%
4368 \end{center}
4369 }
4370 \renewcommand{\date}{%
4371 \longdate{\today}%
4372 }
4373 \newcommand{\authorandplace}[2]{%
4374 \rightline{%
4375 {\innerAuthorFormat #1},\space{}{\innerPlaceFormat #2}%
4376 }%
4377 \par %
4378 }
4379 \newcommand{\newsection}[1]{%
4380 \renewcommand{\xepersian@section}{#1}
4381 }
4382 \newenvironment{article}[5]
4383 {
4384 \xepersian@say{Adding a new piece of article}
4385 \renewcommand{\xepersian@ncolumns}{#1}
4386 \begin{multicols}{#1}[
4387 \xepersian@pages{#4}
4388 \xepersian@innerTitle{#2}%
4389 \xepersian@innerSubtitle{#3}%
4390 ] [4cm]%
4391 \label{#5}
4392 \ifnum #1 > \minraggedcols
4393 \raggedFormat
4394 \fi
4395 }
4396 {~\innerTextFinalMark{}}
4397 \end{multicols}
4398 }
4399 \newcommand{\articlesep}{%
4400 \setlength{\xepersian@pageneed}{16000pt}
4401 \setlength\xepersian@pageleft{\pagegoal}

```

```

4402 \addtolength\xepersian@pageleft{-\pagetotal}
4403
4404 \xepersian@say{How much left \the\xepersian@pageleft}
4405
4406 \ifdim \xepersian@pageneed < \xepersian@pageleft
4407 \xepersian@say{Not enough space}
4408 \else
4409 \xepersian@say{Adding sep line between articles}
4410 \vspace*{10pt plus 10pt minus 5pt}
4411 \hrule
4412 \vspace*{10pt plus 5pt minus 5pt}
4413 \fi
4414
4415 }
4416 \newcommand{\xepersian@editorialTit}[2]{
4417 \setlength{\arrayrulewidth}{.1pt}
4418 \begin{center}
4419 \begin{tabular}{c}
4420 \noindent
4421 \xepersian@editorialTitle{#1}
4422 \vspace{2pt plus 1pt minus 1pt}
4423 \\
4424 \hline
4425 \vspace{2pt plus 1pt minus 1pt}
4426 \\
4427 \editorialAuthorFormat{#2}
4428 \end{tabular}
4429 \end{center}
4430 }
4431 \newenvironment{editorial}[4]
4432 {
4433 \xepersian@say{Adding a new editorial}
4434 \begin{multicols}{#1}[%
4435 \xepersian@editorialTit{#2}{#3}%
4436 ][4cm]
4437 \label{#4}
4438 \ifnum #1 > \minraggedcols
4439 \raggedFormat
4440 \fi
4441 }
4442 {
4443 \end{multicols}
4444 }
4445 \newcommand{\xepersian@shortarticleTit}[2]{
4446 \begin{center}
4447 \vbox{%
4448 \noindent
4449 \xepersian@shortarticleTitle{#1}
4450 \vspace{4pt plus 2pt minus 2pt}
4451 \hrule

```

```

4452 \vspace{4pt plus 2pt minus 2pt}
4453 \xepersian@shortarticleSubtitle{#2}
4454 }
4455 \end{center}
4456 }
4457 \newenvironment{shortarticle}[4]
4458 {
4459 \xepersian@say{Adding a short article block}
4460 \begin{multicols}{#1}[\xepersian@shortarticleTit{#2}{#3}] [4cm] %
4461 \label{#4}
4462 \par %
4463 \ifnum #1 > \minraggedcols
4464 \raggedFormat
4465 \fi
4466 }
4467 {
4468 \end{multicols}
4469 }
4470 \newcommand{\shortarticleitem}[2]{
4471 \goodbreak
4472 \vspace{5pt plus 3pt minus 3pt}
4473 {\vbox{\noindent\xepersian@shortarticleItemTitle{#1}}}
4474 \vspace{5pt plus 3pt minus 3pt}
4475 {\noindent #2}\\
4476 }

```

## 7.56 xepersian-mathsdigtspec.sty

```

4477 \NeedsTeXFormat{LaTeX2e}
4478 \ProvidesPackage{xepersian-mathsdigtspec}
4479 [2014/07/10 v1.0.6 Unicode Persian maths digits in XeLaTeX]
4480 \def\new@mathgroup{\alloc@8\mathgroup\chardef\@cclvi}
4481 \let\newfam\new@mathgroup
4482 \def\select@group#1#2#3#4{%
4483 \ifx\math@bgroup\math@bgroup\else\relax\expandafter\@firstofone\fi
4484 {%
4485 \ifmmode
4486 \ifnum\csname c@mv@\math@version\endcsname<\@cclvi
4487 \begingroup
4488 \escapechar\m@ne
4489 \getanddefine@fonts{\csname c@mv@\math@version\endcsname}#3%
4490 \globaldefs\@ne \math@fonts
4491 \endgroup
4492 \init@restore@version
4493 \xdef#1{\noexpand\use@mathgroup\noexpand#2%
4494 {\number\csname c@mv@\math@version\endcsname}%
4495 \global\advance\csname c@mv@\math@version\endcsname\@ne
4496 \else
4497 \let#1\relax
4498 \@latex@error{Too many math alphabets used in

```

```

4499           version \math@version}%
4500           \@eha
4501           \fi
4502 \else \expandafter\non@alpherr\fi
4503 #1{#4}%
4504 }%
4505 }
4506 \def\document@select@group#1#2#3#4{%
4507 \ifx\math@bgroup\@group\else\relax\expandafter\@firstofone\fi
4508 \%
4509 \ifmmode
4510   \ifnum\csname c@mv@\math@version\endcsname<\@ccvi
4511     \begingroup
4512       \escapechar\m@ne
4513       \getanddefine@fonts{\csname c@mv@\math@version\endcsname}#3%
4514       \globaldefs\@ne \math@fonts
4515     \endgroup
4516     \expandafter\extract@alph@from@version
4517       \csname mv@\math@version\expandafter\endcsname
4518       \expandafter{\number\csname
4519         c@mv@\math@version\endcsname}%
4520       #1%
4521       \global\advance\csname c@mv@\math@version\endcsname\@ne
4522 \else
4523   \let#1\relax
4524   \@latex@error{Too many math alphabets used
4525     in version \math@version}%
4526   \@eha
4527   \fi
4528 \else \expandafter\non@alpherr\fi
4529 #1{#4}%
4530 }%
4531 }
4532 \ExplSyntaxOn
4533 \bool_set_false:N \g_fonts_spec_math_bool
4534 \ExplSyntaxOff
4535 \def\@preamblecmds{}
4536 \newcommand\xepersian{not@onlypreamble[1]{}{%
4537   \def\do##1{\ifx##1\else\noexpand\do\noexpand##1\fi}%
4538   \xdef\@preamblecmds{\@preamblecmds{}}
4539 \xepersian{not@onlypreamble\@preamblecmds
4540 \def\xepersian{notprerr{ can be used only in preamble (\on@line)}%
4541 \AtBeginDocument{%
4542   \def\do#1{\noexpand\do\noexpand#1}%
4543   \edef\@preamblecmds{%
4544     \def\noexpand\do##1{%
4545       \def##1{\noexpand\xepersian{NotprerrMessage##1}\noexpand\@eha}%
4546     \@preamblecmds}%
4547 \def\xepersian{NotprerrMessage#1}%
4548 \PackageError{xepersian}{%

```

```

4549   {\noexpand\string#1 \noexpand\xepersian@notprerr}{}}%
4550 }
4551 \@ifpackageloaded{natbib}{%
4552 \renewcommand\nocite[1]{\@bsphack
4553   \for@\citereb:=#1\do{%
4554     \safe@activestrue
4555     \edef@\citereb{\expandafter\firstoone@\citereb\empty}%
4556     \safe@activesfalse
4557     \if@filesw\immediate\write\auxout{\string\citation{\citereb}}\fi
4558     \if*\citereb\else
4559       \ifundefined{b@\citereb}\extra@b@\citereb}{%
4560         \NAT@citeundefined \PackageWarning{natbib}{%
4561           {Citation `@\citereb' undefined}}{}\fi}%
4562   \esphack}%
4563 }{%
4564 \def\nocite#1{%
4565   \setbox0=\hbox{\cite{#1}}\esphack}%
4566 }
4567 \newcommand\xepersian@PackageInfo[1]{\PackageInfo{xepersian-mathsdigtspec}{#1}}
4568 \newcommand\SetMathCode[4]{%
4569   \mathcode`#1=\mathchar@type#2 \csname sym#3\endcsname #4\relax}
4570 \newcommand\SetMathCharDef[4]{%
4571   \mathchardef`#1=\mathchar@type#2 \csname sym#3\endcsname #4\relax}
4572 \ExplSyntaxOn
4573 \cs_new_eq:NN \orig_mathbf:n \mathbf
4574 \cs_new_eq:NN \orig_mathit:n \mathit
4575 \cs_new_eq:NN \orig_mathrm:n \mathrm
4576 \cs_new_eq:NN \orig_mathsf:n \mathsf
4577 \cs_new_eq:NN \orig_mathtt:n \mathtt
4578 \NewDocumentCommand \new@mathbf { m } {
4579   \orig_mathbf:n {
4580     \int_step_inline:nnnn { `0 } { \c_one } { `9 } {
4581       \mathcode`#1 = \numexpr "100 * \symnew@mathbf@font@digits + ##1 \relax
4582     }
4583     #1
4584   }
4585 }
4586 \NewDocumentCommand \new@mathit { m } {
4587   \orig_mathit:n {
4588     \int_step_inline:nnnn { `0 } { \c_one } { `9 } {
4589       \mathcode`#1 = \numexpr "100 * \symnew@mathit@font@digits + ##1 \relax
4590     }
4591     #1
4592   }
4593 }
4594 \NewDocumentCommand \new@mathrm { m } {
4595   \orig_mathrm:n {
4596     \int_step_inline:nnnn { `0 } { \c_one } { `9 } {
4597       \mathcode`#1 = \numexpr "100 * \symnew@mathrm@font@digits + ##1 \relax
4598     }

```

```

4599     #1
4600 }
4601 }
4602 \NewDocumentCommand \new@mathsf{ m } {
4603   \orig_mathsf:n {
4604     \int_step_inline:nnnn { `0 } { \c_one } { `9 } {
4605       \mathcode ##1 = \numexpr "100 * \symnew@mathsf@font@digits + ##1 \relax
4606     }
4607     #1
4608   }
4609 }
4610 \NewDocumentCommand \new@mathtt{ m } {
4611   \orig_mathtt:n {
4612     \int_step_inline:nnnn { `0 } { \c_one } { `9 } {
4613       \mathcode ##1 = \numexpr "100 * \symnew@mathtt@font@digits + ##1 \relax
4614     }
4615     #1
4616   }
4617 }
4618 \newcommand\setdigitfont[2][]{%
4619   \let\glb@currsize\relax
4620   \fontspec_set_family:Nnn \xepersian@digits@family {Mapping=parsidigits,#1}{#2}
4621   \xepersian@PackageInfo{Defining the default Persian maths digits font as '#2'}
4622   \DeclareSymbolFont{OPERATORS} {EU1}{\xepersian@digits@family}{m}{n}
4623   \DeclareSymbolFont{new@mathbf@font@digits}{EU1}{\xepersian@digits@family}{bx}{n}
4624   \DeclareSymbolFont{new@mathit@font@digits}{EU1}{\xepersian@digits@family}{m}{it}
4625   \DeclareSymbolFont{new@mathrm@font@digits}{EU1}{\xepersian@digits@family}{m}{n}
4626   \def\persianmathsdigits{%
4627     \SetMathCode`0{\mathalpha}{OPERATORS}{`0}
4628     \SetMathCode`1{\mathalpha}{OPERATORS}{`1}
4629     \SetMathCode`2{\mathalpha}{OPERATORS}{`2}
4630     \SetMathCode`3{\mathalpha}{OPERATORS}{`3}
4631     \SetMathCode`4{\mathalpha}{OPERATORS}{`4}
4632     \SetMathCode`5{\mathalpha}{OPERATORS}{`5}
4633     \SetMathCode`6{\mathalpha}{OPERATORS}{`6}
4634     \SetMathCode`7{\mathalpha}{OPERATORS}{`7}
4635     \SetMathCode`8{\mathalpha}{OPERATORS}{`8}
4636     \SetMathCode`9{\mathalpha}{OPERATORS}{`9}
4637     \SetMathCharDef{\%}{\mathbin}{OPERATORS}{`%}
4638     \SetMathCharDef{\decimalseparator}{\mathord}{OPERATORS}{066B}
4639     \cs_set_eq:NN \mathbf \new@mathbf
4640     \cs_set_eq:NN \mathit \new@mathit
4641     \cs_set_eq:NN \mathrm \new@mathrm
4642   }
4643 \DeclareDocumentCommand \setmathsf digitfont { O{} m } {
4644   \fontspec_set_family:Nnn \g_fontspec_mathsfs_tl {Mapping=parsidigits,#1}{#2}
4645   \DeclareSymbolFont{new@mathsf@font@digits}{EU1}{\g_fontspec_mathsfs_tl}{m}{n}
4646   \def\persianmathsdigits{\cs_set_eq:NN \mathsf \new@mathsf}
4647 }

```

```

4648 \DeclareDocumentCommand \setmathttdigitfont { O{} m } {
4649   \fontspec_set_family:Nnn \g_fontspec_mathtt_t1 {Mapping=parsidigits,#1}{#2}
4650   \ DeclareSymbolFont{new@mathtt@font@digits}{EU1}{\g_fontspec_mathtt_t1}{m}{n}
4651   \def\persianmathttdigits{\cs_set_eq:NN \mathtt \new@mathtt}
4652 }
4653 \ExplSyntaxOff
4654 \ifx\newcommand\undefined\else
4655   \newcommand{\ZifferAn}{}
4656 \fi
4657 \mathchardef\ziffer@Dot@ori="013A
4658 {\ZifferAn
4659 \catcode`\.=\active\gdef .{\begingroup\obeyspaces\futurelet\n\ziffer@dcheck}
4660 \def\ziffer@dcheck{\ziffer@check\ZifferLeer\ziffer@Dot@ori}
4661 \def\ziffer@check#1#2{%
4662   \ifx\n1\endgroup#1\else
4663     \ifx\n2\endgroup#1\else
4664       \ifx\n3\endgroup#1\else
4665         \ifx\n4\endgroup#1\else
4666           \ifx\n5\endgroup#1\else
4667             \ifx\n6\endgroup#1\else
4668               \ifx\n7\endgroup#1\else
4669                 \ifx\n8\endgroup#1\else
4670                   \ifx\n9\endgroup#1\else
4671                     \ifx\n0\endgroup#1\else
4672                       \endgroup#2%
4673                     \fi
4674                   \fi
4675                 \fi
4676               \fi
4677             \fi
4678           \fi
4679         \fi
4680       \fi
4681     \fi
4682   \fi}
4683 \mathcode`.=8000\relax
4684 \def\ZifferLeer{\ifx\decimalseparator\undefined .\else \decimalseparator\fi}
4685 \def\DefaultMathsDigits{\def\SetMathsDigits{}}
4686 \def\PersianMathsDigits{\def\SetMathsDigits{\%}
4687 \ifx\persianmathsdigits\undefined\else\persianmathsdigits\fi\%
4688 \ifx\persianmathsfdigits\undefined\else\persianmathsfdigits\fi\%
4689 \ifx\persianmathttdigits\undefined\else\persianmathttdigits\fi\%
4690 \def\AutoMathsDigits{\def\SetMathsDigits{\%
4691 \ifx\persianmathsdigits\undefined\else\if@Latin\else\persianmathsdigits\fi\fi\%
4692 \ifx\persianmathsfdigits\undefined\else\if@Latin\else\persianmathsfdigits\fi\fi\%
4693 \ifx\persianmathttdigits\undefined\else\if@Latin\else\persianmathttdigits\fi\fi\fi\}}
4694 \AutoMathsDigits
4695 \everymath\expandafter{\the\everymath\SetMathsDigits}
4696 \g@addto@macro\document{\everydisplay\expandafter{\the\everydisplay\SetMathsDigits}}

```

## 7.57 xepersian-multiplechoice.sty

```
4697 \NeedsTeXFormat{LaTeX2e}
4698 \ProvidesPackage{xepersian-multiplechoice}[2010/07/25 v0.2
4699             Multiple Choice Questionnaire class for Persian in XeLaTeX]
4700 \RequirePackage{pifont}
4701 \RequirePackage{fullpage}
4702 \RequirePackage{ifthen}
4703 \RequirePackage{calc}
4704 \RequirePackage{verbatim}
4705 \RequirePackage{tabularx}
4706 \def\@headerfont{\bfseries}
4707 \newcommand\headerfont[1]{\gdef\@headerfont{#1}}
4708 \def\@X{X}
4709 \newcommand\X[1]{\gdef\@X{#1}}
4710 \def\pbs#1{\let\tmp=\#1\let\==\tmp}
4711 \newcolumntype{D}{>{\pbs\centering}X}
4712 \newcolumntype{Q}{>{\@headerfont}X}
4713
4714 \renewcommand\tabularxcolumn[1]{m{#1}}
4715 \newcommand\makeform@nocorrection{%
4716   \addtocontents{frm}{\protect\end{tabularx}}
4717   \starttoc{frm}}
4718 \newcommand\makeform@correction{%
4719   \addtocontents{frm}{\protect\end{tabularx}}}
4720 \newcommand\makemask@nocorrection{%
4721   \addtocontents{msk}{\protect\end{tabularx}}}
4722   \starttoc{msk}}
4723 \newcommand\makemask@correction{%
4724   \addtocontents{msk}{\protect\end{tabularx}}}
4725 \newlength\questionspace
4726 \setlength\questionspace{0pt}
4727 \newcommand\answerstitle[1]{\gdef\@answerstitle{#1}}
4728 \def\@answerstitlefont{\bfseries}
4729 \newcommand\answerstitlefont[1]{\gdef\@answerstitlefont{#1}}
4730 \def\@answernumberfont{\bfseries}
4731 \newcommand\answernumberfont[1]{\gdef\@answernumberfont{#1}}
4732 \newcounter{question}\stepcounter{question}
4733 \newcounter{@choice}
4734 \def\@initorcheck{%
4735   \xdef\@choices{\the@choice}%
4736   \setcounter{@choice}{1}%
4737   \gdef\@arraydesc{|Q||}%
4738   \gdef\@headerline{}%
4739   \whiledo{\not{\value{@choice}>\@choices}}{%
4740     \xdef\@arraydesc{\@arraydesc D|}%
4741     \def\@appendheader{\g@addto@macro\@headerline}%
4742     \@appendheader{\&\protect\@headerfont}%
4743     \edef\@the@choice{\alph{@choice}}%
4744     \expandafter\@appendheader\@the@choice
```

```

4745   \stepcounter{@choice}%%
4746   \addtocontents{frm}{%
4747     \protect\begin{tabularx}{\protect\linewidth}{@arraydesc}
4748     \protect\hline
4749     @headerline\protect\\ \protect\hline\protect\hline}%
4750   \addtocontents{msk}{%
4751     \protect\begin{tabularx}{\protect\linewidth}{@arraydesc}
4752     \protect\hline
4753     @headerline\protect\\ \protect\hline\protect\hline}%
4754 \gdef\@initorcheck{%
4755   \ifthenelse{\value{@choice} = \@choices}{}{%
4756     \ClassError{xepersian-multiplechoice}{Question \thequestion: wrong number of choices
4757       (\the@choice space instead of \@choices)}{%
4758         Questions must all have the same number of proposed answers.%}
4759       \MessageBreak
4760     Type X <return> to quit, fix your MCQ (multiple choice question) and rerun XeLaTeX.}}}}}
4761 \newenvironment{question}[1]{%
4762   %% \begin{question}
4763   \begin{minipage}{\textwidth}
4764     \xdef\@formanswerline{\@questionheader}%
4765     \xdef\@maskanswerline{\@questionheader}%
4766     \fbox{\parbox[c]{\linewidth}{#1}}
4767     \vspace\questionspace\par
4768     {\@answertitlefont\@answertitle}
4769     \begin{list}{\@answernumberfont\alph{@choice})~}{\usecounter{@choice}}}%
4770   %% \end{question}
4771   \end{list}
4772   \end{minipage}
4773   \addtocontents{frm}{\@formanswerline\protect\\ \protect\hline}%
4774   \addtocontents{msk}{\@maskanswerline\protect\\ \protect\hline}%
4775 \end{minipage}
4776 \stepcounter{question}
4777 \def\@truesymbol{\ding{52}~}
4778 \def\@falsesymbol{\ding{56}~}
4779 \newcommand\truesymbol[1]{\gdef\@truesymbol{#1}}
4780 \newcommand\falsesymbol[1]{\gdef\@falsesymbol{#1}}
4781 \def\@true@nocorrection{\item}
4782 \def\@false@nocorrection{\item}
4783 \def\@true@correction{\item[\@truesymbol\refstepcounter{@choice}]}
4784 \def\@false@correction{\item[\@falsesymbol\refstepcounter{@choice}]}
4785 \newcommand\true{%
4786   \xdef\@formanswerline{\@formanswerline&}%
4787   \xdef\@maskanswerline{\@maskanswerline&\@X}%
4788   \@true}%
4789 \newcommand\false{%
4790   \xdef\@formanswerline{\@formanswerline&}%
4791   \xdef\@maskanswerline{\@maskanswerline&}%
4792   \@false}%
4793 \def\@correctionstyle{\itshape}
4794 \newcommand\correctionstyle[1]{\gdef\@correctionstyle{#1}}

```

```

4795 \newenvironment{@correction}{\@correctionstyle}{}
4796 \def\@questionheader{ \thequestion}
4797 \answerstitle{ :
4798 \DeclareOption{nocorrection}{%
4799   \let\@true\@true@nocorrection
4800   \let\@false\@false@nocorrection
4801   \let\correction\comment
4802   \let\endcorrection\endcomment
4803   \def\makeform{\makeform@nocorrection}
4804   \def\makemask{\makemask@nocorrection}}
4805 \DeclareOption{correction}{%
4806   \let\@true\@true@correction
4807   \let\@false\@false@correction
4808   \let\correction\@correction
4809   \let\endcorrection\end@correction
4810   \def\makeform{\makeform@correction}
4811   \def\makemask{\makemask@correction}}
4812 \ExecuteOptions{nocorrection}
4813 \newcommand\questiontitle[1]{\gdef\@questiontitle{#1}}
4814 \def\@questiontitlefont{\bfseries}
4815 \newcommand\questiontitlefont[1]{\gdef\@questiontitlefont{#1}}
4816 \newlength\questiontitlespace
4817 \setlength\questiontitlespace{5pt}
4818 \newlength\questionsepspace
4819 \setlength\questionsepspace{20pt}
4820 \gdef\questionsepspace{0pt}
4821 \let\old@question\question
4822 \let\old@endquestion\endquestion
4823 \renewenvironment{question}[1]{%
4824   %% \begin{question}
4825   \vspace{\questionsepspace}
4826   \fbox{\parbox[c]{0.25\linewidth}{\@questiontitlefont\@questiontitle}}
4827   \nopagebreak\vspace{\questiontitlespace}\par
4828   \old@question{#1}}{%
4829   %% \end{question}
4830   \old@endquestion
4831   \gdef\@questionsepspace{\questionsepspace}}
4832 \questiontitle{ \thequestion:}
4833 \ProcessOptions

```

## 7.58 xepersian-persiancal.sty

```

4834 \NeedsTeXFormat{LaTeX2e}
4835 \ProvidesPackage{xepersian-persiancal}[2012/07/25 v0.2 provides Persian calendar]
4836
4837 \newif\ifXePersian@leap \newif\ifXePersian@kabiseh
4838 \newcount\XePersian@i \newcount\XePersian@y \newcount\XePersian@m \newcount\XePersian@d
4839 \newcount\XePersian@latini \newcount\XePersian@persiani
4840 \newcount\XePersian@latinii \newcount\XePersian@persianii
4841 \newcount\XePersian@latiniii \newcount\XePersian@persianiii

```

```

4842 \newcount\XePersian@latiniv    \newcount\XePersian@persianiv
4843 \newcount\XePersian@latinv     \newcount\XePersian@persianv
4844 \newcount\XePersian@latinvi   \newcount\XePersian@persianvi
4845 \newcount\XePersian@latinvii  \newcount\XePersian@persianvii
4846 \newcount\XePersian@latinviii \newcount\XePersian@persianviii
4847 \newcount\XePersian@latinix   \newcount\XePersian@persianix
4848 \newcount\XePersian@latinx   \newcount\XePersian@persianx
4849 \newcount\XePersian@latinxi  \newcount\XePersian@persianxi
4850 \newcount\XePersian@latinxii \newcount\XePersian@persianxii
4851                               \newcount\XePersian@persianxiii
4852
4853 \newcount\XePersian@temp
4854 \newcount\XePersian@temptwo
4855 \newcount\XePersian@tempthree
4856 \newcount\XePersian@yModHundred
4857 \newcount\XePersian@thirtytwo
4858 \newcount\XePersian@dn
4859 \newcount\XePersian@sn
4860 \newcount\XePersian@mminusone
4861
4862
4863 \XePersian@y=\year \XePersian@m=\month \XePersian@d=\day
4864 \XePersian@temp=\XePersian@y
4865 \divide\XePersian@temp by 100\relax
4866 \multiply\XePersian@temp by 100\relax
4867 \XePersian@yModHundred=\XePersian@y
4868 \advance\XePersian@yModHundred by -\XePersian@temp\relax
4869 \ifodd\XePersian@yModHundred
4870   \XePersian@leapfalse
4871 \else
4872   \XePersian@temp=\XePersian@yModHundred
4873   \divide\XePersian@temp by 2\relax
4874   \ifodd\XePersian@temp\XePersian@leapfalse
4875   \else
4876     \ifnum\XePersian@yModHundred=0%
4877       \XePersian@temp=\XePersian@y
4878       \divide\XePersian@temp by 400\relax
4879       \multiply\XePersian@temp by 400\relax
4880     \ifnum\XePersian@y=\XePersian@temp\XePersian@leaptrue\else\XePersian@leapfalse\fi
4881     \else\XePersian@leaptrue
4882     \fi
4883   \fi
4884 \fi
4885 \XePersian@latinii=31\relax
4886 \ifXePersian@leap
4887   \XePersian@latinii = 29\relax
4888 \else
4889   \XePersian@latinii = 28\relax
4890 \fi
4891 \XePersian@latinii = 31\relax

```

```

4892 \XePersian@latiniv = 30\relax
4893 \XePersian@latinv = 31\relax
4894 \XePersian@latinvi = 30\relax
4895 \XePersian@latinvii = 31\relax
4896 \XePersian@latinviii = 31\relax
4897 \XePersian@latinix = 30\relax
4898 \XePersian@latinx = 31\relax
4899 \XePersian@latinxi = 30\relax
4900 \XePersian@latinxii = 31\relax
4901 \XePersian@thirtytwo=32\relax
4902 \XePersian@temp=\XePersian@y
4903 \advance\XePersian@temp by -17\relax
4904 \XePersian@temptwo=\XePersian@temp
4905 \divide\XePersian@temptwo by 33\relax
4906 \multiply\XePersian@temptwo by 33\relax
4907 \advance\XePersian@temp by -\XePersian@temptwo
4908 \ifnum\XePersian@temp=\XePersian@thirtytwo\XePersian@kabisehfalse
4909 \else
4910   \XePersian@temptwo=\XePersian@temp
4911   \divide\XePersian@temptwo by 4\relax
4912   \multiply\XePersian@temptwo by 4\relax
4913   \advance\XePersian@temp by -\XePersian@temptwo
4914 \ifnum\XePersian@temp=\z@\XePersian@kabisehtrue\else\XePersian@kabisehfalse\fi
4915 \fi
4916 \XePersian@tempthree=\XePersian@y          % Number of Leap years
4917 \advance\XePersian@tempthree by -1
4918 \XePersian@temp=\XePersian@tempthree        % T := (MY-1) div 4
4919 \divide\XePersian@temp by 4\relax
4920 \XePersian@temptwo=\XePersian@tempthree      % T := T - ((MY-1) div 100)
4921 \divide\XePersian@temptwo by 100\relax
4922 \advance\XePersian@temp by -\XePersian@temptwo
4923 \XePersian@temptwo=\XePersian@tempthree      % T := T + ((MY-1) div 400)
4924 \divide\XePersian@temptwo by 400\relax
4925 \advance\XePersian@temp by \XePersian@temptwo
4926 \advance\XePersian@tempthree by -611          % Number of Kabise years
4927 \XePersian@temptwo=\XePersian@tempthree      % T := T - ((SY+10) div 33) * 8
4928 \divide\XePersian@temptwo by 33\relax
4929 \multiply\XePersian@temptwo by 8\relax
4930 \advance\XePersian@temp by -\XePersian@temptwo
4931 \XePersian@temptwo=\XePersian@tempthree      %
4932 \divide\XePersian@temptwo by 33\relax
4933 \multiply\XePersian@temptwo by 33\relax
4934 \advance\XePersian@tempthree by -\XePersian@temptwo
4935 \ifnum\XePersian@tempthree=32\advance\XePersian@temp by 1\fi % if (SY+10) mod 33=32 then Inc(T);
4936 \divide\XePersian@tempthree by 4\relax    % T := T - ((SY+10) mod 33) div 4
4937 \advance\XePersian@temp by -\XePersian@tempthree
4938 \advance\XePersian@temp by -137           % T := T - 137 Adjust the value
4939 \XePersian@persiani=31
4940 \advance\XePersian@persiani by -\XePersian@temp          % now 31 - T is the persiani
4941 \XePersian@persianii = 30\relax

```

```

4942 \ifXePersian@kabiseh
4943   \XePersian@persianiii = 30\relax
4944 \else
4945   \XePersian@persianiii = 29\relax
4946 \fi
4947 \XePersian@persianiv = 31\relax
4948 \XePersian@persianv = 31\relax
4949 \XePersian@persianvi = 31\relax
4950 \XePersian@persianvii = 31\relax
4951 \XePersian@persianviii= 31\relax
4952 \XePersian@persianix = 31\relax
4953 \XePersian@persianx = 30\relax
4954 \XePersian@persianxi = 30\relax
4955 \XePersian@persianxii = 30\relax
4956 \XePersian@persianxiii= 30\relax
4957 \XePersian@dn= 0\relax
4958 \XePersian@sn= 0\relax
4959 \XePersian@mminusone=\XePersian@m
4960 \advance\XePersian@mminusone by -1\relax
4961 \XePersian@i=0\relax
4962 \ifnum\XePersian@i < \XePersian@mminusone
4963 \loop
4964 \advance \XePersian@i by 1\relax
4965 \advance\XePersian@dn by \csname XePersian@latin\romannumeral\the\XePersian@i\endcsname
4966 \ifnum\XePersian@i<\XePersian@mminusone \repeat
4967 \fi
4968 \advance \XePersian@dn by \XePersian@d
4969 \XePersian@i=1\relax
4970 \XePersian@sn = \XePersian@persiani
4971 \ifnum \XePersian@sn<\XePersian@dn
4972 \loop
4973 \advance \XePersian@i by 1\relax
4974 \advance\XePersian@sn by \csname XePersian@persian\romannumeral\the\XePersian@i\endcsname
4975 \ifnum \XePersian@sn<\XePersian@dn \repeat
4976 \fi
4977 \ifnum \XePersian@i < 4
4978   \XePersian@m = 9 \advance\XePersian@m by \XePersian@i
4979   \advance \XePersian@y by -622\relax
4980 \else
4981   \XePersian@m = \XePersian@i \advance \XePersian@m by -3\relax
4982   \advance \XePersian@y by -621\relax
4983 \fi
4984 \advance\XePersian@sn by -\csname XePersian@persian\romannumeral\the\XePersian@i\endcsname
4985 \endcsname
4986 \ifnum\XePersian@i = 1
4987   \XePersian@d = \XePersian@dn \advance \XePersian@d by 30 \advance\XePersian@d by -\XePersian@pe
4988 \else
4989   \XePersian@d = \XePersian@dn \advance \XePersian@d by -\XePersian@sn
4990 \fi
4991 \newcommand*\persiantoday}{%

```

```
4992 \number\XePersian@d\space%
4993 \XePersian@persian@month{\XePersian@m}\space\number\XePersian@y%
4994 }
4995 \let\persianyear\XePersian@y
4996 \let\persianmonth\XePersian@m
4997 \let\persianday\XePersian@d
4998 \def\XePersian@persian@month#1{\ifcase#1\or \or \
4999 \or \
5000 \or \or \
5001 \or \
5002 \or \or \
5003 \or \or \
5004 \or \or \
5005 {fi\
```

# Index

Symbols	
\!	2647
\%	4637
\.	1746, 4659
\@and	3263
\@do@wrglossary	1636
\@if@newlist .	1482, 1502, 3185, 3238
\@math	317
\@maybeautodot .	2862, 2863, 2881, 2896, 2897, 2915, 2926, 2927, 2945
\@par	2174
\@Alph .	1642, 1657, 2875, 2909, 2939, 3516, 3519, 3523
\@False	305, 307
\@LTrbidituftesidenote@sidenote .	174
\@LTrfootnotetext .	50, 66, 112, 127, 186, 193, 1548, 1565, 1816, 1831, 2204
\@LTrmarginparreset .	3161
\@Latincitex	164, 165, 2438, 2447, 2637, 3169, 3170
\@Latinfalse	3151
\@Latintrue	3150, 3152, 3156
\@M .	321, 1745, 1758, 1840, 3303, 3404, 3490
\@MM	20, 37, 56, 82, 99, 118, 1515, 1534, 1553, 1786, 1803, 1822
\@Mi	317
\@Mii	2097
\@Miii	2099
\@RTL@footnotefalse	3152, 3156
\@RTL@footnotetrue .	3154, 3157
\@RTLbidituftesidenote@sidenote .	201
\@RTLfalse .	16, 52, 78, 114, 287, 299, 312, 1511, 1549, 1571, 1604, 1741, 1782, 1818, 3224, 3234
\@RTLfootnotetext .	31, 65, 93, 126, 213, 220, 1529, 1564, 1797, 1830, 2205
\@RTLtrue .	16, 33, 78, 95, 1511, 1530, 1571, 1589, 1741, 1782, 1799, 3224, 3234
\@Roman ..	1643, 1653, 2877, 2911, 2941
\@SepMark	1853, 1854, 1855, 1856, 2033
\@SetTab .	2948
\@True .	300, 306
\@X .	4708, 4709, 4787
\@acol .	2329, 2337
\@acolampacol .	2327, 2329, 2335, 2337
\@adadi ..	1632, 1645, 1661, 2873, 2907, 2937, 3277, 3279, 3282
\@addamp .	2328, 2336
\@addtopreamble .	2296
\@alph	1641, 1655, 2876, 2910, 2940, 2949, 3515, 3518, 3522
\@ampacol .	2327, 2335
\@ansernumberfont	4730, 4731, 4769
\@anserstitle .	4727, 4768
\@anserstitlefont	4728, 4729, 4768
\@appendheader .	4741, 4742, 4744
\@arrayclassz .	2327
\@arraydesc ..	4737, 4740, 4747, 4751
\@arrayrule ..	2275, 2276, 2277, 2319, 2320, 2321
\@author .	3884, 3896
\@autodottrue ..	2865, 2866, 2867, 2868, 2869, 2870, 2871, 2872, 2873, 2874, 2875, 2876, 2877, 2878, 2879, 2899, 2900, 2901, 2902, 2903, 2904, 2905, 2906, 2907, 2908, 2909, 2910, 2911, 2912, 2913, 2929, 2930, 2931, 2932

2933, 2934, 2935, 2936, 2937,  
 2938, 2939, 2940, 2941, 2942,  
 2943  
`\@auxout` ..... 3175, 4557  
`\begin{tempboxa}` ..... 2174  
`\begindvi` ..... 3217  
`\biblabel` ..... 1742, 2439, 2448  
`\bibsetup` ..... 2440, 2449  
`\bibtitlestyle` ..... 1738  
`\bidi@list@minipage@parbox@not@nobtrue`  
      ..... 2171, 2193  
`\bidi@list@minipage@parboxtrue`  
      ..... 2172, 2194  
`\bidiutfesidenote@citations`  
      ... 176, 203, 230, 237  
`\bidiutfesidenote@infofootnote@cite`  
      ... 175, 202, 229, 236  
`\bidiutfesidenote@margin@par`  
      ..... 231, 238  
`\bidiutfesidenote@marginnote@font`  
      ..... 231, 238  
`\bidiutfesidenote@marginnote@justify`  
      ..... 231, 238  
`\bidiutfesidenote@normal@cite`  
      ... 196, 223, 233, 240  
`\bidiutfesidenote@print@citations`  
      ... 195, 222, 232, 239  
`\bidiutfesidenote@sidenote@vertical`  
      ... 178, 180, 186, 193, 205,  
          207, 213, 220  
`\bsphack` ..... 2096, 4552, 4565  
`\capttype` 2084, 2147, 2394, 2404  
`\cclvi` ..... 4480, 4486, 4510  
`\chapapp` ..... 253, 264, 271,  
      283, 1463, 1475, 2039, 2829,  
      2836, 2843, 2851, 2892, 2922  
`\chclass` 2209, 2217, 2225, 2240,  
      2254, 2259, 2274, 2290, 2310,  
      2318, 2348, 2371, 2385  
`\chnum` ... 2211, 2212, 2213, 2214,  
      2215, 2216, 2226, 2233, 2247,  
      2260, 2267, 2283, 2296, 2312,  
      2313, 2314, 2315, 2316, 2317,  
      2331, 2339, 2349, 2356, 2378  
`\choices` 4735, 4739, 4755, 4757  
`\@cite` ... 2426, 2433, 2445, 2461,  
      2550, 3172  
`\@cite@ofmt` ..... 3180  
`\@citea` ... 2466, 2480, 2494, 2503,  
      2504, 2505, 2510, 2525, 2533,  
      2534, 2535, 2569, 2585, 2603,  
      3171, 3173  
`\@citeb` ... 2462, 2464, 2466, 2469,  
      2471, 2472, 2474, 2497, 2528,  
      2551, 2553, 2555, 2558, 2560,  
      2561, 2563, 3172, 3174, 3175,  
      3176, 3179, 3180, 4553, 4555,  
      4557, 4558, 4559, 4561  
`\@citex` ..... 2437, 2446  
`\@classx` ..... 2293  
`\@classz` ..... 2293  
`\@cleartopmattertags` ... 1876  
`\@colht` ..... 3239  
`\@correction` ..... 4808  
`\@correctionstyle` . 4793, 4794,  
      4795  
`\@extremr` ..... 3273  
`\@currbox` 2104, 2150, 2154, 2393,  
      2397, 2403, 2407  
`\@currentlabel` 22, 39, 58, 84, 101,  
      120, 1517, 1536, 1555, 1576,  
      1594, 1609, 1788, 1805, 1824  
`\@fisheenvir` ... 2711, 2713, 2714  
`\@customlogo` ..... 3984, 3993  
`\@custommagazinename` 3753, 3986  
`\@customminilogo` ... 3985, 3999  
`\@customwwwTxt` . 3714, 3717, 3769  
`\@date` ..... 3887, 3897  
`\@dgroup` ..... 299  
`\@dmath` ..... 287, 316  
`\@do@glsl@getcounterprefix` 1674,  
      1677  
`\@doendpe` ..... 2728  
`\@dseries` ..... 312  
`\@eha` ..... 4500, 4526, 4545  
`\@empty` 302, 1740, 1862, 2091, 2451,  
      2461, 2464, 2550, 2553, 2682,  
      3171, 3174, 3203, 3204, 3206,  
      3207, 3362, 3368, 3371, 3374,  
      3470, 3895, 3896, 3897, 3898,  
      4555

\emptytoks . . . . . 301  
 \enGroup . . . . . 1350  
 \enLabel 1341, 1342, 1343, 1344,  
     1345, 1346, 1347, 1348  
 \enOther . . . . . 1352  
 \enSpace . . . . . 1349  
 \end@tempboxa . . . . . 2189  
 \endpbbox . . . . . 2303, 2304  
 \enhook . . . . . 1353  
 \enloop@ . . . . . 1340  
 \entemp . 1341, 1342, 1343, 1344,  
     1345, 1346, 1347, 1348, 1349,  
     1350, 1351  
 \enum@ . . . . . 1351  
 \esphack . . . . . 4562, 4565  
 \evenfoot . . . . . 3201  
 \evenhead . . . . . 3200  
 \extra@b@citeb . . . . .  
     ... 2466, 2472, 2474, 2497,  
     2528, 2555, 2561, 2563, 4559  
 \extrafootnotefeaturestrue .  
     . . . . . 3569  
 \false . . . . . 4792, 4800, 4807  
 \false@correction . 4784, 4807  
 \false@nocorrection 4782, 4800  
 \falsesymbol . 4778, 4780, 4784  
 \finalstrut . 1522, 1541, 1560,  
     1580, 1598, 1613  
 \firststampfalse . . . . . 2329, 2337  
 \firststofone . . . . .  
     ... 1732, 1733, 2464, 2553,  
     3174, 4483, 4507, 4555  
 \float@HH . . . . . 2390, 2391  
 \float@Hx . . . . . 2389, 2390  
 \float@ . . . . . 2390, 2401  
 \floatboxreset 2160, 2399, 2409  
 \floatcapt . . . . . 2394, 2404  
 \floatpenalty . 2097, 2099, 2102  
 \flstylefalse . . . . . 2396, 2406  
 \flstyletrue . . . . . 2396, 2406  
 \ftovf . . . . . 2152  
 \footnotemark 186, 193, 213, 220  
 \footnotetext . . . . . 14, 64, 76,  
     125, 1510, 1563, 1780, 1829,  
     2203  
 \for . . . . . 2462, 2551, 3172, 4553  
 \formanswerline . . . . . 4764, 4773,  
     4786, 4790  
 \fps 2085, 2086, 2088, 2091, 2108  
 \fpsadddefault . . . . . 2089, 2092  
 \freelist . . . . . 2104  
 \glo@check@mkidxrangechar . .  
     . . . . . 1680  
 \glo@counterprefix 1670, 1691,  
     1698  
 \glo@numfmt . . . . . 1697, 1701  
 \glo@prefix . . . . . 1682, 1685  
 \glo@range . . . . . 1681, 1683, 1686,  
     1693  
 \glo@suffix . . . . . 1692  
 \gls@checkmkidxchars . . . . . 1668,  
     1673  
 \gls@counter . . . . . 1692, 1697  
 \gls@encapchar . . . . . 1701  
 \gls@getcounterprefix . . . . . 1674  
 \glsHlocref . . . . . 1672, 1673, 1675  
 \glslocref . . . . . 1666, 1668, 1675,  
     1691, 1701  
 \glsnumberformat . . . . . 1680, 1697  
 \gobble . . . . . 1351, 1490, 1491, 1492,  
     3213, 3214, 3215  
 \charfi . . . . . 12, 74, 134,  
     140, 146, 152, 254, 265, 272,  
     284, 1453, 1464, 1476, 1630,  
     1644, 1659, 1766, 2040, 2830,  
     2837, 2844, 2852, 2859, 2872,  
     2893, 2906, 2923, 2936, 3271,  
     3274, 3275  
 \headerfont . 4706, 4707, 4712,  
     4742  
 \headerline . 4738, 4741, 4749,  
     4753  
 \idxitem . . . . . 1755, 1760  
 \ifclassloaded . . . . .  
     ... 3543, 3544, 3545, 3546,  
     3547, 3548, 3549, 3550, 3551,  
     3552, 3553, 3554, 3555, 3556,  
     3557, 3558, 3559, 3560, 3561,  
     3562, 3563, 3564, 3565, 3566,  
     3573, 3583, 3593  
 \ifdefinable . . . . . 2746, 2748

\@ifdefinitionfileloaded . . .	1865
.. 2081, 2224, 2257, 2347,	
2388, 3526	
\@ifempty . . . . .	1841
\@ifnextchar .	2390, 2631, 2637,
3169	
\@ifnum ..	2568, 2570, 2572, 2579,
2580, 2583, 2595, 2618, 2620	
\@ifpackageloaded . . . . .	167, 1955, 1959, 2640,
2644, 2736, 2744, 3244, 3527,	
3528, 3529, 3530, 3531, 3532,	
3533, 3534, 3535, 3536, 3537,	
3538, 3539, 3540, 3541, 3542,	
3543, 4551	
\@ifstar . . . . .	2630
\@ifundefined ..	163, 2466, 2472,
2555, 2561, 3176, 4559	
\@ignoretrue . . . . .	323
\@iiiminipage . . . . .	2190
\@iiiparbox . . . . .	2168
\@indexfile ..	3575, 3585, 3595
\@inextitlestyle . . . .	1753
\@initorcheck ..	4734, 4754, 4772
\@inlabelfalse . . . . .	290
\@input@ . . . . .	3577, 3587, 3597
\@lastchclass . . . . .	2209, 2210, 2226, 2227,
2228, 2229, 2231, 2260, 2261,	
2262, 2263, 2265, 2310, 2311,	
2327, 2335, 2349, 2350, 2351,	
2352, 2354	
\@latex@error . . . .	4498, 4524
\@latex@warning . . . .	1748, 3178
\@latinAlph . . . . .	3516, 3523
\@latinalph ..	2949, 3515, 3522
\@listdepth . . . . .	2206
\@m ..	1746, 2443, 3173, 3302, 3403,
3488	
\@mainmatterfalse ..	248, 259, 277,
1457, 2886	
\@makefnmark . . . . .	1773
\@makefntext ..	24, 41, 60, 86, 103,
122, 1521, 1540, 1559, 1579,	
1597, 1612, 1790, 1807, 1826	
\@maketitle . . . . .	1867
\@maketitle@hook . . . . .	1865
\@maskanswerline ..	4765, 4774,
4787, 4791	
\@memfront . . . . .	2031
\@minipagefalse . . . . .	3166
\@minipagerestore . . . . .	2207
\@minipagetrue . . . . .	3165
\@mpLTRfootnotetext ..	1602, 2204
\@mpRTLfootnotetext ..	1587, 2205
\@mpargs . . . . .	2196
\@mpfn ..	184, 190, 211, 217, 2202
\@mpfootins ..	1571, 1572, 1589,
1590, 1604, 1605	
\@mpfootnotetext ..	1569, 2203
\@mplistdepth . . . . .	2206
\@namedef ..	2420, 2474, 2563, 2727
\@nameuse . . . . .	3195
\@ne ..	1570, 1588, 1603, 2114, 2120,
2213, 2214, 2217, 2226, 2236,	
2237, 2241, 2260, 2270, 2271,	
2275, 2276, 2277, 2314, 2315,	
2319, 2320, 2321, 2349, 2359,	
2360, 2372, 2568, 2580, 2582,	
2595, 2603, 3289, 3330, 3337,	
3349, 3354, 3390, 3431, 3438,	
3450, 3455, 4490, 4495, 4514,	
4521	
\@newlistfalse . . . .	1483, 3186
\@next . . . . .	2104
\@nextchar ..	2232, 2234, 2235, 2236,
2237, 2238, 2239, 2241, 2242,	
2243, 2244, 2245, 2248, 2249,	
2250, 2251, 2252, 2253, 2266,	
2268, 2269, 2270, 2271, 2272,	
2273, 2275, 2276, 2277, 2278,	
2279, 2280, 2281, 2284, 2285,	
2286, 2287, 2288, 2289, 2301,	
2303, 2304, 2355, 2357, 2358,	
2359, 2360, 2361, 2362, 2363,	
2364, 2365, 2366, 2367, 2368,	
2369, 2370, 2372, 2373, 2374,	
2375, 2376, 2379, 2380, 2381,	
2383, 2384	
\@nextchar . . . . .	2382
\@nil ..	1680, 2657, 2661, 2662, 2667,
2669, 3320, 3323, 3421, 3424	

\cnodecument	2083
\cnoitemerr	1748
\cnx	1871, 1872
\coddfoot	3198, 3207
\coddhead	3198, 3206
\conelevel@sanitize	2086
\coutputbox	1500, 3230
\coutputpage	1478, 3181
\cparboxrestore	<ul style="list-style-type: none"> <li>..... 21, 38, 57, 83, 100, 119, 1483, 1516, 1535, 1554, 1575, 1593, 1608, 1787, 1804, 1823, 2159, 2174, 2201, 2398, 2408, 3187</li> </ul>
\cparboxto	2177, 2186
\cparmerr	2102
\cboxswfalse	2170, 2192
\cboxswtrue	2184
\cplus	1756, 1834
\cnumwidth	1847, 1849
\cpreamble	2330, 2338
\cpreamblecmds	4535, 4538, 4539, 4543, 4546
\preamerr	2220, 2254, 2290, 2324, 2385
\questionheader	4764, 4765, 4796
\questionsepspace	4820, 4825, 4831
\questiontitle	4813, 4826
\questiontitlefont	4814, 4815, 4826
\resetactivechars	1481, 3184
\restonecolfalse	1751
\restonecoltrue	1751
\roman	2878, 2912, 2942
\safe@activesfalse	2465, 2554, 4556
\safe@activestrue	2463, 2552, 4554
\secpenalty	1839
\set@glo@numformat	1697
\setcopyright	1859
\setfontsize	<ul style="list-style-type: none"> <li>.. 3684, 3690, 3692, 3695, 3702, 3708, 3709, 3710, 3711,</li> </ul>
\setfpsbit	2124, 2127, 2130, 2133, 2136, 2139
\setminipage	2208
\setnobreak	2399, 2409
\sharp	2332, 2333, 2334, 2340, 2341, 2342
\smemfront	2032
\specialpagefalse	3195
\specialstyle	3195
\spctoken	1349
\startpbox	2303, 2304
\startsection	1833
\starttoc	3247, 4717, 4722
\stop	2863, 2897, 2927
\sx@xepersian@localize@verbatim	<ul style="list-style-type: none"> <li>..... 2420</li> </ul>
\tabclassz	2335
\tartibi	<ul style="list-style-type: none"> <li>..... 9, 70, 130, 136, 142, 148, 245, 256, 267, 279, 1449, 1459, 1471, 1631, 1646, 1663, 1763, 2034, 2035, 2825, 2832, 2839, 2847, 2855, 2874, 2888, 2908, 2918, 2938, 3383, 3385, 3388</li> </ul>
\tempa	<ul style="list-style-type: none"> <li>.. 1341, 1342, 1343, 1344, 1345, 1346, 1347, 1348, 1349, 1350, 1351, 1352, 1355, 1870, 1873, 2667, 2669, 2752, 2753, 2754, 2755, 2756, 2757, 2758, 2759, 2760, 2761, 2762</li> </ul>
\tempboxa	2197, 3220, 3227, 3228
\tempc	<ul style="list-style-type: none"> <li>.. 2682, 2695, 2705, 2707, 2708, 2711, 2719</li> </ul>
\tempcnta	<ul style="list-style-type: none"> <li>2106, 2112, 2114, 2118, 2120, 2142, 2143, 2149, 2150, 2294, 2577, 2578, 2579, 2582, 2583</li> </ul>
\tempcntb	2147, 2148, 2149
\tempdima	<ul style="list-style-type: none"> <li>1842, 1844, 1846, 1848, 2173, 2174, 2195, 2199</li> </ul>
\tempdimb	2176, 2177
\tempswafalse	2595, 3169
\tempswatrue	2594, 3169
\temptokena	<ul style="list-style-type: none"> <li>.. 1868, 1872, 2668, 2675,</li> </ul>

\] . . . . .	2647
\^ . . . . .	2648
\_ . . . . .	1387
\  . . . . .	4161
\~ . . . . .	2648
\u . . . . .	1622, 1624, 3173, 3326, 3332, 3351, 3357, 3427, 3433, 3452, 3458, 3760, 3769
<b>A</b>	
\abj@num@i . . .	3484, 3499, 3506
\abj@num@ii . . .	3486, 3503, 3510
\abj@num@iii . . .	3488, 3507, 3513
\abj@num@iv . . . .	3490, 3511
\abjad@zero . . . .	3498, 3502
\abjadnumeral . . .	3479, 3518, 3519
\abovedisplayshortskip . . . .	3687, 3688, 3698, 3699, 3705, 3706
\abovedisplayskip . .	3685, 3686, 3696, 3697, 3703, 3704
\abstractname . . . . .	3260
\active . . . . .	2648, 4659
\adadi . . . . .	1342, 2866, 2900, 2930, 3276
\adadinumeral . . . . .	3282
\addfontfeatures . .	287, 299, 312
\addpenalty . . . . .	1839
\addtocontents . . . . .	4716, 4719, 4721, 4724, 4746, 4750, 4773, 4774
\addtolength . . . . .	3912, 3913, 3916, 4335, 4336, 4337, 4338, 4402
\addvspace . . . . .	1839
\adl@argarraydashrule . . .	2277, 2321
\adl@arraydashrule . .	2276, 2320
\adl@arrayrule . . . .	2275, 2319
\adl@box . . . . .	2301, 2303, 2304
\adl@class@iiiorvii . . .	2307, 2344
\adl@class@start . . .	2306, 2343
\adl@endmbox . . . . .	2302

\adl@putlrc .....	2298, 2299, 2300, 2332, 2333, 2334, 2340, 2341, 2342
\adl@startmbox .....	2301
\advance .	1625, 1743, 1846, 2114, 2120, 2143, 2149, 2582, 3676, 3680, 3948, 3951, 4495, 4521, 4868, 4903, 4907, 4913, 4917, 4922, 4925, 4926, 4930, 4934, 4935, 4937, 4938, 4940, 4960, 4964, 4965, 4968, 4973, 4974, 4978, 4979, 4981, 4982, 4984, 4987, 4989
\aftergroup ..	1485, 1487, 3182, 3190, 3191
\ALG@name .....	5, 7
\algorithmicensure .....	3
\algorithmicrequire .....	2
\ALGS@name .....	6, 7
\aliasfontfeature .....	1358, 1971, 1972, 1973, 1974, 1975, 1976, 1977, 1978, 1979, 1980, 1981, 1982, 1983, 1984, 1985, 1986, 1987, 1988, 1989, 1990, 1991, 1992, 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008, 2009, 2010, 2011, 2012, 2013, 2014, 2015, 2016, 2017, 2018, 2019, 2020, 2021, 2022, 2023
\aliasfontfeatureoption .....	2024, 2025, 2026, 2027, 2028, 2029
\alloc@ .....	4480
\Alph	1344, 1725, 1726, 2868, 2902, 2932
\alph	1345, 2869, 2903, 2933, 2956, 4743, 4769
\anappendixtrue .....	2041
\and .....	3902
\andify .....	1863
\answernumberfont .....	4731
\answerstitle .....	4727, 4797
\answerstitlefont .....	4729
\appendix .....	10, 71, 131, 137, 143, 149, 250, 261, 268, 280, 1450, 1460, 1472, 1722, 1723, 1764, 2036, 2826, 2833, 2840, 2848, 2856, 2889, 2919
\appendixautorefname .....	1711
\appendixname .....	11, 73, 253, 264, 271, 283, 1463, 1475, 1765, 2039, 2829, 2836, 2843, 2851, 2892, 2922, 3257
\arabic ..	1348, 1740, 1853, 1854, 1855, 1856
\arrayrulewidth .....	4417
\articlesep .....	4399
\AtBeginDocument .....	162, 1721, 1930, 2420, 2627, 2732, 3674, 3678, 4541
\AtEndOfClass .....	3672
\author .....	3900
\authorandplace .....	4373
\AutoMathsDigits ...	4690, 4694

## B

\backrefpagesname .....	154
\baselineskip ...	231, 238, 1493, 3216, 3231
\begin	2641, 2642, 3156, 3157, 3245, 3728, 3731, 3784, 3799, 3812, 3818, 3839, 3870, 3876, 3883, 3907, 3961, 3967, 4039, 4042, 4047, 4054, 4069, 4084, 4101, 4135, 4153, 4158, 4178, 4185, 4186, 4207, 4209, 4210, 4232, 4237, 4238, 4274, 4275, 4283, 4309, 4317, 4323, 4324, 4332, 4362, 4386, 4418, 4419, 4434, 4446, 4460, 4747, 4751, 4762, 4763, 4769, 4824
\begingroup .....	189, 216, 295, 1479, 1637, 1840, 1866, 2412, 2629, 2645, 2725, 2727, 3014, 3016, 3182, 4487, 4511, 4659
\beginL ..	3166, 3224, 3234, 3760, 4161

\beginR ..	1769, 3224, 3234, 3764, 3765, 3766, 3777, 3778, 3779, 3984, 3985, 3986, 4004, 4025, 4026, 4027, 4028, 4029, 4030, 4181, 4276	\boolean ..	3661, 3673, 3682, 3786, 3801, 3820, 3841, 4037, 4038, 4068, 4100, 4134, 4152, 4176, 4206, 4230, 4257
\belowdisplayshortskip ..	3688, 3699, 3706	\botmark .....	1505, 3241
\belowdisplayskip ..	3686, 3697, 3704	\box .....	301, 1500, 3228, 3230
\bfseries ..	1835, 2467, 2556, 3176, 3720, 3726, 3745, 3753, 3781, 3797, 3816, 3830, 3834, 3859, 3864, 3868, 3993, 3999, 4706, 4728, 4730, 4814	\BR@Latincitex .....	155, 165
\bgroup ..	1350, 2157, 2197, 2398, 2408, 4483, 4507	\BRorg@Latincitex .....	156, 164
\biblofont .....	1739	<b>C</b>	
\bibname .....	3264	\C .....	2649
\bidi@csdefcs .....	938, 1953	\c ..	4580, 4588, 4596, 4604, 4612
\bidi@csletcs ..	633, 1953, 1957, 1958, 1961, 1962	\c@book .....	2034
\bidi@footdir@footnote ..	64, 125, 1563, 1829	\c@chapter ..	72, 74, 254, 265, 272, 284, 1464, 1476, 2040, 2830, 2837, 2844, 2852, 2893, 2923
\bidi@isloaded .....	.. 1924, 1925, 1926, 1927, 1928, 1929, 1932, 1935, 1938, 1941, 1944, 1947	\c@footnote .....	1875
\bidi@mpfootnoterule ..	1570, 1588, 1603	\c@mpfootnote ..	1570, 1588, 1603, 2202
\bidi@newrobustcmd ..	3150, 3151	\c@page ..	1630, 1631, 1632, 1648, 1650, 1652, 1654, 1656, 1658, 1660, 1662, 1664
\bidi@reflect@box .....	3251	\c@part .....	9, 70, 130, 136, 142, 148, 245, 256, 267, 279, 1449, 1459, 1471, 1763, 2035, 2825, 2832, 2839, 2847, 2855, 2888, 2918
\blacktriangleleft ..	1620, 1622	\c@section ..	10, 12, 72, 134, 140, 146, 152, 1453, 1764, 1766, 2859
\blacktriangleright ..	1620, 1622	\c@subsection .....	10, 1764
\bm@c .....	2165	\c@tocdepth .....	1837
\bm@c .....	2162	\catcode ..	1951, 2412, 2413, 2414, 2648, 4659
\bm@c1 .....	2163	\ccname .....	3266
\bm@c r .....	2164	\centering ..	3923, 4211, 4711
\bm@c s .....	2167	\cftchapname .....	2968
\bm@c t .....	2166	\cftfigname .....	2974
\bm@c .....	2166	\cftparaname .....	2972
\bm@c .....	2164	\cftsecname .....	2969
\bm@c .....	2165	\cftsubfigname .....	2975
\bm@c .....	2162	\cftsubparaname .....	2973
\bm@c .....	2163	\cftsubsecname .....	2970
\bm@c .....	2167	\cftsubsubsecname .....	2971
\bool .....	4533	\cftsubtabname .....	2977
		\cfttabname .....	2976

```

\chapterautorefname .... 1712
\chaptername ..... 73, 3265
\chardef . 1879, 1881, 1882, 1883,
    1884, 1885, 4480
\charlist 1889, 1890, 1892, 1896
\citation ..... 3175, 4557
\cite 175, 196, 202, 223, 229, 233,
    236, 240, 4565
\citemumfont ..... 2606
\citeyear ..... 2428
\citeyearpar ..... 2428
\ClassError ..... .
    .. 4058, 4090, 4124, 4144,
        4165, 4190, 4215, 4241, 4264,
        4756
\ClassWarning . 3643, 3645, 3647,
    3917, 3931
\cleardoubleoddpage .... 2885
\cleardoublepage . 69, 247, 258,
    276, 1456
\clearpage ..... 2885, 4021
\closeout .... 3575, 3585, 3595
\clubpenalty ..... 1745
\color@begingroup ..... .
    .. 1520, 1539, 1558, 1578,
        1596, 1611, 2198
\color@endbox .... 3225, 3235
\color@endgroup 1523, 1542, 1561,
    1581, 1599, 1614
\color@hbox ..... 3222, 3232
\color@vbox ... 2155, 2397, 2407
\columnlines . 3617, 3618, 3650,
    3979
\columnsep .... 1752, 3913, 4336
\columnseprule .... 1752, 3979
\columntitle ..... 4330
\columnwidth . 20, 37, 56, 82, 99,
    118, 1516, 1535, 1554, 1574,
    1592, 1607, 1768, 1786, 1803,
    1822, 2158, 2200, 2398, 2408,
    3912, 4335
\comment ..... 4801
\contentsname ..... 3245, 3254
\copyright ..... 3769
\correction ..... 4801, 4808
\correctionstyle ..... 4794
\count ... 2150, 3198, 3947, 3948,
    3950, 3951, 3960, 3966
\count@ ..... 2294
\cs 2735, 2737, 3049, 3064, 3065,
    4573, 4574, 4575, 4576, 4577,
    4639, 4640, 4641, 4646, 4651
\csname ..... 23,
    40, 59, 85, 102, 121, 190,
    217, 1518, 1537, 1556, 1577,
    1595, 1610, 1689, 1690, 1699,
    1700, 1789, 1806, 1825, 1842,
    1954, 2147, 2187, 2392, 2395,
    2402, 2405, 2422, 2729, 2746,
    2747, 2748, 2749, 2750, 2860,
    2894, 2924, 3015, 3018, 3024,
    3026, 3180, 3274, 3277, 3383,
    4486, 4489, 4494, 4495, 4510,
    4513, 4517, 4518, 4521, 4569,
    4571, 4965, 4974, 4984
\currenttime ..... 3743
\customlogo ..... 3984
\custommagazinename ..... 3986
\customminilogo ..... 3985
\customwwwTxt ..... 3714

```

## D

```

\d@llarbegin .. 2298, 2299, 2300
\d@llarend ... 2298, 2299, 2300
\date .... 3742, 3753, 3901, 4370
\datename ..... 3262
\day ..... 4863
\decimalseparator .. 4638, 4684
\DeclareDocumentCommand .... .
    .. 1358, 3041, 3054, 3066,
        3075, 3114, 3118, 3122, 3126,
        3131, 3136, 4643, 4648
\DeclareOption ..... .
    .. 3567, 3568, 3569, 3570,
        3581, 3591, 3639, 3640, 3641,
        3642, 3644, 3646, 3648, 3649,
        3650, 3651, 3652, 4798, 4805
\DeclareRobustCommand ..... .
    .. 2628, 3044, 3057, 3069,
        3078, 3090, 3093, 3096, 3099,
        3102, 3105, 3168

```

```

\DeclareSymbolFont    4622, 4623,
                    4624, 4625, 4645, 4650
\DeclareTextFontCommand . . .
                    .. 3108, 3109, 3110, 3111,
                    3112, 3113
\def . . . . . 2, 3, 5, 6, 7, 10, 12,
                    14, 31, 50, 69, 71, 74, 76,
                    93, 112, 154, 155, 168, 174,
                    201, 243, 287, 299, 312, 319,
                    323, 1340, 1341, 1342, 1343,
                    1344, 1345, 1346, 1347, 1348,
                    1478, 1510, 1529, 1548, 1569,
                    1587, 1602, 1617, 1619, 1621,
                    1623, 1647, 1649, 1651, 1653,
                    1655, 1657, 1659, 1661, 1663,
                    1670, 1681, 1683, 1686, 1705,
                    1706, 1707, 1708, 1709, 1710,
                    1711, 1712, 1713, 1714, 1715,
                    1716, 1717, 1718, 1719, 1720,
                    1723, 1734, 1748, 1751, 1760,
                    1761, 1762, 1764, 1766, 1767,
                    1771, 1773, 1780, 1797, 1816,
                    1833, 1836, 1857, 1869, 1886,
                    1889, 1891, 1892, 1897, 1921,
                    1922, 2044, 2045, 2046, 2047,
                    2048, 2049, 2050, 2051, 2052,
                    2082, 2084, 2085, 2087, 2168,
                    2190, 2196, 2202, 2209, 2225,
                    2259, 2293, 2306, 2307, 2310,
                    2327, 2335, 2343, 2344, 2348,
                    2390, 2391, 2394, 2401, 2404,
                    2417, 2418, 2427, 2430, 2442,
                    2443, 2453, 2456, 2469, 2484,
                    2514, 2546, 2550, 2575, 2637,
                    2651, 2655, 2657, 2658, 2661,
                    2667, 2669, 2671, 2687, 2690,
                    2706, 2707, 2710, 2723, 2725,
                    2728, 2745, 2979, 2980, 3011,
                    3012, 3013, 3019, 3020, 3024,
                    3142, 3146, 3152, 3153, 3154,
                    3155, 3159, 3160, 3161, 3170,
                    3173, 3181, 3250, 3252, 3253,
                    3254, 3255, 3256, 3257, 3258,
                    3259, 3260, 3261, 3262, 3263,
                    3264, 3265, 3266, 3267, 3268,
                    3269, 3270, 3271, 3274, 3283,
                    3288, 3297, 3323, 3336, 3347,
                    3361, 3367, 3370, 3373, 3377,
                    3389, 3398, 3424, 3437, 3448,
                    3462, 3469, 3479, 3498, 3499,
                    3503, 3507, 3511, 3517, 3521,
                    3714, 3984, 3985, 3986, 4480,
                    4482, 4506, 4535, 4537, 4540,
                    4542, 4544, 4545, 4547, 4564,
                    4626, 4646, 4651, 4660, 4661,
                    4684, 4685, 4686, 4690, 4706,
                    4708, 4710, 4728, 4730, 4734,
                    4741, 4777, 4778, 4781, 4782,
                    4783, 4784, 4793, 4796, 4803,
                    4804, 4810, 4811, 4814, 4998
\def@NAT@last@cyr ... 2585, 2587
\DefaultMathsDigits . . . . . 4685
\define@key . . . . . 2751
\deflatinfont . . . . . 3075
\defpersianfont . . . . . 3066
\depth . . . . . 2759, 2760
\ding . . . . . 4777, 4778
\display@setup . . . . . 288, 313
\divide .. 3953, 3954, 4865, 4873,
          4878, 4905, 4911, 4919, 4921,
          4924, 4928, 4932, 4936
\do 2109, 2462, 2551, 2752, 3172,
      4537, 4542, 4544, 4553
\document . . . . . 4696
\document@select@group .. 4506
\dosetclass ... 1890, 1891, 1895
\doublebox . . . . . 4292, 4345
\dp . . . . . 19, 36, 55, 81, 98,
          117, 1515, 1534, 1553, 1785,
          1802, 1821, 3227
\dquad . . . . . 321, 323
\dsseries@display@setup . . . 313

E
\edef 1674, 1870, 2177, 2232, 2266,
      2330, 2338, 2355, 2464, 2553,
      2713, 2987, 3009, 3018, 3021,
      3174, 4543, 4555, 4743
\edition . . . . . 4011
\editionFormat . . . . . 3720, 3723
\editorialAuthorFormat .. 3863,
                        4427

```

\editorialTitleFormat . . .	3861,
3862	
\else . . . . .	2, 3, 5, 7,
16, 25, 78, 87, 154, 243, 291,	
321, 1341, 1342, 1343, 1344,	
1345, 1346, 1347, 1348, 1349,	
1350, 1351, 1467, 1511, 1522,	
1570, 1571, 1580, 1620, 1622,	
1624, 1648, 1650, 1652, 1654,	
1656, 1658, 1660, 1662, 1664,	
1671, 1684, 1696, 1705, 1706,	
1707, 1708, 1709, 1710, 1711,	
1712, 1713, 1714, 1715, 1716,	
1717, 1718, 1719, 1720, 1741,	
1757, 1782, 1791, 1835, 1838,	
1846, 1847, 1863, 1894, 1921,	
1922, 1931, 1934, 1937, 1940,	
1943, 1946, 2044, 2045, 2046,	
2047, 2048, 2049, 2050, 2051,	
2052, 2090, 2098, 2103, 2113,	
2119, 2172, 2175, 2180, 2181,	
2182, 2183, 2184, 2194, 2209,	
2210, 2211, 2212, 2213, 2214,	
2215, 2216, 2217, 2218, 2219,	
2220, 2226, 2227, 2228, 2230,	
2231, 2234, 2235, 2236, 2237,	
2238, 2239, 2241, 2242, 2243,	
2244, 2245, 2248, 2249, 2250,	
2251, 2252, 2253, 2260, 2261,	
2262, 2264, 2265, 2268, 2269,	
2270, 2271, 2272, 2273, 2275,	
2276, 2277, 2278, 2279, 2280,	
2281, 2284, 2285, 2286, 2287,	
2288, 2289, 2309, 2310, 2311,	
2312, 2313, 2314, 2315, 2316,	
2317, 2319, 2320, 2321, 2322,	
2323, 2324, 2349, 2350, 2351,	
2353, 2354, 2357, 2358, 2359,	
2360, 2361, 2362, 2363, 2364,	
2365, 2366, 2367, 2368, 2369,	
2370, 2372, 2373, 2374, 2375,	
2376, 2379, 2380, 2381, 2382,	
2383, 2384, 2396, 2406, 2431,	
2444, 2476, 2481, 2490, 2493,	
2507, 2511, 2520, 2524, 2527,	
2539, 2543, 2544, 2565, 2586,	
2600, 2602, 2605, 2619, 2621,	
2632, 2655, 2666, 2679, 2681,	
2684, 2699, 2701, 2707, 2715,	
2723, 2750, 2753, 2754, 2755,	
2756, 2757, 2758, 2759, 2760,	
2761, 2864, 2885, 2898, 2928,	
2952, 2968, 2969, 2970, 2971,	
2972, 2973, 2974, 2975, 2976,	
2977, 3035, 3200, 3205, 3211,	
3224, 3234, 3252, 3253, 3254,	
3255, 3256, 3257, 3258, 3259,	
3260, 3261, 3262, 3263, 3264,	
3265, 3266, 3267, 3268, 3269,	
3270, 3273, 3291, 3293, 3301,	
3302, 3303, 3304, 3305, 3306,	
3307, 3308, 3326, 3341, 3355,	
3368, 3371, 3392, 3394, 3402,	
3403, 3404, 3405, 3406, 3407,	
3408, 3409, 3427, 3442, 3455,	
3456, 3481, 3483, 3485, 3487,	
3489, 3578, 3588, 3598, 3930,	
4408, 4483, 4496, 4502, 4507,	
4522, 4528, 4537, 4558, 4654,	
4662, 4663, 4664, 4665, 4666,	
4667, 4668, 4669, 4670, 4671,	
4684, 4687, 4688, 4689, 4691,	
4692, 4693, 4871, 4875, 4880,	
4881, 4888, 4909, 4914, 4944,	
4980, 4988	
\empty . . . . .	1893
\enclname . . . . .	3267
\end . . . . .	1890, 1891, 1896, 1897, 2641,
2642, 2713, 2724, 3156, 3157,	
3248, 3728, 3733, 3790, 3804,	
3814, 3823, 3846, 3885, 3888,	
3891, 3908, 3963, 3969, 4046,	
4052, 4056, 4082, 4088, 4122,	
4142, 4157, 4163, 4199, 4200,	
4201, 4224, 4225, 4226, 4250,	
4251, 4252, 4277, 4278, 4281,	
4311, 4315, 4326, 4327, 4364,	
4368, 4397, 4428, 4429, 4443,	
4455, 4468, 4716, 4719, 4721,	
4724, 4770, 4771, 4775, 4829	
\end@correction . . . . .	4809
\endcomment . . . . .	4802

\endcorrection . . . . .	4802, 4809	\eqcommand . . . . .	327, 328, 329, 330,
\endcsname . . . . .	23, 40, 59, 85, 102, 121, 190, 217, 1518, 1537, 1556, 1577, 1595, 1610, 1689, 1690, 1699, 1700, 1789, 1806, 1825, 1842, 1954, 2147, 2187, 2392, 2395, 2402, 2405, 2422, 2729, 2746, 2747, 2748, 2749, 2750, 2860, 2894, 2924, 3015, 3018, 3024, 3026, 3180, 3274, 3277, 3383, 4486, 4489, 4494, 4495, 4510, 4513, 4517, 4519, 4521, 4569, 4571, 4965, 4974, 4985	331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 350, 351, 352, 353, 354, 355, 356, 357, 358, 359, 360, 361, 362, 363, 364, 365, 366, 367, 368, 369, 370, 371, 372, 373, 374, 375, 376, 377, 378, 379, 380, 381, 382, 383, 384, 385, 386, 387, 388, 389, 390, 391, 392, 393, 394, 395, 396, 397, 398, 399, 400, 401, 402, 403, 404, 405, 406, 407, 408,	
\endgroup . . . . .	192, 219, 1486, 1667, 1851, 1874, 2650, 2728, 3014, 3022, 3182, 3190, 4491, 4515, 4662, 4663, 4664, 4665, 4666, 4667, 4668, 4669, 4670, 4671, 4672	409, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 420, 421, 422, 423, 424, 425, 426, 427, 428, 429, 430, 431, 432, 433, 434, 435, 436, 437, 438, 439, 440, 441, 442, 443, 444, 445, 446, 447, 448, 449, 450, 451, 452, 453, 454, 455, 456, 457, 458, 459, 460, 461, 462, 463, 464, 465, 466, 467, 468, 469, 470, 471, 472, 473, 474, 475, 476, 477, 478, 479, 480, 481, 482, 483, 484, 485, 486, 487, 488, 489, 490, 491, 492, 493, 494, 495, 496, 497, 498, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 547, 548, 549, 550, 551, 552, 553, 554, 555, 556, 557, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 578, 579, 580, 581, 582, 583, 584, 585, 586, 587, 588, 589, 590, 591, 592, 593, 594, 595, 596, 597, 598, 599, 600,	
\endL . . . . .	3224, 3234, 3760, 4161		
\endlatin . . . . .	3153		
\endlist . . . . .	1749		
\endLTR . . . . .	3153		
\endMakeFramed . . . . .	1628		
\endmath . . . . .	318		
\endpersian . . . . .	3155		
\endquestion . . . . .	4822		
\endR . . . . .	1770, 3224, 3234, 3764, 3765, 3766, 3777, 3778, 3779, 3984, 3985, 3986, 4004, 4025, 4026, 4027, 4028, 4029, 4030, 4181, 4276		
\endRTL . . . . .	3155		
\ends@math . . . . .	318		
\endtrivlist . . . . .	2418, 2728		
\end . . . . .	2418, 2422, 2728, 2729		
\eq@addpunct . . . . .	323		
\eq@group . . . . .	291, 300		
\eq@GRP@first@dmath . . . . .	300		
\eq@prelim . . . . .	291, 308		
\eq@setnumber . . . . .	294		
\eq@setup@a . . . . .	296		
\eq@startup . . . . .	297		
\eq@wdCond . . . . .	315		

601, 602, 603, 604, 605, 606,  
607, 608, 609, 610, 611, 612,  
613, 614, 615, 616, 617, 618,  
619, 620, 621, 622, 623, 624,  
625, 626, 627, 628, 629, 630,  
631, 632, 634, 635, 636, 637,  
638, 639, 640, 641, 642, 643,  
644, 645, 646, 647, 648, 649,  
650, 651, 652, 653, 654, 655,  
656, 657, 658, 659, 660, 661,  
662, 663, 664, 665, 666, 667,  
668, 669, 670, 671, 672, 673,  
674, 675, 676, 677, 678, 679,  
680, 681, 682, 683, 684, 685,  
686, 687, 688, 689, 690, 691,  
692, 693, 694, 695, 696, 697,  
698, 699, 700, 701, 702, 703,  
704, 705, 706, 707, 708, 709,  
710, 711, 712, 713, 714, 715,  
716, 717, 718, 719, 720, 721,  
722, 723, 724, 725, 726, 727,  
728, 729, 730, 731, 732, 733,  
734, 735, 736, 737, 738, 739,  
740, 741, 742, 743, 744, 745,  
746, 747, 748, 749, 750, 751,  
752, 753, 754, 755, 756, 757,  
758, 759, 760, 761, 762, 763,  
764, 765, 766, 767, 768, 769,  
770, 771, 772, 773, 774, 775,  
776, 777, 778, 779, 780, 781,  
782, 783, 784, 785, 786, 787,  
788, 789, 790, 791, 792, 793,  
794, 795, 796, 797, 798, 799,  
800, 801, 802, 803, 804, 805,  
806, 807, 808, 809, 810, 811,  
812, 813, 814, 815, 816, 817,  
818, 819, 820, 821, 822, 823,  
824, 825, 826, 827, 828, 829,  
830, 831, 832, 833, 834, 835,  
836, 837, 838, 839, 840, 841,  
842, 843, 844, 845, 846, 847,  
848, 849, 850, 851, 852, 853,  
854, 855, 856, 857, 858, 859,  
860, 861, 862, 863, 864, 865,  
866, 867, 868, 869, 870, 871,  
872, 873, 874, 875, 876, 877,  
878, 879, 880, 881, 882, 883,  
884, 885, 886, 887, 888, 889,  
890, 891, 892, 893, 894, 895,  
896, 897, 898, 899, 900, 901,  
902, 903, 904, 905, 906, 907,  
908, 909, 910, 911, 912, 913,  
914, 915, 916, 917, 918, 919,  
920, 921, 922, 923, 924, 925,  
926, 927, 928, 929, 930, 931,  
932, 933, 934, 935, 936, 937,  
939, 940, 941, 942, 943, 944,  
945, 946, 947, 948, 949, 950,  
951, 952, 953, 954, 955, 956,  
957, 958, 959, 960, 961, 962,  
963, 964, 965, 966, 967, 968,  
969, 970, 971, 972, 973, 974,  
975, 976, 977, 978, 979, 980,  
981, 982, 983, 984, 985, 986,  
987, 988, 989, 990, 991, 992,  
993, 994, 995, 996, 997, 998,  
999, 1000, 1001, 1002, 1003,  
1004, 1005, 1006, 1007, 1008,  
1009, 1010, 1011, 1012, 1013,  
1014, 1015, 1016, 1017, 1018,  
1019, 1020, 1021, 1022, 1023,  
1024, 1025, 1026, 1027, 1028,  
1029, 1030, 1031, 1032, 1033,  
1034, 1035, 1036, 1037, 1038,  
1039, 1040, 1041, 1042, 1043,  
1044, 1045, 1046, 1047, 1048,  
1049, 1050, 1051, 1052, 1053,  
1054, 1055, 1056, 1057, 1058,  
1059, 1060, 1061, 1062, 1063,  
1064, 1065, 1066, 1067, 1068,  
1069, 1070, 1071, 1072, 1073,  
1074, 1075, 1076, 1077, 1078,  
1079, 1080, 1081, 1082, 1083,  
1084, 1085, 1086, 1087, 1088,  
1089, 1090, 1091, 1092, 1093,  
1094, 1095, 1096, 1097, 1098,  
1099, 1100, 1101, 1102, 1103,  
1104, 1105, 1106, 1107, 1108,  
1109, 1110, 1111, 1112, 1113,  
1114, 1115, 1116, 1117, 1118,  
1119, 1120, 1121, 1122, 1123,  
1124, 1125, 1126, 1127, 1128,

1129, 1130, 1131, 1132, 1133,  
 1134, 1135, 1136, 1137, 1138,  
 1139, 1140, 1141, 1142, 1143,  
 1144, 1145, 1146, 1147, 1148,  
 1149, 1150, 1151, 1152, 1153,  
 1154, 1155, 1156, 1157, 1158,  
 1159, 1160, 1161, 1162, 1163,  
 1164, 1165, 1166, 1167, 1168,  
 1169, 1170, 1171, 1172, 1173,  
 1174, 1175, 1176, 1177, 1178,  
 1179, 1180, 1181, 1182, 1183,  
 1184, 1185, 1186, 1187, 1188,  
 1189, 1190, 1191, 1192, 1193,  
 1194, 1195, 1196, 1197, 1198,  
 1199, 1200, 1201, 1202, 1203,  
 1204, 1205, 1206, 1207, 1208,  
 1209, 1210, 1211, 1212, 1213,  
 1214, 1215, 1216, 1217, 1218,  
 1219, 1220, 1221, 1222, 1223,  
 1224, 1225, 1226, 1227, 1228,  
 1229, 1230, 1231, 1232, 1233,  
 1234, 1235, 1236, 1237, 1238,  
 1239, 1240, 1241, 1242, 1243,  
 1244, 1245, 1246, 1247, 1248,  
 1249, 1250, 1251, 1252, 1253,  
 1254, 1255, 1256, 1257, 1258,  
 1259, 1260, 1261, 1262, 1263,  
 1264, 1265, 1266, 1267, 1268,  
 1269, 1280, 1281, 1282, 1283,  
 1284, 1285, 1286, 1287, 1288,  
 1289, 1290, 1291, 1292, 1293,  
 1294, 1295, 1296, 1297, 1298,  
 1299, 1300, 1301, 1302, 1303,  
 1304, 1305, 1306, 1307, 1308,  
 1309, 1310, 1311, 1312, 1313,  
 1314, 1315, 1316, 1317, 1318,  
 1319, 1320, 1321, 1322, 1323,  
 1324, 1325, 1326, 1327, 1328,  
 1329, 1330, 1331, 1332, 1333,  
 1334, 1335, 1336, 1337, 1338,  
 1953  
**\eqenvironment** .....  
 . . . 1395, 1396, 1397, 1398,  
 1399, 1400, 1401, 1402, 1403,  
 1404, 1405, 1406, 1407, 1408,  
 1409, 1410, 1411, 1412, 1413,  
 1414, 1415, 1416, 1417, 1418,  
 1419, 1420, 1421, 1422, 1423,  
 1424, 1425, 1426, 1427, 1428,  
 1429, 1430, 1431, 1432, 1433,  
 1434, 1435, 1436, 1438, 1439,  
 1440, 1441, 1442, 1443, 1444,  
 1445, 1446, 1447, 1954  
**\eqstyle** ..... 293  
**\equal** 3959, 4114, 4286, 4291, 4296,  
 4301, 4306, 4339, 4344, 4349,  
 4354, 4359  
**\equationautorefname** . . . 1705  
**\escapechar** . . . 3017, 4488, 4512  
**\evensidemargin** ..... 3201  
**\everydisplay** ..... 288, 4696  
**\everyjob** ..... 3009, 3010  
**\everymath** ..... 4695  
**\everypar** ..... 3166  
**\ExecuteOptions** . . . 3601, 4812  
**\exp** 3044, 3045, 3046, 3057, 3058,  
 3059, 3069, 3070, 3071, 3078,  
 3079, 3080  
**\expandafter** .....  
 . . . 288, 1669, 1680, 1682,  
 1685, 1890, 1896, 2107, 2108,  
 2232, 2266, 2355, 2392, 2395,  
 2402, 2405, 2422, 2464, 2553,  
 2669, 2674, 2675, 2680, 2685,  
 2686, 2692, 2693, 2694, 2695,  
 2702, 2703, 2704, 2705, 2707,  
 2716, 2717, 2718, 2719, 2729,  
 2746, 2747, 2748, 2749, 3014,  
 3015, 3018, 3021, 3022, 3024,  
 3025, 3174, 3274, 3277, 3292,  
 3298, 3383, 3393, 3399, 3484,  
 3486, 3488, 3490, 4483, 4502,  
 4507, 4516, 4517, 4518, 4528,  
 4555, 4695, 4696, 4744  
**\expandedtitle** ..... 4280  
**\ExplSyntaxOff** 1393, 2421, 2743,  
 3140, 4534, 4653  
**\ExplSyntaxOn** . 1357, 2419, 2731,  
 3040, 4532, 4572  
**\extract@alph@from@version** ..  
 . . . . . 4516

**F**

- \false . . . . . 4789  
\falsesymbol . . . . . 4780  
\fancyfoot 4024, 4028, 4029, 4030  
\fancyhead 4023, 4025, 4026, 4027  
\FancyVerbLineautorefname 1718  
\fbox 3908, 3923, 4138, 4766, 4826  
\fboxrule 1617, 1619, 1621, 1623,  
3980  
\fboxsep . 1617, 1619, 1621, 1623,  
3911, 4104, 4136, 4208, 4236,  
4284, 4333  
\fi . . . . . 2, 3, 5, 7, 16, 25,  
78, 87, 154, 159, 243, 287,  
289, 290, 291, 299, 310, 312,  
321, 1354, 1467, 1511, 1522,  
1570, 1571, 1580, 1588, 1603,  
1620, 1622, 1624, 1648, 1650,  
1652, 1654, 1656, 1658, 1660,  
1662, 1664, 1678, 1687, 1688,  
1702, 1705, 1706, 1707, 1708,  
1709, 1710, 1711, 1712, 1713,  
1714, 1715, 1716, 1717, 1718,  
1719, 1720, 1741, 1751, 1757,  
1760, 1761, 1762, 1782, 1791,  
1835, 1846, 1847, 1852, 1864,  
1895, 1921, 1922, 1933, 1936,  
1939, 1942, 1945, 1948, 2044,  
2045, 2046, 2047, 2048, 2049,  
2050, 2051, 2052, 2093, 2094,  
2100, 2115, 2116, 2121, 2122,  
2125, 2128, 2131, 2134, 2137,  
2140, 2144, 2145, 2153, 2171,  
2172, 2178, 2185, 2188, 2193,  
2194, 2213, 2214, 2215, 2216,  
2220, 2221, 2222, 2236, 2237,  
2238, 2239, 2254, 2255, 2270,  
2271, 2272, 2273, 2290, 2291,  
2305, 2314, 2315, 2316, 2317,  
2324, 2325, 2329, 2334, 2337,  
2342, 2345, 2359, 2360, 2361,  
2362, 2385, 2386, 2396, 2406,  
2418, 2436, 2454, 2475, 2477,  
2488, 2492, 2501, 2502, 2506,  
2518, 2523, 2527, 2531, 2532,  
2536, 2541, 2542, 2543, 2544,  
2564, 2566, 2588, 2596, 2604,  
2605, 2614, 2615, 2621, 2624,  
2634, 2655, 2670, 2688, 2708,  
2721, 2724, 2750, 2762, 2865,  
2866, 2867, 2868, 2869, 2870,  
2871, 2872, 2873, 2874, 2875,  
2876, 2877, 2878, 2879, 2880,  
2885, 2899, 2900, 2901, 2902,  
2903, 2904, 2905, 2906, 2907,  
2908, 2909, 2910, 2911, 2912,  
2913, 2914, 2929, 2930, 2931,  
2932, 2933, 2934, 2935, 2936,  
2937, 2938, 2939, 2940, 2941,  
2942, 2943, 2944, 2954, 2968,  
2969, 2970, 2971, 2972, 2973,  
2974, 2975, 2976, 2977, 3028,  
3029, 3037, 3175, 3196, 3202,  
3203, 3204, 3206, 3207, 3208,  
3211, 3224, 3234, 3252, 3253,  
3254, 3255, 3256, 3257, 3258,  
3259, 3260, 3261, 3262, 3263,  
3264, 3265, 3266, 3267, 3268,  
3269, 3270, 3273, 3295, 3309,  
3321, 3326, 3327, 3330, 3332,  
3333, 3345, 3349, 3351, 3352,  
3354, 3357, 3359, 3365, 3368,  
3371, 3375, 3380, 3396, 3410,  
3422, 3427, 3428, 3431, 3433,  
3434, 3446, 3450, 3452, 3453,  
3455, 3458, 3460, 3467, 3473,  
3491, 3492, 3493, 3494, 3495,  
3496, 3501, 3502, 3505, 3506,  
3509, 3510, 3512, 3513, 3580,  
3590, 3600, 3607, 3933, 3934,  
4139, 4156, 4320, 4394, 4413,  
4440, 4465, 4483, 4501, 4502,  
4507, 4527, 4528, 4537, 4557,  
4561, 4656, 4673, 4674, 4675,  
4676, 4677, 4678, 4679, 4680,  
4681, 4682, 4684, 4687, 4688,  
4689, 4691, 4692, 4693, 4880,  
4882, 4883, 4884, 4890, 4914,  
4915, 4935, 4946, 4967, 4976,  
4983, 4990, 5005  
\figureautorefname . . . . . 1708  
\figurename . . . . . 3252

\finishsetclass .... 1893, 1897  
 \firstarticle . 4035, 4059, 4060,  
     4062  
 \FirstFrameCommand .... 1619  
 \firstimage .. 4132, 4145, 4146,  
     4148  
 \firstmark .... 1505, 3241  
 \firstTextFormat ... 3793, 3795  
 \firstTitleFormat . 3781, 3787,  
     3788  
 \float@box .... 2393, 2403  
 \float@endH .... 2392, 2402  
 \floatingpenalty .... 20, 37,  
     56, 82, 99, 118, 1515, 1534,  
     1553, 1786, 1803, 1822  
 \flushright ... 3781, 3800, 3819  
 \fontencoding . 3045, 3058, 3070,  
     3079  
 \fontfamily ....  
     .. 3046, 3059, 3071, 3080,  
     3092, 3095, 3098, 3101, 3104,  
     3107  
 \fontsize .... 1775  
 \fontspec 2420, 2738, 3042, 3055,  
     3067, 3076, 3115, 3119, 3123,  
     3127, 3132, 3137, 4620, 4644,  
     4649  
 \foot .... 3776  
 \footdir@ORG@xepersian@amsart@footnotetextfont  
     .... 64  
 \footdir@ORG@xepersian@amsart@LTRfootnotetextframe  
     .... 66  
 \footdir@ORG@xepersian@amsart@RTLfootnotetextframe  
     .... 65  
 \footdir@ORG@xepersian@amsbook@footnotetextfontlet  
     .... 125  
 \footdir@ORG@xepersian@amsbook@LTRfootnotetext G  
     .... 127  
 \footdir@ORG@xepersian@amsbook@RTLfootnotetext G  
     .... 126  
 \footdir@ORG@xepersian@footnotetext G@refundefinedtrue  
     .... 1563  
 \footdir@ORG@xepersian@imsproc@footnotetext g .  
     .... 1829  
 \footdir@ORG@xepersian@imsproc@LTRfootnotetext g@addtomacro  
     .... 1831  
                 \g . 3045, 3058, 3070, 3079, 4533,  
                 4644, 4645, 4649, 4650  
                 \g@addtomacro .... 4696, 4741  
                 \G@refundefinedtrue .... 3177  
                 \gdef .... 134, 140, 146,  
                 152, 176, 203, 230, 237, 253,  
                 254, 264, 265, 271, 272, 283,  
                 284, 1453, 1463, 1464, 1475,  
                 1476, 1725, 1726, 2039, 2040,

\textcolor{blue}{2829}, \textcolor{blue}{2830}, \textcolor{blue}{2836}, \textcolor{blue}{2837}, \textcolor{blue}{2843},	301
\textcolor{blue}{2844}, \textcolor{blue}{2851}, \textcolor{blue}{2852}, \textcolor{blue}{2859}, \textcolor{blue}{2892},	310
\textcolor{blue}{2893}, \textcolor{blue}{2922}, \textcolor{blue}{2923}, \textcolor{blue}{3714}, \textcolor{blue}{3984},	307
\textcolor{blue}{3985}, \textcolor{blue}{3986}, \textcolor{blue}{4659}, \textcolor{blue}{4707}, \textcolor{blue}{4709},	303
\textcolor{blue}{4727}, \textcolor{blue}{4729}, \textcolor{blue}{4731}, \textcolor{blue}{4737}, \textcolor{blue}{4738},	304
\textcolor{blue}{4754}, \textcolor{blue}{4779}, \textcolor{blue}{4780}, \textcolor{blue}{4794}, \textcolor{blue}{4813},	303
\textcolor{blue}{4815}, \textcolor{blue}{4820}, \textcolor{blue}{4831}	303
\textcolor{blue}{\getanddefine@fonts} . . . . .	4489, 4513
\textcolor{blue}{\Gin@boolkey} . . . . .	2745
\textcolor{blue}{\glb@currsize} . . . . .	4619
\textcolor{blue}{\global} .. . . . .	164, 165, 290, 300, 301,
	302, 303, 304, 305, 306, 307,
	315, 1482, 1483, 1502, 1570,
	1571, 1588, 1589, 1603, 1604,
	2150, 2154, 2474, 2563, 3185,
	3186, 3195, 3238, 3239, 3893,
	3894, 3895, 3896, 3897, 3898,
	3899, 3900, 3901, 3902, 4495,
	4521
\textcolor{blue}{\globaldefs} . . . . .	4490, 4514
\textcolor{blue}{\glossary} . . . . .	1492, 1689, 1699, 3215
\textcolor{blue}{\glossaryentry} . . . . .	1700
\textcolor{blue}{\glshere@adadipage} . . . . .	1632, 1634, 1662
\textcolor{blue}{\glshere@Alphpage} . . . . .	1634, 1658
\textcolor{blue}{\glshere@alphpage} . . . . .	1634, 1656
\textcolor{blue}{\glshere@disablepagerefexpansion} . . . . .	1665
\textcolor{blue}{\glshere@harfipage} . . . . .	1630, 1634, 1660
\textcolor{blue}{\glshere@numberpage} . . . . .	1634, 1648, 1650
\textcolor{blue}{\glshere@protected@pagefmts} . . . . .	1633
\textcolor{blue}{\glshere@Romanpage} . . . . .	1634, 1654
\textcolor{blue}{\glshere@romanpage} . . . . .	1634, 1652
\textcolor{blue}{\glshere@tartibipage} .. . . . .	1631, 1634, 1664
\textcolor{blue}{\goodbreak} . . . . .	4471
\textcolor{blue}{\grid} . . . . .	3675, 3679, 3941
\textcolor{blue}{\Grot@x} .. . . . .	2753, 2754, 2755, 2756
\textcolor{blue}{\Grot@y} .. . . . .	2757, 2758, 2759, 2760, 2761, 2762
\textcolor{blue}{\group} . . . . .	2738
\textcolor{blue}{\grp@aligned} . . . . .	306
\textcolor{blue}{\GRP@box} . . . . .	301
\textcolor{blue}{\grp@eqs@numbered} . . . . .	305
\textcolor{blue}{\grp@hasNumber} . . . . .	310
\textcolor{blue}{\GRP@label} . . . . .	302
\textcolor{blue}{\grp@linewidth} . . . . .	304
\textcolor{blue}{\GRP@queue} . . . . .	301
\textcolor{blue}{\grp@setnumber} . . . . .	310
\textcolor{blue}{\grp@shiftnumber} . . . . .	307
\textcolor{blue}{\grp@wdL} . . . . .	303
\textcolor{blue}{\grp@wdNum} . . . . .	304
\textcolor{blue}{\grp@wdR} . . . . .	303
\textcolor{blue}{\grp@wdT} . . . . .	303
\textcolor{blue}{\gsetlength} . . . . .	178, 180, 205, 207
<b>H</b>	
\textcolor{blue}{\hangindent} . . . . .	1760, 1761, 1762
\textcolor{blue}{\harfi} . . . . .	1341, 2033, 2865, 2899, 2929, 3274
\textcolor{blue}{\harfinumeral} . . . . .	3275
\textcolor{blue}{\hb@xt@} . . . . .	3224, 3234
\textcolor{blue}{\hbox} . . . . .	231, 238, 1768, 1775, 1849, 2301, 3176, 3250, 3251, 4565
\textcolor{blue}{\headDateTimeFormat} . . . . .	3740, 3742
\textcolor{blue}{\headerfont} . . . . .	4707
\textcolor{blue}{\headheight} . . . . .	1498, 3220, 3974
\textcolor{blue}{\heading} . . . . .	3763
\textcolor{blue}{\headrulewidth} . . . . .	3975, 4031
\textcolor{blue}{\headsep} . . . . .	1499, 3229
\textcolor{blue}{\headtoname} . . . . .	3269
\textcolor{blue}{\height} . . . . .	2757, 2758
\textcolor{blue}{\hfil} . . . . .	1770, 1849, 2297, 2298, 2299, 2300, 2332, 2333, 2334, 2340, 2341, 2342, 3203, 3204, 3206, 3207
\textcolor{blue}{\hline} . . . . .	4424, 4748, 4749, 4752, 4753, 4773, 4774
\textcolor{blue}{\hrule} . . . . .	1770, 1772, 1887, 4307, 4313, 4360, 4366, 4411, 4451
\textcolor{blue}{\hrulefill} . . . . .	3989, 3994, 4008
\textcolor{blue}{\hsize} . . . . .	20, 37, 56, 82, 99, 118, 1516, 1535, 1554, 1574, 1592, 1607, 1625, 1786, 1803, 1822, 2158, 2174, 2199, 2200, 2398, 2408
\textcolor{blue}{\hskip} . . . . .	1848, 1887, 2299, 2300, 2342
\textcolor{blue}{\hspace} . . . . .	1761, 1762, 3742, 3760, 3989, 3995, 4007, 4009, 4187
\textcolor{blue}{\hss} . . . . .	2186
\textcolor{blue}{\Huge} . . . . .	3712, 3781, 3837

\huge	.....	3711
\Hy@appendixstring	.....	1727
\Hy@backout	.....	160, 168
\Hy@chapapp	.....	1727
\Hy@org@appendix	....	1722, 1728
\hyper@natlinkbreak	2496,	2527
\hyper@natlinkstart	.....	168
\hyphenpenalty	.....	1758, 1840
<b>I</b>		
\if	.....	291, 310, 1682, 1685, 2111, 2117, 2123, 2126, 2129, 2132, 2135, 2138, 2141, 2172, 2179, 2180, 2181, 2182, 2194, 2211, 2212, 2213, 2214, 2215, 2216, 2217, 2218, 2219, 2220, 2234, 2235, 2236, 2237, 2238, 2239, 2241, 2242, 2243, 2244, 2245, 2248, 2249, 2250, 2251, 2252, 2253, 2268, 2269, 2270, 2271, 2272, 2273, 2275, 2276, 2277, 2278, 2279, 2280, 2281, 2284, 2285, 2286, 2287, 2288, 2289, 2312, 2313, 2314, 2315, 2316, 2317, 2319, 2320, 2321, 2322, 2323, 2324, 2357, 2358, 2359, 2360, 2361, 2362, 2363, 2364, 2365, 2366, 2367, 2368, 2369, 2370, 2372, 2373, 2374, 2375, 2376, 2379, 2380, 2381, 2382, 2383, 2384, 2479, 2509, 2527, 2537, 2543, 2544, 2605, 2621, 2653, 2673, 2679, 2681, 2691, 2699, 2701, 2723, 2753, 2754, 2755, 2756, 2757, 2758, 2759, 2760, 2761, 2762, 4558
\if@bidi@algorithmicloaded@	.	..... 1931
\if@bidi@algorithmloaded@	1934	
\if@bidi@backrefloaded@	.	1937
\if@bidi@csprimitive	...	1953
\if@bidi@csundef	.....	3478
\if@bidi@enumerateloaded@	1940	
\if@bidi@tocloftloaded@	.	1943
\if@bidi@urlloaded@	....	1946
\if@extrafootnotefeatures	3604	
\if@files_w	.....	3175, 4557
\if@inlabel	.....	290
\if@Latin	....	4691, 4692, 4693
\if@LTrbibitems	.....	1741
\if@newlist	..	1482, 1502, 2418, 3185, 3238
\if@noskipsec	.....	289
\if@pboxsw	.....	2188
\if@RT	.....	1921
\if@RTL	.....	2, 3, 5, 7, 154, 243, 287, 299, 312, 1620, 1622, 1624, 1705, 1706, 1707, 1708, 1709, 1710, 1711, 1712, 1713, 1714, 1715, 1716, 1717, 1718, 1719, 1720, 1741, 1757, 1760, 1761, 1762, 1835, 1846, 1847, 1922, 2044, 2045, 2046, 2047, 2048, 2049, 2050, 2051, 2052, 2172, 2194, 2968, 2969, 2970, 2971, 2972, 2973, 2974, 2975, 2976, 2977, 3252, 3253, 3254, 3255, 3256, 3257, 3258, 3259, 3260, 3261, 3262, 3263, 3264, 3265, 3266, 3267, 3268, 3269, 3270
\if@RTL@footnote	...	16, 25, 78, 87, 1467, 1511, 1522, 1570, 1571, 1580, 1782, 1791
\if@RTLbibitems	.....	1741
\if@RTLmain	...	3211, 3224, 3234
\if@RTLtab	2171, 2193, 2213, 2214, 2215, 2216, 2236, 2237, 2238, 2239, 2270, 2271, 2272, 2273, 2314, 2315, 2316, 2317, 2359, 2360, 2361, 2362	
\if@specialpage	.....	3194
\if@tempswa	.....	2596
\if@twocolumn	.....	1751
\if@twoside	.....	2885, 3197
\ifadl@usingarypkg	....	2258
\ifbidi@autofootnoterule	1570, 1588, 1603	
\ifBR@verbose	.....	157
\ifcase	..	2296, 2327, 2331, 2335, 2339, 2478, 2508, 2601, 3271

3299, 3362, 3368, 3371, 3374,  
 3378, 3400, 3463, 3470, 3500,  
 3504, 3508, 3512, 4998  
`\ifdim` ..... 320, 3921, 4406  
`\ifglsxindy` ..... 1679  
`\ifhmode` ..... 2095  
`\ifinner` ..... 2101  
`\ifmmode` ..... 2183, 4485, 4509  
`\ifNAT@full` ..... 2476, 2565  
`\ifNAT@longnames` ... 2472, 2561  
`\ifNAT@numbers` .... 2425, 2632  
`\ifNAT@super` ..... 2426  
`\ifNAT@swa` 2478, 2543, 2567, 2619  
`\ifnum` 321, 1570, 1588, 1603, 1837,  
 2142, 2209, 2210, 2226, 2227,  
 2228, 2229, 2231, 2260, 2261,  
 2262, 2263, 2265, 2310, 2311,  
 2349, 2350, 2351, 2352, 2354,  
 2950, 3033, 3289, 3291, 3300,  
 3301, 3302, 3303, 3304, 3305,  
 3306, 3307, 3324, 3326, 3328,  
 3330, 3332, 3337, 3348, 3349,  
 3351, 3353, 3354, 3357, 3390,  
 3392, 3401, 3402, 3403, 3404,  
 3405, 3406, 3407, 3408, 3425,  
 3427, 3429, 3431, 3433, 3438,  
 3449, 3450, 3452, 3454, 3455,  
 3458, 3480, 3482, 3484, 3486,  
 3488, 3490, 3502, 3506, 3510,  
 3513, 4318, 4392, 4438, 4463,  
 4486, 4510, 4876, 4880, 4908,  
 4914, 4935, 4962, 4966, 4971,  
 4975, 4977, 4986  
`\ifodd` ... 2112, 2118, 3198, 4869,  
 4874  
`\ifthenelse` ..... 177, 182, 204,  
 209, 3661, 3673, 3682, 3786,  
 3801, 3820, 3841, 3959, 4037,  
 4038, 4068, 4100, 4114, 4134,  
 4152, 4176, 4206, 4230, 4257,  
 4286, 4291, 4296, 4301, 4306,  
 4339, 4344, 4349, 4354, 4359,  
 4755  
`\ifwritexviii` . 3032, 3572, 3582,  
 3592  
`\ifx` 1341, 1342, 1343, 1344, 1345,  
 1346, 1347, 1348, 1349, 1350,  
 1351, 1648, 1650, 1652, 1654,  
 1656, 1658, 1660, 1662, 1664,  
 1669, 1862, 1893, 2088, 2091,  
 2175, 2395, 2405, 2482, 2483,  
 2485, 2512, 2513, 2515, 2584,  
 2602, 2662, 2711, 2750, 2863,  
 2865, 2866, 2867, 2868, 2869,  
 2870, 2871, 2872, 2873, 2874,  
 2875, 2876, 2877, 2878, 2879,  
 2897, 2899, 2900, 2901, 2902,  
 2903, 2904, 2905, 2906, 2907,  
 2908, 2909, 2910, 2911, 2912,  
 2913, 2927, 2929, 2930, 2931,  
 2932, 2933, 2934, 2935, 2936,  
 2937, 2938, 2939, 2940, 2941,  
 2942, 2943, 3015, 3023, 3203,  
 3204, 3206, 3207, 4483, 4507,  
 4537, 4654, 4662, 4663, 4664,  
 4665, 4666, 4667, 4668, 4669,  
 4670, 4671, 4684, 4687, 4688,  
 4689, 4691, 4692, 4693  
`\ifXePersian@kabiseh` 4837, 4942  
`\ifXePersian@leap` .. 4837, 4886  
`\ifxetex` ..... 3914, 4137, 4154  
`\ignorespaces` ..... 25, 42,  
 61, 87, 104, 123, 197, 224,  
 324, 1522, 1541, 1560, 1580,  
 1598, 1613, 1791, 1808, 1827,  
 1869, 2400, 2410, 3732, 3785,  
 3795, 3800, 3808, 3813, 3819,  
 3827, 4087, 4113, 4262  
`\image` ..... 3909  
`\immediate` 3175, 3575, 3576, 3585,  
 3586, 3595, 3596, 4557  
`\includegraphics` .. 3924, 4138,  
 4155  
`\index` ..... 1491, 3214  
`\indexEntryFormat` .. 3730, 3732  
`\indexEntryPageFormat` ... 3736,  
 3738  
`\indexEntryPageTxt` . 3735, 3738  
`\indexEntrySeparator` 3734, 4262  
`\indexFormat` ..... 3726, 3728  
`\indexitem` 4255, 4265, 4266, 4268

```

\indexname ..... 3258
\init@restore@version ... 4492
\innerAuthorFormat . 3858, 4375
\innerPlaceFormat .. 3859, 4375
\innerSubtitleFormat 3848, 3849
\innerTextFinalMark 3860, 4396
\innerTitleFormat . 3837, 3842,
                   3843
\input 1964, 1965, 1966, 1967, 1968,
       1969, 1970, 3526, 3527, 3528,
       3529, 3530, 3531, 3532, 3533,
       3534, 3535, 3536, 3537, 3538,
       3539, 3540, 3541, 3542, 3543,
       3544, 3545, 3546, 3547, 3548,
       3549, 3550, 3551, 3552, 3553,
       3554, 3555, 3556, 3557, 3558,
       3559, 3560, 3561, 3562, 3563,
       3564, 3565, 3566, 3567, 3568,
       3605, 3606
\insert ..... 15, 32,
           51, 77, 94, 113, 1510, 1529,
           1548, 1781, 1798, 1817
\insert@column 2298, 2299, 2300,
              2301, 2303, 2304
\int 4580, 4588, 4596, 4604, 4612
\interfootnotelinepenalty ...
                           ..... 18, 35,
                           54, 80, 97, 116, 1513, 1532,
                           1551, 1784, 1801, 1820
\interlinepenalty ..... 18, 35,
                      54, 80, 97, 116, 1513, 1532,
                      1551, 1784, 1801, 1820
\intermath@penalty ..... 323
\iranicdefault . 3086, 3098, 3137
\iranicfamily .. 3096, 3097, 3110
\isempty ..... 177, 182, 204, 209
\item 1755, 4781, 4782, 4783, 4784
\itemautorefname ..... 1707
\itshape ..... 4793

J
\jobname . 3576, 3577, 3586, 3587,
            3596, 3597

K
\KashidaOff ..... 1918
\KashidaOn ..... 1917, 1919
\kern ..... 198, 199,
           225, 226, 1769, 1770, 1771,
           1772, 2430, 3251
\keys 1360, 1362, 1363, 1366, 1368,
       1369, 1372, 1374, 1375, 1378,
       1380, 1383
\keyval@eq@alias@key 1956, 1960

L
\l .. 3046, 3049, 3059, 3071, 3080
\label ... 1490, 3213, 4391, 4437,
          4461
\labelsep ..... 1739, 1743
\labelwidth ..... 1742, 1743
\LARGE ... 3710, 3797, 3861, 3864,
          3877, 3879
\Large ... 3709, 3816, 3866, 3993,
          4276, 4310
\large 3708, 3720, 3726, 3806, 3825,
       3848, 3868, 3881, 3887, 3999
\LastFrameCommand ..... 1623
\lastpenalty ..... 321
\lastskip ..... 320
\latin ..... 3152
\LatinAlphs ... 3152, 3156, 3521
\Latincite ..... 2628, 3168
\latinfont ...
               .. 25, 61, 87, 123, 186, 193,
               231, 1467, 1468, 1522, 1560,
               1580, 1613, 1791, 1827, 3057,
               3143, 3145, 3150, 3163
\latintoday ..... 3159
\lccode ..... 2647, 2648, 2649
\leaders ..... 1887
\leavevmode ..... 289,
                 290, 1774, 1848, 2169, 2191,
                 2418, 3170, 3250
\left@footnoterule 1570, 1603,
                   1771
\leftmargin ..... 1743
\leftskip ..... 1846, 1847
\let .. 11, 73, 164, 165, 175, 196,
       202, 223, 229, 233, 236, 240,
       300, 302, 305, 306, 307, 313,
       318, 1349, 1350, 1351, 1352,

```

\longdate . . . . .	4371
\loop . . . . .	4963, 4972
\lower . . . . .	3250
\lowercase . . . . .	2650
\lr . . . . .	1732, 2461, 2550, 3150, 3159, 3172, 3714, 3769, 4161
\LRE . . . . .	3150
\lstlistingname . . . . .	1921
\lstlistlistingname . . . . .	1922
\LTR . . . . .	3152
\LTRbidituftesidenotemarginpar .....	231
\LTRfoottextfont . . . . .	1468
\LTRmarginnote . . . . .	228
\ltx@ifundefined . . . . .	1724
<b>M</b>	
\m@ne . . . . .	2578, 4488, 4512
\m@th . . . . .	2188
\makeform . . . . .	4803, 4810
\makeform@correction	4718, 4810
\makeform@nocorrection ..	4715, 4803
\MakeFramed . . . . .	1625
\makemask . . . . .	4804, 4811
\makemask@correction	4723, 4811
\makemask@nocorrection ..	4720, 4804
\maketitle . . . . .	1857, 3870, 3894
\MakeUppercase . . . . .	1872, 3836
\makezwnjletter . . . . .	1951, 1952
\markboth . . . . .	1871
\math@bgroup . . . . .	4483, 4507
\math@fonts . . . . .	4490, 4514
\math@version . . . . .	4486, 4489, 4494, 4495, 4499, 4510, 4513, 4517, 4519, 4521, 4525
\mathalpha . . . . .	4627, 4628, 4629, 4630, 4631, 4632, 4633, 4634, 4635, 4636
\mathbf . . . . .	4573, 4639
\mathbin . . . . .	4637
\mathchar@type . . . . .	4569, 4571
\mathchardef . . . . .	4657

\mathcode 4581, 4589, 4597, 4605,  
     4613, 4683  
 \mathgroup ..... 4480  
 \mathiranic ..... 3097  
 \mathit ..... 4574, 4640  
 \mathnavar ..... 3100  
 \mathord ..... 4638  
 \mathpersiansf ..... 3091  
 \mathpersiantt ..... 3094  
 \mathpook ..... 3103  
 \mathrm ..... 4575, 4641  
 \mathsayeh ..... 3106  
 \mathsf ..... 4576, 4646  
 \mathsurround ..... 317  
 \mathtt ..... 4577, 4651  
 \mbox ..... 2432  
 \meaning ..... 3018, 3021  
 \MessageBreak .....  
     ... 2487, 2488, 2517, 2518,  
         4059, 4091, 4125, 4145, 4166,  
         4169, 4191, 4216, 4242, 4265,  
         4268, 4759  
 \MidFrameCommand ..... 1621  
 \minilogo ..... 3998, 4212  
 \minaggedcols .....  
     ... 3637, 3638, 3676, 3680,  
         4318, 4392, 4438, 4463  
 \mlftitle ..... 2048  
 \mlttitle ..... 2049  
 \month ..... 4863  
 \moveright ..... 1496, 3219  
 \mtctitle ..... 2047  
 \multido ..... 3960, 3966  
 \multiplefootnotemarker .. 198,  
     199, 225, 226  
 \multiply ..... 2148, 4866, 4879, 4906,  
     4912, 4929, 4933  
 \mylogo ..... 4003  
  
**N**  
 \n . 4659, 4662, 4663, 4664, 4665,  
     4666, 4667, 4668, 4669, 4670,  
     4671  
 \NAT@close ..... 2544, 2623  
 \NAT@Latin@citelp 2631, 2635,  
     2636, 2637  
  
 \NAT@@open ..... 2527, 2603  
 \NAT@alias 2505, 2535, 2570, 2613  
 \NAT@call@names 2473, 2476, 2562,  
     2565  
 \NAT@aysep ..... 2497  
 \NAT@biblabel ..... 2448  
 \NAT@biblabelnum ..... 2439  
 \NAT@bibsetnum ..... 2440  
 \NAT@bibsetup ..... 2449  
 \NAT@cite ..... 2445  
 \NAT@cite@list ..... 2462, 2551  
 \NAT@citea@mbox ..... 2596  
 \NAT@citemum ..... 2433  
 \NAT@citesuper ..... 2426  
 \NAT@citeundefined 2467, 2557,  
     4560  
 \NAT@citex ..... 2446  
 \NAT@citexnum ..... 2437  
 \NAT@close ..... 2441, 2452  
 \NAT@cmprs ..... 2572, 2618  
 \NAT@cmt ..... 2543, 2621  
 \NAT@ctype 2478, 2508, 2568, 2570,  
     2601, 2609, 2611, 2620, 2629  
 \NAT@date 2452, 2469, 2479, 2480,  
     2491, 2499, 2504, 2509, 2522,  
     2529, 2534, 2537, 2544  
 \NAT@def@citea . 2506, 2538, 2599  
 \NAT@def@citea@box ..... 2607  
 \NAT@def@citea@close ... 2540  
 \NAT@exlab 2485, 2489, 2515, 2519  
 \NAT@fullfalse ..... 2630  
 \NAT@fulltrue ..... 2630  
 \NAT@hyper@ .....  
     ... 2480, 2489, 2491, 2494,  
         2503, 2504, 2505, 2510, 2519,  
         2522, 2525, 2533, 2534, 2535,  
         2570, 2606  
 \NAT@hyper@citea@space .. 2609,  
     2611, 2613  
 \NAT@idxtxt ..... 2441, 2452  
 \NAT@ifcat@num ..... 2573, 2576  
 \NAT@last@nm . 2470, 2482, 2512,  
     2559, 2602  
 \NAT@last@num . 2559, 2576, 2577,  
     2595

\NAT@last@yr . 2470, 2483, 2513,  
     2550, 2584, 2618  
 \NAT@last@yr@mbox .. 2580, 2590  
 \NAT@Latin@cites .. 2630, 2631  
 \NAT@Latin@citex .. 2447, 2455,  
     2456  
 \NAT@Latin@citexnum 2438, 2545,  
     2546  
 \NAT@mbox 2427, 2432, 2603, 2606,  
     2623  
 \NAT@merge .. 2580, 2595  
 \NAT@name 2441, 2452, 2473, 2477,  
     2562, 2566  
 \NAT@nm .. 2461, 2470, 2476, 2477,  
     2480, 2482, 2495, 2503, 2510,  
     2512, 2526, 2533, 2550, 2559,  
     2565, 2566, 2574, 2575, 2579,  
     2583, 2602  
 \NAT@nfmt 2480, 2495, 2503, 2510,  
     2526, 2533  
 \NAT@num . 2441, 2550, 2559, 2573,  
     2574, 2595, 2606  
 \NAT@open .. 2441, 2452  
 \NAT@parse .. 2471, 2560  
 \NAT@partrue .. 2629  
 \NAT@penalty . 2443, 2451, 2587,  
     2602  
 \NAT@reset@citea .. 2460, 2549  
 \NAT@reset@parser .. 2458, 2547  
 \NAT@set@cites .. 2424, 2627  
 \NAT@sort@cites .. 2459, 2548  
 \NAT@space 2429, 2434, 2450, 2602  
 \NAT@spacechar ..  
     .. 2434, 2441, 2450, 2452,  
     2490, 2497, 2521, 2527, 2603,  
     2605  
 \NAT@super@kern 2430, 2435, 2603  
 \NAT@swafalse .. 2633  
 \NAT@swatru .. 2629  
 \NAT@temp 2484, 2485, 2514, 2515  
 \NAT@test 2570, 2603, 2609, 2611  
 \NAT@year 2461, 2470, 2483, 2513  
 \NAT@yrsep .. 2482, 2512, 2602  
 \natexlab .. 2442, 2453  
 \navardefault .. 3087, 3101, 3123  
 \navarfam .. 3099, 3100, 3111  
 \NeedsTeXFormat 2978, 3608, 4477,  
     4697, 4834  
 \new@mathbf .. 4578, 4639  
 \new@mathgroup .. 4480, 4481  
 \new@mathit .. 4586, 4640  
 \new@mathrm .. 4594, 4641  
 \new@mathsf .. 4602, 4646  
 \new@mathtt .. 4610, 4651  
 \newboolean .. 3619, 3621, 3623,  
     3625, 3627, 3629, 3631  
 \newcolumntype .. 4711, 4712  
 \newcommand ..  
     1630, 1631, 1632, 1917,  
     1918, 1951, 1953, 1954, 1956,  
     1960, 2455, 2545, 2631, 2636,  
     2956, 3084, 3085, 3086, 3087,  
     3088, 3089, 3243, 3276, 3279,  
     3382, 3385, 3616, 3671, 3715,  
     3716, 3719, 3720, 3721, 3726,  
     3727, 3730, 3731, 3734, 3735,  
     3736, 3737, 3740, 3741, 3745,  
     3746, 3749, 3750, 3751, 3752,  
     3755, 3758, 3763, 3768, 3771,  
     3773, 3776, 3781, 3782, 3793,  
     3794, 3797, 3798, 3806, 3807,  
     3810, 3811, 3816, 3817, 3825,  
     3826, 3828, 3829, 3830, 3831,  
     3834, 3835, 3837, 3838, 3848,  
     3849, 3850, 3851, 3852, 3853,  
     3858, 3859, 3860, 3861, 3862,  
     3863, 3864, 3865, 3866, 3867,  
     3868, 3869, 3904, 3909, 3941,  
     3973, 3987, 3998, 4003, 4011,  
     4035, 4066, 4098, 4132, 4151,  
     4255, 4273, 4280, 4322, 4330,  
     4373, 4379, 4399, 4416, 4445,  
     4470, 4536, 4567, 4568, 4570,  
     4618, 4654, 4655, 4707, 4709,  
     4715, 4718, 4720, 4723, 4727,  
     4729, 4731, 4779, 4780, 4785,  
     4789, 4794, 4813, 4815, 4991  
 \newcount 3633, 3634, 3637, 3939,  
     3940, 4838, 4839, 4840, 4841,  
     4842, 4843, 4844, 4845, 4846,  
     4847, 4848, 4849, 4850, 4851,  
     4853, 4854, 4855, 4856, 4857,

4858, 4859, 4860  
 \newcounter ..... 4732, 4733  
 \newdimen ..... 3937, 3938  
 \NewDocumentCommand 4578, 4586,  
     4594, 4602, 4610  
 \newenvironment .....  
     .. 1737, 1954, 2641, 2642,  
     3156, 3157, 3906, 4012, 4174,  
     4204, 4228, 4382, 4431, 4457,  
     4761, 4795  
 \newfam ..... 4481  
 \newfontlanguage ..... 3039  
 \newfontscript ..... 3038  
 \newif ..... 3032, 4837  
 \newlength 3611, 3612, 3613, 3614,  
     3615, 3617, 4725, 4816, 4818  
 \newpage . 3574, 3584, 3594, 4022  
 \newsavebox ..... 3905  
 \newsection ..... 4379  
 \next 1893, 1895, 1896, 2654, 2655,  
     2656, 2660, 2662, 2665, 2669,  
     2670, 2672, 2678, 2683, 2687,  
     2689, 2698, 2700, 2706, 2709,  
     2713, 2720, 2722  
 \nobreak . 1848, 1850, 1886, 2427  
 \nocite ..... 4552, 4564  
 \noexpand 1480, 1674, 2653, 2673,  
     2679, 2681, 2691, 2699, 2701,  
     2713, 2714, 2723, 3183, 4493,  
     4537, 4542, 4544, 4545, 4549  
 \nohyphens 3787, 3802, 3821, 3842  
 \noindent ..... 231,  
     238, 3732, 3747, 3785, 3795,  
     3800, 3808, 3813, 3819, 3827,  
     3832, 3836, 3840, 3989, 4006,  
     4087, 4113, 4138, 4185, 4262,  
     4276, 4310, 4325, 4363, 4420,  
     4448, 4473, 4475  
 \non@alpherr ..... 4502, 4528  
 \nopagebreak ..... 4827  
 \normalcolor . 2156, 2397, 2407,  
     3223, 3233  
 \normalfont .. 17, 34, 53, 79, 96,  
     115, 1739, 1775, 1783, 1800,  
     1819, 1835, 3050, 3116, 3120,  
     3124, 3128, 3133, 3138, 3143,  
     3144, 3147, 3148  
 \normalparindent 21, 38, 57, 83,  
     100, 119, 1787, 1804, 1823  
 \normalsfcodes ..... 1489, 3212  
 \normalsize .....  
     .. 1489, 3164, 3210, 3683,  
     3684, 3730, 4325, 4363  
 \NOT ..... 177, 204  
 \not ..... 4739  
 \not@math@alphabet 3091, 3094,  
     3097, 3100, 3103, 3106  
 \null ..... 3874, 3890  
 \number .. 1639, 1649, 1842, 3289,  
     3291, 3292, 3390, 3392, 3393,  
     3484, 3486, 3488, 3490, 4494,  
     4518, 4992, 4993  
 \numexpr . 4581, 4589, 4597, 4605,  
     4613

## O

\obeyspaces ..... 4659  
 \oddsidemargin ..... 3199  
 \old@endquestion ... 4822, 4830  
 \old@question ..... 4821, 4828  
 \on@line ..... 4540  
 \or 2298, 2299, 2300, 2302, 2303,  
     2327, 2328, 2329, 2333, 2334,  
     2335, 2336, 2337, 2341, 2342,  
     2503, 2504, 2505, 2533, 2534,  
     2535, 2608, 2610, 2612, 3271,  
     3272, 3273, 3310, 3311, 3312,  
     3313, 3314, 3315, 3316, 3317,  
     3318, 3319, 3323, 3362, 3363,  
     3364, 3365, 3368, 3371, 3374,  
     3375, 3378, 3379, 3380, 3411,  
     3412, 3413, 3414, 3415, 3416,  
     3417, 3418, 3419, 3420, 3424,  
     3463, 3464, 3465, 3466, 3467,  
     3470, 3471, 3472, 3473, 3500,  
     3501, 3504, 3505, 3508, 3509,  
     3512, 4998, 4999, 5000, 5001,  
     5002, 5003, 5004  
 \orgadadi ..... 1645, 1662  
 \orgAlph ..... 1642, 1658  
 \orgalph ..... 1641, 1656  
 \orgharfi ..... 1644, 1660

\orgnumber .....	1639, 1650	\parallel .....	3742
\orgRoman .....	1643, 1654	\parbox .....	4766, 4826
\orgromannumeral ...	1640, 1652	\parfillskip .....	1847
\orgtartibi .....	1646, 1664	\parindent .....	21, 38, 57, 83, 100, 119, 1756, 1787, 1804, 1823, 1846
\orgthe .....	1638, 1648	\parskip .....	1756
\orig 4573, 4574, 4575, 4576, 4577, 4579, 4587, 4595, 4603, 4611		\part .....	1833
\originaltoday .....	3158, 3159	\partautorefname .....	1710
\Ovalbox .....	4302, 4355	\partname .....	3261
\ovalbox .....	4297, 4350	\PassOptionsToClass 3639, 3640, 3641	
<b>P</b>			
\p@ 1752, 1756, 1769, 1770, 1771, 1772, 2430, 3875		\pbs .....	4710, 4711
\p@enumiv .....	1740	\pdfstringdefDisableCommands .....	1731
\PackageError .....		\penalty ... 317, 323, 2443, 3173	
.. 1932, 1935, 1938, 1941, 1944, 1947, 3249, 3284, 3573, 3579, 3583, 3589, 3593, 3599, 4548		\persian .....	3154
\PackageInfo ... 158, 170, 4567		\PersianAlphs . 3154, 3157, 3517, 3525	
\PackageWarning 2468, 2557, 3476, 3571, 4560		\persianday .....	4997
\PackageWarningNoLine ... 2485, 2515		\persianfont . 42, 104, 213, 220, 238, 1469, 1541, 1598, 1808, 3044, 3147, 3149, 3151	
\page@free .....	3919, 3921	\PersianMathsDigits ... 4686	
\pageautorefname .....	1720	\persianmathsdigits 4626, 4687, 4691	
\pagegoal .....	4401	\persianmathsfdigits ... 4646, 4688, 4692	
\pagename .....	3268	\persianmathtdigits ... 4651, 4689, 4693	
\pagenumbering 69, 249, 260, 278, 1458, 2032, 2886		\persianmonth .....	4996
\pageref .....	3760, 4258	\persiansfdefault . 3084, 3092, 3115	
\pagesFormat .....	3834, 3836	\persiansffamily ... 3090, 3091, 3108	
\pagestyle .....	3977	\persiantoday .....	3160, 4991
\pagetotal .....	4402	\persianttdefault . 3085, 3095, 3119	
\par .....	10, 25, 42, 61, 71, 87, 104, 123, 131, 137, 143, 149, 250, 261, 268, 280, 938, 1450, 1460, 1472, 1760, 1761, 1762, 1764, 1791, 1808, 1827, 1839, 1849, 1857, 2036, 2826, 2833, 2840, 2848, 2856, 2889, 2919, 3877, 3879, 3885, 3887, 3888, 4377, 4462, 4767, 4827	\persianttfamily ... 3093, 3094, 3109	
\paragraphautorefname ... 1716		\persianyear .....	4995
		\pictureCaptionFormat ... 3830, 3832	
		\plftitle .....	2045
		\plq .....	3012
		\pltttitle .....	2046

```

\pookdefault . . . 3088, 3104, 3127
\pookfamily . . . 3102, 3103, 3112
\postmath . . . . . 323
\PrefixCurrentTab . . . . . 2956
\premath . . . . . 319
\prepnext@tok . . . . . 2295, 2305
\printindex . . . . . 3574, 3584, 3594
\ProcessOptions 3602, 3653, 4833
\proofname . . . . . 3270
\protect . 1480, 3183, 4059, 4060,
          4062, 4091, 4092, 4094, 4125,
          4126, 4128, 4145, 4146, 4148,
          4166, 4167, 4169, 4265, 4266,
          4268, 4716, 4719, 4721, 4724,
          4742, 4747, 4748, 4749, 4751,
          4752, 4753, 4773, 4774
\protected@edef . . . . .
          . . . . . 22, 39, 58, 84, 101,
          120, 1517, 1536, 1555, 1576,
          1594, 1609, 1672, 1788, 1805,
          1824
\protected@xdef . 185, 212, 1666
\providecommand . . . . . 3475
\ProvidesClass . . . . . 3609
\ProvidesFile . . . . . 1, 4, 8, 68,
          129, 135, 141, 147, 153, 173,
          242, 244, 255, 266, 274, 286,
          326, 1279, 1339, 1356, 1394,
          1437, 1448, 1454, 1466, 1470,
          1477, 1506, 1615, 1629, 1704,
          1736, 1878, 1920, 1923, 1950,
          2030, 2043, 2053, 2423, 2824,
          2831, 2838, 2846, 2854, 2883,
          2917, 2947, 2967
\ProvidesPackage . . . 2981, 4478,
          4698, 4835
\prq . . . . . 3011
\ptctitle . . . . . 2044

    Q
\question . . . . . 4821
\questionsepspace . 4818, 4819,
          4831
\questionspace . 4725, 4726, 4767
\questiontitle . . . . . 4813, 4832
\questiontitlefont . . . . . 4815

    R
\raggedFormat . 3671, 4319, 4393,
          4439, 4464
\RaggedLeft . . . . . 3671
\raggedleft . . . . . 1757, 1835
\raggedright . . . . . 1757, 1835
\raise . . . . . 1775
\raisebox . . . . . 3717, 3722
\refname . . . . . 243, 3259
\refstepcounter . . . . . 4783, 4784
\relax . . . . . 190, 199, 217,
          226, 1682, 1685, 1739, 1756,
          1836, 1842, 1844, 1846, 1848,
          1951, 2143, 2175, 2310, 2311,
          2332, 2333, 2334, 2395, 2405,
          2429, 2435, 2479, 2509, 2537,
          2544, 2550, 2577, 2584, 2595,
          2750, 2863, 2897, 2927, 2950,
          3015, 3033, 3653, 3872, 3893,
          3894, 3899, 3900, 3901, 3902,
          4483, 4497, 4507, 4523, 4569,
          4571, 4581, 4589, 4597, 4605,
          4613, 4619, 4683, 4865, 4866,
          4868, 4873, 4878, 4879, 4885,
          4887, 4889, 4891, 4892, 4893,
          4894, 4895, 4896, 4897, 4898,
          4899, 4900, 4901, 4903, 4905,
          4906, 4911, 4912, 4919, 4921,
          4924, 4928, 4929, 4932, 4933,
          4936, 4941, 4943, 4945, 4947,
          4948, 4949, 4950, 4951, 4952,
          4953, 4954, 4955, 4956, 4957,
          4958, 4960, 4961, 4964, 4969,
          4973, 4979, 4981, 4982
\renewcommand . . . 9, 70, 130, 131,
          136, 137, 142, 143, 148, 149,
          228, 235, 245, 246, 250, 256,
          257, 261, 267, 268, 275, 279,
          280, 1449, 1450, 1455, 1459,
          1460, 1467, 1468, 1469, 1471,
          1472, 1633, 1636, 1740, 1763,
          1853, 1854, 1855, 1856, 2031,
          2033, 2034, 2035, 2036, 2424,

```

2441, 2452, 2825, 2826, 2832,  
 2833, 2839, 2840, 2847, 2848,  
 2855, 2856, 2862, 2884, 2888,  
 2889, 2896, 2918, 2919, 2926,  
 2948, 2968, 2969, 2970, 2971,  
 2972, 2973, 2974, 2975, 2976,  
 2977, 3574, 3584, 3594, 3683,  
 3690, 3692, 3694, 3701, 3708,  
 3709, 3710, 3711, 3712, 3764,  
 3765, 3766, 3777, 3778, 3779,  
 3870, 3975, 4011, 4031, 4370,  
 4380, 4385, 4552, 4714  
`\ renewenvironment` .. 1616, 4823  
`\ repeat` .. 4966, 4975  
`\ RequirePackage` ..  
 . . . . . 2983, 2984, 2985, 2986,  
 3610, 3655, 3656, 3657, 3658,  
 3659, 3660, 3662, 3664, 3666,  
 3667, 3668, 3669, 3670, 4700,  
 4701, 4702, 4703, 4704, 4705  
`\ reserved@a` ..  
 . . . . . 2107, 2111, 2117, 2123,  
 2126, 2129, 2132, 2135, 2138,  
 2141  
`\ reserved@b` .. . . . . 2087, 2088  
`\ reset@font` ..  
 . . . . . 1489, 1512, 1531, 1550,  
 1573, 1591, 1606, 2467, 2556,  
 3144, 3148, 3162, 3176, 3209  
`\ resetlatinfont` 3142, 3152, 3156,  
 3211  
`\ right@footnoterule` 1570, 1588,  
 1767  
`\ rightline` .. . . . . 4374  
`\ rightskip` .. . . . . 1846, 1847  
`\ rl` .. . . . . 1733, 3151, 3160  
`\ RLE` .. . . . . 3151  
`\ rmdefault` .. . . . . 3049  
`\ Roman` ... 1347, 2870, 2904, 2934  
`\ roman` ... 1346, 2871, 2905, 2935  
`\ romannumeral` ..  
 . . . . . 1640, 1651, 2879, 2913,  
 2943, 4965, 4974, 4984  
`\ RTL` .. . . . . 3154  
`\ RTLbidituftesidenotemarginpar`  
 .. . . . . 238  
`\RTLfoottextfont` .. . . . . 1469  
`\RTLmarginnote` .. . . . . 235  
`\rule` .. . . . . 25, 42, 61, 87, 104,  
 123, 1522, 1541, 1560, 1580,  
 1598, 1613, 1791, 1808, 1827,  
 3734, 3860, 3962, 3968, 4055,  
 4087  
**S**  
`\sayehdefault` .. 3089, 3107, 3132  
`\sayehfamily` .. 3105, 3106, 3113  
`\scriptsize` .. . . . . 3692  
`\secondarticle` 4066, 4091, 4092,  
 4094  
`\secondSubtitleFormat` .. . . . . 3806,  
 3808  
`\secondTextFormat` .. . . . . 3810, 3813  
`\secondTitleFormat` 3797, 3802,  
 3803  
`\section` .. . . . . 3245  
`\sectionautorefname` .. . . . . 1713  
`\sectionname` .. . . . . 11, 1765  
`\select@group` .. . . . . 4482  
`\selectfont` .. . . . .  
 . . . . . 3046, 3059, 3071, 3080,  
 3092, 3095, 3098, 3101, 3104,  
 3107  
`\set@typeset@protect` .. . . . . 1484,  
 1488, 3189, 3191  
`\setboolean` .. . . . .  
 . . . . . 2957, 2958, 3620, 3622,  
 3624, 3626, 3628, 3630, 3632,  
 3648, 3649, 3651, 3652, 4014,  
 4032, 4177, 4202, 4231, 4253  
`\setbox` 301, 1571, 1589, 1604, 2154,  
 2197, 2301, 2303, 2304, 2394,  
 2397, 2404, 2407, 3220, 4565  
`\setclass` 1889, 1899, 1900, 1901,  
 1902, 1903, 1904, 1905, 1906  
`\setcounter` .. . . . . 132, 133, 138,  
 139, 144, 145, 150, 151, 251,  
 252, 262, 263, 269, 270, 281,  
 282, 1451, 1452, 1461, 1462,  
 1473, 1474, 1504, 2037, 2038,  
 2827, 2828, 2834, 2835, 2841,  
 2842, 2849, 2850, 2857, 2858,

2890, 2891, 2920, 2921, 2951,  
 2955, 2959, 2960, 2961, 2962,  
 2963, 2964, 2965, 3892, 4736  
`\setdigitfont` ..... 3053, 4618  
`\setiranicfont` ..... 3136, 3141  
`\setkeys` ..... 292, 309  
`\setlatinmonofont` ..... 3065  
`\setlatinsansfont` ..... 3064  
`\setlatintextfont` .. 3054, 3063  
`\setlength` 2173, 2176, 2195, 3618,  
     3650, 3685, 3686, 3687, 3688,  
     3696, 3697, 3698, 3699, 3703,  
     3704, 3705, 3706, 3911, 3915,  
     3956, 3957, 3974, 3979, 3980,  
     4104, 4136, 4208, 4233, 4236,  
     4284, 4285, 4333, 4334, 4400,  
     4401, 4417, 4726, 4817, 4819  
`\SetMathCharDef` 4570, 4637, 4638  
`\SetMathCode` .....  
     .. 4568, 4627, 4628, 4629,  
     4630, 4631, 4632, 4633, 4634,  
     4635, 4636  
`\SetMathsDigits` 4685, 4686, 4690,  
     4695, 4696  
`\setmathsf digitfont` .... 4643  
`\setmathtt digitfont` .... 4648  
`\setmonofont` ..... 3065  
`\setnavarfont` ..... 3122  
`\setpersianfont` 3146, 3154, 3157,  
     3211  
`\setpersianmonofont` .... 3118  
`\setpersiansansfont` .... 3114  
`\setpookfont` ..... 3126, 3130  
`\setsansfont` ..... 3064  
`\setsayehfont` ..... 3131, 3135  
`\settextfont` ..... 3041, 3052  
`\setthesection` ..... 2033  
`\settowidth` ..... 1742  
`\sf@size` ..... 1775  
`\sfcode` ..... 1746  
`\sffamily` ..... 3715  
`\shadowbox` ..... 4287, 4340  
`\shadowsize` ... 4285, 4334, 4338  
`\shipout` ..... 1484, 3188  
`\shortarticleitem` ..... 4470  
`\shortarticleItemTitleFormat`  
     ..... 3868, 3869  
`\shortarticleSubtitleFormat` ..  
     ..... 3866, 3867  
`\shortarticleTitleFormat` 3864,  
     3865  
`\shortauthors` .. 1862, 1863, 1868  
`\shorttitle` ... 1861, 1862, 1868  
`\sixt@cn` ..... 2106, 2143  
`\slftitle` ..... 2051  
`\sloppy` . 21, 38, 57, 83, 100, 119,  
     1745, 1787, 1804, 1823  
`\sltttitle` ..... 2052  
`\small` 3246, 3694, 3695, 3749, 3753,  
     3759, 3830, 3852, 3871  
`\smash` ..... 3250  
`\space` 2469, 2558, 2981, 3179, 3482,  
     3918, 3919, 4059, 4060, 4062,  
     4091, 4092, 4094, 4125, 4126,  
     4128, 4145, 4146, 4148, 4166,  
     4167, 4169, 4265, 4266, 4268,  
     4375, 4757, 4992, 4993  
`\splitmaxdepth` ..... 19, 36,  
     55, 81, 98, 117, 1515, 1534,  
     1553, 1785, 1802, 1821  
`\splittopskip` ..... 19, 36,  
     55, 81, 98, 117, 1514, 1533,  
     1552, 1785, 1802, 1821  
`\stctitle` ..... 2050  
`\stepcounter` 184, 211, 1503, 2953,  
     3240, 4732, 4745, 4776  
`\string` 158, 1691, 1692, 1700, 2232,  
     2266, 2355, 2724, 3175, 4549,  
     4557  
`\strut` .. 25, 42, 61, 87, 104, 123,  
     1791, 1808, 1827  
`\strutbox` .... 19, 36, 55, 81, 98,  
     117, 1515, 1522, 1534, 1541,  
     1553, 1560, 1580, 1598, 1613,  
     1785, 1802, 1821  
`\subitem` ..... 1761  
`\subparagraphautorefname` 1717  
`\subsectionautorefname` .. 1714  
`\subsubitem` ..... 1762  
`\subsubsectionautorefname` 1715

\symnew@mathbf@font@digits .....	4581	\thechapter .....	74, 254, 265, 272, 284, 1464, 1476, 2033, 2040, 2830, 2837, 2844, 2852, 2893, 2923
\symnew@mathit@font@digits .....	4589	\theclass .....	1889, 1894
\symnew@mathrm@font@digits .....	4597	\theenumiv .....	1740, 1742
\symnew@mathsf@font@digits .....	4605	\theglsentrycounter .....	1666, 1669
\symnew@mathhtt@font@digits .....	4613	\theHchapter .....	1726
		\theHglsentrycounter .....	1669, 1672
		\theHsection .....	1725
		\theindex .....	1751
		\thempfn .....	185, 191, 212, 218, 2202
		\thempfootnote .....	2202
		\theoremautorefname .....	1719
		\thepage .....	2469, 2486, 2516, 2558, 3179, 3760
		\theparagraph .....	1855, 1856
		\thepart .....	9, 70, 130, 136, 142, 148, 245, 256, 267, 279, 1449, 1459, 1471, 1763, 2035, 2825, 2832, 2839, 2847, 2855, 2888, 2918
		\thequestion .....	4756, 4796, 4832
		\thesection .....	12, 134, 140, 146, 152, 1453, 1766, 1853, 2859
		\thesubparagraph .....	1856
		\thesubsection .....	1853, 1854
		\thesubsubsection .....	1854, 1855
		\thirdarticle .....	4098, 4125, 4126, 4128
		\thirdSubtitleFormat .....	3825, 3827
		\thirdTextFormat .....	3828, 3829
		\thirdTitleFormat .....	3816, 3821, 3822
		\thispagestyle .....	1754, 1860, 4015, 4020
		\thr@@ .....	2229, 2248, 2249, 2263, 2284, 2285, 2311, 2323, 2324, 2352, 2379, 2380
		\timestamp .....	3853, 4050, 4080, 4116
		\timestampFormat .....	3852, 3854
		\timestampSeparator .....	3851, 3856
		\timestampTxt .....	3850, 3855
		\tiny .....	3690
		\title .....	3899

\TitleBarFrame	1618, 1620, 1622, 1624	2197, 2304, 2394, 2398, 2404, 2408, 3188, 3219, 3220, 4447, 4473
\tmp	4710	\vcenter ..... 2183, 2184
\today	3158, 3160, 4371	\verbatim@addtoline ..... 2659, 2674, 2685, 2692, 2694, 2702, 2704, 2716, 2718
\toks	1869, 1871	\verbatim@finish ..... 2712
\toks@	1868, 1872	\verbatim@processline ... 2663, 2676, 2696
\topmargin	1496, 3218	\verbatim@startline 2652, 2664, 2677, 2697
\TPHorizModule	.. 3731, 3956, 4055, 4087, 4138, 4185, 4186, 4209, 4210, 4233	\vfil ..... 3221, 3874, 3890
\TPVertModule	3957	\voidb@x ..... 301
\true	4785	\vrb@catcodes ..... 2646
\truesymbol	4779	\vskip 1496, 1498, 1499, 3218, 3229, 3875, 3878, 3880, 3886
\tw@	2124, 2127, 2209, 2215, 2216, 2218, 2228, 2238, 2239, 2262, 2272, 2273, 2310, 2316, 2317, 2322, 2351, 2361, 2362, 2570	\vspace ..... 231, 238, 3910, 3929, 3991, 4001, 4044, 4048, 4071, 4074, 4078, 4085, 4103, 4107, 4111, 4120, 4179, 4183, 4239, 4260, 4308, 4312, 4331, 4361, 4365, 4410, 4412, 4422, 4425, 4450, 4452, 4472, 4474, 4767, 4825, 4827
\twocolumnstableofcontents	.. ..... 3243	\vss ..... 2186
\typeout	3008, 3010, 3904	\vtop ..... 2181, 2182, 2303
<b>U</b>		
\Umathchardef	4571	
\Umathcode	4569	
\undefined	2064, 4654, 4684, 4687, 4688, 4689, 4691, 4692, 4693	
\unhbox	2186	
\unpenalty	323	
\unrestored@protected@xdef	191, 218	
\unskip	25, 42, 61, 87, 104, 123, 197, 224, 320, 1791, 1808, 1827, 2340, 2341, 2342, 2427, 2490, 2521	
\unvbox	.. 1572, 1590, 1605, 2186	
\uppercaseonnonmath	1861	
\use	3043, 3056, 3068, 3077	
\use@mathgroup	4493	
\usebox	3908	
\usecounter	1744, 4769	
<b>V</b>		
\value	2950, 4739, 4755	
\vbox	1484, 1497, 1571, 1589, 1604, 1769, 2157, 2174, 2179, 2180,	
<b>W</b>		
\weatherFormat	3745, 3747	
\weatheritem	. 4151, 4166, 4167, 4169	
\weatherTempFormat	. 3749, 4159	
\weatherUnits	3750, 4161	
\whiledo	4739	
\widowpenalty	1745	
\width	1626, 2755, 2756	
\write	.. 3175, 3576, 3586, 3596, 4557	
\writexviiifalse	..... 3036	
\writexviiittrue	..... 3034	
<b>X</b>		
\X	..... 4709	
\x	..... 3018, 3023	

```

\xdef 1727, 4493, 4538, 4735, 4740,
      4764, 4765, 4786, 4787, 4790,
      4791
\xEPersian .... 1734, 3250, 3769
\xepersian ..... 2733, 2735
\xepersian@adadi .. 3298, 3323
\xepersian@adadi@tartibi 3399,
      3424
\xepersian@A . 1884, 1899, 1913,
      1915
\xepersian@adadi ... 3292, 3297
\xepersian@adadi@tartibi 3393,
      3398
\xepersian@cmds@temp 3013, 3031
\xepersian@coltitsize .....
      .. 3612, 4335, 4336, 4337,
      4338, 4341, 4346, 4351, 4356
\xepersian@cx .. 3939, 3944, 3961
\xepersian@cy .. 3940, 3945, 3967
\xEPersian@d .. 4838, 4863, 4968,
      4987, 4989, 4992, 4997
\xepersian@D .....
      .. 1881, 1901, 1902, 1903,
      1904, 1908, 1909, 1910, 1912,
      1913
\xepersian@dahgan . 3356, 3377,
      3457
\xepersian@digits@family 4620,
      4622, 4623, 4624, 4625
\xEPersian@dn .....
      .. 4858, 4957, 4965, 4968,
      4971, 4975, 4987, 4989
\xepersian@dx . 3937, 3942, 3953,
      3956
\xepersian@dy . 3938, 3943, 3954,
      3957
\xepersian@edition 3719, 3723,
      3759, 3879, 4011
\xepersian@editionLogo .. 3721,
      3989, 4007
\xepersian@editorialTit . 4416,
      4435
\xepersian@editorialTitle 3862,
      4421
\xepersian@everyjob 3009, 3010
\xepersian@firstText 3794, 4050
\xepersian@firstTitle ... 3782,
      4045
\xepersian@fmbox .. 3905, 3907,
      3908
\xepersian@footcenter ... 3771,
      3778, 4030
\xepersian@footleft 3773, 3777,
      4029
\xepersian@footright ... 3768,
      3779, 4028
\xepersian@gridcolumns .. 3634,
      3636, 3675, 3679
\xepersian@gridrows 3633, 3635,
      3675, 3679
\xepersian@headcenter ... 3755,
      3765, 4027
\xepersian@headDateTime . 3741,
      3995, 4009
\xepersian@headleft 3752, 3764,
      4026
\xepersian@headright ... 3758,
      3766, 4025
\xEPersian@i .....
      .. 4838, 4961, 4962, 4964,
      4965, 4966, 4969, 4973, 4974,
      4977, 4978, 4981, 4984, 4986
\xepersian@imgsize 3611, 3912,
      3913, 3915, 3924, 3925
\xepersian@incolumntitle 4322,
      4341, 4346, 4351, 4356
\xepersian@indexEntry ... 3731,
      4258
\xepersian@indexEntryPage 3737,
      4258
\xepersian@indexFrameTitle ...
      .... 3727, 4234
\xepersian@indexwidth ... 3615,
      3734, 4233, 4237, 4238
\xepersian@inxpandedtitle ...
      .. 4273, 4288, 4293, 4298,
      4303
\xepersian@innerSubtitle 3849,
      4389
\xepersian@innerTitle ... 3838,
      4388

```

\XePersian@kabisehfalse . 4908,  
     4914  
 \XePersian@kabisehtrue .. 4914  
 \xepersian@kashida .....  
     .. 1886, 1908, 1909, 1910,  
     1911, 1912, 1913, 1914  
 \xepersian@L . 1882, 1905, 1909,  
     1910, 1911, 1914, 1915  
 \XePersian@latini .. 4839, 4885  
 \XePersian@latinii 4840, 4887,  
     4889  
 \XePersian@latiniii 4841, 4891  
 \XePersian@latiniv . 4842, 4892  
 \XePersian@latinix . 4847, 4897  
 \XePersian@latinv .. 4843, 4893  
 \XePersian@latinvi .. 4844, 4894  
 \XePersian@latinvii 4845, 4895  
 \XePersian@latinviii 4846, 4896  
 \XePersian@latinx .. 4848, 4898  
 \XePersian@latinxi .. 4849, 4899  
 \XePersian@latinxii 4850, 4900  
 \XePersian@leapfalse .. 4870,  
     4874, 4880  
 \XePersian@leaptrue 4880, 4881  
 \xepersian@localize@verbatim@  
     .. 2654, 2655, 2657, 2665,  
     2678, 2687, 2698, 2706, 2720  
 \xepersian@localize@verbatim@  
     ..... 2657, 2658  
 \xepersian@localize@verbatim@  
     ..... 2660, 2661  
 \xepersian@localize@verbatim@  
     ..... 2700, 2710  
 \xepersian@localize@verbatim@rescan  
     ..... 2714, 2723  
 \xepersian@localize@verbatim@start  
     . 2651, 2726, 2727, 2738  
 \xepersian@localize@verbatim@test  
     ... 2669, 2671, 2672  
 \xepersian@localize@verbatim@testend  
     ..... 2683, 2690  
 \XePersian@m . 4838, 4863, 4959,  
     4978, 4981, 4993, 4996  
 \xepersian@milyoongan ... 3325,  
     3336  
 \xepersian@milyoongan@tartibi  
     ..... 3426, 3437  
 \XePersian@mminusone ... 4860,  
     4959, 4960, 4962, 4966  
 \xepersian@ncol .... 3966, 3967  
 \xepersian@ncolumns 3616, 4317,  
     4318, 4385  
 \xepersian@not@onlypreamble ..  
     ..... 4536, 4539  
 \xepersian@notprerr 4540, 4549  
 \xepersian@NotprerrMessage ..  
     ..... 4545, 4547  
 \xepersian@nrow .... 3960, 3961  
 \xepersian@numberoutoffrange ..  
     ... 3283, 3294, 3395  
 \xepersian@numberstring . 3280,  
     3288  
 \xepersian@numberstring@tartibi  
     ..... 3386, 3389  
 \xepersian@PackageInfo .. 4567,  
     4621  
 \xepersian@pageleft 3614, 4401,  
     4402, 4404, 4406  
 \xepersian@pageneed .....  
     .. 3613, 3915, 3916, 3918,  
     3921, 4400, 4406  
 \xepersian@pages .. 3835, 4070,  
     4102, 4387  
 \XePersian@persian@month 4993,  
     4998  
 \XePersian@persiani 4839, 4939,  
     4940, 4970, 4987  
 \XePersian@persianii 4840, 4941  
 \XePersian@persianiii ... 4841,  
     4943, 4945  
 \XePersian@persianiv 4842, 4947  
 \XePersian@persianix 4847, 4952  
 \XePersian@persianv 4843, 4948  
 \XePersian@persianvi 4844, 4949  
 \XePersian@persianvii ... 4845,  
     4950  
 \XePersian@persianviii ... 4846,  
     4951  
 \XePersian@persianx 4848, 4953  
 \XePersian@persianxi 4849, 4954

\XePersian@persianxii ... 4850,  
     4955  
 \XePersian@persianxiii .. 4851,  
     4956  
 \xepersian@pictureCaption 3831,  
     3927, 4141  
 \xepersian@R . 1883, 1900, 1912,  
     1914  
 \xepersian@sadgan .....  
     .. 3329, 3334, 3338, 3342,  
         3347, 3430, 3443  
 \xepersian@sadgan@tartibi 3435,  
     3439, 3448  
 \xepersian@say 3904, 4384, 4404,  
     4407, 4409, 4433, 4459  
 \xepersian@secondSubtitle 3807,  
     4076  
 \xepersian@secondText ... 3811,  
     4080  
 \xepersian@secondTitle .. 3798,  
     4072  
 \xepersian@section 3751, 3756,  
     4380  
 \xepersian@shellescape .. 3033  
 \xepersian@shortarticleItemTitle  
     ..... 3869, 4473  
 \xepersian@shortarticleSubtitle  
     ..... 3867, 4453  
 \xepersian@shortarticleTit ..  
     ..... 4445, 4460  
 \xepersian@shortarticleTitle  
     ..... 3865, 4449  
 \XePersian@sn .....  
     .. 4859, 4958, 4970, 4971,  
         4974, 4975, 4984, 4989  
 \xepersian@tartibi . 3386, 3462  
 \XePersian@temp .....  
     .. 4853, 4864, 4865, 4866,  
         4868, 4872, 4873, 4874, 4877,  
         4878, 4879, 4880, 4902, 4903,  
         4904, 4907, 4908, 4910, 4913,  
         4914, 4918, 4919, 4922, 4925,  
         4930, 4935, 4937, 4938, 4940  
 \XePersian@tempthree .....  
     .. 4855, 4916, 4917, 4918,  
         4920, 4923, 4926, 4927, 4931,  
             4934, 4935, 4936, 4937  
 \XePersian@temptwo .....  
     .. 4854, 4904, 4905, 4906,  
         4907, 4910, 4911, 4912, 4913,  
         4920, 4921, 4922, 4923, 4924,  
         4925, 4927, 4928, 4929, 4930,  
         4931, 4932, 4933, 4934  
 \xepersian@thirdSubtitle 3826,  
     4109  
 \xepersian@thirdText 3829, 4116  
 \xepersian@thirdTitle ... 3817,  
     4105  
 \XePersian@thirtytwo ... 4857,  
     4901, 4908  
 \xepersian@V ..... 1885, 1906  
 \xepersian@weather . 3746, 4181  
 \xepersian@www ..... 3716, 3989  
 \xepersian@wwwFormat 3715, 3717  
 \XePersian@y .....  
     .. 4838, 4863, 4864, 4867,  
         4877, 4880, 4902, 4916, 4979,  
         4982, 4993, 4995  
 \xepersian@yekani . 3329, 3357,  
     3361, 3368, 3371, 3430  
 \xepersian@yekanii 3280, 3342,  
     3367, 3443  
 \xepersian@yekaniii 3338, 3370,  
     3439  
 \xepersian@yekaniv 3349, 3373,  
     3450  
 \xepersian@yekanv .. 3458, 3469  
 \XePersian@yModHundred .....  
     .. 4856, 4867, 4868, 4869,  
         4872, 4876  
 \xepersian@zwj . 1879, 1886, 1887  
 \xepersiandate . 2980, 2981, 2997  
 \xepersianInit ..... 3672, 3973  
 \xepersianversion . 2979, 2981,  
     2997  
 \XeTeXcharclass ..... 1894  
 \XeTeXcharglyph ..... 1887  
 \XeTeXglyphbounds ..... 1887  
 \XeTeXinterchartokenstate 1917,  
     1918  
 \XeTeXinterchartoks .....  
     .. 1908, 1909, 1910, 1911,

1912, 1913, 1914, 1915	\	2066, 2071
\xpg@warning ..	3475, 3480, 3482	\ 2066, 2067, 2072, 2076
<b>Y</b>		\ 2061, 2062
\y .....	3019, 3021, 3023	\ 2066, 2068, 2073, 2078
\year .....	4863	@ \ 2055, 2059
<b>Z</b>		
\z .....	3020, 3021	@ \ .. 2763, 2764, 2765, 2766,
\z@ .....	10, 25, 42, 61, 72,	2767, 2768, 2769, 2770, 2771,
	87, 104, 123, 303, 304, 315,	2772, 2773, 2774, 2775, 2776,
	317, 1495, 1522, 1541, 1560,	2777, 2778, 2779, 2780, 2781,
	1580, 1598, 1613, 1752, 1756,	2782, 2783, 2784
	1764, 1775, 1791, 1808, 1827,	@ \ .. 2055
	1834, 1846, 1858, 1875, 2102,	\ .. 2061
	2202, 2206, 2211, 2212, 2220,	\ .. 2055, 2059
	2230, 2234, 2235, 2240, 2254,	\ .. 2417, 2725
	2264, 2268, 2269, 2274, 2290,	\ .. 2639
	2312, 2313, 2324, 2342, 2353,	\ .. 2062, 2414, 2415
	2357, 2358, 2371, 2385, 2572,	\ .. 2054
	2618, 2620, 2629, 2753, 2754,	\ .. 2057
	2761, 2762, 3198, 3216, 3227,	\ .. 2056, 2058
	3324, 3326, 3328, 3332, 3348,	
	3351, 3357, 3425, 3427, 3429,	
	3433, 3449, 3452, 3458, 3482,	
	3502, 3506, 3510, 3513, 4914	
\z@skip .....	1493, 1494, 3216	
\ziffer@check .....	4660, 4661	
\ziffer@dcheck .....	4659, 4660	
\ziffer@DotOri .....	4657, 4660	
\ZifferAn .....	4655, 4658	
\ZifferLeer .....	4660, 4684	
\ .....	1270, 2042, 2638	
\ ..	2066, 2068, 2071, 2078	
\ .....	2071	
\ ..	2056, 2063, 2064, 2067, 2068,	
	2076, 2078	
\ ..	2061, 2062, 2066, 2073	
\ ..	2054, 2060, 2061, 2066, 2071,	
	2072	
\ ..	1271, 1272, 1273, 1274, 1275,	
	1276, 1277, 1278, 2064	
\ ..	2066, 2067, 2072, 2073, 2075,	
	2076	

## 8 Change History

v13.1	General: Added implementation of the package. . . . .	1	v13.5	General: Fixed the extra space after Persian decimal separator. . . .	<a href="#">152</a>
v13.2	General: Replaced <code>\reflect</code> with <code>\bidi@reflect@box</code> . . . . .	<a href="#">124</a>	v13.6	General: Used <code>\XeTeXglyphbounds</code> to find the true height and depth of the Kashida character.	<a href="#">96</a>