

NAME

dvitype – translate a dvi file for humans

SYNOPSIS

dvitype *dvi_name[.dvi]*

DESCRIPTION

This manual page is not meant to be exhaustive. The complete documentation for this version of \TeX can be found in the info file or manual *Web2C: A \TeX implementation*.

The **dvitype** program translates a DVI (DeVice Independent) file output by (for example) **tex**(1) or **gftodvi**(1), to a file that humans can read. It also serves as a DVI file-validating program (i.e., if **dvitype** can read it, it's correct) and as an example of a DVI-reading program for future device drivers.

The output file can include all commands, just the important ones, or none at all (in which case only errors are reported). A subinterval of pages may be selected for transliteration; the magnification and resolution of the “output device” may be changed; and so on. All options are specified with an on-line dialog.

The *.dvi* extension is supplied if omitted from *dvi_name*. The output goes to *stdout*.

ENVIRONMENT

The environment variable `TEXFONTS` is used to search for the TFM files used in the DVI file. See **tex**(1) for the details of the searching. If `TEXFONTS` is not set, it uses the system default.

SEE ALSO

gftype(1), **pktype**(1).

Donald E. Knuth, *\TeX for troffware*.

BUGS

The interactive dialog should be replaced by command-line options, as with **gftype**.

AUTHORS

Donald E. Knuth wrote the program. It was published as part of the *\TeX for troffware* technical report, available from the \TeX Users Group. Howard Trickey and Pavel Curtis originally ported it to Unix.