

NAME

font2afm – create font metrics (in *afm* format) for (almost) any font file

SYNOPSIS

font2afm [options] *font* ...

font2afm [options] @*filelist*

DESCRIPTION

font2afm generates font metrics (in Adobe's *afm* format) for Type1, TrueType and OpenType fonts.

font2afm is just a wrapper script around several utilities (**cfftot1**, **pf2afm**, **ttf2afm**, **pfm2kpx** and **ot2kpx**) that do the real work. All these utilities need to be available on your system.

OPTIONS

-f Force overwriting of existing *afm* files.

FILES

font

This can be any Type1 (in either *pfa* or *pfb* format), TrueType or OpenType (both PostScript- and TrueType-flavored) font.

filelist

This should contain a newline-separated list of font filenames.

SEE ALSO

pf2afm (part of *GhostScript*), *ttf2afm* (part of *pdfTeX*), *afm2afm*, *autoinst*, *cmap2enc*, *ot2kpx*, *pfm2kpx*, *cfftot1* (part of Eddie Kohler's *LCDF TypeTools*).

AUTHOR

Marc Penninga <marc@penninga.info>

HISTORY

2005-04-15 First version

2005-04-29 Improved the documentation

2005-05-23 Bugfix.

2005-07-29 Added support for PostScript-flavored (*otf*) OpenType fonts.

2005-08-08 Bugfix.