

NAME

getnonfreefonts – download and install fonts which cannot be distributed on a CD/DVD for the current user

getnonfreefonts-sys – download and install fonts which cannot be distributed on a CD/DVD system-wide

SYNOPSIS

getnonfreefonts [*options*] [*fontlist*]

getnonfreefonts-sys [*options*] [*fontlist*]

DESCRIPTION

Some font suppliers provided fonts which can be used freely but they disallow that money is charged for the distribution. Hence, for distributions on CD or DVD it is usually impossible to include these fonts.

getnonfreefonts is a script which downloads and installs these fonts. Actually, it first downloads the program **getfont**<year> from tug.org which is then executed. **getfont**<year> does the real work. It will be updated occasionally to support more fonts. <year> denotes the TeXLive release.

getnonfreefonts and **getnonfreefonts-sys** are identical except that **getnonfreefonts** installs files to \$TEXMFHOME while **getnonfreefonts-sys** installs files to \$TEXMFLOCAL.

getfont<year> will not be installed permanently on your system. It only exists in a temporary directory while **getnonfreefonts** is running.

Run **getnonfreefonts --lsfonts** to get a list of supported fonts.

OPTIONS

-a, --all Install all fonts.

-d, --debug

Provide additional messages for debugging. These messages are sent to STDERR.

-f, --force

Install fonts even if they are installed already.

-h, --help

Print a help message. Nothing is installed but the directories where the fonts will be installed and the temporary directory are shown. <PID> will be replaced by the process ID of the current process.

-H, --http

Use HTTP instead of FTP. This option is only useful if you are behind a firewall which blocks FTP. Not all fonts are available via HTTP.

-l, --lsfonts

List all available fonts and tell whether they are installed already.

--sys If you call **getnonfreefonts** with the **--sys** option it behaves exactly like **getnonfree-fonts-sys**.

-v, --verbose

Be more verbose. This option is only needed for debugging.

--version

Print version number.

ENVIRONMENT

One of the environment variables **TMP**, **TEMP**, or **TMPDIR** must exist. They are used to determine where to put the temporary files. The directory must exist and must be writable. **/tmp** will be used if none of the variables is defined.

REQUIREMENTS

Though this program is supposed to be used with **TeX Live** it might work with other TeX distributions too. The programs **wget** or **curl**, **unzip**, and **kpsewhich** have to be installed and a recent version of **updmap** is required which supports the **--enable** option.

FONT LICENSES

If you intend to modify these fonts, please check the licenses first.

SEE ALSO

texmf-doc/doc/english/texlive-en/texlive-en.pdf .

BUGS

Please report bugs to Reinhard Kotucha <reinhard.kotucha@web.de>.