MFT(1) MFT(1)

### **NAME**

mft - translate Metafont or MetaPost code to TeX code for prettyprinting

#### **SYNOPSIS**

```
mft [OPTIONS] mf_file_name[.mf|.mp]
```

#### DESCRIPTION

This manual page is not meant to be exhaustive. The complete documentation for this version of T<sub>E</sub>X can be found in the info file or manual *Web2C: A TeX implementation*.

The **mft** program creates a TEX file from a METAFONT or MetaPost program. It takes appropriate care of typographic details like page layout and the use of indentation, italics, boldface, etc., as illustrated in the book *Computer Modern Typefaces*. Special conventions in METAFONT and MetaPost comments allow you to control things that would not otherwise come out right; section 1 of the MFT source program in the *METAFONTware* report explains these rules.

The **mft** program uses an optional change file (which works just as the change files to **tangle**(1) and **weave**(1) do) and one or several style files (which are prepended to everything). If no style file is specified, the style file **plain.mft** for METAFONT (or **mplain.mft** for MetaPost) is automatically used.

The *mf\_file\_name*, optional *change\_file\_name*, and *style\_file\_name* files are searched for using the MFINPUTS (for METAFONT) or MPINPUTS (for MetaPost) and MFTINPUTS environment variables if you have set them, or else the corresponding system defaults.

The output T<sub>E</sub>X file name is formed by using .tex in place of the extension of mf\_file\_name.

# **OPTIONS**

```
-change=change_file_name[.ch]
```

Apply the change file *change\_file\_name* to *mf\_file\_name*.

### -metapost

Assume *mf\_file\_name* is a MetaPost source file (this is the default if *mf\_file\_name* has the extension .mp).

```
-style=style_file_name[.mft]
```

Use the style file *style\_file\_name* insted of **plain.mft** (or **mplain.mft**); this option can be given more than once.

# **FILES**

```
mftmac.tex
```

TEX macros used by **mft** output.

plain.mft, mplain.mft

Default style files.

cmbase.mft

Style file for Computer Modern.

#### SEE ALSO

```
\mathbf{mf}(1), weave(1).
```

Donald E. Knuth, *Computer Modern Typefaces* (Volume E of *Computers and Typesetting*), Addison-Wesley, 1986, ISBN 0-201-13446-2.

Donald E. Knuth et al., METAFONTware.

MFT(1)

# **AUTHORS**

Donald E. Knuth wrote the program, and he ported it to Unix with the help of Pierre MacKay and the Unix port of **weave** by Howard Trickey and Pavel Curtis. The program is published in the *METAFONTware* technical report, available from the T<sub>E</sub>X Users Group.