

NAME

texmfstart – run ConTeXt scripts, make ConTeXt wrapper scripts, view documents

SYNOPSIS

texmfstart [*options ...*] [*filename*] [*arguments ...*]

DESCRIPTION

ConTeXt is a typesetting system based on the .BR **tex** (1) family of programs. **texmfstart** is a ConTeXt meta-script that can run subordinate scripts (subscripts?) such as **texexec**(1), **ctx-tools**(1), or **pdftools**(1). It can also generate short wrapper scripts to simplify common uses. These scripts are often called *stubs* in the ConTeXt documentation. The options control **texmfstart**'s behaviour, and the arguments are passed to the program identified by *filename*.

If the filename is a document, then **texmfstart** will start a viewer for that document. For example:

`texmfstart showcase.pdf`

will start an appropriate viewer for *showcase.pdf*. See the **EXAMPLES** section.

OPTIONS**General:****--help, --version**

print version information, usage, and examples.

--verbose

print status and progress information, for example what commands are being executed.

--clear don't pass info about locations to child processes.**Running a program:****--arguments=*str***

an alternative for providing the arguments to be passed. For example,

`texmfstart --arguments=b.tex texexec`

will pass *b.tex* as the argument to **texexec**.

--report

dry run: report what command would be run, but do not run it

--locate

dry run: like --report but doesn't print the trailing newline.

--browser

view the document in a web browser (for Windows).

--file=*filename*

an alternative way to specify the file (the program to run or document to open).

--direct

run a program without searching for its location (assumes that the program is on the PATH).

--execute

use the **ruby(1)** *exec* function instead of its *system* function.

--program=*str*

the program space where **kpsewhich(1)** will search (default: context). This information is given to **kpsewhich** as its *-progname* option. Usually you don't need this option.

Creating startup scripts:

--make create a wrapper script or batch file to run the given file. The wrapper scripts are put in the current path, which usually means the current directory. If *all* is given as the file, e.g.

```
texmfstart --make all
```

then make all the ConTeXt wrapper scripts (the stubs).

--windows

when making a wrapper script (stub), create a Windows batch (.bat) file. Usually you do not need to specify this option, as **texmfstart** will figure out what operating system you are using.

--linux when making a wrapper script, create a Unix shell script. Usually you do not need to specify this option, as **texmfstart** will figure out what operating system you are using.

--stupath=*path*

specify where to put the wrapper scripts (stubs).

--indirect

always use *texmfstart* in the wrapper script (stub).

Document viewing:**--page=***number*

open the document at this page.

Environments and paths:**--path=***str*

change to the specified path.

--tree=*str*

use the given TEXMF tree.

--autotree

automatically determine the TEXMF tree to use (the default).

--environment=*str*

use the given environment file. Its syntax is given in the *m texmfstart.pdf* manual.

--showenv

print the environment variables known at runtime

Conditional execution:**--iftouched=***file1,file2*

run only when the given files have different timestamps.

--ifchanged=str

run only when the given file has changed (based on its last-computed MD5 checksum).

Special features:

--edit open the given file in an editor.

FILENAME PREFIXES**Optional prefixes determine the method used to search for the specified file:**

bin:filename

expanded name based on the PATH environment variable

kpse:filename

expanded name based on **kpsewhich(1)** result

rel:filename

expanded name relative to the current directory

env:name

expanded pathname based on environment variable *name*

path:filename

path part of filename as located by **kpsewhich(1)**

EXAMPLES

`texmfstart texexec.rb file.tex`

Locate the *texexec.rb* script and run it with *file.tex* as its argument. In other words, make *file.pdf* from *file.tex*. If **texexec(1)** is properly installed on your system, this common invocation can be shortened to

`texexec file.tex`

`texmfstart texexec file.tex`

Locate the **texexec(1)** program (currently a **ruby(1)** script, *texexec.rb*) and run it with *file.tex* as its argument, producing *file.pdf*. This invocation can be shortened to

`texexec file.tex`

`texmfstart ctxtools --updatecontext`

Run the **ctxtools(1)** script, updating the ConTeXt installation. This invocation is equivalent to

`ctxtools --updatecontext`

`texmfstart pstopdf --method=3 cow.eps`

Convert *cow.eps* to PDF using method 3 of **pstopdf(1)**. This invocation is equivalent to
`pstopdf --method=3 cow.eps`

`texmfstart --make --stubpath=/usr/local/bin texexec`

Make a wrapper script (stub), either a shell script */usr/local/bin/texexec* on Unix, or a batch file *\usr\local\bin\texexec.bat* on Windows. On Unix (and maybe on Windows?), you need to make the script executable; see **chmod(1)**.

`texmfstart --edit kpse:cont-sys.tex`

Locate and edit the *cont-sys.tex* configuration file.

```
texmfstart --ifchanged=whatever.mp texexec --mpgraphic whatever.mp
```

Rerun **texexec** if *whatever.mp* has changed since the last use of *--ifchanged*.

```
texmfstart --ifchanged=whatever.mp bin:echo rerun MetaPost
```

If the *whatever.mp* source file has changed since the last use of *--ifchanged*, then use the **echo(1)** command to tell the user to rerun MetaPost (see **mpost(1)**). This example shows that **texmfstart** can be used to run any script, not just ConTeXt scripts. The **bin:** prefix tells **texmfstart** not to search for *echo* in the TEXMF tree(s), but to assume that it's an executable somewhere on the PATH.

```
texmfstart --ifchanged=whatever.mp --direct echo rerun MetaPost
```

This invocation has the same effect as the preceding example, but using *--direct* instead of the **bin:** prefix, again to tell **texmfstart** not to search for the *echo* command.

FILES

file.md5

MD5 checksum file used for the *--ifchanged* option.

ENVIRONMENT

PATH For expanding filenames given with a *bin* prefix.

TEXMFSTART_EDITOR, EDITOR, editor

Editor to use with *--edit*. The environment variables are looked up in that order, with the first setting found taking priority.

SEE ALSO

ctxtools(1), **kpsewhich(1)**, **makempy(1)**, **mpost(1)**, **pdftools(1)**, **pstopdf(1)**, **texexec(1)**, **texfont(1)**, **texutil(1)**.

[ConTeXt wiki](http://www.contextgarden.net) (<http://www.contextgarden.net>).

The **texmfstart** manual, *m texmfstart.pdf*, available from **PRAGMA ADE** (<http://www.pragma-ade.com/dir/general/manuals/>).

BUGS

On Unix, opening a PDF document first tries **pdfopen** then **acroread**, neither of which may be present on your system.

The *--report* option doesn't work if you specify a filename prefix (i.e. it does a real run instead of a dry run).

AUTHOR

ConTeXt is written and maintained by [Hans Hagen](http://www.pragma-ade.com) (<http://www.pragma-ade.com>). This man page, which is in the public domain, was written by Sanjoy Mahajan <sanjoy@mit.edu> based on the *m texmfstart.pdf* manual.