

NAME

tlmgr – the TeX Live Manager

SYNOPSIS

tlmgr [*option*]... *action* [*option*]... [*operand*]...

DESCRIPTION

tlmgr manages an existing TeX Live installation, both packages and configuration options. It performs many of the same actions as **texconfig**(1), and more besides. (**texconfig** continues to be included and supported, but **tlmgr** is now preferred.)

The most up-to-date version of this documentation is available at [<http://tug.org/texlive/tlmgr.html>](http://tug.org/texlive/tlmgr.html).

OPTIONS

The following options to **tlmgr** have to be given *before* you specify the main action to perform.

--location *location*

Specifies the location from which packages should be installed or updated, overriding the location found in the installation's TeX Live Package Database (TLPDB).

--gui [*action*]

You can give this option together with an action to be brought directly into the respective screen of the GUI. For example, running

```
tlmgr --gui update
```

starts you directly at the update screen.

--gui-lang *llcode*

Normally the GUI tries to deduce your language from the environment (on Windows via the registry, on Unix via LC_MESSAGES). If that fails you can select a different language by giving this option a two-letter language code.

--package-logfile *file*

tlmgr logs all package actions (install, remove, update, failed updates, failed restores) to a separate log file, by default `TEXMFSYSVAR/web2c/tlmgr.log`. This option allows you to select a different file for that. This is separate from normal logging; for that, see the option `-v` below, and `TeXLive::TLUtils`.

--pause

This option make **tlmgr** wait for a user input before exiting.

The standard options are also accepted: `--help/-h/-?`, `--version`, `-q` (no informational messages), `-v` (debugging messages, can be repeated). For the details about the latter, see the `TeXLive::TLUtils` documentation.

The `--version` option shows version information about the TeX Live release as well as the **tlmgr** script itself.

ACTIONS

help

Gives this help information (same as `--help`).

version

Gives version information (same as `--version`).

gui Start the graphical user interface.

install [*option*]... *pkg*...

Install each *pkg* given on the command line. By default this installs all packages that the given *pkgs* are dependent on, also. Options:

--reinstall

Reinstall a package (including dependencies for collections) even if it seems to be already installed (i.e, is present in the TLPDB). This is useful to recover from accidental removal of files in the hierarchy.

When re-installing, only dependencies on normal packages are followed (not those of category Scheme or Collection).

--no-depends

Do not install dependencies. (By default, installing a package ensures that all dependencies of this package are fulfilled.)

--no-depends-at-all

When you install a package which ships binary files the respective binary package will also be installed. (So for package bin-foobar also the package bin-foobar.i386-linux will be installed on an i386-linux system.) This switch supresses this behaviour, and also implies **--no-depends**. Don't use it unless you are really sure what you are doing.

--dry-run

Nothing is actually installed; instead, the actions to be performed are written to the terminal.

update [*option*] [*pkg*...]

Updates the packages given as arguments to the latest version available at the installation source. Either **--all** or at least one *pkg* name must be specified. Options:

--all Update all installed packages. For packages contained in an installed collection, also install new packages and remove deleted packages in those collections. Packages not contained in an installed collection are not considered for addition or removal.

More precisely, if both the server and the local installation have a collection C, and C on the server contains a package A that is not present locally, A will be added. Conversely, if the local collection C contains a package B, but B is no longer in the server's C, then B will be deleted.

--list Concisely list the packages which would be updated, newly installed, or removed, without actually changing anything.

--dry-run

Nothing is actually installed; instead, the actions to be performed are written to the terminal. This is a more detailed report than **--list**.

--no-remove

Under normal circumstances tlmgr tries to remove packages which have disappeared on the server when called with **--all**, as described above. This prevents any such removals.

--backupdir *directory*

directory specifies a directory where the package as installed will be saved before updates are performed. Then you can restore later if the update turns out to be problematic; see the `restore` action for details.

--no-depends

If you call for updating a package normally all depending packages will also be checked for updates and updated if necessary. This switch supresses this behaviour.

--no-depends-at-all

When you update a package which ships binary files the respective binary package will also be updated. (So for package `bin-foobar` also the package `bin-foobar.i386-linux` will be updated on an `i386-linux` system.) This switch supresses this behaviour, and also implies `--no-depends`. Don't use it unless you are really sure what you are doing.

If the package on the server is older than the package already installed (e.g., if the selected mirror is out of date), `tlmgr` does not downgrade. Also, packages for uninstalled platforms are not installed.

backup **--backupdir** *dir* [**--all**] [*pkg...*]

Makes a backup of the given packages, or all packages with `--all`, to *dir*, which must exist and be writable. Options:

--backupdir *directory*

The *directory* argument is required and must specify an existing directory where backups are to be placed.

--all Make a backup of all packages in the TeX Live installation. This will take quite a lot of space and time.

restore **--backupdir** *dir* [*pkg* [*rev*]]

Restore a package from a previously-made backup.

If neither *pkg* nor *rev* are given, list the available backup revisions for all packages.

With *pkg* given but no *rev*, list all available backup revisions of *pkg*.

With both *pkg* and *rev*, tries to restore the package from the specified backup.

Options:

--dry-run

Nothing is actually restored; instead, the actions to be performed are written to the terminal.

--backupdir *directory*

This is an obligatory argument and has to specify a directory where backups are to be found.

remove [*option*]... *pkg...*

Remove each *pkg* specified. Removing a collection removes all package dependencies, but not collection dependencies, in that collection (unless `--no-depends` is specified). However, when removing a package, dependencies are never removed. Options:

--no-depends

Do not remove dependent packages.

--no-depends-at-all

When you remove a package which ships binary files the respective binary package will also be removed. (So for package `bin-foobar` also the package `bin-foobar.i386-linux` will be removed on an `i386-linux` system.) This switch suppresses this behaviour, and also implies `--no-depends`. Don't use it unless you are really sure what you are doing.

--force By default, removal of a package or collection that is a dependency of another collection or scheme is not allowed. With this option, the package will be removed unconditionally. Use with care.

--dry-run

Nothing is actually removed; instead, the actions to be performed are written to the terminal.

option [show]**option key [value]**

The first form shows the global TeX Live settings currently saved in the TLPDB.

In the second form, if *value* is not given, the setting for *key* is displayed. If *value* is present, *key* is set to *value*.

Possible values for *key* are: `location` (default installation location), `formats` (create formats at installation time), `docfiles` (install documentation files), `srcfiles` (install source files).

Perhaps the most common use for this is if you originally installed from DVD, and want to permanently change the installation to get further updates from the Internet. To do this, you can run

```
tlmgr option location http://mirror.ctan.org/systems/texlive/tlnet/YYYY
```

where YYYY is the TeX Live release year.

paper a4**paper letter****[xdvi|dvips|pdftex|dvipdfm|dvipdfmx|context] paper [help|papersize|--list]**

Configures the system wide paper settings, either for all programs at once (first two forms), or just for the specified program (third form). The third form with `--list` outputs all known papersizes for the specified program.

arch list|add arch...

`arch list` lists the TeX Live names of all the architectures (`i386-linux`, ...) available at the default install location.

`arch add arch` adds the executables for each given architecture *arch* to the installation. Options:

--dry-run

Nothing is actually installed; instead, the actions to be performed are written to the terminal.

search [*option...*] *what*

By default searches the names, short and long descriptions of all locally installed packages for the given argument (interpreted as regexp). Options:

--file List all filenames containing *what*.

--global

Search the TeX Live Database of the installation medium, instead of the local installation.

show *pkg...*

Shows information about *pkg*: the name, category, installation status, short and long description. Searches in the remote installation source for the package if it is not locally installed.

list [*collections*|*schemes*]

With no argument, lists all packages available at the default install location, prefixing those already installed with "i".

With an argument lists only collections or schemes, as requested.

check [*option...*] [*files*|*collections*|*all*]

Executes one (or all) check(s) on the consistency of the installation.

files Checks that all files listed in the TeX Live Database (`texlive.tlpdb`) are actually present, and lists those missing.

collections

Lists those packages which occur as dependencies in an installed collections, but are themselves not installed.

Available options are:

--use-svn

Use svn status instead of listing the files, for checking the development repository.

uninstall

Uninstalls the entire TeX Live installation. Options:

--force Do not ask for confirmation, remove immediately.

generate language**generate language.dat****generate language.def****generate fmtutil****generate updmap**

The *generate* action overwrites any manual changes made in the respective files: it recreates them from scratch.

For fmtutil and the language files, this is normal, and both the TeX Live installer and `tlmgr` routinely call *generate* for them.

For updmap, however, neither the installer nor `tlmgr` use *generate*, because the result would be to disable all maps which have been manually installed via `updmap-sys --enable`, e.g., for proprietary or local fonts. Only the changes in the `--localcfg` file mentioned below are incorporated by *generate*.

On the other hand, if you only use the fonts and font packages within TeX Live, there is

nothing wrong with using *generate updmap*. Indeed, we use it to generate the `updmap.cfg` file that is maintained in the live source repository.

In more detail: *generate* remakes any of the four config files `language.dat`, `language.def`, `fmtutil.cnf`, and `updmap.cfg` from the information present in the local TLPDB. If the files `language-local.dat`, `language-local.def`, `fmtutil-local.cnf`, or `updmap-local.cfg` are present under `TEXMFLOCAL` in the respective directories, their contents will be simply merged into the final files, with no error checking of any kind.

The form `generate language` recreates both the `language.dat` and the `language.def` files, while the forms with extension only recreates the given file.

Options:

--dest *output file*

specifies the output file (defaults to the respective location in `TEXMFSYSVAR`). If **--dest** is given to `generate language`, its value will be used for the `language.dat` output, and `.def` will be appended to the value for the name of the `language.def` output file. (This is just to avoid overwriting; if you really want a specific name for each output file, we recommend invoking `tlmgr` twice.)

--localcfg *local conf file*

specifies the (optional) local additions (defaults to the respective location in `TEXMFSYSVAR`).

The respective locations are as follows:

`tex/generic/config/language.dat` (and `language-local.dat`)
`tex/generic/config/language.def` (and `language-local.def`)
`web2c/fmtutil.cnf` (and `fmtutil-local.cnf`)
`web2c/updmap.cfg` (and `updmap-local.cfg`)

AUTHORS AND COPYRIGHT

This script and its documentation were written for the TeX Live distribution (<http://tug.org/texlive>) and both are licensed under the GNU General Public License Version 2 or later.