# NAME

weave - translate WEB to TeX

#### SYNOPSIS

weave [ -x ] webfile[.web] [ changefile[.ch] ]

## DESCRIPTION

This manual page is not meant to be exhaustive. The complete documentation for this version of  $T_EX$  can be found in the info file or manual *Web2C: A TeX implementation*.

The **weave** program is used to create a T<sub>E</sub>X file for viewing a WEB program. It takes appropriate care of typographic details like page layout and the use of indentation, italics, boldface, etc., and it supplies extensive cross-index information that it gathers automatically. The command line arguments are the same as for **tangle** except for the option:  $-\mathbf{x}$  says to omit the index, module name list, and table of contents pages. (A *CONTENTS.tex* file will still be written when the T<sub>E</sub>X file is processed, however, unless some macros in *webmac.tex* are redefined.)

The output T<sub>E</sub>X file name is formed by adding *.tex* to the root of the WEB file name.

There are several macros that probably should be redefined by the programmer at the beginning of the WEB file. It is a good idea to set \title to the name of the program. And, to cause output of only changed modules, one can say \let\maybe=\iffalse (usually as the first change in the change file).

# FILES

*\$TEXMFMAIN/tex/plain/base/webmac.tex* T<sub>E</sub>X macros used by **weave** output.

### **SEE ALSO**

**tangle**(1) for references, authors, and other information.